

Test of APIN0224, APIN0225 802.11a/b/g/n/ac

To: FCC 47 CFR Part 15.407 & IC RSS-210

Test Report Serial No.: ARUB145-U2 Rev A



TEST REPORT
FROM
MiCOM Labs

Test of APIN0224, APIN0225 802.11a/b/g/n/ac

to

To FCC 47 CFR Part 15.407 & IC RSS-210

Test Report Serial No.: ARUB145-U2 Rev A

Note: this report contains data with regard to the 5,150 - 5,250 (non-DFS) bands for Aruba Networks, APIN0224 and APIN0225 Wireless Access Point. 2.4 and 5.8 GHz test data are reported in MiCOM Labs test report ARUB145-U1

This report supersedes None

Applicant: Aruba Networks
1344 Crossman Avenue
Sunnyvale, California 94089
USA

Product Function: Wireless Access Point

Copy No: pdf Issue Date: 13th May 2013

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
440 Boulder Court, Suite 200
Pleasanton, CA 94566 USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



TEST CERTIFICATE #2381.01

MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 3 of 167

This page has been left intentionally blank

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF CONTENTS

ACCREDITATION, LISTINGS & RECOGNITION	5
TESTING ACCREDITATION	5
RECOGNITION	6
PRODUCT CERTIFICATION	7
1. TEST RESULT CERTIFICATE	9
2. REFERENCES AND MEASUREMENT UNCERTAINTY	10
2.1. Normative References.....	10
2.2. Test and Uncertainty Procedures.....	11
3. PRODUCT DETAILS AND TEST CONFIGURATIONS	12
3.1. Technical Details.....	12
3.2. Scope of Test Program	13
3.3. Equipment Model(s) and Serial Number(s).....	17
3.4. Antenna Details	17
3.5. Cabling and I/O Ports	18
3.6. Test Configurations	19
3.7. Equipment Modifications	20
3.8. Deviations from the Test Standard.....	20
3.9. Subcontracted Testing or Third Party Data.....	20
4. TESTING EQUIPMENT CONFIGURATION(S)	21
4.1. Conducted RF Emission Test Set-up	21
4.2. Radiated Spurious Emission Test Set-up > 1 GHz	22
4.3. Digital Emissions Test Set-up (0.03 – 1 GHz).....	23
4.4. ac Wireline Emission Test Set-up	24
5. TEST SUMMARY	25
6. TEST RESULTS	27
6.1. Device Characteristics.....	27
6.1.1. <i>Conducted Testing</i>	27
6.1.2. <i>Radiated Emission Testing</i>	57
6.1.3. <i>AC Wireline Conducted Emissions (150 kHz – 30 MHz)</i>	91
7. PHOTOGRAPHS	95
7.1. Test Setup - Digital Emissions below 1 GHz.....	95
7.2. Radiated Emissions Test Setup >1 GHz – ANT-19	97
8. TEST EQUIPMENT DETAILS	98
APPENDIX	99
A. SUPPORTING INFORMATION	99
A.1. CONDUCTED TEST PLOTS	99
A.1.1. <i>26 dB & 99% Bandwidth</i>	100
A.1.2. <i>Peak Power Spectral Density</i>	133
A.1.3. <i>Peak Excursion Ratio</i>	162

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 5 of 167

ACCREDITATION, LISTINGS & RECOGNITION

TESTING ACCREDITATION

MiCOM Labs, Inc. is an accredited Electrical testing laboratory per the international standard EN ISO/IEC 17025. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



Accredited Laboratory

A2LA has accredited

MICOM LABS

Pleasanton, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-LAF Communiqué dated 8 January 2009).

Presented this 27th day of March 2012.

President & CEO
For the Accreditation Council
Certificate Number 2381.01
Valid to November 30, 2013



For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 6 of 167

RECOGNITION

MiCOM Labs, Inc has widely recognized Electrical testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA** countries. Our test reports are widely accepted for global type approvals.

Country	Recognition Body	Status	Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	US0159 Listing #: 102167
Canada	Industry Canada (IC)	FCB	APEC MRA 2	US0159 Listing #: 4143A-2
Japan	MIC (Ministry of Internal Affairs and Communication)	CAB	APEC MRA 2	RCB 210
	VCCI	--	--	A-0012
Europe	European Commission	NB	EU MRA	NB 2280
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)	CAB	APEC MRA 1	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	CAB	APEC MRA 1	
Singapore	Infocomm Development Authority (IDA)	CAB	APEC MRA 1	
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)	CAB	APEC MRA 1	
Vietnam	Ministry of Communication (MIC)	CAB	APEC MRA 1	

**APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement.

Is a recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.

Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

N/A – Not Applicable

**EU MRA – European Union Mutual Recognition Agreement.

Is a recognition agreement under which test lab is accredited to regulatory standards of the EU member countries.

**NB – Notified Body

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 7 of 167

PRODUCT CERTIFICATION

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard EN ISO/IEC Guide 65. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-02.pdf>



The American Association for Laboratory Accreditation

"World Class Accreditation"

Accredited Product Certification Body

A2LA has accredited

MICOM LABS

Pleasanton, CA

for technical competence as a

Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system.

Presented this 27th day of March 2012.





President & CEO
For the Accreditation Council
Certificate Number 2381.02
Valid to November 30, 2013

For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation

USA Telecommunication Certification Body (TCB) - TCB Identifier – US0159

Industry Canada Certification Body - CAB Identifier – US0159

European Notified Body - Notified Body Identifier - 2280

Japan – Recognized Certification Body (RCB) - RCB Identifier - 210

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 8 of 167

DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft		
Rev A	13 th May 2013	Initial release

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 9 of 167

1. TEST RESULT CERTIFICATE

Applicant:	Aruba Networks 1344 Crossman Avenue Sunnyvale, California 94089 USA	Tested By:	MiCOM Labs, Inc. 440 Boulder Court Suite 200 Pleasanton California, 94566, USA
EUT:	Wireless LAN Access point	Tel:	+1 925 462 0304
Model:	APIN0224 & APIN0225	Fax:	+1 925 462 0306
S/N:	BX0000206		
Test Date(s):	15th January - 30th March 2013	Website:	www.micomlabs.com


STANDARD(S)	TEST RESULTS
FCC 47 CFR Part 15.407 & IC RSS-210 (non-DFS Bands)	EQUIPMENT COMPLIES

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.


Approved & Released for MiCOM Labs, Inc. by:



Graeme Grieve
Quality Manager MiCOM Labs,



TESTING CERTIFICATE #2381.01



Gordon Hurst
President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

2. REFERENCES AND MEASUREMENT UNCERTAINTY

2.1. Normative References

Ref.	Publication	Year	Title
(i)	FCC 47 CFR Part 15.407	2012	Code of Federal Regulations
(ii)	FCC 06-96	June 2006	Memorandum Opinion and Order
(iii)	FCC OET KDB 662911	4 th April 2011	Emissions Testing of Transmitters with Multiple Outputs in the Same Band
(iv)	Industry Canada RSS-210	2010	Low Power License-Exempt Radiocommunication Devices (All Frequency Bands): Category 1 Equipment
(v)	Industry Canada RSS-Gen	2010	General Requirements and Information for the Certification of Radiocommunication Equipment
(vi)	ANSI C63.4	2009	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
(vii)	CISPR 22/ EN 55022	2008 2006+A1:2007	Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment
(viii)	M 3003	Edition 1 Dec. 1997	Expression of Uncertainty and Confidence in Measurements
(ix)	LAB34	Edition 1 Aug 2002	The expression of uncertainty in EMC Testing
(x)	ETSI TR 100 028	2001	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
(xi)	A2LA	July 2012	Reference to A2LA Accreditation Status – A2LA Advertising Policy
(xii)	FCC Public Notice – DA 02-2138	2002	Guidelines for Assessing Unlicensed National Information Infrastructure (U-NII) Devices

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 11 of 167

2.2. Test and Uncertainty Procedures

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor $k = 2$, providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 12 of 167

3. PRODUCT DETAILS AND TEST CONFIGURATIONS

3.1. Technical Details

Details	Description
Purpose:	Test of the APIN0224, APIN0225 802.11a/b/g/n/ac in the frequency range 5,150 - 5,250 MHz to FCC Part 15.407 and Industry Canada RSS-210 regulations.
Applicant:	Aruba Networks 1344 Crossman Avenue Sunnyvale, California 94089, USA
Manufacturer:	As applicant
Laboratory performing the tests:	MiCOM Labs, Inc. 440 Boulder Court, Suite 200 Pleasanton, California 94566 USA
Test report reference number:	ARUB145-U2 Rev A
Date EUT received:	4 th January 2013
Standard(s) applied:	FCC 47 CFR Part 15.407 & IC RSS-210
Dates of test (from - to):	15th January - 30th March 2013
No of Units Tested:	One
Type of Equipment:	802.11a/b/g/n/ac Wireless Access Point 3x3 Spatial Multiplexing MIMO configuration
Applicants Trade Name:	Wireless Access Point
Model(s):	APIN0224, APIN0225
Location for use:	Indoor only
Declared Frequency Range(s):	5,150 – 5,250 MHz
Hardware Rev	6.3.0.0
Software Rev	37654
Type of Modulation:	Per 802.11 – OFDM
EUT Modes of Operation:	Legacy 802.11a, 802.11n HT-20, HT-40, ac-40, ac-80
Declared Nominal Output Power: (Average Power)	802.11a: Legacy +15 dBm 802.11n: HT-20 +15 dBm 802.11n: HT-40 +15 dBm 802.11ac-40 +15 dBm 802.11ac-80 +15 dBm
Transmit/Receive Operation:	Time Division Duplex
Rated Input Voltage and Current:	POE 12 Vdc 1.25 A
Operating Temperature Range:	Declared range 0° to +40°C
ITU Emission Designator:	802.11a 17M7D1D 802.11n HT-20 17M7D1D 802.11n HT-40 36M4D1D 802.11ac-40 36M9D1D 802.11ac-80 75M9D1D
Equipment Dimensions:	203mm x 203mm x 65mm / 8.0"x8.0"x2.6" (WxDxH)
Weight:	750 g / 27 oz
Primary function of equipment:	Wireless Access Point for transmitting data and voice.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 13 of 167

3.2. Scope of Test Program

Aruba Networks APIN0224, APIN0225 Access Point RF Testing

The scope of the test program was to test the Aruba Networks APIN0224, APIN0225 Wireless LAN Access Point, 3X3 Spatial Multiplexing MIMO configurations in the frequency range 5,150 - 5,250 MHz for compliance against FCC 47 CFR Part 15.407 and Industry Canada RSS-210 specifications.

FCC OET KDB Implementation

This test program implements the following FCC KDB – 662911 4/4/2011;

Emissions Testing of Transmitters with Multiple Outputs in the Same Band

The KDB document provides guidance for measurements of conducted output emissions of devices that employ a single transmitter with multiple outputs in the same band, with the outputs occupying the same or overlapping frequency ranges. It applies to EMC compliance measurements on devices that transmit on multiple antennas simultaneously in the same or overlapping frequency ranges through a coordinated process. Examples include, but are not limited to, devices employing beam forming or multiple-input and multiple-output (MIMO.) This guidance applies to both licensed and unlicensed devices wherever the FCC rules call for conducted output measurements. Guidance is provided for in-band, out-of-band and spurious emission measurements.

This guidance does not apply to the multiple transmitters included in a composite device, such as a device that combines an 802.11 modem with a cell phone in one enclosure with each driving its own antenna.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Aruba Networks Inc
APIN0224 External Antenna 802.11 a/b/g/n/ac Wireless Access Point



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Aruba Networks Inc
APIN0225 Integral Antenna 802.11 a/b/g/n/ac Wireless Access Point



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Aruba Networks Inc
802.11 a/b/g/n/ac Wireless Access Point (Rear)



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 17 of 167

3.3. Equipment Model(s) and Serial Number(s)

Type (EUT/ Support)	Equipment Description (Including Brand Name)	Mfr	Model No.	Serial No.
EUT	Wireless LAN Access Point	Aruba Networks	APIN0224	BX0000206
Support	Laptop PC	IBM	Thinkpad	None

3.4. Antenna Details

Model	Type	Gain	Freq. Band	Note
		dBi	MHz	
AP-ANT-1B	Omni	3.8	2400 - 2500	3x per unit
		5.8	4900 - 5875	
AP-ANT-13B	Omni	4.4	2400 - 2500	3x per unit
		3.3	4900 - 5900	
AP-ANT-16	Omni	3.9	2400 - 2500	3x per unit
		4.7	4900 - 5900	
AP-ANT-17	Directional 120degr.	6.0	2400 - 2500	3x per unit
		5.0	4900 - 5875	
AP-ANT-18	Directional 60degr.	7.5	2400 - 2500	3x per unit
		7.5	5150 - 5875	
AP-ANT-19	Omni	3.0	2400 - 2500	3 x per unit
		6.0	5150 - 5875	

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

APIN0225 Integrated Antennas

Model	Type	Gain	Freq. Band	Note
		dBi	MHz	
metal sheet	Omni	4.0	2400 - 2500	3x per band, per unit
		4.5	4900 - 5875	

3.5. Cabling and I/O Ports

Number and type of I/O ports

1. 2 x 10/100/1000 Ethernet ENET0, ENET1
2. Console - Serial maintenance terminal
3. 12 Vdc, supply connector
4. RF Antenna Connectors (x3) – Reverse SMA (APIN0224 Only)
5. USB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3.6. Test Configurations

Testing was performed to determine the highest power level versus bit rate. The variant with the highest power was used to exercise the product.

Matrix of test configurations

Operational Mode(s) (802.11)	Variant	Data Rates with Highest Power	Frequencies (MHz)
5150-5250 MHz	Legacy	6 MBit/s	5180/5200/5240
	HT-20	6.5 MBit/s	
	HT-40	13.5 MBit/s	5190, 5230
	ac-40		
	ac-80	29.3 MBit/s	5210

Spurious Emission and Band-Edge Test Strategy

Bands 5,150 – 5250

11a	11n HT-20	11n HT-40	11ac-40	11ac-80
SE 5180	SE 5180	SE 5190	SE 5190	SE 5210
SE 5200	SE 5200			
SE 5240	SE 5240	SE 5230	SE 5230	
BE 5150	BE 5150	BE 5150	BE 5150	BE 5150

KEY:-

SE – Spurious Emissions

BE – Band-Edge

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. NONE

3.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. NONE

3.9. Subcontracted Testing or Third Party Data

1. NONE

4. TESTING EQUIPMENT CONFIGURATION(S)


4.1. Conducted RF Emission Test Set-up

The following tests were performed using the conducted test set-up shown in the diagram below.

1. Section 6.1.1.1. 26 dB and 99% Bandwidth
2. Section 6.1.1.2. Maximum Conducted Output Power
3. Section 6.1.1.3. Peak Power Spectral Density
4. Section 6.1.1.4. Peak Excursion Ratio

Conducted Test Set-Up Pictorial Representation

3 - Port Test Configuration




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

4.2. Radiated Spurious Emission Test Set-up > 1 GHz

The following tests were performed using the conducted test set-up shown in the diagram below.

Radiated Emission Measurement Setup – Above 1 GHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

4.3. Digital Emissions Test Set-up (0.03 – 1 GHz)

The following tests were performed using the conducted test set-up shown in the diagram below.

1. Section 6.1.2.4. Digital Emissions

Digital Emission Measurement Setup – Below 1 GHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

4.4. ac Wireline Emission Test Set-up

The following tests were performed using the conducted test set-up shown in the diagram below.

1. Section 6.1.3 ac Wireline Conducted Emissions

Conducted Test Set-Up Pictorial Representation



Measurement set up for ac Wireline Conducted Emissions Test

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 25 of 167

5. TEST SUMMARY

List of Measurements

The following table represents the list of measurements required under the **FCC CFR47 Part 15.407** and **Industry Canada RSS-210** and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.407(a) A9.2(2) 4.4	26dB and 99% Emission BW	Emission bandwidth measurement	Conducted	Complies	6.1.1.1 A.1.1
15.407(a) A9.2(2) 4.6	Maximum Conducted Output Power	Power Measurement	Conducted	Complies	6.1.1.2
15.407(a) A9.2(2)	Peak Power Spectral Density	PPSD	Conducted	Complies	6.1.1.3 A.1.2
15.407(a)(6)	Peak Excursion Ratio	<13dB in any 1MHz bandwidth	Conducted	Complies	6.1.1.4 A.1.3
15.407(g) 15.31 2.1 4.5	Frequency Stability	Limits: contained within band of operation at all times.	Applicant declaration	Complies	6.1.1.5
15.407(f) 5.5	Radio Frequency Radiation Exposure	Exposure to radio frequency energy levels, Maximum Permissible Exposure (MPE)	Conducted	See included MPE exhibit	--

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 26 of 167

List of Measurements (continued)

The following table represents the list of measurements required under the **FCC CFR47 Part 15.407** and **Industry Canada RSS-210** and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.407(b)(2) 15.205(a) 15.209(a) 2.2 2.6 A9.3(2) 4.7	Radiated Emissions		Radiated		6.1.2
	Transmitter Radiated Spurious Emissions	Emissions above 1 GHz		Complies	6.1.2.1 6.1.2.2 6.1.2.3
	Radiated Band Edge	Band edge results		Complies	6.1.2.1 6.1.2.2 6.1.2.3
15.407(b)(6) 15.205(a) 15.209(a) 2.2	Radiated Emissions	Emissions <1 GHz (30M-1 GHz)		Complies	6.1.2.4
15.407(b)(6) 15.207 7.2.2	AC Wireline Conducted Emissions 150 kHz–30 MHz	Conducted Emissions	Conducted	Complies ac/dc adaptor only, POE not marketed with equipment	6.1.3

Note 1: Test results reported in this document relate only to the items tested

Note 2: The required tests demonstrated compliance as per client declaration of test configuration, monitoring methodology and associated pass/fail criteria

Note 3: Section 3.7 Equipment Modifications highlights the equipment modifications that were required to bring the product into compliance with the above test matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 27 of 167

6. TEST RESULTS

6.1. Device Characteristics

6.1.1. Conducted Testing

6.1.1.1. 26 dB and 99 % Bandwidth

Conducted Test Conditions for 26 dB and 99% Bandwidth			
Standard:	FCC CFR 47:15.407	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	26 dB and 99 % Bandwidth	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.407 (a)	Pressure (mBars):	999 - 1001
Reference Document(s):	KDB 789033 - D01 DTS General UNII Test Procedures v01		

Test Procedure for 26 dB and 99% Bandwidth Measurement

The bandwidth at 26 dB and 99 % is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency. KDB 789033 Section 5.1 Emission Bandwidth was used in order to prove compliance. The Resolution Bandwidth was set to approximately 1% of the emission bandwidth.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 28 of 167

Measurement Results for 26 dB and 99 % Operational Bandwidth(s)

Equipment Configuration for 26 dB & 99% Occupied Bandwidth											
Variant:	802.11a		Duty Cycle (%):	99%							
Data Rate:	6 MBit/s		Antenna Gain (dBi):	Not Applicable							
Modulation:	OFDM		Beam Forming Gain (Y):	Not Applicable							
TPC:	Not Applicable										
Engineering Test Notes:	Not Applicable										
Test Measurement Results											
Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)						
	Port(s)										
MHz	a	b	c	d	Highest	Lowest					
5180.0	20.641	20.541	20.541	-	20.641	20.541					
5200.0	20.641	20.541	20.441	-	20.641	20.441					
5240.0	20.741	20.441	20.441	-	20.741	20.441					
Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)						
	Port(s)										
MHz	a	b	c	d	Highest	Lowest					
5180.0	17.936	17.735	17.735	-	17.936	17.735					
5200.0	17.936	17.735	17.735	-	17.936	17.735					
5240.0	17.836	17.735	17.735	-	17.836	17.735					

Traceability to Industry Recognized Test Methodologies							
		Work Instruction: WI-03 MEASURING RF SPECTRUM MASK					
		Measurement Uncertainty: ±2.81 dB					

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 29 of 167

Equipment Configuration for 26 dB & 99% Occupied Bandwidth

Variant:	802.11n HT-20	Duty Cycle (%):	99%
Data Rate:	6.5 Mbit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:	Not Applicable		

Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)			
	Port(s)							
MHz	a	b	c	d	Highest	Lowest		
5180.0	20.641	20.641	20.441	-	20.641	20.441		
5200.0	20.641	20.541	20.441	-	20.641	20.441		
5240.0	20.641	20.541	20.441	-	20.641	20.441		

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)			
	Port(s)							
MHz	a	b	c	d	Highest	Lowest		
5180.0	17.735	17.735	17.735	-	17.735	17.735		
5200.0	17.735	17.735	17.735	-	17.735	17.735		
5240.0	17.936	17.735	17.735	-	17.936	17.735		

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 30 of 167

Equipment Configuration for 26 dB & 99% Occupied Bandwidth

Variant:	802.11n HT-40	Duty Cycle (%):	99%
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:	Not Applicable		

Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)			
	Port(s)							
MHz	a	b	c	d	Highest	Lowest		
5190.0	40.481	39.679	39.880	-	40.481	39.679		
5230.0	40.281	39.880	39.880	-	40.281	39.880		

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)			
	Port(s)							
MHz	a	b	c	d	Highest	Lowest		
5190.0	36.673	36.273	36.473	-	36.673	36.273		
5230.0	36.673	36.273	36.473	-	36.673	36.273		

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 31 of 167

Equipment Configuration for 26 dB & 99% Occupied Bandwidth

Variant:	802.11ac-40	Duty Cycle (%):	99%
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:	Not Applicable		

Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)			
	Port(s)							
MHz	a	b	c	d	Highest	Lowest		
5190.0	47.295	56.112	62.725	-	62.725	47.295		
5230.0	41.082	57.916	51.303	-	57.916	41.082		

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)			
	Port(s)							
MHz	a	b	c	d	Highest	Lowest		
5190.0	36.874	36.673	36.874	-	36.874	36.673		
5230.0	36.673	36.673	36.673	-	36.673	36.673		

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 32 of 167

Equipment Configuration for 26 dB & 99% Occupied Bandwidth

Variant:	802.11ac-80	Duty Cycle (%):	99%
Data Rate:	29.3 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:	Not Applicable		

Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5210.0	90.581	117.034	101.804	-	117.034	90.581
Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	D	Highest	Lowest
5210.0	76.553	76.553	76.553	-	76.553	76.553

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 33 of 167

Specification

Limits

FCC, Part 15 §15.407 (a)(1), (a)(2) and Industry Canada RSS-210 § A9.2(2)

(a)(1) For the band 5.15-5.25 GHz the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or $+4 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed +4 dBm in any 1 megahertz band.

(a)(2) For the 5.25-5.35 GHz band the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or $+11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed +11 dBm in any 1 megahertz band.

Industry Canada RSS-Gen 4.4

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

Traceability

Test Equipment Used
0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 34 of 167

6.1.1.2. Maximum Conducted Output Power

Conducted Test Conditions for Maximum Conducted Output Power			
Standard:	FCC CFR 47:15.407	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Maximum Conducted Output Power	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.407 (a)	Pressure (mBars):	999 - 1001
Reference Document(s):	KDB 789033 - D01 DTS General UNII Test Procedures v01		

Test Procedure for Maximum Conducted Output Power Measurement

Method PM (Measurement using an RF average power meter). Section C) 4) of KDB 789033 defines a methodology using an average wideband power meter. Measurements were made while the EUT was operating in a continuous transmission mode (100% duty cycle) at the appropriate center frequency. All cable losses and offsets were taken into consideration in the measured result. All operational modes and frequency bands were measured independently and the resultant \square calculated. For multiple outputs, the measurements were made simultaneously on each output port and summed in a linear fashion. This technique was used in order to prove compliance.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 35 of 167

Antenna Beam and Non-Beam Forming Power Levels

15. 407 (a)(1), (a) (2) Operation with directional antenna gains greater than 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. Further FCC KDB 662911 D01 Multiple Transmitter Output v01 requires that the gain of antennas transmitting the same data (legacy 802.11a mode) must be increased by $10 * \log (N)$ when N is the number of antenna elements.

Operating Frequency Band 5150-5250 MHz

5150 – 5250 MHz Uncorrelated Operation (MIMO)

Antenna	Gain	Max. Allowable Conducted Peak Power (dBm)		Maximum EIRP
(dB)	(dBi)	Uncorrelated	Max. Power Per Chain	(dBm)
Integral	6.0	+17.00	+12.23	+23.0

5150 – 5250 MHz Correlated Operation (Non-MIMO i.e. Legacy)

Antenna	Gain dBi	Antenna Gain Increase V's No. Antenna Ports		Total Gain	Max. Allowable Conducted Peak Power	Maximum EIRP
(dB)		Ports	dB	dBi	Σ (dBm)	(dBm)
Integral	6.0	3	4.77	10.77	+12.23	+23.0

The APIN0224 and APIN0225 does not implement beam-forming

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Maximum Transmit (Conducted) Power, FCC Limits and Industry Canada Limits

Bands 5150 – 5250 MHz

FCC Limits

Conducted Power Limit lesser of: 50 mW or $4 \text{ dBm} + 10 \log (B) \text{ dBm}$. B is the 26 dB emission bandwidth in MHz.

Mode	Frequency Range (MHz)	Minimum 26 dB Bandwidth (MHz)	4 + 10 Log (B) (dBm)	Limit (dBm)
a	5150 – 5250	20.441	+17.11	+17.00
HT-20		20.441	+17.11	+17.00
HT-40		39.679	+19.99	+17.00
ac-40		41.082	+20.14	+17.00
ac-80		90.581	+23.57	+17.00

Industry Canada Limits

EIRP Limit 5150 – 5250 MHz: Lesser of 200 mW (+23 dBm) or $10 + 10 \log (B) \text{ dBm}$. B is the 99% emission bandwidth in MHz.

Mode	Frequency Range (MHz)	Minimum 99 % Bandwidth (MHz)	4 + 10 Log (B) (dBm)	Limit (dBm)
a	5150 – 5250	17.735	+16.49	+16.18
HT-20		17.735	+16.49	+16.49
HT-40		36.273	+19.60	+17.00
ac-40		36.673	+19.64	+17.00
ac-80		76.563	+22.84	+17.00

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 37 of 167

APIN0224 and APIN0225 EUT Maximum Power Settings

Operational Mode Maximum Power Settings provided by the client

Operational Mode	Power Setting
802.11 a	18.0
802.11 n HT-20	18.0
802.11 n HT-40	14.0
802.11 ac-40	14.0
802.11 ac-80	12.0

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 38 of 167

Equipment Configuration for Peak Transmit Power

Variant:	802.11a	Duty Cycle (%):	99%
Data Rate:	6 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	Σ Port(s) dBm	MHz	dBm	dBm	
5180.0	11.69	12.78	11.94	--	16.93	20.541	17.00	-0.07	12.50
5200.0	11.76	12.63	11.87	--	16.88	20.441	17.00	-0.12	12.50
5240.0	11.56	12.41	11.75	--	16.69	20.441	17.00	-0.31	12.50

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 39 of 167

Equipment Configuration for Peak Transmit Power

Variant:	802.11n HT-20	Duty Cycle (%):	99%
Data Rate:	6.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	Σ Port(s) dBm	MHz	dBm	dBm	
5180.0	11.57	12.83	11.93	--	16.91	20.441	17.00	-0.09	12.50
5200.0	11.63	12.91	11.87	--	16.94	20.441	17.00	-0.06	12.50
5240.0	11.55	12.83	11.78	--	16.86	20.441	17.00	-0.14	12.50

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 40 of 167

Equipment Configuration for Peak Transmit Power

Variant:	802.11n HT-40	Duty Cycle (%):	99%
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	Σ Port(s) dBm	MHz	dBm	dBm	
5190.0	10.84	11.91	11.17	--	16.10	39.078	17.00	-0.90	11.50
5230.0	10.63	11.94	11.33	--	16.10	39.078	17.00	-0.90	11.50

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 41 of 167

Equipment Configuration for Peak Transmit Power

Variant:	802.11ac-40	Duty Cycle (%):	99%
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	Σ Port(s) dBm	MHz	dBm	dBm	
5190.0	10.79	12.00	11.44	--	16.21	39.078	17.00	-0.79	11.50
5230.0	10.63	11.94	11.33	--	16.10	39.078	17.00	-0.90	11.50

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 42 of 167

Equipment Configuration for Peak Transmit Power

Variant:	802.11ac-80	Duty Cycle (%):	99%
Data Rate:	29.3 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	Σ Port(s) dBm	MHz	dBm	dBm	
5210.0	11.14	12.32	11.93	--	16.60	80.561	17.00	-0.40	12.00

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 43 of 167

Measurement Results for Maximum Conducted Output Power

Specification Limits

FCC, Part 15 §15.407 (a)(1), (a)(2) and Industry Canada RSS-210 § A9.2(2)

(a)(1) For the band 5.15-5.25 GHz the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or $+4 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed +4 dBm in any 1 megahertz band.

(a)(2) For the 5.25-5.35 and 5470-5725 MHz GHz band the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or $+11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed +11 dBm in any 1 megahertz band.

Industry Canada RSS-210 §A9.2(2)

For the band 5150-5250 MHz, the maximum equivalent isotropically radiated power (e.i.r.p.) shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

For the band 5250-5350 MHz and 5470-5725 MHz, the maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever power is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band. The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.

Traceability

Test Equipment Used
0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 44 of 167

6.1.1.3. Peak Power Spectral Density

Conducted Test Conditions for Power Spectral Density			
Standard:	FCC CFR 47:15.407	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Power Spectral Density	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (a)	Pressure (mBars):	999 - 1001
Reference Document(s):	KDB 789033 - D01 DTS General UNII Test Procedures v01		

Test Procedure for Power Spectral Density

The In-Band power spectral density was measured using the measure and sum approach per FCC KDB 662911 (D01 Multiple Transmitter Output v01.)

Measure and sum the spectra across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The individual spectra are then summed mathematically in linear power units. Unlike in-band power measurements, in which the sum involves a single measured value (output power) from each output, measurements for compliance with PSD limits involve summing entire spectra across corresponding frequency bins on the various outputs. Consistency is maintained for any device with N transmitter outputs to be certain the individual outputs are all aligned with the same span and same number of points. In this instance, the linear power spectrum value within the first spectral bin of output 0 is summed with that in the first spectral bin of output 1, and the first spectral bin of output 2, and so on up to the Nth output to obtain the true value for the first frequency bin of the summed spectrum. The summed spectrum value for each frequency bin is computed in this fashion. These summed spectral values were calculated on a computer, and the results read back into the spectrum analyzer as a data file to produce a representative plot of total spectral power density.

Calculated Power = $A + 10 \log (1/x)$ dBm

A = Total Power Spectral Density $[10 \log_{10} (10a/10 + 10b/10 + 10c/10 + 10d/10)]$

x = Duty Cycle

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 45 of 167

Equipment Configuration for Peak Power Spectral Density

Variant:	802.11a	Duty Cycle (%):	99%
Data Rate:	6 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density (dBm)		Limit	Margin
	Port(s)							
MHz	a	b	c	d	S Port(s)	Conversion to 3 kHz RBW	dBm	dB
5180.0	-5.291	-4.396	-5.329	--	-0.212	N/A	≤ 4.00	-4.21
5200.0	-5.251	-4.969	-5.348	--	-0.415	N/A	≤ 4.00	-4.42
5240.0	-5.023	-4.502	-5.563	--	-0.237	N/A	≤ 4.00	-4.24

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 46 of 167

Equipment Configuration for Peak Power Spectral Density

Variant:	802.11n HT-20	Duty Cycle (%):	99%
Data Rate:	6.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density (dBm)		Limit	Margin
	Port(s)							
MHz	a	b	c	d	S Port(s)	Conversion to 3 kHz RBW	dBm	dB
5180.0	-5.139	-4.323	-5.259	--	-0.115	N/A	≤ 4.00	-4.12
5200.0	-5.650	-4.656	-5.384	--	-0.438	N/A	≤ 4.00	-4.44
5240.0	-5.234	-3.764	-5.478	--	0.014	N/A	≤ 4.00	-3.99

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 47 of 167

Equipment Configuration for Peak Power Spectral Density

Variant:	802.11n HT-40	Duty Cycle (%):	99%
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density (dBm)		Limit	Margin
	Port(s)							
MHz	a	b	c	d	S Port(s)	Conversion to 3 kHz RBW	dBm	dB
5190.0	-5.049	-3.624	-3.891	--	0.626	N/A	≤ 4.00	-3.37

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 48 of 167

Equipment Configuration for Peak Power Spectral Density

Variant:	802.11ac-40	Duty Cycle (%):	99%
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density (dBm)	Limit	Margin
	Port(s)						
MHz	a	b	c	d	Σ Port(s)	dBm	dB
5190.0	-2.903	-1.740	-2.266	--	2.494	≤ 4.00	-1.51
5230.0	-3.039	-2.122	-2.702	--	2.167	≤ 4.00	-1.83

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 49 of 167

Equipment Configuration for Peak Power Spectral Density

Variant:	802.11ac-80	Duty Cycle (%):	99%
Data Rate:	29.3 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density (dBm)	Limit	Margin
	Port(s)						
MHz	a	b	c	d	Σ Port(s)	dBm	dB
5210.0	-5.651	-4.797	-5.095	--	-0.396	≤ 4.00	-4.40

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 50 of 167

Specification

FCC, Part 15 §15.407 (a)(1), (a)(2)

5150 – 5250 MHz

(a)(1) The peak power spectral density shall not exceed +4 dBm in any 1 megahertz band.

5250 – 5350 MHz & 5470 – 5725 MHz

(a)(2) The peak power spectral density shall not exceed +11 dBm in any 1 megahertz band.

Industry Canada RSS-210 § A9.2(1), A9.2(2)

5150 – 5250 MHz

§ A9.2(1) The eirp spectral density shall not exceed +10 dBm in any 1 MHz band

5250 – 5350 MHz & 5470 – 5725 MHz

§ A9.2(2) The power spectral density shall not exceed +11 dBm in any 1 MHz band

Traceability

Test Equipment Used
0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 51 of 167

6.1.1.4. Peak Excursion Ratio

Conducted Test Conditions for Peak Excursion Ratio			
Standard:	FCC CFR 47:15.407	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Peak Excursion Ratio	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.407 (a)(6)	Pressure (mBars):	999 - 1001
Reference Document(s):	KDB 789033 - D01 DTS General UNII Test Procedures v01		

Test Procedure for Peak Excursion Ratio

Compliance with the peak excursion requirement is demonstrated by confirming the ratio of the maximum of the peak-hold spectrum to the maximum of the average spectrum during continuous transmission. Section F) of KDB 789033 was used in order to prove compliance. This is a conducted measurement using a spectrum analyzer using dual traces. Peak Excursion Ratio is the difference in amplitude (dB) between both traces; The following identifies two spectrum traces on the same plot. Trace 1 is the max hold Peak detector, and Trace 2 is the recalled trace data from Peak Power Spectral Density measurements. Each frequency and operational mode is recalled in order to prove compliance.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 52 of 167

Equipment Configuration for Peak Excursion Ratio

Variant:	802.11a	Duty Cycle (%):	100
Data Rate:	6 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Peak Excursion (dB)				Ratio (dB)		Limit	Lowest Margin
	Port(s)							
MHz	a	b	c	d	Highest	Lowest	dB	MHz
5180.0	9.73	--	--	--	9.73	9.73	13.0	-3.27

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB
Equipment Configuration for Peak Excursion Ratio	

Variant:	802.11n HT-20	Duty Cycle (%):	100
Data Rate:	6.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Peak Excursion (dB)				Ratio (dB)		Limit	Lowest Margin
	Port(s)							
MHz	a	b	c	d	Highest	Lowest	dB	MHz
5180.0	10.64				10.64	10.64	13.0	-2.36

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 53 of 167

Equipment Configuration for Peak Excursion Ratio

Variant:	802.11n HT-40	Duty Cycle (%):	100
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Peak Excursion (dB)				Ratio (dB)		Limit	Lowest Margin
	Port(s)							
MHz	a	b	c	d	Highest	Lowest	dB	MHz
5190.0	9.29				9.29	9.29	13.0	-3.71

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Equipment Configuration for Peak Excursion Ratio

Variant:	802.11ac-40	Duty Cycle (%):	100
Data Rate:	13.5 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Peak Excursion (dB)				Ratio (dB)		Limit	Lowest Margin
	Port(s)							
MHz	a	b	c	d	Highest	Lowest	dB	MHz
5190.0	10.10				10.10	10.10	13.0	-2.90

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 54 of 167

Equipment Configuration for Peak Excursion Ratio

Variant:	802.11ac-80	Duty Cycle (%):	100
Data Rate:	29.3 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	OFDM	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable		
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Peak Excursion (dB)				Ratio (dB)		Limit	Lowest Margin
	Port(s)							
MHz	a	b	c	d	Highest	Lowest	dB	MHz
5210.0	7.07				7.07	7.07	13.0	-5.93

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 55 of 167

Specification

Limits

§15.407 (a)(6) The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the peak transmit power (measured as specified in this paragraph) shall not exceed 13dB across any 1MHz bandwidth or the emission bandwidth whichever is less

Traceability

Test Equipment Used

0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.1.5. Frequency Stability

FCC, Part 15 Subpart C §15.407(g)
Industry Canada RSS-210 §2.1

Test Procedure

The manufacturer of the equipment is responsible for ensuring that the frequency stability is such that emissions are always maintained within the band of operation under all conditions.

Manufacturer Declaration

The frequency stability of the reference oscillator sets the frequency stability of the RF transceiver signals. Therefore all of the RF signals should have ± 20 ppm stability.

This stability accounts for room temp tolerance of the crystal oscillator circuit, frequency variation across temperature, and crystal ageing.

± 20 ppm at 5.250 GHz translates to a maximum frequency shift of ± 105 KHz. As the edge of the channels is at least one MHz from either of the band edges, ± 105 KHz is more than sufficient to guarantee that the intentional emission will remain in the band over the entire operating range of the EUT.

Specification

Limits

§15.407 (g) Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2. Radiated Emission Testing

FCC, Part 15 Subpart C §15.407(b)(2), §15.205(a)/15.209(a)
Industry Canada RSS-210 §A9.3(2); §2.2; §2.6; RSS-Gen §4.7

Test Procedure

Testing was performed in a 3-meter anechoic chamber. Preliminary radiated emissions were measured on every azimuth and with the receiving antenna in both horizontal and vertical polarizations. Preliminary emissions were recorded with in Spectrum Analyzer mode, using a maximum peak detector while in peak hold mode. Depending on the frequency band spanned a notch filter and/or waveguide filter was used to remove the fundamental frequency.

Emissions nearest the limits were chosen for maximization and formal measurement using a CISPR compliant receiver. Emissions above 1000 MHz are measured utilizing a CISPR compliant average detector with a tuned receiver, using a bandwidth of 1 MHz. Emissions from 30 MHz – 1000 MHz are measured utilizing a CISPR compliant quasi-peak detector with a tuned receiver, using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$\mathbf{FS = R + AF + CORR - FO}$$

FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

$$\mathbf{CORR = Correction\ Factor = CL - AG + NFL}$$

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

Field Strength Calculation Example:

Given receiver input reading of 51.5 dB μ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$\mathbf{FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3\ dB\mu V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:

$$\mathbf{Level\ (dB\mu V/m) = 20 * Log\ (level\ (\mu V/m))}$$

$$\mathbf{40\ dB\mu V/m = 100\ \mu V/m}$$

$$\mathbf{48\ dB\mu V/m = 250\ \mu V/m}$$

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 58 of 167

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength (dB μ V/m);

$$E = 1000000 \times \sqrt{30P} / 3 \text{ } \mu\text{V/m}$$

where P is the EIRP in Watts

Therefore: -27 dBm/MHz = 68.23 dB μ V/m

Note: The data in this Section identifies that the EUT is in compliance with the -27dBm/MHz EIRP limit (68.23 dB μ V/m) for out of band emissions. All out of band emissions are less than 68.23 dB μ V/m.

Operational Modes

Operational mode(s) tested for spurious emissions were the mode(s) which delivered maximum spectral density which was 802.11a.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Specification

Radiated Spurious Emissions

15.407 (b)(2). All emissions outside of the 5,150-5,350MHz band shall not exceed an EIRP of -27dBm/MHz.

FCC §15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

FCC §15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC §15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

RSS-210 §A9.3(2) For transmitters operating in the 5250-5350 MHz band, all emissions outside the 5150-5350 MHz band shall not exceed -27 dBm/MHz e.i.r.p. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band shall not exceed out of band emission limit of 27 dBm/MHz e.i.r.p. in the 5150-5250 MHz band in order to operate indoor/outdoor, or alternatively shall comply with the spectral power density for operation within the 5150-5250 MHz band and shall be labeled "for indoor use only".

RSS-Gen §4.7 The search for unwanted emissions shall be from the lowest frequency internally generated or used in the device (local oscillator, intermediate of carrier frequency), or from 30 MHz , whichever is the lowest frequency, to the 5th harmonic of the highest frequency generated without exceeding 40 GHz.

RSS-Gen §6 Receiver Spurious Emission Standard

If a radiated measurement is made, all spurious emissions shall comply with the limits of the following Table. The resolution bandwidth of the spectrum analyzer shall be 100 kHz for spurious emission measurements below 1.0 GHz and 1.0 MHz for measurements above 1.0 GHz



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 60 of 167

Table 1: FCC 15.209 Spurious Emissions Limits

Frequency (MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3


Traceability:

Test Equipment Used
0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.1. Integral Antenna – Spurious Emissions

Test Freq.	5180 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	34
Power Setting	12.5	Press. (mBars)	1009
Antenna	Integral	Duty Cycle (%)	100
Test Notes 1	EUT Position Horizontal; BE emissions were higher when the EUT was in Hozi position vs Vert;		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5156.313	62.6	4.6	-9.9	57.2	Peak [Scan]	H						FUND
6893.78758	56.0	5.3	-6.5	54.8	Peak [Scan]	V						NRB
14865.731	47.0	8.2	-2.5	52.6	Peak [Scan]	V						NRB
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


Test Freq.	5200 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	34
Power Setting	12.5	Press. (mBars)	1009
Antenna	Integral	Duty Cycle (%)	100
Test Notes 1	EUT Position Horizontal; BE emissions were higher when the EUT was in Hozi position vs Vert;		
Test Notes 2			



Formally measured emission peaks													
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments	
15912.228	45.2	8.9	-0.1	53.9	Peak Max	H	139	119	74	-20.1	Pass		
15912.228	30.5	8.9	-0.1	39.2	Average Max	H	139	119	54	-14.8	Pass		
5190.381	64.2	4.6	-9.9	58.9	Peak [Scan]	V						FUND	
6927.85571	53.3	5.4	-6.5	52.2	Peak [Scan]	V						NRB	
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205													

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5240 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	34
Power Setting	12.5	Press. (mBars)	1009
Antenna	Integral	Duty Cycle (%)	100
Test Notes 1	EUT Position Horizontal; BE emissions were higher when the EUT was in Hozi position vs Vert;		
Test Notes 2			




Formally measured emission peaks												
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5224.449	67.9	4.6	-9.8	62.7	Peak [Scan]	V						FUND
6995.99198	54.4	5.4	-6.4	53.4	Peak [Scan]	V						NRB
15206.413	45.4	8.2	-1.5	52.1	Peak [Scan]	H						NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.2. ANT-1B – Spurious Emissions


Test Freq.	5180 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-1B	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			



Formally measured emission peaks												
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5190.381	54.5	4.6	-9.9	49.2	Peak [Scan]	V	150					FUND
Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission											
	NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205											

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5200 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-1B	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5196.381	59.2	4.6	-9.9	53.9	Peak [Scan]	V	100					FUND
<hr/>												
Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission											
	NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205											

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5240 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-1B	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks												
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5224.449	63.0	4.6	-9.8	57.8	Peak [Scan]	V	100					FUND
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.3. ANT-13B – Spurious Emissions


Test Freq.	5180 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-13B	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			



Formally measured emission peaks												
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5190.381	54.5	4.6	-9.9	49.2	Peak [Scan]	H	150					FUND
Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission											
	NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205											

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5200 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-13B	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5196.381	59.2	4.6	-9.9	53.9	Peak [Scan]	H	100					FUND
<hr/>												
Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission											
	NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205											

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5240 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-13B	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks												
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5224.449	63.0	4.6	-9.8	57.8	Peak [Scan]	H	100					FUND
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.4. ANT-16 – Spurious Emissions


Test Freq.	5180 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-16	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			



Formally measured emission peaks													
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments	
5156.313	59.5	4.8	-9.9	54.3	Peak [Scan]	H	100					FUND	
6893.78758	52.8	5.6	-6.5	51.8	Peak [Scan]	H	100	0	54.0	-2.2	Pass	NRB	
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission													
NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205													

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5200 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-16	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5190.381	62.4	4.8	-9.9	57.3	Peak [Scan]	H	150					FUND
6927.85571	50.9	5.7	-6.5	50.1	Peak [Scan]	H	100	0	54.0	-3.9	Pass	NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission												
NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5240 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-16	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.5. ANT-18 – Spurious Emissions

Test Freq.	5180 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-18	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5156.313	63.4	4.6	-9.9	58.1	Peak [Scan]	H	150					FUND
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


Test Freq.	5200 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-18	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			



Formally measured emission peaks												
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5190.381	62.7	4.6	-9.9	57.5	Peak [Scan]	H	100					FUND
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission												
NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5240 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-18	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5224.449	62.6	4.6	-9.8	57.4	Peak [Scan]	H	150					FUND
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.6. ANT-19 – Spurious Emissions

Test Freq.	5180 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-19	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5156.313	57.5	4.6	-9.9	52.1	Peak [Scan]	V	100					FUND
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5200 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-19	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5190.381	62.6	4.6	-9.9	57.3	Peak [Scan]	V	100					FUND
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	5240 MHz	Engineer	SB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	34
Power Setting	12.5	Press. (mBars)	1003
Antenna	AP-ANT-19	Duty Cycle (%)	100
Test Notes 1	POE located outside the chamber with ferrite a clamp on cables.		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5224.449	64.2	4.6	-9.8	59.0	Peak [Scan]	V	100					FUND
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non-Restricted Band. Limit = 68.23 dBuV/m; RB = Restricted Band. Limits per 15.205												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.7. Integral Antenna - Radiated Band-Edge

Peak Limit 74.0 dB μ V, Peak Limit 54.0 dB μ V

5150 MHz			
Operational Mode	dB μ V		Power Setting
	Peak	Average	
a	56.08	45.15	12.5
n HT-20	56.38	45.08	12.5
n HT-40	54.53	42.21	11.5
ac-40	54.84	40.89	11.5
ac-80	58.13	42.76	12.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.8. ANT1B - Radiated Band-Edge

Peak Limit 74.0 dB μ V, Peak Limit 54.0 dB μ V

5150 MHz			
Operational Mode	dB μ V		Power Setting
	Peak	Average	
a	59.95	48.37	12.5
n HT-20	59.06	48.18	12.5
n HT-40	56.41	44.80	11.5
ac-40	56.11	43.19	11.5
ac-80	56.11	43.19	12.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 81 of 167

6.1.2.9. ANT13B - Radiated Band-Edge

Peak Limit 74.0 dB μ V, Peak Limit 54.0 dB μ V

5150 MHz			
Operational Mode	dB μ V		Power Setting
	Peak	Average	
a	55.48	43.92	12.5
n HT-20	55.36	44.07	12.5
n HT-40	51.91	40.78	11.5
ac-40	51.23	39.86	11.5
ac-80	57.22	42.11	12.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 82 of 167

6.1.2.10.ANT16 - Radiated Band-Edge

Peak Limit 74.0 dB μ V, Peak Limit 54.0 dB μ V

5150 MHz			
Operational Mode	dB μ V		Power Setting
	Peak	Average	
a	54.93	44.72	12.5
n HT-20	54.18	44.46	12.5
n HT-40	51.04	40.48	11.5
ac-40	51.12	39.28	11.5
ac-80	56.65	39.28	11.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.11.ANT18 - Radiated Band-Edge

Peak Limit 74.0 dB μ V, Peak Limit 54.0 dB μ V

5150 MHz			
Operational Mode	dB μ V		Power Setting
	Peak	Average	
a	55.48	43.92	12.5
n HT-20	55.36	44.07	12.5
n HT-40	51.91	40.78	11.5
ac-40	51.23	39.86	11.5
ac-80	57.22	42.11	12.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.12.ANT19 - Radiated Band-Edge

Peak Limit 74.0 dB μ V, Peak Limit 54.0 dB μ V

5150 MHz			
Operational Mode	dB μ V		Power Setting
	Peak	Average	
a	55.46	43.84	12.5
n HT-20	55.30	43.76	12.5
n HT-40	52.48	40.55	11.5
ac-40	51.97	39.46	11.5
ac-80	58.85	40.66	12.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.2.13. Digital Emissions (30M-1 GHz)

FCC, Part 15 Subpart C §15.205/ §15.209 Industry Canada RSS-210 §2.2

Test Procedure

Testing 30M-1 GHz was performed in a 3-meter anechoic chamber using a CISPR compliant receiver. Preliminary radiated emissions were measured on every azimuth and with the receiving antenna in both horizontal and vertical polarizations. To further maximize emissions the receive antenna was varied between 1 and 4 meters. The emissions are recorded with receiver in peak hold mode. Emissions closest to the limits are measured in the quasi-peak mode with the tuned receiver using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed. The anechoic chamber test set-up is identified in Section 6 Test Set-Up Photographs.

The EUT had two methods of powering on ac/dc converter and Power over Ethernet (POE). Both modes were tested for emissions below 1GHz.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. In this test facility, the Antenna Factor, Cable Loss, and Amplifier Gains are loaded into the Rohde & Schwarz Receiver and the corrected field strength can be read directly on the receiver.

$$FS = R + AF + CORR$$

where:

FS = Field Strength

R = Measured Receiver Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL – AG + NFL

CL = Cable Loss

AG = Amplifier Gain

For example:

Given a Receiver input reading of 51.5dB μ V; Antenna Factor of 8.5dB; Cable Loss of 1.3dB; Falloff Factor of 0dB, an Amplifier Gain of 26dB and Notch Filter Loss of 1dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3\text{dB}\mu\text{V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:


$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log (level (\mu V/m))}$$

$$40 \text{ dB}\mu\text{V/m} = 100\mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250\mu\text{V/m}$$

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	2437 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	19.5
Freq. Range	30 MHz - 1000 MHz	Rel. Hum. (%)	34
Power Setting	18	Press. (mBars)	1001
Antenna	Integral		
Test Notes 1	Eut: Position Horizontal; S/N:;C-84 Only		
Test Notes 2	PSU: POE (support equipment not in chamber ferrite clamp on cables)		




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
34.088	46.4	3.6	-13.0	37.0	Quasi Max	V	102	208	40	-3.0	Pass	
98.040	57.9	4.1	-21.8	40.1	Quasi Max	V	117	88	43.5	-3.4	Pass	
68.990	50.5	3.9	-23.2	31.2	Quasi Max	V	155	304	40	-8.8	Pass	
399.240	40.7	5.5	-14.8	31.4	Peak [Scan]	V	155	304	46	-14.6	Pass	
599.681	38.6	6.2	-11.6	33.2	Peak [Scan]	V	155	304	46	-12.8	Pass	
249.879	38.6	4.9	-19.0	24.5	Peak [Scan]	H	155	304	46	-21.5	Pass	
Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	2437 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	19.5
Freq. Range	30 MHz - 1000 MHz	Rel. Hum. (%)	34
Power Setting	18	Press. (mBars)	1001
Antenna	Integral		
Test Notes 1	Eut: Position Vertical; S/N:;C-84 Only		
Test Notes 2	PSU: POE (support equipment not in chamber ferrite clamp on cables)		




Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
34.092	45.5	3.6	-13.0	36.1	Quasi Max	V	117	116	40	-3.9	Pass	
98.125	58.9	4.1	-21.8	41.2	Quasi Max	V	109	360	43.5	-2.3	Pass	
154.412	42.0	4.4	-18.9	27.5	Peak [Scan]	H	108	360	43.5	-16.0	Pass	
249.466	44.5	4.9	-19.0	30.4	Peak [Scan]	H	108	360	46	-15.6	Pass	
399.553	37.1	5.5	-14.8	27.8	Peak [Scan]	V	108	360	46	-18.2	Pass	
278.716	33.2	5.0	-17.4	20.8	Peak [Scan]	H	108	360	46	-25.2	Pass	
Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	2437 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	19.5
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	34
Power Setting	18	Press. (mBars)	1001
Antenna	Integral		
Test Notes 1	Eut: Position Vertical; S/N:;C-84 Only		
Test Notes 2	PSU: AC/DC 110VAC		



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
46.005	49.9	3.7	-21.5	32.2	Peak [Scan]	V	98	360	40	-7.8	Pass	
399.570	37.9	5.5	-14.8	28.6	Peak [Scan]	V	98	360	46	-17.4	Pass	
598.905	35.7	6.2	-11.6	30.4	Peak [Scan]	V	98	360	46	-15.7	Pass	
148.825	40.2	4.4	-18.8	25.8	Peak [Scan]	V	98	360	43.5	-17.7	Pass	
97.415	48.5	4.1	-22.0	30.6	Peak [Scan]	V	98	360	43.5	-12.9	Pass	
250.089	42.6	4.9	-19.0	28.5	Peak [Scan]	H	98	360	46	-17.6	Pass	

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency

NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Freq.	2437 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	19.5
Freq. Range	30 MHz - 1000 MHz	Rel. Hum. (%)	34
Power Setting	18	Press. (mBars)	1001
Antenna	Integral		
Test Notes 1	Eut: Position Horizontal; S/N:;C-84 Only		
Test Notes 2	PSU: AC/DC 110VAC		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
48.456	49.3	3.7	-22.6	30.4	Quasi Max	V	113	143	40	-9.6	Pass	
97.569	49.1	4.1	-22.0	31.2	Peak [Scan]	V	98	360	43.5	-12.3	Pass	
599.443	40.9	6.2	-11.6	35.5	Peak [Scan]	V	98	360	46	-10.5	Pass	
148.825	38.9	4.4	-18.8	24.5	Peak [Scan]	V	98	360	43.5	-19.0	Pass	
249.652	43.9	4.9	-19.0	29.8	Peak [Scan]	H	98	360	46	-16.2	Pass	
399.147	40.9	5.5	-14.8	31.6	Peak [Scan]	H	98	360	46	-14.4	Pass	

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency

NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 90 of 167

Specification

Limits

§15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

§15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

§15.209 (a) and RSS-Gen §2.2 Limit Matrix

Frequency(MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.1.3. AC Wireline Conducted Emissions (150 kHz – 30 MHz)

FCC, Part 15 Subpart C §15.207
Industry Canada RSS-Gen §7.2.2

Test Procedure


The EUT is configured in accordance with ANSI C63.4. The conducted emissions are measured in a shielded room with a spectrum analyzer in peak hold in the first instance. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation. The highest emissions relative to the limit are listed.

Measurement Results for AC Wireline Conducted Emissions (150 kHz – 30 MHz)

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

Test Measurement Set up



Measurement set up for AC Wireline Conducted Emissions Test


Measurement Results for AC Wireline Conducted Emissions (150 kHz – 30 MHz)

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

ac/dc Adaptor

Test Freq.	N/A	Engineer	SB
Variant	AC Line Emissions	Temp (°C)	20
Freq. Range	0.150 MHz - 30 MHz	Rel. Hum.(%)	32
Power Setting	18	Press. (mBars)	1011
Antenna	Integral		
Test Notes 1	Eut: Position Horizontal; S/N:;C-84 Only		
Test Notes 2	PSU: AC/DC 110VAC		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line	Limit dBuV	Margin dB	Pass /Fail	Comments
0.174	46.4	9.9	0.1	56.4	Quasi Peak	Live	64.77	-8.4	Pass	
0.236	37.6	9.9	0.1	47.6	Quasi Peak	Live	62.24	-14.7	Pass	
0.489	27.4	9.9	0.1	37.4	Quasi Peak	Neutral	56.18	-18.8	Pass	
0.414	30.4	9.9	0.1	40.4	Quasi Peak	Neutral	57.57	-17.2	Pass	
0.291	29.9	9.9	0.1	39.9	Quasi Peak	Neutral	60.5	-20.6	Pass	
0.174	28.1	9.9	0.1	38.1	Average	Live	54.77	-16.7	Pass	
0.236	20.4	9.9	0.1	30.3	Average	Live	52.24	-21.9	Pass	
0.489	16.7	9.9	0.1	26.7	Average	Neutral	46.18	-19.5	Pass	
0.414	18.8	9.9	0.1	28.8	Average	Neutral	47.57	-18.8	Pass	
0.291	18.0	9.9	0.1	28.0	Average	Neutral	50.5	-22.5	Pass	
5.882	31.4	10.2	0.3	41.9	Peak [Scan]	Live	50	-8.1	Pass	

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Specification

Limit

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu\Omega$ line impedance stabilization network (LISN), see §15.207 (a) matrix below. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

RSS-Gen §7.2.2

The radio frequency voltage that is conducted back into the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in the table below. The tighter limit applies at the frequency range boundaries.

§15.207 (a) and RSS-Gen §7.2.2 Limit Matrix

The lower limit applies at the boundary between frequency ranges

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency

Laboratory Measurement Uncertainty for Conducted Emissions

Measurement uncertainty	± 2.64 dB
-------------------------	---------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-EMC-01 'Measurement of Conducted Emissions'	0158, 0184, 0287, 0190, 0293, 0307

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 94 of 167

Measurement Uncertainty Time/Power

Measurement uncertainty	
- Time	4%
- Power	1.33dB

Traceability


Test Equipment Used

0072, 0083, 0098, 0116, 0132, 0158, 0313, 0314, 0193, 0223, 0252, 0253, 0251, 0256, 0328, 0329

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

7. PHOTOGRAPHS

7.1. Test Setup - Conducted




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

7.2. Test Setup - Digital Emissions < 1 GHz



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

7.3. Radiated Emissions Test Setup >1 GHz



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 98 of 167

8. TEST EQUIPMENT DETAILS

Asset #	Instrument	Manufacturer	Part #	Serial #	Calibration Due Date
0070	Power Meter	Hewlett Packard	437B	3125U11552	28 th Nov 13
0117	Power Sensor	Hewlett Packard	8487D	3318A00371	15 th Nov 13
0223	Power Meter	Hewlett Packard	EPM-442A	US37480256	15 th Nov 13
0374	Power Sensor	Hewlett Packard	8485A	3318A19694	29 th Nov 13
0158	Barometer /Thermometer	Control Co.	4196	E2846	8 th Dec 13
0193	EMI Receiver	Rhode & Schwartz	ESI 7	838496/007	2 nd Dec 13
0287	EMI Receiver	Rhode & Schwartz	ESIB40	100201	16 th Nov 13
0338	30 - 3000 MHz Antenna	Sunol	JB3	A052907	8 th Nov 13
0335	1-18 GHz Horn Antenna	EMCO	3117	00066580	7 th Nov 13
0252	SMA Cable	Megaphase	Sucoflex 104	None	N/A
0293	BNC Cable	Megaphase	1689 1GVT4	15F50B001	N/A
0307	BNC Cable	Megaphase	1689 1GVT4	15F50B002	N/A
0310	2m SMA Cable	Micro-Coax	UFA210A-0-0787-3G03G0	209089-001	N/A
0312	3m SMA Cable	Micro-Coax	UFA210A-1-1181-3G0300	209092-001	N/A
0314	30dB N-Type Attenuator	ARRA	N9444-30	1623	N/A
	EMC Test Software	EMISoft	Vasona	5.0051	N/A
	RF Conducted Test Software	National Instruments	Labview	Version 8.2	N/A
	RF Conducted Test Software	MiCOM Labs ATS		Version 1.5	N/A

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: APIN0224, APIN0225 802.11a/b/g/n/ac
To: FCC 47 CFR Part 15.407 & IC RSS-210
Serial #: ARUB145-U2 Rev A
Issue Date: 13th May 2013
Page: 99 of 167

APPENDIX

A. SUPPORTING INFORMATION

A.1. CONDUCTED TEST PLOTS


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

A.1.1. 26 dB & 99% Bandwidth



26 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5180.00 MHz, Chain a, Temp: Ambient, Voltage: Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5169.629 MHz : -25.016 dBm M2 : 5178.747 MHz : 2.298 dBm Delta1 : 20.641 MHz : 2.064 dB T1 : 5171.032 MHz : -3.869 dBm T2 : 5188.968 MHz : -3.946 dBm OBW : 17.936 MHz	Measured 26 dB Bandwidth: 20.641 MHz Measured 99% Bandwidth: 17.936 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.