



Title: Aruba Networks APIN0314, APIN0315
To: FCC Part 15.407, IC RSS-247(DFS Bands)
Serial #: ARUB204-U10_Radiated Rev A
Issue Date: 27th May 2016
Page: 152 of 294


APPENDIX A - GRAPHICAL IMAGES

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1. Radiated

A.1.1. Radiated TX Spurious Emissions

A.1.1.1. AP-ANT-13B



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5264.89	87.40	3.67	-11.27	79.80	Fundamental	Horizontal	101	0	--	--	
2	7013.26	54.59	4.18	-7.42	51.35	Peak (NRB)	Horizontal	101	71	--	--	Pass
3	10522.41	50.19	5.43	-4.20	51.42	Peak (NRB)	Horizontal	101	3	--	--	Pass


Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5305.70	79.22	3.79	-11.08	71.93	Fundamental	Horizontal	100	1	--	--	
2	7066.63	52.12	4.18	-7.34	48.96	Peak (NRB)	Horizontal	100	151	--	--	Pass
3	10600.56	40.86	5.58	-3.93	42.51	Max Avg	Horizontal	161	301	54.0	-11.5	Pass
4	10600.56	55.76	5.58	-3.93	57.41	Max Peak	Horizontal	161	301	74.0	-16.6	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-13B, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5326.05	78.22	3.73	-11.06	70.89	Fundamental	Horizontal	101	1	--	--	
2	7093.30	54.42	4.23	-7.33	51.32	Peak (NRB)	Horizontal	101	27	--	--	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-13B, Power Setting: 19, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5506.73	69.49	3.75	-11.18	62.06	Fundamental	Vertical	101	41	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5582.00	81.99	3.80	-11.20	74.59	Fundamental	Horizontal	101	1	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5723.68	68.91	3.79	-10.72	61.98	Fundamental	Horizontal	101	0	--	--	
2	11436.48	41.73	5.36	-4.92	42.17	Max Avg	Horizontal	151	339	54.0	-11.8	Pass
3	11436.48	56.12	5.36	-4.92	56.56	Max Peak	Horizontal	151	339	74.0	-17.4	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.1.2. AP-ANT-19



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-19, Power Setting: 21, Duty Cycle (%): 100




Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5258.72	91.27	3.65	-11.29	83.63	Fundamental	Vertical	151	1	--	--	
2	7013.26	58.56	4.18	-7.42	55.32	Peak (NRB)	Vertical	151	51	--	--	Pass
3	10525.14	52.95	5.43	-4.19	54.19	Peak (NRB)	Vertical	151	0	--	--	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)

RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-19, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5298.00	88.23	3.81	-11.10	80.94	Fundamental	Vertical	151	0	--	--	
2	7066.69	54.41	4.18	-7.34	51.25	Peak (NRB)	Vertical	151	0	--	--	Pass
3	10601.82	38.31	5.57	-3.93	39.95	Max Avg	Vertical	158	289	54.0	-14.1	Pass
4	10601.82	53.35	5.57	-3.93	54.99	Max Peak	Vertical	158	289	74.0	-19.0	Pass
5	13206.89	48.82	5.34	-6.39	47.77	Peak (NRB)	Horizontal	151	176	--	--	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-19, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB _u V	Cable Loss	AF dB	Level dB _u V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB _u V/m	Margin dB	Pass /Fail
1	5318.08	78.93	3.75	-11.07	71.61	Fundamental	Vertical	101	1	--	--	
2	7093.23	51.94	4.23	-7.33	48.84	Peak (NRB)	Vertical	101	1	--	--	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.1.3. AP-ANT-1W



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5255.43	83.31	3.64	-11.32	75.63	Fundamental	Horizontal	200	1	--	--	
2	7013.23	53.66	4.18	-7.42	50.42	Peak (NRB)	Horizontal	148	0	--	--	Pass
3	10525.98	49.20	5.42	-4.18	50.44	Peak (NRB)	Vertical	148	94	--	--	Pass


Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5296.00	83.47	3.79	-11.11	76.15	Fundamental	Horizontal	101	1	--	--	
2	7066.59	51.87	4.18	-7.34	48.71	Peak (NRB)	Horizontal	151	140	--	--	Pass
3	10600.52	38.15	5.58	-3.93	39.80	Max Avg	Vertical	191	2	54.0	-14.2	Pass
4	10600.52	53.01	5.58	-3.93	54.66	Max Peak	Vertical	191	2	74.0	-19.3	Pass

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-1W, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5316.83	79.60	3.76	-11.07	72.29	Fundamental	Horizontal	151	14	--	--	
2	7093.29	51.87	4.23	-7.33	48.77	Peak (NRB)	Horizontal	151	62	--	--	Pass

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5500.56	71.27	3.75	-11.17	63.85	Fundamental	Horizontal	200	7	--	--	
2	7333.26	47.12	4.28	-7.24	44.16	Max Avg	Horizontal	176	125	54.0	-9.8	Pass
3	7333.26	54.10	4.28	-7.24	51.14	Max Peak	Horizontal	176	125	74.0	-22.9	Pass

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5584.01	82.76	3.79	-11.19	75.36	Fundamental	Horizontal	101	1	--	--	

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5714.03	68.40	3.82	-10.76	61.46	Fundamental	Horizontal	101	38	--	--	

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.1.4. AP-ANT-20W



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5265.05	85.64	3.67	-11.27	78.04	Fundamental	Horizontal	151	1	--	--	
2	7013.34	55.13	4.18	-7.42	51.89	Peak (NRB)	Horizontal	151	1	--	--	Pass
3	10513.03	49.75	5.47	-4.24	50.98	Peak (NRB)	Vertical	151	158	--	--	Pass


Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5272.59	49.46	3.70	-11.23	41.93	Fundamental	Horizontal	151	31	--	--	
2	7066.70	51.94	4.18	-7.34	48.78	Peak (NRB)	Horizontal	151	31	--	--	Pass
3	10601.57	39.78	5.57	-3.93	41.42	Max Avg	Horizontal	156	298	54.0	-12.6	Pass
4	10601.57	54.07	5.57	-3.93	55.71	Max Peak	Horizontal	156	298	74.0	-18.3	Pass

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-20W, Power Setting: 17.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5315.31	76.50	3.76	-11.07	69.19	Fundamental	Horizontal	101	11	--	--	
2	7093.28	54.21	4.23	-7.33	51.11	Peak (NRB)	Horizontal	101	141	--	--	Pass

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5494.30	67.72	3.72	-11.17	60.27	Fundamental	Horizontal	101	1	--	--	

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5574.63	80.34	3.81	-11.21	72.94	Fundamental	Horizontal	101	1	--	--	
2	11156.76	36.26	5.98	-4.06	38.18	Max Avg	Horizontal	140	81	54.0	-15.8	Pass
3	11156.76	50.47	5.98	-4.06	52.39	Max Peak	Horizontal	140	81	74.0	-21.6	Pass


Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5716.31	66.21	3.81	-10.76	59.26	Fundamental	Horizontal	101	32	--	--	

Test Notes: EUT on 150cm table, powered by POE. Connected to laptop outside chamber.

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.1.5. AP-ANT-40



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5258.08	87.95	3.65	-11.30	80.30	Fundamental	Horizontal	200	23	--	--	
2	7013.29	55.26	4.18	-7.42	52.02	Peak (NRB)	Horizontal	200	23	--	--	Pass
3	10521.84	55.23	5.43	-4.20	56.46	Peak (NRB)	Horizontal	200	58	--	--	Pass


Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber.

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5293.11	81.09	3.77	-11.13	73.73	Fundamental	Horizontal	151	0	--	--	
2	7066.54	54.85	4.18	-7.34	51.69	Peak (NRB)	Horizontal	151	50	--	--	Pass
3	10607.42	38.95	5.55	-3.92	40.58	Max Avg	Horizontal	158	56	54.0	-13.4	Pass
4	10607.42	54.55	5.55	-3.92	56.18	Max Peak	Horizontal	158	56	74.0	-17.8	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-40, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5313.78	79.01	3.76	-11.07	71.70	Fundamental	Horizontal	151	29	--	--	
2	7093.32	52.73	4.23	-7.33	49.63	Peak (NRB)	Horizontal	151	29	--	--	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-40, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5503.92	73.38	3.75	-11.18	65.95	Fundamental	Horizontal	101	60	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5577.72	81.93	3.81	-11.20	74.54	Fundamental	Horizontal	101	65	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	3810.43	46.31	3.25	-10.85	38.71	Max Avg	Horizontal	165	63	54.0	-15.3	Pass
2	3810.43	60.77	3.25	-10.85	53.17	Max Peak	Horizontal	165	63	74.0	-20.8	Pass
3	5713.95	69.71	3.82	-10.76	62.77	Fundamental	Horizontal	101	69	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber.

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.1.6. AP-ANT-45



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5258.56	87.75	3.65	-11.29	80.11	Fundamental	Vertical	101	0	--	--	
2	7013.31	53.24	4.18	-7.42	50.00	Peak (NRB)	Vertical	151	0	--	--	Pass
3	10527.34	50.43	5.42	-4.18	51.67	Peak (NRB)	Vertical	151	0	--	--	Pass


Test Notes: Eut on 150cm table powered by POE. Connected to laptop outside chamber.

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5294.39	88.24	3.78	-11.12	80.90	Fundamental	Horizontal	101	1	--	--	
2	7066.63	52.36	4.18	-7.34	49.20	Peak (NRB)	Vertical	151	2	--	--	Pass
3	10600.52	41.87	5.58	-3.93	43.52	Max Avg	Horizontal	151	358	54.0	-10.5	Pass
4	10600.52	57.08	5.58	-3.93	58.73	Max Peak	Horizontal	151	358	74.0	-15.3	Pass


Test Notes: Eut on 150cm table powered by POE. Connected to laptop outside chamber.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-45, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5317.95	79.67	3.75	-11.07	72.35	Fundamental	Vertical	151	0	--	--	
2	7093.35	52.81	4.23	-7.33	49.71	Peak (NRB)	Horizontal	151	0	--	--	Pass


Test Notes: Eut on 150cm table powered by POE. Connected to laptop outside chamber.

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-45, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB _u V	Cable Loss	AF dB	Level dB _u V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB _u V/m	Margin dB	Pass /Fail
1	5497.43	70.47	3.73	-11.17	63.03	Fundamental	Vertical	151	1	--	--	

Test Notes: Eut on 150cm table powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5578.72	86.13	3.80	-11.20	78.73	Fundamental	Vertical	151	0	--	--	
2	11159.57	37.63	5.85	-4.07	39.41	Max Avg	Vertical	128	30	54.0	-14.6	Pass
3	11159.57	51.91	5.85	-4.07	53.69	Max Peak	Vertical	128	30	74.0	-20.3	Pass

Test Notes: Eut on 150cm table powered by POE. Connected to laptop outside chamber.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5714.27	70.97	3.82	-10.76	64.03	Fundamental	Horizontal	101	0	--	--	

Test Notes: Eut on 150cm table powered by POE. Connected to laptop outside chamber.

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.1.7. AP-ANT-48



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5254.31	92.33	3.64	-11.32	84.65	Fundamental	Vertical	151	1	--	--	
2	7013.22	56.54	4.18	-7.42	53.30	Peak (NRB)	Horizontal	151	1	--	--	Pass
3	10529.66	54.49	5.44	-4.16	55.77	Peak (NRB)	Vertical	151	21	--	--	Pass


Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5294.31	92.43	3.78	-11.12	85.09	Fundamental	Vertical	151	1	--	--	
2	7066.52	55.49	4.18	-7.34	52.33	Peak (NRB)	Vertical	151	21	--	--	Pass
3	10602.37	38.38	5.57	-3.93	40.02	Max Avg	Vertical	172	314	54.0	-14.0	Pass
4	10602.37	53.07	5.57	-3.93	54.71	Max Peak	Vertical	172	314	74.0	-19.3	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-48, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB _u V	Cable Loss	AF dB	Level dB _u V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB _u V/m	Margin dB	Pass /Fail
1	5314.10	79.81	3.76	-11.07	72.50	Fundamental	Vertical	151	0	--	--	
2	7093.40	53.54	4.23	-7.33	50.44	Peak (NRB)	Vertical	151	0	--	--	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-48, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5493.26	72.32	3.72	-11.18	64.86	Fundamental	Vertical	200	0	--	--	
2	7333.23	46.56	4.28	-7.24	43.60	Max Avg	Vertical	150	356	54.0	-10.4	Pass
3	7333.23	53.38	4.28	-7.24	50.42	Max Peak	Vertical	150	356	74.0	-23.6	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5584.89	84.12	3.79	-11.19	76.72	Fundamental	Horizontal	101	0	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	3813.71	48.44	3.24	-10.85	40.83	Max Avg	Horizontal	186	15	54.0	-13.2	Pass
2	3813.71	62.88	3.24	-10.85	55.27	Max Peak	Horizontal	186	15	74.0	-18.7	Pass
3	5721.16	71.45	3.80	-10.73	64.52	Fundamental	Vertical	101	0	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.1.8. Metal Sheet



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5254.87	85.38	3.64	-11.32	77.70	Fundamental	Horizontal	101	24	--	--	
2	7013.34	59.68	4.18	-7.42	56.44	Peak (NRB)	Horizontal	101	51	--	--	Pass
3	10524.05	55.03	5.43	-4.19	56.27	Peak (NRB)	Horizontal	101	51	--	--	Pass


Test Notes: EUT on 150cm table powered by POE, connected to laptop outside table.

[back to matrix](#)



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5303.61	85.94	3.80	-11.08	78.66	Fundamental	Horizontal	153	37	--	--	
2	7066.73	57.12	4.18	-7.34	53.96	Peak (NRB)	Horizontal	148	0	--	--	Pass
3	10603.88	45.77	5.56	-3.92	47.41	Max Avg	Horizontal	185	277	54.0	-6.6	Pass
4	10603.88	61.22	5.56	-3.92	62.86	Max Peak	Horizontal	185	277	74.0	-11.1	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: Metal Sheet, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5314.51	78.95	3.76	-11.07	71.64	Fundamental	Horizontal	101	19	--	--	
2	7093.34	59.06	4.23	-7.33	55.96	Peak (NRB)	Horizontal	101	68	--	--	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: Metal Sheet, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5493.66	72.60	3.72	-11.17	65.15	Fundamental	Horizontal	101	25	--	--	

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5574.55	82.78	3.81	-11.21	75.38	Fundamental	Horizontal	101	18	--	--	
2	11161.20	37.25	5.81	-4.07	38.99	Max Avg	Horizontal	150	307	54.0	-15.0	Pass
3	11161.20	51.28	5.81	-4.07	53.02	Max Peak	Horizontal	150	307	74.0	-21.0	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100




Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5725.13	69.89	3.79	-10.72	62.96	Fundamental	Horizontal	151	30	--	--	
2	11449.54	43.23	5.44	-4.92	43.75	Max Avg	Horizontal	169	55	54.0	-10.3	Pass
3	11449.54	57.61	5.44	-4.92	58.13	Max Peak	Horizontal	169	55	74.0	-15.9	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)

A.1.2. Restricted Band and Band-Edge Emissions

A.1.2.1. AP-ANT-13B



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5447.54	29.22	3.77	34.30	67.29	Max Peak	Horizontal	153	30	74.0	-6.7	Pass
2	5449.04	14.60	3.77	34.30	52.67	Max Avg	Horizontal	153	30	54.0	-1.3	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.79	27.72	3.479	34.32	65.83	Max Avg	Horizontal	153	30	68.2*	-2.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-13B, Power Setting: 13.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5457.35	33.44	3.80	34.30	71.54	Max Peak	Horizontal	153	30	74.0	-2.5	Pass
2	5458.90	14.79	3.79	34.31	52.89	Max Avg	Horizontal	153	30	54.0	-1.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.20	14.13	3.79	34.31	52.23	Max Avg	Horizontal	153	30	68.2*	-16.0	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-13B, Power Setting: 19, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5447.82	28.45	3.77	34.30	66.52	Max Peak	Horizontal	153	30	74.0	-7.5	Pass
2	5448.80	14.49	3.77	34.30	52.56	Max Avg	Horizontal	153	30	54.0	-1.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.24	27.70	3.79	34.32	65.81	Max Avg	Horizontal	153	30	68.2*	-2.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS
 Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-13B, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.18	12.80	3.79	34.31	50.90	Max Avg	Horizontal	153	30	54.0	-3.1	Pass
2	5459.98	28.27	3.79	34.31	66.37	Max Peak	Horizontal	153	30	74.0	-7.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.26	12.11	3.79	34.31	50.21	Max Avg	Horizontal	153	30	68.2*	-18.0	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-13B, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	14.00	3.70	34.51	52.21	Max Avg	Horizontal	171	317	54.0	-1.8	Pass
2	5350.00	30.72	3.70	34.51	68.93	Max Peak	Horizontal	171	317	74.0	-5.1	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-13B, Power Setting: 11.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
2	5358.44	35.28	3.71	34.49	73.48	Max Peak	Horizontal	171	317	74.0	-0.5	Pass
3	5359.34	14.56	3.71	34.49	52.76	Max Avg	Horizontal	171	317	54.0	-1.2	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-13B, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	12.64	3.70	34.51	50.85	Max Avg	Horizontal	171	317	54.0	-3.2	Pass
2	5350.00	29.88	3.70	34.51	68.09	Max Peak	Horizontal	171	317	74.0	-5.9	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-13B, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
2	5357.92	33.43	3.71	34.49	71.63	Max Peak	Horizontal	171	317	74.0	-2.4	Pass
3	5358.82	15.57	3.71	34.49	53.77	Max Avg	Horizontal	171	317	54.0	-0.2	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

80 + 80



RESTRICTED UPPER BAND-EDGE EMISSIONS
 Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-13B, Power Setting: 13.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5357.41	33.15	3.71	34.49	71.35	Max Peak	Horizontal	171	317	74.0	-2.7	Pass
3	5359.08	14.88	3.71	34.49	53.08	Max Avg	Horizontal	171	317	54.0	-0.9	Pass
4	5448.63	12.55	3.77	34.30	50.62	Max Avg	Horizontal	171	317	54.0	-3.4	Pass
5	5449.27	29.68	3.77	34.30	67.75	Max Peak	Horizontal	171	317	74.0	-5.3	Pass
6	5460.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
7	5468.84	13.79	3.79	34.32	51.90	Max Avg	Horizontal	153	30	68.2*	-16.3	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-13B, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5143.89	14.28	3.70	34.12	52.10	Max Avg	Vertical	200	357	54.0	-1.9	Pass
2	5143.89	29.86	3.70	34.12	67.68	Max Peak	Vertical	200	357	74.0	-6.3	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-13B, Power Setting: 14.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5457.86	32.11	3.80	34.30	70.21	Max Peak	Vertical	199	357	74.0	-3.8	Pass
2	5458.68	15.39	3.79	34.31	53.49	Max Avg	Vertical	199	357	54.0	-0.5	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.32	15.10	3.79	34.31	53.20	Max Avg	Horizontal	153	30	68.2*	-15.0	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-13B, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	5355.03	14.87	3.71	34.50	53.08	Max Avg	Vertical	200	357	54.0	-0.9	Pass
3	5356.07	31.83	3.71	34.50	70.04	Max Peak	Vertical	200	357	74.0	-4.0	Pass
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.2.2. AP-ANT-19



RESTRICTED LOWER BAND-EDGE EMISSIONS



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5456.93	14.68	3.80	34.30	52.78	Max Avg	Vertical	145	15	54.0	-1.2	Pass
2	5457.07	29.60	3.80	34.30	67.70	Max Peak	Vertical	145	15	74.0	-6.3	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.52	20.75	3.79	34.32	58.86	Max Avg	Horizontal	153	30	68.2*	-9.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5446.13	32.93	3.76	34.30	70.99	Max Peak	Vertical	145	15	74.0	-3.0	Pass
2	5446.55	14.50	3.76	34.30	52.56	Max Avg	Vertical	145	15	54.0	-1.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.43	16.05	3.79	34.32	54.16	Max Avg	Horizontal	153	30	68.2*	-14.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-19, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.51	29.37	3.80	34.30	67.47	Max Peak	Vertical	145	15	74.0	-6.5	Pass
2	5457.49	13.91	3.80	34.30	52.01	Max Avg	Vertical	145	15	54.0	-2.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	20.04	3.79	34.32	58.15	Max Avg	Horizontal	153	30	68.2*	-10.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS
 Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-19, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.04	30.62	3.79	34.31	68.72	Max Peak	Vertical	145	15	74.0	-5.3	Pass
2	5459.46	14.14	3.79	34.31	52.24	Max Avg	Vertical	145	15	54.0	-1.8	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.99	18.05	3.79	34.32	56.16	Max Avg	Horizontal	153	30	68.2*	-12.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-19, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	5350.36	30.10	3.70	34.51	68.31	Max Peak	Vertical	163	1	74.0	-5.7	Pass
3	5350.48	14.34	3.70	34.51	52.55	Max Avg	Vertical	163	1	54.0	-1.5	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--


Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber

[back to matrix](#)



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-19, Power Setting: 11, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	5361.30	35.68	3.70	34.48	73.86	Max Peak	Vertical	0	0	74.0	-0.1	Pass
3	5362.73	15.59	3.70	34.48	53.77	Max Avg	Vertical	0	0	54.0	-0.2	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-19, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	5350.36	29.86	3.70	34.51	68.07	Max Peak	Vertical	163	1	74.0	-5.9	Pass
3	5351.26	13.52	3.71	34.51	51.74	Max Avg	Vertical	163	1	54.0	-2.3	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-19, Power Setting: 15, Duty Cycle (%): 100




Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	5362.46	14.47	3.70	34.48	52.65	Max Avg	Vertical	163	1	54.0	-1.4	Pass
3	5362.61	30.88	3.70	34.48	69.06	Max Peak	Vertical	163	1	74.0	-4.9	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Num	Frequency MHz	Raw dBpV	Cable Loss	AF dB	Level dBpV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBpV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5362.40	15.50	3.70	34.48	53.68	Max Avg	Vertical	163	1	54.0	-0.3	Pass
3	5362.42	34.72	3.70	34.48	72.90	Max Peak	Vertical	163	1	74.0	-1.1	Pass
4	5453.45	14.50	3.76	34.30	48.13	Max Avg	Vertical	163	1	54.0	-5.9	Pass
5	5456.78	27.07	3.76	34.30	65.13	Max Peak	Vertical	163	1	74.0	-8.9	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5469.80	9.84	3.79	34.32	47.95	Max Avg	Horizontal	153	30	68.2*	-20.3	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB_uV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-19, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5135.47	15.62	3.69	34.12	53.43	Max Avg	Vertical	200	201	54.0	-0.6	Pass
2	5150.00	33.80	3.67	34.11	71.58	Max Peak	Vertical	200	201	74.0	-2.4	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-19, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5453.93	32.41	3.79	34.30	70.50	Max Peak	Vertical	141	201	74.0	-3.5	Pass
2	5454.89	14.25	3.79	34.30	52.34	Max Avg	Vertical	141	201	54.0	-1.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.93	12.79	3.79	34.32	50.90	Max Avg	Horizontal	153	30	68.2*	-17.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-19, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
2	5359.90	14.89	3.70	34.49	53.08	Max Avg	Vertical	200	201	54.0	-0.9	Pass
3	5360.42	31.85	3.70	34.49	70.04	Max Peak	Vertical	200	201	74.0	-4.0	Pass
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.2.3. AP-ANT-1W



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5452.55	24.54	3.79	34.30	62.63	Max Peak	Horizontal	175	46	74.0	-11.4	Pass
2	5459.12	10.56	3.79	34.31	48.66	Max Avg	Horizontal	175	46	54.0	-5.3	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.71	17.68	3.79	34.32	55.79	Max Avg	Horizontal	153	30	68.2*	-12.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-1W, Power Setting: 13.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5454.95	33.16	3.79	34.30	71.25	Max Peak	Horizontal	175	46	74.0	-2.8	Pass
2	5455.81	15.19	3.80	34.30	53.29	Max Avg	Horizontal	175	46	54.0	-0.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.96	15.09	3.79	34.32	53.20	Max Avg	Horizontal	153	30	68.2*	-15.0	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5458.04	10.89	3.80	34.30	48.99	Max Avg	Horizontal	175	46	54.0	-5.0	Pass
2	5458.96	26.20	3.79	34.31	64.30	Max Peak	Horizontal	175	46	74.0	-9.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5465.87	17.91	3.79	34.32	56.02	Max Avg	Horizontal	153	30	68.2*	-12.2	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-1W, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5455.65	15.09	3.80	34.30	53.19	Max Avg	Horizontal	175	46	54.0	-0.8	Pass
2	5456.65	30.81	3.80	34.30	68.91	Max Peak	Horizontal	175	46	74.0	-5.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.96	18.87	3.79	34.32	56.98	Max Avg	Horizontal	153	30	68.2*	-11.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-1W, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
2	5350.78	28.92	3.71	34.51	67.14	Max Peak	Horizontal	181	328	74.0	-6.9	Pass
3	5350.86	13.40	3.71	34.51	51.62	Max Avg	Horizontal	181	328	54.0	-2.4	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--


Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-1W, Power Setting: 13, Duty Cycle (%): 100




Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
2	5362.73	14.25	3.70	34.48	52.43	Max Avg	Horizontal	181	328	54.0	-1.6	Pass
3	5363.77	31.98	3.70	34.48	70.16	Max Peak	Horizontal	181	328	74.0	-3.8	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)

RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-1W, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
2	5350.84	13.28	3.71	34.51	51.50	Max Avg	Horizontal	181	328	54.0	-2.5	Pass
3	5352.61	28.43	3.71	34.50	66.64	Max Peak	Horizontal	181	328	74.0	-7.4	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--


Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber

[back to matrix](#)



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-1W, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	5362.10	15.00	3.70	34.48	53.18	Max Avg	Horizontal	181	328	54.0	-0.8	Pass
3	5362.61	30.98	3.70	34.48	69.16	Max Peak	Horizontal	181	328	74.0	-4.8	Pass
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-1W, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5356.73	32.38	3.71	34.49	70.58	Max Peak	Horizontal	180	328	74.0	-3.4	Pass
3	5359.94	14.89	3.70	34.49	53.08	Max Avg	Horizontal	180	328	54.0	-0.9	Pass
4	5456.97	26.62	3.79	34.30	64.71	Max Peak	Horizontal	180	328	74.0	-9.3	Pass
5	5459.86	8.66	3.80	34.30	46.76	Max Avg	Horizontal	180	328	54.0	-7.2	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5461.78	8.66	3.79	34.32	46.76	Max Avg	Horizontal	153	30	68.2*	-21.5	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-1W, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5150.00	15.76	3.67	34.11	53.54	Max Avg	Horizontal	158	319	54.0	-0.5	Pass
2	5150.00	33.29	3.67	34.11	71.07	Max Peak	Horizontal	158	319	74.0	-2.9	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-1W, Power Setting: 14.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5455.91	33.23	3.80	34.30	71.33	Max Peak	Horizontal	157	313	74.0	-2.7	Pass
2	5458.60	15.77	3.79	34.31	53.87	Max Avg	Horizontal	157	313	54.0	-0.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.64	15.39	3.79	34.32	53.50	Max Avg	Horizontal	153	30	68.2*	-14.7	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-1W, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5351.14	15.36	3.71	34.51	53.58	Max Avg	Horizontal	153	317	54.0	-0.4	Pass
3	5351.48	31.98	3.71	34.51	70.20	Max Peak	Horizontal	153	317	74.0	-3.8	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

A.1.2.4. AP-ANT-20W



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.51	28.27	3.80	34.30	66.37	Max Peak	Horizontal	152	16	74.0	-7.6	Pass
2	5457.49	13.18	3.80	34.30	51.28	Max Avg	Horizontal	152	16	54.0	-2.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	18.27	3.79	34.32	56.38	Max Avg	Horizontal	153	30	68.2*	-11.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-20W, Power Setting: 14.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.16	30.87	3.79	34.31	68.97	Max Peak	Horizontal	152	16	74.0	-5.0	Pass
2	5460.00	13.79	3.79	34.31	51.89	Max Avg	Horizontal	152	16	54.0	-2.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5467.56	16.04	3.79	34.32	54.15	Max Avg	Horizontal	153	30	68.2*	-14.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5457.78	12.11	3.80	34.30	50.21	Max Avg	Horizontal	152	16	54.0	-3.8	Pass
2	5458.20	26.32	3.80	34.30	64.42	Max Peak	Horizontal	152	16	74.0	-9.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	17.54	3.79	34.32	55.65	Max Avg	Horizontal	153	30	68.2*	-12.6	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS
 Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-20W, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5460.00	13.67	3.79	34.31	51.77	Max Avg	Horizontal	152	16	54.0	-2.2	Pass
2	5460.00	28.89	3.79	34.31	66.99	Max Peak	Horizontal	152	16	74.0	-7.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5467.56	18.81	3.79	34.32	56.92	Max Avg	Horizontal	153	30	68.2*	-11.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-20W, Power Setting: 17.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	15.37	3.70	34.51	53.58	Max Avg	Vertical	158	342	54.0	-0.4	Pass
2	5350.00	31.93	3.70	34.51	70.14	Max Peak	Vertical	158	342	74.0	-3.9	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-20W, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
2	5357.92	32.81	3.71	34.49	71.01	Max Peak	Vertical	158	342	74.0	-3.0	Pass
3	5358.30	14.98	3.71	34.49	53.18	Max Avg	Vertical	158	342	54.0	-0.8	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-20W, Power Setting: 17.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	15.08	3.70	34.51	53.29	Max Avg	Vertical	158	342	54.0	-0.7	Pass
2	5350.00	32.67	3.70	34.51	70.88	Max Peak	Vertical	158	342	74.0	-3.1	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-20W, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
2	5353.87	15.75	3.71	34.50	53.96	Max Avg	Vertical	158	342	54.0	0.0	Pass
3	5355.05	30.79	3.71	34.50	69.00	Max Peak	Vertical	158	342	74.0	-5.0	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-20W, Power Setting: 14.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5352.81	30.24	3.71	34.50	68.45	Max Peak	Vertical	158	342	74.0	-5.6	Pass
3	5357.60	14.01	3.71	34.49	52.21	Max Avg	Vertical	158	342	54.0	-1.8	Pass
4	5447.67	6.22	3.79	34.31	44.32	Max Avg	Horizontal	158	342	54.0	-9.7	Pass
5	5449.27	20.69	3.79	34.31	58.79	Max Peak	Horizontal	158	342	74.0	-15.2	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5468.20	7.28	3.79	34.32	45.39	Max Avg	Horizontal	153	30	68.2*	-22.8	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-20W, Power Setting: 15, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5453.65	31.72	3.79	34.30	69.81	Max Peak	Horizontal	154	313	74.0	-4.2	Pass
2	5455.47	14.47	3.79	34.30	52.56	Max Avg	Horizontal	154	313	54.0	-1.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.64	15.19	3.79	34.32	53.30	Max Avg	Horizontal	153	30	68.2*	-14.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-20W, Power Setting: 14.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5148.85	16.04	3.67	34.11	53.82	Max Avg	Horizontal	152	321	54.0	-0.2	Pass
2	5150.00	33.15	3.67	34.11	70.93	Max Peak	Horizontal	152	321	74.0	-3.1	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-20W, Power Setting: 14.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5364.75	15.42	3.69	34.47	53.58	Max Avg	Horizontal	143	-8	54.0	-0.4	Pass
3	5365.29	31.64	3.69	34.47	69.80	Max Peak	Horizontal	143	-8	74.0	-4.2	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.2.5. AP-ANT-40



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-40, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5460.00	15.20	3.79	34.31	53.30	Max Avg	Horizontal	148	24	54.0	-0.7	Pass
2	5460.00	28.20	3.79	34.31	66.30	Max Peak	Horizontal	148	24	74.0	-7.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	22.33	3.79	34.32	60.44	Max Avg	Horizontal	153	30	68.2*	-7.8	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-40, Power Setting: 13.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5451.18	32.31	3.78	34.30	70.39	Max Peak	Horizontal	148	24	74.0	-3.6	Pass
2	5452.16	15.01	3.78	34.30	53.09	Max Avg	Horizontal	148	24	54.0	-0.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	15.39	3.79	34.32	53.50	Max Avg	Horizontal	153	30	68.2*	-14.7	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS
 Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-40, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5460.00	14.47	3.79	34.31	52.57	Max Avg	Horizontal	148	24	54.0	-1.4	Pass
2	5460.00	27.53	3.79	34.31	65.63	Max Peak	Horizontal	148	24	74.0	-8.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	21.97	3.79	34.32	60.08	Max Avg	Horizontal	153	30	68.2*	-8.2	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-40, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5451.74	29.60	3.78	34.30	67.68	Max Peak	Horizontal	148	24	74.0	-6.3	Pass
2	5453.01	14.03	3.79	34.30	52.12	Max Avg	Horizontal	148	24	54.0	-1.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	19.62	3.79	34.32	57.73	Max Avg	Horizontal	153	30	68.2*	-10.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-40, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	14.00	3.70	34.51	52.21	Max Avg	Horizontal	157	321	54.0	-1.8	Pass
2	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
3	5350.02	29.85	3.71	34.51	68.07	Max Peak	Horizontal	157	321	74.0	-5.9	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-40, Power Setting: 13, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
2	5360.26	33.38	3.70	34.49	71.57	Max Peak	Horizontal	157	321	74.0	-2.4	Pass
3	5360.90	15.10	3.70	34.48	53.28	Max Avg	Horizontal	157	321	54.0	-0.7	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-40, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	12.91	3.70	34.51	51.12	Max Avg	Horizontal	157	321	54.0	-2.9	Pass
3	5350.10	30.52	3.70	34.51	68.73	Max Peak	Horizontal	157	321	74.0	-5.3	Pass
2	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-40, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5349.96	13.89	3.70	34.51	52.10	Max Avg	Horizontal	157	321	54.0	-1.9	Pass
2	5350.00	28.99	3.70	34.51	67.20	Max Peak	Horizontal	157	321	74.0	-6.8	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-40, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5362.73	15.30	3.70	34.48	53.48	Max Avg	Horizontal	157	321	54.0	-0.5	Pass
3	5364.99	31.63	3.69	34.47	69.79	Max Peak	Horizontal	157	321	74.0	-4.2	Pass
4	5446.39	26.86	3.70	34.51	65.07	Max Peak	Horizontal	157	321	74.0	-8.9	Pass
5	5446.71	9.91	3.70	34.51	48.12	Max Avg	Horizontal	157	321	54.0	-5.9	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5469.80	10.38	3.79	34.32	48.49	Max Avg	Horizontal	153	30	68.2*	-19.7	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-40, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5150.00	15.37	3.67	34.11	53.15	Max Avg	Horizontal	200	42	54.0	-0.9	Pass
2	5150.00	33.58	3.67	34.11	71.36	Max Peak	Horizontal	200	42	74.0	-2.6	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--


Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-40, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5355.39	14.77	3.71	34.50	52.98	Max Avg	Horizontal	200	42	54.0	-1.0	Pass
3	5355.57	32.23	3.71	34.50	70.44	Max Peak	Horizontal	200	42	74.0	-3.6	Pass


Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-40, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5460.00	15.20	3.79	34.31	53.30	Max Avg	Horizontal	141	41	54.0	-0.7	Pass
2	5460.00	31.70	3.79	34.31	69.80	Max Peak	Horizontal	141	41	74.0	-4.2	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5462.12	15.77	3.79	34.31	53.87	Max Avg	Horizontal	153	30	68.2*	-14.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.2.6. AP-ANT-45



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-45, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.51	29.33	3.80	34.30	67.43	Max Peak	Horizontal	163	22	74.0	-6.6	Pass
2	5457.49	15.29	3.80	34.30	53.39	Max Avg	Horizontal	163	22	54.0	-0.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	17.30	3.79	34.32	55.41	Max Avg	Horizontal	153	30	68.2*	-12.8	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-45, Power Setting: 13, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5448.10	32.92	3.77	34.30	70.99	Max Peak	Horizontal	163	22	74.0	-3.0	Pass
2	5448.80	14.04	3.77	34.30	52.11	Max Avg	Horizontal	163	22	54.0	-1.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.68	16.23	3.79	34.32	54.34	Max Avg	Horizontal	153	30	68.2*	-13.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-45, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5457.78	14.57	3.80	34.30	52.67	Max Avg	Horizontal	163	22	54.0	-1.3	Pass
2	5458.48	29.47	3.80	34.30	67.57	Max Peak	Horizontal	163	22	74.0	-6.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	16.57	3.79	34.32	54.68	Max Avg	Horizontal	153	30	68.2*	-13.6	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-45, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5448.24	14.16	3.77	34.30	52.23	Max Avg	Horizontal	163	22	54.0	-1.8	Pass
2	5448.66	30.49	3.77	34.30	68.56	Max Peak	Horizontal	163	22	74.0	-5.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.40	23.26	3.79	34.31	61.36	Max Avg	Horizontal	153	30	68.2*	-6.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-45, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	15.27	3.70	34.51	53.48	Max Avg	Horizontal	167	345	54.0	-0.5	Pass
2	5350.00	31.33	3.70	34.51	69.54	Max Peak	Horizontal	167	345	74.0	-4.5	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-45, Power Setting: 13, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
2	5350.22	15.37	3.70	34.51	53.58	Max Avg	Horizontal	167	345	54.0	-0.4	Pass
3	5350.62	31.75	3.71	34.51	69.97	Max Peak	Horizontal	167	345	74.0	-4.0	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-45, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	15.18	3.70	34.51	53.39	Max Avg	Horizontal	167	345	54.0	-0.6	Pass
2	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
3	5350.26	32.75	3.70	34.51	70.96	Max Peak	Horizontal	167	345	74.0	-3.0	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-45, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	13.53	3.70	34.51	51.74	Max Avg	Horizontal	167	345	54.0	-2.3	Pass
2	5350.00	30.64	3.70	34.51	68.85	Max Peak	Horizontal	167	345	74.0	-5.2	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-45, Power Setting: 13.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5350.24	29.99	3.70	34.51	68.20	Max Peak	Horizontal	167	345	74.0	-5.8	Pass
3	5350.32	13.65	3.70	34.51	51.86	Max Avg	Horizontal	167	345	54.0	-2.1	Pass
4	5444.14	26.90	3.77	34.30	64.97	Max Peak	Horizontal	163	22	74.0	-9.0	Pass
5	5446.71	9.49	3.77	34.30	47.56	Max Avg	Horizontal	163	22	54.0	-6.4	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5468.52	10.21	3.79	34.32	48.32	Max Avg	Horizontal	153	30	68.2*	-19.9	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-45, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5138.73	33.12	3.70	34.12	70.94	Max Peak	Horizontal	151	6	74.0	-3.1	Pass
2	5140.18	16.08	3.70	34.12	53.90	Max Avg	Horizontal	151	6	54.0	-0.1	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-45, Power Setting: 14, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5454.01	33.02	3.79	34.30	71.11	Max Peak	Horizontal	150	6	74.0	-2.9	Pass
2	5454.71	15.87	3.79	34.30	53.96	Max Avg	Horizontal	150	6	54.0	0.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.94	15.67	3.79	-34.32	53.78	Max Avg	Horizontal	153	30	68.2*	-14.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-45, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	5354.35	14.45	3.71	34.50	52.66	Max Avg	Horizontal	151	6	54.0	-1.3	Pass
3	5354.61	31.18	3.71	34.50	69.39	Max Peak	Horizontal	151	6	74.0	-4.6	Pass
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

A.1.2.7. AP-ANT-48



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-48, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.63	14.46	3.80	34.30	52.56	Max Avg	Horizontal	154	347	54.0	-1.4	Pass
2	5457.76	28.18	3.80	34.30	66.28	Max Peak	Horizontal	154	347	74.0	-7.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	27.31	3.79	34.32	65.42	Max Avg	Horizontal	153	30	68.2*	-2.8	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-48, Power Setting: 12, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.18	15.68	3.79	34.31	53.78	Max Avg	Horizontal	154	347	54.0	-0.2	Pass
2	5459.72	35.47	3.79	34.31	73.57	Max Peak	Horizontal	154	347	74.0	-0.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.26	15.09	3.79	34.31	53.19	Max Avg	Horizontal	153	30	68.2*	-15.0	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-48, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.93	14.47	3.80	34.30	52.57	Max Avg	Horizontal	154	347	54.0	-1.4	Pass
2	5457.92	28.99	3.80	34.30	67.09	Max Peak	Horizontal	154	347	74.0	-6.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	26.79	3.79	34.32	64.90	Max Avg	Horizontal	153	30	68.2*	-3.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-48, Power Setting: 15, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.60	33.37	3.79	34.31	71.47	Max Peak	Horizontal	154	347	74.0	-2.5	Pass
2	5459.74	15.49	3.79	34.31	53.59	Max Avg	Horizontal	154	347	54.0	-0.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.26	15.39	3.79	34.31	53.49	Max Avg	Horizontal	153	30	68.2*	-14.7	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-48, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	12.64	3.70	34.51	50.85	Max Avg	Horizontal	152	346	54.0	-3.2	Pass
2	5350.00	26.99	3.70	34.51	65.20	Max Peak	Horizontal	152	346	74.0	-8.8	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-48, Power Setting: 11.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
2	5360.90	15.40	3.70	34.48	53.58	Max Avg	Horizontal	152	346	54.0	-0.4	Pass
3	5361.30	35.79	3.70	34.48	73.97	Max Peak	Horizontal	152	346	74.0	0.0	Pass

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-48, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	14.45	3.70	34.51	52.66	Max Avg	Horizontal	152	346	54.0	-1.3	Pass
2	5350.00	31.99	3.70	34.51	70.20	Max Peak	Horizontal	152	346	74.0	-3.8	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-48, Power Setting: 15, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	15.18	3.70	34.51	53.39	Max Avg	Horizontal	152	346	54.0	-0.6	Pass
3	5350.26	32.51	3.70	34.51	70.72	Max Peak	Horizontal	152	346	74.0	-3.3	Pass
2	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE, connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-48, Power Setting: 12, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5359.50	33.37	3.71	34.49	71.57	Max Peak	Horizontal	147	346	74.0	-2.4	Pass
3	5361.76	14.48	3.70	34.48	52.66	Max Avg	Horizontal	147	346	54.0	-1.3	Pass
4	5458.58	29.60	3.79	34.31	67.70	Max Peak	Horizontal	154	347	74.0	-6.3	Pass
5	5459.86	11.21	3.79	34.31	49.31	Max Avg	Horizontal	154	347	54.0	-4.7	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5463.39	11.74	3.79	34.31	49.63	Max Avg	Horizontal	153	30	68.2*	-18.6	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-48, Power Setting: 12.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dB ^u V	Cable Loss	AF dB	Level dB ^u V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB ^u V/m	Margin dB	Pass /Fail
1	5141.58	16.08	3.70	34.12	53.90	Max Avg	Horizontal	182	-6	54.0	-0.1	Pass
2	5141.58	34.47	3.70	34.12	72.29	Max Peak	Horizontal	182	-6	74.0	-1.7	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-48, Power Setting: 12.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5352.87	31.89	3.71	34.50	70.10	Max Peak	Horizontal	182	-6	74.0	-3.9	Pass
3	5353.65	14.55	3.71	34.50	52.76	Max Avg	Horizontal	182	-6	54.0	-1.2	Pass


Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-48, Power Setting: 13, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5458.10	14.79	3.80	34.30	52.89	Max Avg	Horizontal	153	-7	54.0	-1.1	Pass
2	5458.14	34.18	3.80	34.30	72.28	Max Peak	Horizontal	153	-7	74.0	-1.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.02	14.36	3.79	34.31	52.46	Max Avg	Horizontal	153	30	68.2*	-15.8	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1.2.8. Metal Sheet



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: Metal Sheet, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.51	27.67	3.80	34.30	65.77	Max Peak	Vertical	179	45	74.0	-8.2	Pass
2	5458.34	14.13	3.80	34.30	52.23	Max Avg	Vertical	179	45	54.0	-1.8	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	14.99	3.79	34.32	53.10	Max Avg	Horizontal	153	30	68.2*	-15.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: Metal Sheet, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5447.96	15.70	3.77	34.30	53.77	Max Avg	Vertical	179	45	54.0	-0.2	Pass
2	5448.94	32.96	3.77	34.30	71.03	Max Peak	Vertical	179	45	74.0	-3.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.12	18.61	3.79	34.32	56.72	Max Avg	Horizontal	153	30	68.2*	-11.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: Metal Sheet, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5457.92	29.77	3.80	34.30	67.87	Max Peak	Vertical	179	45	74.0	-6.1	Pass
2	5458.06	14.89	3.80	34.30	52.99	Max Avg	Vertical	179	45	54.0	-1.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.79	13.90	3.79	34.32	52.01	Max Avg	Horizontal	153	30	68.2*	-16.2	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS
 Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: Metal Sheet, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5446.69	30.45	3.76	34.30	68.51	Max Peak	Vertical	179	45	74.0	-5.5	Pass
2	5448.52	15.12	3.77	34.30	53.19	Max Avg	Vertical	179	45	54.0	-0.8	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.40	25.44	3.79	34.32	63.55	Max Avg	Horizontal	153	30	68.2*	-4.7	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: Metal Sheet, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	14.87	3.70	34.51	53.08	Max Avg	Vertical	180	324	54.0	-0.9	Pass
2	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
3	5350.52	30.46	3.71	34.51	68.68	Max Peak	Vertical	180	324	74.0	-5.3	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: Metal Sheet, Power Setting: 11.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
2	5361.16	14.90	3.70	34.48	53.08	Max Avg	Vertical	180	324	54.0	-0.9	Pass
3	5361.56	34.70	3.70	34.48	72.88	Max Peak	Vertical	180	324	74.0	-1.1	Pass


Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS
 Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: Metal Sheet, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	14.55	3.70	34.51	52.76	Max Avg	Vertical	180	324	54.0	-1.2	Pass
2	5350.00	33.41	3.70	34.51	71.62	Max Peak	Vertical	180	324	74.0	-2.4	Pass
3	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--


Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS
 Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: Metal Sheet, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band-Edge	--	--	--	--	--	--
2	5351.52	13.88	3.71	34.51	52.10	Max Avg	Vertical	180	324	54.0	-1.9	Pass
3	5362.08	30.44	3.70	34.48	68.62	Max Peak	Vertical	180	324	74.0	-5.4	Pass

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: Metal Sheet, Power Setting: 13, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5355.99	14.45	3.71	34.50	52.66	Max Avg	Vertical	180	324	54.0	-1.3	Pass
3	5356.97	32.37	3.71	34.49	70.57	Max Peak	Vertical	180	324	74.0	-3.4	Pass
4	5447.68	13.82	3.77	34.30	50.89	Max Avg	Vertical	179	45	54.0	-3.1	Pass
5	5449.28	29.95	3.77	34.30	67.02	Max Peak	Vertical	179	45	74.0	-7.0	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5468.52	27.72	3.79	34.32	53.00	Max Avg	Horizontal	153	30	68.2*	-15.2	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by POE. Connected to Laptop outside chamber

*Note 68.2 dB μ V/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: Metal Sheet, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5138.68	14.60	3.70	34.12	52.42	Max Avg	Horizontal	152	63	54.0	-1.6	Pass
2	5147.39	32.26	3.68	34.11	70.05	Max Peak	Horizontal	152	63	74.0	-4.0	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: Metal Sheet, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
2	5359.52	14.99	3.70	34.49	53.18	Max Avg	Horizontal	152	63	54.0	-0.8	Pass
3	5361.12	34.13	3.70	34.48	72.31	Max Peak	Horizontal	152	63	74.0	-1.7	Pass
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--


Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: Metal Sheet, Power Setting: 13.5, Duty Cycle (%): 91



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5457.29	32.31	3.80	34.30	70.41	Max Peak	Horizontal	152	63	74.0	-3.6	Pass
2	5457.72	14.79	3.80	34.30	52.89	Max Avg	Horizontal	152	63	54.0	-1.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5461.22	14.57	3.79	34.31	52.67	Max Avg	Horizontal	153	30	68.2*	-15.6	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com