

RADIATED ADDENDUM TEST REPORT



Test of: Hewlett Packard Enterprise APINH303
to

To: FCC CFR 47 Part 15 Subpart E 15.407 (Non-DFS)

Test Report Serial No.: HWP85-U8 Radiated Rev A

This report supersedes: NONE

Issue Date:1st December 2016

Master Document Number	Addendum Reports
HWP85-U8_Master	HWP85-U8_Conducted
	HWP85-U8_Radiated
	HWP85-G4 (FCC Part 15B & ICES-003)



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 2 of 46

Table of Contents

1. TEST SUMMARY	3
2. MEASUREMENT AND PRESENTATION OF TEST DATA	4
3. TEST RESULTS	5
3.1. Radiated	5
3.1.1. <i>TX Spurious & Restricted Band Emissions</i>	8
3.1.2. <i>Restricted Edge & Band-Edge Emissions</i>	14
A. APPENDIX - GRAPHICAL IMAGES	27
A.1. Radiated	28
A.1.1. <i>TX Spurious & Restricted Band Emissions</i>	28
A.1.2. <i>Restricted Edge & Band-Edge Emissions</i>	34

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 3 of 46

1. TEST SUMMARY

List of Measurements

Test Header	Result	Data Link
Radiated	Complies	-
TX Spurious & Restricted Band Emissions	Complies	-
Aruba Metal sheet	Complies	View Data
Restricted Edge & Band-Edge Emissions	Complies	-
Aruba Metal sheet	Complies	View Data

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 4 of 46

2. MEASUREMENT AND PRESENTATION OF TEST DATA

The measurement and graphical data presented in this test report was generated automatically using state-of-the-art technology creating an easy to read report structure. Numerical measurement data is separated from supporting graphical data (plots) through hyperlinks. Numerical measurement data can be reviewed without scrolling through numerous graphical pages to arrive at the next data matrix.

Plots have been relegated into the Appendix 'Graphical Data'.

Test and report automation was performed by [MiTest](#). [MiTest](#) is an automated test system developed by MiCOM Labs. [MiTest](#) is the first cloud based modular test system enabling end-to-end automation of regulatory compliance testing.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 5 of 46

3. TEST RESULTS

3.1. Radiated

Radiated Test Conditions for Radiated Spurious and Band-Edge Emissions			
Standard:	FCC CFR 47:15.407	Ambient Temp. (°C):	20.0 - 24.5
Test Heading:	Radiated Spurious and Band-Edge Emissions	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.407 (b), 15.205, 15.209	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Radiated Spurious and Band-Edge Emissions

Radiated emissions for restricted bands above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned.

Measurements on any restricted band frequency or frequencies above 1 GHz are based on the use of measurement instrumentation employing peak and average detectors. All measurements were performed using a resolution bandwidth of 1 MHz.

Test configuration and setup for Undesirable Measurement were per the Radiated Test Set-up specified in this document.

15.407 (b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

(7) The provisions of §15.205 apply to intentional radiators operating under this section.

(8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

Limits for Restricted Bands (15.205, 15.209)

Peak emission: 74 dBuV/m

Average emission: 54 dBuV/m

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWPDP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 6 of 46

FS = R + AF + CORR - FO

where:

FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = **CL** – **AG** + **NFL**

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss

Example:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength (dBμV/m);

$$E = 1000000 \times \sqrt[3]{30P} \text{ } \mu\text{V/m}$$

where P is the EIRP in Watts

Therefore: -27 dBm/MHz equates to 68.23 dBuV/m

Conversion between dBmV/m (or dBmV) and mV/m (or mV) are as follows:

Level (dBmV/m) = 20 * Log (level (mV/m))

40 dBmV/m = 100 mV/m

48 dBmV/m = 250 mV/m

Restricted Bands of Operation (15.205)

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Frequency Band			
MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWPDP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 7 of 46

12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

(b) Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e) of this section, regardless of the field strength limits specified elsewhere in this subpart, the provisions of this section apply to emissions from any intentional radiator.

(d) The following devices are exempt from the requirements of this section:

(1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a) of this section, the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a) of this section, and the fundamental emission is outside of the bands listed in paragraph (a) of this section more than 99% of the time the device is actively transmitting, without compensation for duty cycle.

(2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.

(3) Cable locating equipment operated pursuant to §15.213.

(4) Any equipment operated under the provisions of §15.253, 15.255, and 15.256 in the frequency band 75-85 GHz, or §15.257 of this part.

(5) Biomedical telemetry devices operating under the provisions of §15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.

(6) Transmitters operating under the provisions of subparts D or F of this part.

(7) Devices operated pursuant to §15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.

(8) Devices operated in the 24.075-24.175 GHz band under §15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in §15.245(b).

(9) Devices operated in the 24.0-24.25 GHz band under §15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in §15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of §15.245 shall not exceed the limits specified in §15.245(b).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 8 of 46

3.1.1. TX Spurious & Restricted Band Emissions

Integral antenna

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5180.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5178.11	74.29	3.69	-11.51	66.47	Fundamental	Vertical	101	1	--	--	
#2	6906.58	60.69	4.11	-7.54	57.26	Peak (NRB)	Vertical	200	1	--	--	Pass
#3	10358.84	52.01	5.56	-5.27	52.30	Peak (NRB)	Vertical	200	30	--	--	Pass

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 9 of 46

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5200.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5203.09	78.56	3.65	-11.45	70.76	Fundamental	Vertical	101	1	--	--	
#2	6933.27	58.38	4.11	-7.49	55.00	Peak (NRB)	Vertical	200	1	--	--	Pass
#3	10404.53	52.81	5.44	-5.00	53.25	Peak (NRB)	Vertical	200	34	--	--	Pass

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 10 of 46

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5240.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	5238.44	81.06	3.63	-11.37	73.32	Fundamental	Vertical	101	0	--	--	
#2	6986.57	56.40	4.13	-7.45	53.08	Peak (NRB)	Vertical	200	0	--	--	Pass
#3	10480.60	50.78	5.41	-4.45	51.74	Peak (NRB)	Vertical	200	26	--	--	Pass

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 11 of 46

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5745.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	3830.01	65.03	3.21	-10.83	57.41	Max Peak	Vertical	155	7	74.0	-16.6	Pass
#2	3830.01	57.83	3.21	-10.83	50.21	Max Avg	Vertical	155	7	54.0	-3.8	Pass
#3	5739.32	58.63	3.82	-10.67	51.78	Fundamental	Vertical	101	53	--	--	
#4	7660.01	53.71	4.37	-6.95	51.13	Max Peak	Horizontal	172	314	74.0	-22.9	Pass
#5	7660.01	46.36	4.37	-6.95	43.78	Max Avg	Horizontal	172	314	54.0	-10.2	Pass

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 12 of 46

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5785.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	3856.63	64.52	3.23	-10.81	56.94	Max Peak	Vertical	144	4	74.0	-17.1	Pass
#2	3856.63	58.68	3.23	-10.81	51.10	Max Avg	Vertical	144	4	54.0	-2.9	Pass
#3	5788.70	60.41	3.79	-10.42	53.78	Fundamental	Vertical	101	1	--	--	

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 13 of 46

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5825.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	3883.31	64.65	3.25	-10.76	57.14	Max Peak	Vertical	140	4	74.0	-16.9	Pass
#2	3883.31	59.96	3.25	-10.76	52.45	Max Avg	Vertical	140	4	54.0	-1.6	Pass
#3	5829.50	67.60	3.84	-10.22	61.22	Fundamental	Vertical	101	1	--	--	

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 14 of 46

3.1.2. Restricted Edge & Band-Edge Emissions

RESULTS SUMMARY FOR RADIATED BAND-EDGE EMISSIONS

5150 - 5250 MHz

Aruba Metal sheet		Band-Edge Freq	Limit 74.0dBµV/m	Limit 54.0dBµV/m	Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dBµV/m	dBµV/m	
802.11a	5180.00	5150.00	72.35	53.25	16.5
802.11ac-80	5210.00	5150.00	67.68	52.95	12.5
802.11n HT-20	5180.00	5150.00	72.17	53.82	16
802.11n HT-40	5190.00	5150.00	69.50	53.72	13.5

5725 MHz Radiated Lower Band-Edge Emissions

Aruba Metal sheet		Band-Edge Freq			Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dBµV/m	dBµV/m	
802.11a	5745.00	5725.00	83.58	73.82	21
802.11ac-80	5775.00	5725.00	84.82	65.76	20.5
802.11n HT-20	5745.00	5725.00	85.26	64.05	21
802.11n HT-40	5755.00	5725.00	83.23	69.11	21

5850 MHz Radiated Higher Band-Edge Emissions

Aruba Metal sheet		Band-Edge Freq			Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dBµV/m	dBµV/m	
802.11a	5825.00	5850.00	75.30	66.84	21
802.11ac-80	5775.00	5850.00	82.71	65.34	21
802.11n HT-20	5825.00	5850.00	76.11	65.93	21
802.11n HT-40	5795.00	5850.00	69.75	62.84	21

Click on the links to view the data.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 15 of 46

Equipment Configuration for Restricted Lower Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5180.00	Data Rate:	6.00 MBit/s
Power Setting:	16.5	Tested By:	JMH

Test Measurement Results

4500.00 - 5200.00 MHz

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5148.10	34.56	3.68	34.11	72.35	Max Peak	Vertical	186	355	74.0	-1.7	Pass
#2	5149.50	15.47	3.67	34.11	53.25	Max Avg	Vertical	186	355	54.0	-0.8	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 16 of 46

Equipment Configuration for Restricted Lower Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11ac-80
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5210.00	Data Rate:	29.30 MBit/s
Power Setting:	12.5	Tested By:	JMH

Test Measurement Results

4500.00 - 5300.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5145.34	15.15	3.69	34.11	52.95	Max Avg	Vertical	186	355	54.0	-1.1	Pass
#2	5145.34	29.88	3.69	34.11	67.68	Max Peak	Vertical	186	355	74.0	-6.3	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--
Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 17 of 46

Equipment Configuration for Restricted Lower Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11n HT-20
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5180.00	Data Rate:	6.50 MBit/s
Power Setting:	16	Tested By:	JMH

Test Measurement Results

4500.00 - 5200.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5150.00	16.04	3.67	34.11	53.82	Max Avg	Vertical	186	355	54.0	-0.2	Pass
#2	5150.00	34.39	3.67	34.11	72.17	Max Peak	Vertical	186	355	74.0	-1.8	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--
Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 18 of 46

Equipment Configuration for Restricted Lower Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11n HT-40
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5190.00	Data Rate:	13.50 MBit/s
Power Setting:	13.5	Tested By:	JMH

Test Measurement Results

4500.00 - 5200.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5148.35	15.93	3.68	34.11	53.72	Max Avg	Vertical	186	355	54.0	-0.3	Pass
#2	5150.00	31.72	3.67	34.11	69.50	Max Peak	Vertical	186	355	74.0	-4.5	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--
Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 19 of 46

Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5745.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

5550.00 - 5755.00 MHz

Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	5719.93	35.67	3.80	34.35	73.82	Max Avg	Vertical	191	355	106.9	-33.1	Pass
#2	5725.00	45.44	3.79	34.35	83.58	Max Avg	Vertical	191	355	122.2	-38.6	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 20 of 46

Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11ac-80
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5775.00	Data Rate:	29.30 MBit/s
Power Setting:	20.5	Tested By:	JMH

Test Measurement Results

5550.00 - 5775.00 MHz

Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	5650.97	27.82	3.76	34.18	65.76	Max Avg	Vertical	191	355	68.9	-3.2	Pass
#2	5713.28	46.66	3.82	34.34	84.82	Max Avg	Vertical	191	355	108.8	-24.0	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limit.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 21 of 46

Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11n HT-20
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5745.00	Data Rate:	6.50 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

5550.00 - 5755.00 MHz

Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	5705.96	25.86	3.86	34.33	64.05	Max Avg	Vertical	191	355	106.9	-42.8	Pass
#2	5725.00	47.12	3.79	34.35	85.26	Max Avg	Vertical	191	355	122.2	-36.9	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 22 of 46

Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11n HT-40
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5755.00	Data Rate:	13.50 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

5550.00 - 5755.00 MHz

Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	5694.87	30.95	3.85	34.31	69.11	Max Avg	Vertical	191	355	101.5	-32.4	Pass
#2	5715.55	45.08	3.81	34.34	83.23	Max Avg	Vertical	191	355	109.7	-26.5	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 23 of 46

Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11a
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5825.00	Data Rate:	6.00 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

5800.00 - 6000.00 MHz

Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	5850.00	36.86	3.81	34.63	75.30	Max Avg	Vertical	194	353	122.2	-46.9	Pass
#3	5860.40	28.33	3.86	34.65	66.84	Max Avg	Vertical	194	353	109.4	-42.6	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 24 of 46

Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11ac-80
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5775.00	Data Rate:	29.30 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

5775.00 - 6000.00 MHz

Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#2	5854.06	44.24	3.83	34.64	82.71	Max Avg	Vertical	194	353	113.1	-30.4	Pass
#3	5917.26	26.68	3.86	34.80	65.34	Max Avg	Vertical	194	353	74.1	-8.8	Pass
#1	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 25 of 46

Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11n HT-20
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5825.00	Data Rate:	6.50 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

5800.00 - 6000.00 MHz

Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
#1	5850.00	37.67	3.81	34.63	76.11	Max Avg	Vertical	194	353	122.2	-46.1	Pass
#3	5863.61	27.43	3.84	34.66	65.93	Max Avg	Vertical	194	353	108.3	-42.4	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 26 of 46

Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions

Antenna:	Aruba Metal sheet	Variant:	802.11n HT-40
Antenna Gain (dBi):	5.00	Modulation:	OFDM
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	5795.00	Data Rate:	13.50 MBit/s
Power Setting:	21	Tested By:	JMH

Test Measurement Results

5795.00 - 6000.00 MHz

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#2	5853.29	31.30	3.82	34.63	69.75	Max Avg	Vertical	194	353	115.4	-45.6	Pass
#3	5876.43	24.33	3.81	34.70	62.84	Max Avg	Vertical	194	353	104.5	-41.6	Pass
#1	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 27 of 46

A. APPENDIX - GRAPHICAL IMAGES

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.


A.1. Radiated

A.1.1. TX Spurious & Restricted Band Emissions



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5180.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5178.11	74.29	3.69	-11.51	66.47	Fundamental	Vertical	101	1	--	--	
2	6906.58	60.69	4.11	-7.54	57.26	Peak (NRB)	Vertical	200	1	--	--	Pass
3	10358.84	52.01	5.56	-5.27	52.30	Peak (NRB)	Vertical	200	30	--	--	Pass

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 29 of 46



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5200.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5203.09	78.56	3.65	-11.45	70.76	Fundamental	Vertical	101	1	--	--	
2	6933.27	58.38	4.11	-7.49	55.00	Peak (NRB)	Vertical	200	1	--	--	Pass
3	10404.53	52.81	5.44	-5.00	53.25	Peak (NRB)	Vertical	200	34	--	--	Pass


Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5240.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5238.44	81.06	3.63	-11.37	73.32	Fundamental	Vertical	101	0	--	--	
2	6986.57	56.40	4.13	-7.45	53.08	Peak (NRB)	Vertical	200	0	--	--	Pass
3	10480.60	50.78	5.41	-4.45	51.74	Peak (NRB)	Vertical	200	26	--	--	Pass

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 31 of 46



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5745.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	3830.01	65.03	3.21	-10.83	57.41	Max Peak	Vertical	155	7	74.0	-16.6	Pass
2	3830.01	57.83	3.21	-10.83	50.21	Max Avg	Vertical	155	7	54.0	-3.8	Pass
3	5739.32	58.63	3.82	-10.67	51.78	Fundamental	Vertical	101	53	--	--	
4	7660.01	53.71	4.37	-6.95	51.13	Max Peak	Horizontal	172	314	74.0	-22.9	Pass
5	7660.01	46.36	4.37	-6.95	43.78	Max Avg	Horizontal	172	314	54.0	-10.2	Pass

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 32 of 46



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5785.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	3856.63	64.52	3.23	-10.81	56.94	Max Peak	Vertical	144	4	74.0	-17.1	Pass
2	3856.63	58.68	3.23	-10.81	51.10	Max Avg	Vertical	144	4	54.0	-2.9	Pass
3	5788.70	60.41	3.79	-10.42	53.78	Fundamental	Vertical	101	1	--	--	

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 33 of 46



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5825.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	3883.31	64.65	3.25	-10.76	57.14	Max Peak	Vertical	140	4	74.0	-16.9	Pass
2	3883.31	59.96	3.25	-10.76	52.45	Max Avg	Vertical	140	4	54.0	-1.6	Pass
3	5829.50	67.60	3.84	-10.22	61.22	Fundamental	Vertical	101	1	--	--	

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 34 of 46

A.1.2. Restricted Edge & Band-Edge Emissions



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5180.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 16.5, Duty Cycle (%): 99



4500.00 - 5200.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5148.10	34.56	3.68	34.11	72.35	Max Peak	Vertical	186	355	74.0	-1.7	Pass
2	5149.50	15.47	3.67	34.11	53.25	Max Avg	Vertical	186	355	54.0	-0.8	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 35 of 46



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5210.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 12.5, Duty Cycle (%): 99



4500.00 - 5300.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5145.34	15.15	3.69	34.11	52.95	Max Avg	Vertical	186	355	54.0	-1.1	Pass
2	5145.34	29.88	3.69	34.11	67.68	Max Peak	Vertical	186	355	74.0	-6.3	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--


Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5180.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 16, Duty Cycle (%): 99



4500.00 - 5200.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5150.00	16.04	3.67	34.11	53.82	Max Avg	Vertical	186	355	54.0	-0.2	Pass
2	5150.00	34.39	3.67	34.11	72.17	Max Peak	Vertical	186	355	74.0	-1.8	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.

[back to matrix](#)




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 37 of 46



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5190.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 13.5, Duty Cycle (%): 99



4500.00 - 5200.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5148.35	15.93	3.68	34.11	53.72	Max Avg	Vertical	186	355	54.0	-0.3	Pass
2	5150.00	31.72	3.67	34.11	69.50	Max Peak	Vertical	186	355	74.0	-4.5	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--


Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5725 MHz RADIATED BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5745.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99




5550.00 - 5755.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5719.93	35.67	3.80	34.35	73.82	Max Avg	Vertical	191	355	106.9	-33.1	Pass
2	5725.00	45.44	3.79	34.35	83.58	Max Avg	Vertical	191	355	122.2	-38.6	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

5725 MHz RADIATED BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5775.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 20.5, Duty Cycle (%): 99




5550.00 - 5775.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5650.97	27.82	3.76	34.18	65.76	Max Avg	Vertical	191	355	68.9	-3.2	Pass
2	5713.28	46.66	3.82	34.34	84.82	Max Avg	Vertical	191	355	108.8	-24.0	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber. Power reduced to meet band edge limit.

[back to matrix](#)

5725 MHz RADIATED BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5745.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99




5550.00 - 5755.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5705.96	25.86	3.86	34.33	64.05	Max Avg	Vertical	191	355	106.9	-42.8	Pass
2	5725.00	47.12	3.79	34.35	85.26	Max Avg	Vertical	191	355	122.2	-36.9	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

5725 MHz RADIATED BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5755.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



5550.00 - 5755.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5694.87	30.95	3.85	34.31	69.11	Max Avg	Vertical	191	355	101.5	-32.4	Pass
2	5715.55	45.08	3.81	34.34	83.23	Max Avg	Vertical	191	355	109.7	-26.5	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)



Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 42 of 46



5850 MHz RADIATED BAND-EDGE EMISSIONS


Variant: 802.11a, Test Freq: 5825.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99

Measurement Distance: 3m

Sweep Time: 10.0 s

RBW: 1 MHz
VBW: 3 MHz

Date: 01 Nov 2016 -



5800.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5850.00	36.86	3.81	34.63	75.30	Max Avg	Vertical	194	353	122.2	-46.9	Pass
3	5860.40	28.33	3.86	34.65	66.84	Max Avg	Vertical	194	353	109.4	-42.6	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--


Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5850 MHz RADIATED BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5775.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



5775.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
2	5854.06	44.24	3.83	34.64	82.71	Max Avg	Vertical	194	353	113.1	-30.4	Pass
3	5917.26	26.68	3.86	34.80	65.34	Max Avg	Vertical	194	353	74.1	-8.8	Pass
1	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)




Title: Hewlett Packard Enterprise APINH303
To: FCC CFR 47 Part 15.407 (Non-DFS)
Serial #: HWP85-U8 Radiated Rev A
Issue Date: 1st December 2016
Page: 44 of 46



5850 MHz RADIATED BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5825.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



5800.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5850.00	37.67	3.81	34.63	76.11	Max Avg	Vertical	194	353	122.2	-46.1	Pass
3	5863.61	27.43	3.84	34.66	65.93	Max Avg	Vertical	194	353	108.3	-42.4	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--


Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5850 MHz RADIATED BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5795.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 21, Duty Cycle (%): 99



5795.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBμV	Cable Loss dB	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
2	5853.29	31.30	3.82	34.63	69.75	Max Avg	Vertical	194	353	115.4	-45.6	Pass
3	5876.43	24.33	3.81	34.70	62.84	Max Avg	Vertical	194	353	104.5	-41.6	Pass
1	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT on table powered by POE 9001GR. Connected to laptop outside chamber.

[back to matrix](#)



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com