

Company: Hewlett Packard Enterprise

Test of: APINH303  
To: FCC CFR 47 Part 15 Subpart E 15.407(DFS)

Report No.: HWPD85-U12\_Conducted Rev A

**TEST REPORT ADDENDUM - CONDUCTED**



Issue Date: 4<sup>th</sup> December 2016

Master Document Number	Addendum Reports
HWPD85-U12_Master	HWPD85-U12_Conducted
	HWPD85-U12_Radiated
	HWPD85-G4 (FCC Part 15B & ICES-003)

## Table of Contents

<b>1. MEASUREMENT AND PRESENTATION OF TEST DATA .....</b>	<b>3</b>
<b>2. TEST SUMMARY .....</b>	<b>4</b>
<b>3. TEST RESULTS .....</b>	<b>5</b>
3.1. Peak Transmit Power .....	5
3.2. 26 dB & 99% Bandwidth .....	11
3.3. Power Spectral Density .....	20
<b>A. APPENDIX - GRAPHICAL IMAGES .....</b>	<b>30</b>
A.1. 26 dB & 99% Bandwidth .....	31
A.2. Power Spectral Density .....	73

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

## 1. MEASUREMENT AND PRESENTATION OF TEST DATA

The measurement and graphical data presented in this test report was generated automatically using state-of-the-art technology creating an easy to read report structure. Numerical measurement data is separated from supporting graphical data (plots) through hyperlinks. Numerical measurement data can be reviewed without scrolling through numerous graphical pages to arrive at the next data matrix.

Plots have been relegated into the Appendix 'Graphical Data'.

Test and report automation was performed by [MiTest](#). [MiTest](#) is an automated test system developed by MiCOM Labs. [MiTest](#) is the first cloud based modular test system enabling end-to-end automation of regulatory compliance testing for conducted RF testing.



The MiCOM Labs "[MiTest](#)" Automated Test System" (Patent Pending)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 4 of 136

---

## 2. TEST SUMMARY

### List of Measurements

Test Header	Result	Data Link
(a) Peak Transmit Power	Complies	<a href="#">View Data</a>
(a) 26 dB & 99% Bandwidth	Complies	<a href="#">View Data</a>
(a)(5) Power Spectral Density	Complies	<a href="#">View Data</a>

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### 3. TEST RESULTS

#### 3.1. Peak Transmit Power

Conducted Test Conditions for Maximum Conducted Output Power			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	Maximum Conducted Output Power	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (a)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	See Normative References		

##### Test Procedure for Maximum Conducted Output Power Measurement

Method PM (Measurement using an RF average power meter). KDB 789033 defines a methodology using an average wideband power meter. Measurements were made while the EUT was operating in a continuous transmission mode (100% duty cycle) at the appropriate center frequency. All operational modes and frequency bands were measured independently and the resultant calculated. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported separately. A summation ( $\Sigma$ ) of each antenna port output power is provided which includes any offset due to Duty Cycle Correction Factor (DCCF). Testing was performed under ambient conditions at nominal voltage.

Test configuration and setup used for the measurement was per the Conducted Test Set-up section specified in this document.

##### Supporting Information

Calculated Power =  $A + G + Y + 10 \log(1/x) \text{ dBm}$

$A$  = Total Power  $[10^{\text{a}/10} + 10^{\text{b}/10} + 10^{\text{c}/10} + 10^{\text{d}/10}]$

$G$  = Antenna Gain

$Y$  = Beamforming Gain

$x$  = Duty Cycle (average power measurements only)

##### Limits Maximum Conducted Output Power

###### Operating Frequency Band 5150-5250 MHz

###### 15. 407 (a)(1)

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Operating Frequency Band 5250-5350 and 5470 – 5725 MHz**

##### 15. 407 (a)(2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Operating Frequency Band 5725 – 5850 MHz**

##### 15. 407 (a)(3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 7 of 136

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.00 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5260.0	15.95	16.71	--	--	19.36	35.190	24.00	-4.64	19.00
5300.0	15.91	16.55	--	--	19.25	32.786	24.00	-4.75	19.00
5320.0	13.31	13.94	--	--	16.65	19.800	23.97	-7.32	16.00

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11ac-80	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5290.0	8.59	9.40	--	--	12.02	82.725	24.00	-11.98	11.50

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 8 of 136

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5260.0	16.00	16.74	--	--	19.40	37.034	24.00	-4.60	19.00
5300.0	15.95	16.63	--	--	19.31	32.786	24.00	-4.69	19.00
5320.0	13.31	13.99	--	--	16.67	20.762	24.00	-7.33	16.00

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5270.0	15.46	16.38	--	--	18.95	72.305	24.00	-5.05	18.00
5310.0	9.51	10.31	--	--	12.94	39.599	24.00	-11.06	12.00

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 9 of 136

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.00 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5500.0	15.52	15.98	--	--	18.77	27.575	24.00	-5.23	18.00
5580.0	17.16	17.92	--	--	20.57	37.675	24.00	-3.43	20.00
5720.0	17.23	18.49	--	--	20.92	38.397	24.00	-3.08	20.00

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11ac-80	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5530.0	9.73	10.16	--	--	12.96	83.046	24.00	-11.04	12.00
5610.0	15.39	16.34	--	--	18.90	151.022	24.00	-5.10	18.00
5690.0	15.56	16.65	--	--	19.15	147.495	24.00	-4.85	18.00

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 10 of 136

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5500.0	14.73	15.11	--	--	17.93	22.525	24.00	-6.07	17.00
5580.0	16.22	17.10	--	--	19.69	35.591	24.00	-4.31	19.00
5720.0	16.45	17.75	--	--	20.16	37.515	24.00	-3.84	19.00

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	$\pm 2.81$ dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

#### Equipment Configuration for Peak Transmit Power

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Conducted Output Power (dBm)				Calculated Total Power	Minimum 26 dB Bandwidth	Limit	Margin	EUT Power Setting
	Port(s)								
MHz	a	b	c	d	$\Sigma$ Port(s) dBm	MHz	dBm	dB	
5510.0	13.10	13.44	--	--	16.28	40.080	24.00	-7.72	15.00
5550.0	15.91	16.61	--	--	19.28	76.313	24.00	-4.72	19.00
5710.0	16.16	17.18	--	--	19.71	77.114	24.00	-4.29	19.00

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	$\pm 2.81$ dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### **3.2. 26 dB & 99% Bandwidth**

Conducted Test Conditions for 26 dB and 99% Bandwidth			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	26 dB and 99 % Bandwidth	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (a)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	See Normative References		
<b>Test Procedure for 26 dB and 99% Bandwidth Measurement</b> The bandwidth at 26 dB and 99 % is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency. The Resolution Bandwidth was set to approximately 1% of the emission bandwidth. Testing was performed under ambient conditions at nominal voltage. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported.  Test configuration and setup used for the measurement was per the Conducted Test Set-up section specified in this document.			



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 12 of 136

**Equipment Configuration for 26 dB & 99% Occupied Bandwidth**

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.00 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

**Test Measurement Results**

<b>Test Frequency</b>	<b>Measured 26 dB Bandwidth (MHz)</b>				<b>26 dB Bandwidth (MHz)</b>	
	<b>Port(s)</b>					
<b>MHz</b>	<b>a</b>	<b>b</b>	<b>c</b>	<b>d</b>	<b>Highest</b>	<b>Lowest</b>
5260.0	<a href="#">35.190</a>	<a href="#">38.156</a>	--	--	38.156	35.190
5300.0	<a href="#">32.786</a>	<a href="#">36.553</a>	--	--	36.553	32.786
5320.0	<a href="#">19.800</a>	<a href="#">21.002</a>	--	--	21.002	19.800

<b>Test Frequency</b>	<b>Measured 99% Bandwidth (MHz)</b>				<b>99% Bandwidth (MHz)</b>	
	<b>Port(s)</b>					
<b>MHz</b>	<b>a</b>	<b>b</b>	<b>c</b>	<b>d</b>	<b>Highest</b>	<b>Lowest</b>
5260.0	<a href="#">17.796</a>	<a href="#">19.479</a>	--	--	19.479	17.796
5300.0	<a href="#">17.074</a>	<a href="#">19.319</a>	--	--	19.319	17.074
5320.0	<a href="#">16.513</a>	<a href="#">16.513</a>	--	--	16.513	16.513

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 13 of 136

#### Equipment Configuration for 26 dB & 99% Occupied Bandwidth

<b>Variant:</b>	802.11ac-80	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5290.0	<a href="#">82.725</a>	<a href="#">83.367</a>	--	--	83.367	82.725
Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5290.0	<a href="#">75.992</a>	<a href="#">75.992</a>	--	--	75.992	75.992

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 14 of 136

#### Equipment Configuration for 26 dB & 99% Occupied Bandwidth

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)				Highest	Lowest
MHz	a	b	c	d	Highest	Lowest
5260.0	<a href="#">37.034</a>	<a href="#">39.359</a>	--	--	39.359	37.034
5300.0	<a href="#">32.786</a>	<a href="#">38.156</a>	--	--	38.156	32.786
5320.0	<a href="#">20.762</a>	<a href="#">21.242</a>	--	--	21.242	20.762

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)				Highest	Lowest
MHz	a	b	c	d	Highest	Lowest
5260.0	<a href="#">18.437</a>	<a href="#">19.880</a>	--	--	19.880	18.437
5300.0	<a href="#">18.036</a>	<a href="#">19.960</a>	--	--	19.960	18.036
5320.0	<a href="#">17.635</a>	<a href="#">17.635</a>	--	--	17.635	17.635

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 15 of 136

Equipment Configuration for 26 dB & 99% Occupied Bandwidth

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)				Highest	Lowest
MHz	a	b	c	d	Highest	Lowest
5270.0	<a href="#">72.305</a>	<a href="#">77.595</a>	--	--	77.595	72.305
5310.0	<a href="#">39.760</a>	<a href="#">39.599</a>	--	--	39.760	39.599

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)				Highest	Lowest
MHz	a	b	c	d	Highest	Lowest
5270.0	<a href="#">36.553</a>	<a href="#">37.675</a>	--	--	37.675	36.553
5310.0	<a href="#">36.072</a>	<a href="#">36.072</a>	--	--	36.072	36.072

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 16 of 136

#### Equipment Configuration for 26 dB & 99% Occupied Bandwidth

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.00 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5500.0	<a href="#">30.782</a>	<a href="#">27.575</a>	--	--	30.782	27.575
5580.0	<a href="#">38.557</a>	<a href="#">37.675</a>	--	--	38.557	37.675
5720.0	<a href="#">38.397</a>	<a href="#">39.599</a>	--	--	39.599	38.397

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5500.0	<a href="#">16.834</a>	<a href="#">16.673</a>	--	--	16.834	16.673
5580.0	<a href="#">22.044</a>	<a href="#">20.922</a>	--	--	22.044	20.922
5720.0	<a href="#">22.525</a>	<a href="#">24.128</a>	--	--	24.128	22.525

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 17 of 136

Equipment Configuration for 26 dB & 99% Occupied Bandwidth

<b>Variant:</b>	802.11ac-80	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5530.0	<a href="#">83.046</a>	<a href="#">84.329</a>	--	--	84.329	83.046
5610.0	<a href="#">151.343</a>	<a href="#">151.022</a>	--	--	151.343	151.022
5690.0	<a href="#">147.495</a>	<a href="#">154.228</a>	--	--	154.228	147.495

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5530.0	<a href="#">75.992</a>	<a href="#">76.313</a>	--	--	76.313	75.992
5610.0	<a href="#">76.954</a>	<a href="#">77.275</a>	--	--	77.275	76.954
5690.0	<a href="#">76.954</a>	<a href="#">77.595</a>	--	--	77.595	76.954

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 18 of 136

#### Equipment Configuration for 26 dB & 99% Occupied Bandwidth

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5500.0	<a href="#">25.892</a>	<a href="#">22.525</a>	--	--	25.892	22.525
5580.0	<a href="#">35.591</a>	<a href="#">35.752</a>	--	--	35.752	35.591
5720.0	<a href="#">37.515</a>	<a href="#">38.798</a>	--	--	38.798	37.515

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5500.0	<a href="#">17.796</a>	<a href="#">17.796</a>	--	--	17.796	17.796
5580.0	<a href="#">18.277</a>	<a href="#">18.357</a>	--	--	18.357	18.277
5720.0	<a href="#">18.517</a>	<a href="#">20.200</a>	--	--	20.200	18.517

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 19 of 136

Equipment Configuration for 26 dB & 99% Occupied Bandwidth

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

Test Measurement Results

Test Frequency	Measured 26 dB Bandwidth (MHz)				26 dB Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5510.0	<a href="#">40.080</a>	<a href="#">40.080</a>	--	--	40.080	40.080
5550.0	<a href="#">76.954</a>	<a href="#">76.313</a>	--	--	76.954	76.313
5710.0	<a href="#">78.557</a>	<a href="#">77.114</a>	--	--	78.557	77.114

Test Frequency	Measured 99% Bandwidth (MHz)				99% Bandwidth (MHz)	
	Port(s)					
MHz	a	b	c	d	Highest	Lowest
5510.0	<a href="#">36.072</a>	<a href="#">36.072</a>	--	--	36.072	36.072
5550.0	<a href="#">36.713</a>	<a href="#">36.874</a>	--	--	36.874	36.713
5710.0	<a href="#">36.874</a>	<a href="#">37.355</a>	--	--	37.355	36.874

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### 3.3. Power Spectral Density

Conducted Test Conditions for Power Spectral Density			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	Power Spectral Density	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (a)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	See Normative References		

#### Test Procedure for Power Spectral Density

The in-band power spectral density was measured using the test technique specified in KDB 789033. A 1 MHz measurement bandwidth was implemented for the analyzer sweep. Once the sweep is complete the analyzer trace data is downloaded and used for post processing purposes.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. The Peak Power Spectral Density is the highest level found across the emission bandwidth. With multiple antenna port measurements the numerical analyzer data from each port is summed (à) and a link to this additional graphic is provided.

Test configuration and setup used for the measurement was per the Conducted Test Set-up section specified in this document.

Measure and sum the spectra across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The individual spectra are then summed mathematically in linear power units. Unlike in-band power measurements, in which the sum involves a single measured value (output power) from each output, measurements for compliance with PSD limits involve summing entire spectra across corresponding frequency bins on the various outputs. Consistency is maintained for any device with multiple transmitter outputs to be certain the individual outputs are all aligned with the same span and same number of points. In this instance, the linear power spectrum value within the first spectral bin of output 0 is summed with that in the first spectral bin of output 1, and the first spectral bin of output 2, and so on up to the Nth output to obtain the true value for the first frequency bin of the summed spectrum. The summed spectrum value for each frequency bin is computed in this fashion. These summed spectral values were post processed and the resulting numerical and graphical data presented.

NOTE: It may be observed that spectrum in some plots break the limit line however this in itself does NOT constitute a failure. In all cases a spectrum summation plot is provided in order to prove compliance. A failure occurs only after the summation of all spectrum plots have been summed and are found to be greater than the limit line.

#### Supporting Information

Calculated Power =  $A + 10 \log (1/x)$  dBm

$A = \text{Total Power Spectral Density} [10^{\text{a}/10} + 10^{\text{b}/10} + 10^{\text{c}/10} + 10^{\text{d}/10}]$

$x = \text{Duty Cycle}$

#### Limits Power Spectral Density

##### Operating Frequency Band 5150-5250 MHz

###### 15. 407 (a)(1)

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Operating Frequency Band 5250-5350 and 5470 – 5725 MHz**

##### **15. 407 (a)(2)**

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Operating Frequency Band 5725 – 5850 MHz**

##### **15. 407 (a)(3)**

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 22 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.00 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5260.0	4.946	4.506	--	--	7.465	11.0	-3.5
5300.0	5.532	4.182	--	--	7.149	11.0	-3.9
5320.0	3.103	2.012	--	--	5.048	11.0	-6.0

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 23 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11ac-80	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5290.0	<a href="#">-8.114</a>	<a href="#">-9.562</a>	--	--	<a href="#">-6.382</a>	9.4	-15.8

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 24 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5260.0	5.116	4.162	--	--	7.693	9.4	-1.7
5300.0	5.383	4.328	--	--	7.922	9.4	-1.5
5320.0	2.580	1.506	--	--	5.102	9.4	-4.3

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 25 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5270.0	<a href="#">1.417</a>	<a href="#">1.174</a>	--	--	<a href="#">4.065</a>	9.4	-5.3
5310.0	<a href="#">-3.760</a>	<a href="#">-5.091</a>	--	--	<a href="#">-1.776</a>	9.4	-11.2

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 26 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.00 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5500.0	5.011	3.520	--	--	6.869	11.0	-4.1
5580.0	7.004	5.429	--	--	9.170	11.0	-1.8
5720.0	7.745	6.157	--	--	9.815	11.0	-1.2

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 27 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11ac-80	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5530.0	<a href="#">-7.215</a>	<a href="#">-9.526</a>	--	--	<a href="#">-5.684</a>	9.4	-15.1
5610.0	<a href="#">-1.699</a>	<a href="#">-2.663</a>	--	--	<a href="#">0.536</a>	9.4	-8.9
5690.0	<a href="#">-0.981</a>	<a href="#">-2.633</a>	--	--	<a href="#">1.258</a>	9.4	-8.2

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 28 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5500.0	4.126	1.923	--	--	5.963	9.4	-3.4
5580.0	6.074	4.501	--	--	8.302	9.4	-1.1
5720.0	6.512	5.365	--	--	9.031	9.4	-0.4

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 29 of 136

#### Equipment Configuration for Power Spectral Density

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	99.0
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	4.60
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	3.00
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	CC
<b>Engineering Test Notes:</b>	None		

#### Test Measurement Results

Test Frequency	Measured Power Spectral Density				Summation Peak Marker + DCCF (+0.04 dB)	Limit	Margin
	Port(s) (dBm/MHz)						
MHz	a	b	c	d	dBm/MHz	dBm/MHz	dB
5510.0	<a href="#">-0.711</a>	<a href="#">-2.635</a>	--	--	<a href="#">1.430</a>	9.4	-8.0
5550.0	<a href="#">2.751</a>	<a href="#">1.123</a>	--	--	<a href="#">4.518</a>	9.4	-4.9
5710.0	<a href="#">3.646</a>	<a href="#">1.699</a>	--	--	<a href="#">5.586</a>	9.4	-3.8

#### Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Hewlett Packard Enterprise APINH303  
**To:** FCC CFR 47 Part 15 Subpart E 15.407 (DFS)  
**Serial #:** HWPD85-U12\_Conducted Rev A  
**Issue Date:** 4<sup>th</sup> December 2016  
**Page:** 30 of 136


---

## **A. APPENDIX - GRAPHICAL IMAGES**

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.


## A.1. 26 dB & 99% Bandwidth



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5242.886 MHz : -18.672 dBm M2 : 5265.010 MHz : 7.738 dBm Delta1 : 35.190 MHz : -0.722 dB T1 : 5251.222 MHz : -7.576 dBm T2 : 5269.018 MHz : -10.324 dBm OBW : 17.796 MHz	Measured 26 dB Bandwidth: 35.190 MHz Measured 99% Bandwidth: 17.796 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5241.122 MHz : -20.303 dBm M2 : 5264.930 MHz : 6.747 dBm Delta1 : 38.156 MHz : -0.242 dB T1 : 5250.421 MHz : -12.823 dBm T2 : 5269.900 MHz : -12.638 dBm OBW : 19.479 MHz	Measured 26 dB Bandwidth: 38.156 MHz Measured 99% Bandwidth: 19.479 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5284.649 MHz : -18.467 dBm M2 : 5304.930 MHz : 7.569 dBm Delta1 : 32.786 MHz : -2.131 dB T1 : 5291.463 MHz : -4.503 dBm T2 : 5308.537 MHz : -6.810 dBm OBW : 17.074 MHz	Measured 26 dB Bandwidth: 32.786 MHz Measured 99% Bandwidth: 17.074 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5281.443 MHz : -19.984 dBm M2 : 5304.930 MHz : 6.646 dBm Delta1 : 36.553 MHz : -1.068 dB T1 : 5290.261 MHz : -12.435 dBm T2 : 5309.579 MHz : -11.170 dBm OBW : 19.319 MHz	Measured 26 dB Bandwidth: 36.553 MHz Measured 99% Bandwidth: 19.319 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5310.020 MHz : -21.800 dBm M2 : 5321.242 MHz : 4.907 dBm Delta1 : 19.800 MHz : 0.254 dB T1 : 5311.703 MHz : -1.022 dBm T2 : 5328.216 MHz : -0.767 dBm OBW : 16.513 MHz	Measured 26 dB Bandwidth: 19.800 MHz Measured 99% Bandwidth: 16.513 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5309.218 MHz : -23.663 dBm M2 : 5318.517 MHz : 3.607 dBm Delta1 : 21.002 MHz : 2.524 dB T1 : 5311.703 MHz : -1.727 dBm T2 : 5328.216 MHz : -3.080 dBm OBW : 16.513 MHz	Measured 26 dB Bandwidth: 21.002 MHz Measured 99% Bandwidth: 16.513 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5248.798 MHz : -22.152 dBm M2 : 5314.850 MHz : 3.904 dBm Delta1 : 82.725 MHz : 2.221 dB T1 : 5252.325 MHz : -3.029 dBm T2 : 5328.317 MHz : -2.309 dBm OBW : 75.992 MHz	Measured 26 dB Bandwidth: 82.725 MHz Measured 99% Bandwidth: 75.992 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5248.156 MHz : -25.658 dBm M2 : 5316.774 MHz : 0.961 dBm Delta1 : 83.367 MHz : 3.514 dB T1 : 5252.004 MHz : -4.369 dBm T2 : 5327.996 MHz : -3.192 dBm OBW : 75.992 MHz	Measured 26 dB Bandwidth: 83.367 MHz Measured 99% Bandwidth: 75.992 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5242.004 MHz : -19.535 dBm M2 : 5262.445 MHz : 7.181 dBm Delta1 : 37.034 MHz : -0.675 dB T1 : 5250.822 MHz : -5.329 dBm T2 : 5269.259 MHz : -7.314 dBm OBW : 18.437 MHz	Measured 26 dB Bandwidth: 37.034 MHz Measured 99% Bandwidth: 18.437 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH  
 Variant: 802.11n HT-20, Channel: 5260.00 MHz, Chain b, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5240.321 MHz : -21.326 dBm M2 : 5258.677 MHz : 6.381 dBm Delta1 : 39.359 MHz : 0.425 dB T1 : 5250.100 MHz : -12.022 dBm T2 : 5269.980 MHz : -12.006 dBm OBW : 19.880 MHz	Measured 26 dB Bandwidth: 39.359 MHz Measured 99% Bandwidth: 19.880 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5284.248 MHz : -18.839 dBm M2 : 5305.010 MHz : 7.740 dBm Delta1 : 32.786 MHz : -1.322 dB T1 : 5290.982 MHz : -2.114 dBm T2 : 5309.018 MHz : -3.515 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 32.786 MHz Measured 99% Bandwidth: 18.036 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH  
 Variant: 802.11n HT-20, Channel: 5300.00 MHz, Chain b, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5280.882 MHz : -20.080 dBm M2 : 5305.010 MHz : 6.623 dBm Delta1 : 38.156 MHz : 1.023 dB T1 : 5290.100 MHz : -12.191 dBm T2 : 5310.060 MHz : -12.954 dBm OBW : 19.960 MHz	Measured 26 dB Bandwidth: 38.156 MHz Measured 99% Bandwidth: 19.960 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5309.539 MHz : -22.630 dBm M2 : 5319.319 MHz : 4.360 dBm Delta1 : 20.762 MHz : 0.952 dB T1 : 5311.142 MHz : -0.511 dBm T2 : 5328.778 MHz : -0.119 dBm OBW : 17.635 MHz	Measured 26 dB Bandwidth: 20.762 MHz Measured 99% Bandwidth: 17.635 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5309.379 MHz : -22.968 dBm M2 : 5324.930 MHz : 3.300 dBm Delta1 : 21.242 MHz : 0.488 dB T1 : 5311.142 MHz : -1.323 dBm T2 : 5328.778 MHz : -1.479 dBm OBW : 17.635 MHz	Measured 26 dB Bandwidth: 21.242 MHz Measured 99% Bandwidth: 17.635 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH  
 Variant: 802.11n HT-40, Channel: 5270.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5235.611 MHz : -19.217 dBm M2 : 5278.577 MHz : 8.165 dBm Delta1 : 72.305 MHz : 0.988 dB T1 : 5251.804 MHz : 1.177 dBm T2 : 5288.357 MHz : 1.569 dBm OBW : 36.553 MHz	Measured 26 dB Bandwidth: 72.305 MHz Measured 99% Bandwidth: 36.553 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5231.603 MHz : -18.890 dBm M2 : 5266.072 MHz : 7.134 dBm Delta1 : 77.595 MHz : 0.130 dB T1 : 5251.323 MHz : -4.461 dBm T2 : 5288.998 MHz : -8.658 dBm OBW : 37.675 MHz	Measured 26 dB Bandwidth: 77.595 MHz Measured 99% Bandwidth: 37.675 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5290.040 MHz : -25.132 dBm M2 : 5319.058 MHz : 2.104 dBm Delta1 : 39.760 MHz : 2.920 dB T1 : 5291.964 MHz : -3.946 dBm T2 : 5328.036 MHz : -2.917 dBm OBW : 36.072 MHz	Measured 26 dB Bandwidth: 39.760 MHz Measured 99% Bandwidth: 36.072 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5290.040 MHz : -25.069 dBm M2 : 5312.164 MHz : 1.252 dBm Delta1 : 39.599 MHz : 2.499 dB T1 : 5291.964 MHz : -4.206 dBm T2 : 5328.036 MHz : -4.263 dBm OBW : 36.072 MHz	Measured 26 dB Bandwidth: 39.599 MHz Measured 99% Bandwidth: 36.072 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5484.168 MHz : -19.638 dBm M2 : 5505.010 MHz : 7.443 dBm Delta1 : 30.782 MHz : -0.423 dB T1 : 5491.543 MHz : -3.336 dBm T2 : 5508.377 MHz : -3.834 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 30.782 MHz Measured 99% Bandwidth: 16.834 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5485.852 MHz : -20.938 dBm M2 : 5502.445 MHz : 5.222 dBm Delta1 : 27.575 MHz : -0.081 dB T1 : 5491.623 MHz : -3.173 dBm T2 : 5508.297 MHz : -3.342 dBm OBW : 16.673 MHz	Measured 26 dB Bandwidth: 27.575 MHz Measured 99% Bandwidth: 16.673 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5560.401 MHz : -17.550 dBm M2 : 5585.010 MHz : 9.841 dBm Delta1 : 38.557 MHz : 2.024 dB T1 : 5568.978 MHz : -9.944 dBm T2 : 5591.022 MHz : -9.299 dBm OBW : 22.044 MHz	Measured 26 dB Bandwidth: 38.557 MHz Measured 99% Bandwidth: 22.044 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5561.683 MHz : -18.180 dBm M2 : 5578.677 MHz : 8.002 dBm Delta1 : 37.675 MHz : -0.071 dB T1 : 5569.459 MHz : -11.335 dBm T2 : 5590.381 MHz : -10.810 dBm OBW : 20.922 MHz	Measured 26 dB Bandwidth: 37.675 MHz Measured 99% Bandwidth: 20.922 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5700.721 MHz : -17.328 dBm M2 : 5724.930 MHz : 10.365 dBm Delta1 : 38.397 MHz : 3.183 dB T1 : 5708.737 MHz : -9.293 dBm T2 : 5731.263 MHz : -9.791 dBm OBW : 22.525 MHz	Measured 26 dB Bandwidth: 38.397 MHz Measured 99% Bandwidth: 22.525 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5700.240 MHz : -17.629 dBm M2 : 5724.930 MHz : 9.129 dBm Delta1 : 39.599 MHz : -0.332 dB T1 : 5708.016 MHz : -9.512 dBm T2 : 5732.144 MHz : -10.438 dBm OBW : 24.128 MHz	Measured 26 dB Bandwidth: 39.599 MHz Measured 99% Bandwidth: 24.128 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5488.156 MHz : -21.749 dBm M2 : 5546.192 MHz : 4.309 dBm Delta1 : 83.046 MHz : 3.805 dB T1 : 5492.004 MHz : -1.135 dBm T2 : 5567.996 MHz : -0.599 dBm OBW : 75.992 MHz	Measured 26 dB Bandwidth: 83.046 MHz Measured 99% Bandwidth: 75.992 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5487.836 MHz : -25.603 dBm M2 : 5531.764 MHz : 1.140 dBm Delta1 : 84.329 MHz : 1.871 dB T1 : 5492.004 MHz : -4.046 dBm T2 : 5568.317 MHz : -3.922 dBm OBW : 76.313 MHz	Measured 26 dB Bandwidth: 84.329 MHz Measured 99% Bandwidth: 76.313 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5534.810 MHz : -18.109 dBm M2 : 5599.900 MHz : 9.725 dBm Delta1 : 151.343 MHz : 1.080 dB T1 : 5571.683 MHz : 3.111 dBm T2 : 5648.637 MHz : 1.401 dBm OBW : 76.954 MHz	Measured 26 dB Bandwidth: 151.343 MHz Measured 99% Bandwidth: 76.954 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5538.016 MHz : -18.569 dBm M2 : 5624.910 MHz : 8.271 dBm Delta1 : 151.022 MHz : -0.100 dB T1 : 5571.683 MHz : 1.254 dBm T2 : 5648.958 MHz : -1.670 dBm OBW : 77.275 MHz	Measured 26 dB Bandwidth: 151.022 MHz Measured 99% Bandwidth: 77.275 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5618.978 MHz : -16.600 dBm M2 : 5714.208 MHz : 10.353 dBm Delta1 : 147.495 MHz : 0.748 dB T1 : 5651.683 MHz : 3.558 dBm T2 : 5728.637 MHz : 1.356 dBm OBW : 76.954 MHz	Measured 26 dB Bandwidth: 147.495 MHz Measured 99% Bandwidth: 76.954 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5613.206 MHz : -19.100 dBm M2 : 5686.313 MHz : 8.069 dBm Delta1 : 154.228 MHz : 1.651 dB T1 : 5651.363 MHz : -0.226 dBm T2 : 5728.958 MHz : -2.004 dBm OBW : 77.595 MHz	Measured 26 dB Bandwidth: 154.228 MHz Measured 99% Bandwidth: 77.595 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5486.894 MHz : -22.103 dBm M2 : 5503.727 MHz : 5.686 dBm Delta1 : 25.892 MHz : 0.875 dB T1 : 5491.062 MHz : -0.556 dBm T2 : 5508.858 MHz : -1.341 dBm OBW : 17.796 MHz	Measured 26 dB Bandwidth: 25.892 MHz Measured 99% Bandwidth: 17.796 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5488.257 MHz : -24.332 dBm M2 : 5497.475 MHz : 4.223 dBm Delta1 : 22.525 MHz : 1.342 dB T1 : 5491.062 MHz : -1.591 dBm T2 : 5508.858 MHz : -2.276 dBm OBW : 17.796 MHz	Measured 26 dB Bandwidth: 22.525 MHz Measured 99% Bandwidth: 17.796 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5561.764 MHz : -18.569 dBm M2 : 5584.930 MHz : 8.407 dBm Delta1 : 35.591 MHz : -1.184 dB T1 : 5570.822 MHz : -4.489 dBm T2 : 5589.098 MHz : -4.853 dBm OBW : 18.277 MHz	Measured 26 dB Bandwidth: 35.591 MHz Measured 99% Bandwidth: 18.277 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5562.244 MHz : -20.070 dBm M2 : 5578.677 MHz : 6.912 dBm Delta1 : 35.752 MHz : -0.476 dB T1 : 5570.741 MHz : -6.917 dBm T2 : 5589.098 MHz : -6.252 dBm OBW : 18.357 MHz	Measured 26 dB Bandwidth: 35.752 MHz Measured 99% Bandwidth: 18.357 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5701.122 MHz : -17.497 dBm M2 : 5718.677 MHz : 8.781 dBm Delta1 : 37.515 MHz : -0.960 dB T1 : 5710.741 MHz : -5.425 dBm T2 : 5729.259 MHz : -6.633 dBm OBW : 18.517 MHz	Measured 26 dB Bandwidth: 37.515 MHz Measured 99% Bandwidth: 18.517 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5700.321 MHz : -20.023 dBm M2 : 5724.930 MHz : 7.892 dBm Delta1 : 38.798 MHz : 1.454 dB T1 : 5709.940 MHz : -11.567 dBm T2 : 5730.140 MHz : -13.173 dBm OBW : 20.200 MHz	Measured 26 dB Bandwidth: 38.798 MHz Measured 99% Bandwidth: 20.200 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5489.719 MHz : -20.666 dBm M2 : 5508.637 MHz : 5.631 dBm Delta1 : 40.080 MHz : 2.540 dB T1 : 5491.964 MHz : 0.618 dBm T2 : 5528.036 MHz : 0.508 dBm OBW : 36.072 MHz	Measured 26 dB Bandwidth: 40.080 MHz Measured 99% Bandwidth: 36.072 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5489.719 MHz : -24.084 dBm M2 : 5501.423 MHz : 3.723 dBm Delta1 : 40.080 MHz : 3.614 dB T1 : 5491.964 MHz : -2.040 dBm T2 : 5528.036 MHz : -1.809 dBm OBW : 36.072 MHz	Measured 26 dB Bandwidth: 40.080 MHz Measured 99% Bandwidth: 36.072 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5511.122 MHz : -18.382 dBm M2 : 5546.232 MHz : 8.893 dBm Delta1 : 76.954 MHz : 0.919 dB T1 : 5531.643 MHz : 1.132 dBm T2 : 5568.357 MHz : 0.896 dBm OBW : 36.713 MHz	Measured 26 dB Bandwidth: 76.954 MHz Measured 99% Bandwidth: 36.713 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5513.206 MHz : -19.407 dBm M2 : 5543.026 MHz : 6.821 dBm Delta1 : 76.313 MHz : 0.140 dB T1 : 5531.643 MHz : -1.274 dBm T2 : 5568.517 MHz : -2.728 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 76.313 MHz Measured 99% Bandwidth: 36.874 MHz

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5670.160 MHz : -17.757 dBm M2 : 5708.798 MHz : 9.566 dBm Delta1 : 78.557 MHz : 0.338 dB T1 : 5691.643 MHz : 1.519 dBm T2 : 5728.517 MHz : 0.073 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 78.557 MHz Measured 99% Bandwidth: 36.874 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 5672.565 MHz : -18.512 dBm M2 : 5705.591 MHz : 7.561 dBm Delta1 : 77.114 MHz : -0.537 dB T1 : 5691.483 MHz : -2.689 dBm T2 : 5728.838 MHz : -6.395 dBm OBW : 37.355 MHz	Measured 26 dB Bandwidth: 77.114 MHz Measured 99% Bandwidth: 37.355 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

## A.2. Power Spectral Density




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5253.737 MHz : 4.946 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5263.657 MHz : 4.506 dBm	Limit: $\leq 7.990$ dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5263.800 MHz : 7.421 dBm M1 + DCCF : 5263.800 MHz : 7.465 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 11.0 dBm Margin: -3.5 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5296.343 MHz : 5.532 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5300.651 MHz : 4.182 dBm	Channel Frequency: 5300.00 MHz

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5296.200 MHz : 7.105 dBm M1 + DCCF : 5296.200 MHz : 7.149 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 11.0 dBm Margin: -3.9 dB


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5320.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5321.152 MHz : 3.103 dBm	Limit: ≤ 7.990 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5320.00 MHz, Chain b, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5321.754 MHz : 2.012 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5315.600 MHz : 5.004 dBm M1 + DCCF : 5315.600 MHz : 5.048 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 11.0 dBm Margin: -6.0 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5312.645 MHz : -8.114 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5301.022 MHz : -9.562 dBm	Limit: ≤ 6.390 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5290.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5301.800 MHz : -6.426 dBm M1 + DCCF : 5301.800 MHz : -6.382 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -15.8 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5262.054 MHz : 5.116 dBm	Limit: ≤ 6.390 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5260.00 MHz, Chain b, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5258.046 MHz : 4.162 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5262.700 MHz : 7.649 dBm M1 + DCCF : 5262.700 MHz : 7.693 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -1.7 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5302.154 MHz : 5.383 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5302.054 MHz : 4.328 dBm	Channel Frequency: 5300.00 MHz

[back to matrix](#)

### POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5300.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5302.200 MHz : 7.878 dBm M1 + DCCF : 5302.200 MHz : 7.922 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -1.5 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5323.056 MHz : 2.580 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5322.555 MHz : 1.506 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5320.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5323.100 MHz : 5.058 dBm M1 + DCCF : 5323.100 MHz : 5.102 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -4.3 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5261.884 MHz : 1.417 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5266.293 MHz : 1.174 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5265.900 MHz : 4.021 dBm M1 + DCCF : 5265.900 MHz : 4.065 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -5.3 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5315.912 MHz : -3.760 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5302.084 MHz : -5.091 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5310.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5315.900 MHz : -1.820 dBm M1 + DCCF : 5315.900 MHz : -1.776 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -11.2 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5504.559 MHz : 5.011 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5501.954 MHz : 3.520 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5504.300 MHz : 6.825 dBm M1 + DCCF : 5504.300 MHz : 6.869 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 11.0 dBm Margin: -4.1 dB


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5580.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5574.639 MHz : 7.004 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5573.136 MHz : 5.429 dBm	Channel Frequency: 5580.00 MHz

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5582.700 MHz : 9.126 dBm M1 + DCCF : 5582.700 MHz : 9.170 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 11.0 dBm Margin: -1.8 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5724.058 MHz : 7.745 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5725.261 MHz : 6.157 dBm	Limit: ≤ 7.990 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5724.000 MHz : 9.771 dBm M1 + DCCF : 5724.000 MHz : 9.815 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 11.0 dBm Margin: -1.2 dB


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5530.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5543.427 MHz : -7.215 dBm	Limit: ≤ 6.390 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5530.00 MHz, Chain b, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5539.018 MHz : -9.526 dBm	Limit: ≤ 6.390 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5530.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5543.400 MHz : -5.728 dBm M1 + DCCF : 5543.400 MHz : -5.684 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -15.1 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5626.232 MHz : -1.699 dBm	Limit: ≤ 6.390 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5610.00 MHz, Chain b, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5617.415 MHz : -2.663 dBm	Channel Frequency: 5610.00 MHz


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

### POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5610.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5613.000 MHz : 0.492 dBm M1 + DCCF : 5613.000 MHz : 0.536 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -8.9 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5695.010 MHz : -0.981 dBm	Limit: ≤ 6.390 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5690.00 MHz, Chain b, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5695.411 MHz : -2.633 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5695.400 MHz : 1.214 dBm M1 + DCCF : 5695.400 MHz : 1.258 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -8.2 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5498.547 MHz : 4.126 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5505.461 MHz : 1.923 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5500.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5496.600 MHz : 5.919 dBm M1 + DCCF : 5496.600 MHz : 5.963 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -3.4 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5577.244 MHz : 6.074 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5577.144 MHz : 4.501 dBm	Channel Frequency: 5580.00 MHz

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5577.100 MHz : 8.258 dBm M1 + DCCF : 5577.100 MHz : 8.302 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -1.1 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5717.244 MHz : 6.512 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5717.244 MHz : 5.365 dBm	Limit: ≤ 6.390 dBm


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5720.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5717.200 MHz : 8.987 dBm M1 + DCCF : 5717.200 MHz : 9.031 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -0.4 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5514.309 MHz : -0.711 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5518.116 MHz : -2.635 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

### POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5510.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5517.500 MHz : 1.386 dBm M1 + DCCF : 5517.500 MHz : 1.430 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -8.0 dB

[back to matrix](#)


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5544.289 MHz : 2.751 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5544.890 MHz : 1.123 dBm	Channel Frequency: 5550.00 MHz


[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5550.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5544.300 MHz : 4.474 dBm M1 + DCCF : 5544.300 MHz : 4.518 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -4.9 dB

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5715.311 MHz : 3.646 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5714.108 MHz : 1.699 dBm	Limit: ≤ 6.390 dBm

[back to matrix](#)

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5714.900 MHz : 5.542 dBm M1 + DCCF : 5714.900 MHz : 5.586 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 9.4 dBm Margin: -3.8 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)