



REGULATORY COMPLIANCE TEST REPORT

FCC CFR 47 Part 15 Subpart C 15.247 (DTS), ISED 15.247 Issue 2

Report No.: HPEN155-U5 (BLE) Rev A

Company: Hewlett Packard Enterprise Company

Model Name: ASIN0304

REGULATORY COMPLIANCE TEST REPORT

Company Name: Hewlett Packard Enterprise Company

Model Name: ASIN0304

To: FCC CFR 47 Part 15 Subpart C 15.247 (DTS), ISED 15.247 Issue 2

Test Report Serial No.: HPEN155-U5 (BLE) Rev A

This report supersedes: NONE

Applicant: Hewlett Packard Enterprise Company
3333 Scott Blvd
Santa Clara, California 95054
USA

Issue Date: 24th July 2021

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

Table of Contents

1. ACCREDITATION, LISTINGS & RECOGNITION	4
1.1. TESTING ACCREDITATION	4
1.2. RECOGNITION	5
1.3. PRODUCT CERTIFICATION	6
2. DOCUMENT HISTORY	7
3. TEST RESULT CERTIFICATE	8
4. REFERENCES AND MEASUREMENT UNCERTAINTY	9
4.1. Normative References	9
4.2. Test and Uncertainty Procedure	10
5. PRODUCT DETAILS AND TEST CONFIGURATIONS	11
5.1. Technical Details	11
5.2. Scope Of Test Program	12
5.3. Equipment Model(s) and Serial Number(s)	12
5.4. Antenna Details	12
5.5. Cabling and I/O Ports	13
5.6. Test Configurations	13
5.7. Equipment Modifications	13
5.8. Deviations from the Test Standard	13
6. TEST SUMMARY	14
7. TEST EQUIPMENT CONFIGURATION(S)	15
7.1. Conducted RF	15
7.2. Radiated Emissions - 3m Chamber	17
8. MEASUREMENT AND PRESENTATION OF TEST DATA	19
9. TEST RESULTS	20
9.1. 6 dB & 99% Bandwidth	20
9.2. Conducted Output Power	22
9.3. Power Spectral Density	25
9.4. Emissions	27
9.4.1. <i>Conducted Emissions</i>	27
9.4.1.1. Conducted Spurious Emissions	27
9.4.1.2. Conducted Band-Edge Emissions	29
9.4.2. <i>Radiated Emissions</i>	32
9.4.2.1. TX Spurious & Restricted Band Emissions	32
9.4.2.2. Restricted Edge & Band-Edge Emissions	37
A. APPENDIX - GRAPHICAL IMAGES	38
A.1. Duty Cycle	39
A.2. 6 dB & 99% Bandwidth	40
A.3. Power Spectral Density	43
A.4. Emissions	49
A.4.1. <i>Conducted Emissions</i>	49
A.4.1.1. Conducted Spurious Emissions	49
A.4.1.2. Conducted Band-Edge Emissions	52
A.4.2. <i>Radiated Emissions</i>	54
A.4.2.3. TX Spurious & Restricted Band Emissions	54
A.4.2.4. Restricted Edge & Band-Edge Emissions	57

1. ACCREDITATION, LISTINGS & RECOGNITION

1.1. TESTING ACCREDITATION

MiCOM Labs, Inc. is an accredited Electrical testing laboratory per the international standard ISO/IEC 17025:2017. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

1.2. RECOGNITION

MiCOM Labs, Inc is widely recognized for its wireless testing and certification capabilities. In addition to being recognized for Testing and Certification under Phase 2 Mutual Recognition Agreements (MRA) with Canada, Europe, United Kingdom and Japan, our international recognition includes Conformity Assessment Body (CAB) designation status under agreements with Asia Pacific (APEC) MRA Phase 1 countries giving acceptance of MiCOM Labs test reports. MiCOM Labs test reports are accepted globally.

Country	Recognition Body	Status	MRA Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	US0159 Test Firm Designation#: US1084
Canada	Industry Canada (ISED)	FCB	APEC MRA 2	US0159 ISED#: 4143A
Japan	MIC (Ministry of Internal Affairs and Communication)	CAB	Japan MRA 2	RCB 210
	Japan Approvals Institute for Telecommunication Equipment (JATE)			
	VCCI	--	--	A-0012
Europe	European Commission	NB	EU MRA 2	NB 2280
United Kingdom	Department for Business, Energy & Industrial Strategy (BEIS)	AB	UK MRA 2	AB 2280
Mexico	Instituto Federal de Telecomunicaciones (IFT)	CAB	Mexico MRA 1	US0159
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)			
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)			
Singapore	Infocomm Development Authority (IDA)			
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)			
Vietnam	Ministry of Communication (MIC)			

TCB – Telecommunications Certification Bodies (TCB)

FCB – Foreign Certification Body

CAB – Conformity Assessment Body

NB – Notified Body

AB – Approved Body

MRA – Mutual Recognition Agreement

MRA Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

1.3. PRODUCT CERTIFICATION

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard ISO/IEC 17065:2012. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-02.pdf>



Accredited Product Certification Body

A2LA has accredited

MiCOM LABS

Pleasanton, CA

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC 17065:2012 Requirements for bodies certifying products, processes and services. This product certification body also meets the A2LA R322 – Specific Requirements – Notified Body Accreditation Requirements and A2LA R308 – Specific Requirements - ISO-IEC 17065 - Telecommunication Certification Body Accreditation Program. This accreditation demonstrates technical competence for a defined scope and the operation of a management system.

Presented this 24th day of February 2020



Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 2381.02
Valid to November 30, 2021



For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation.

United States of America – Telecommunication Certification Body (TCB)

Industry Canada – Certification Body, CAB Identifier – US0159

Europe – Notified Body (NB), NB Identifier - 2280

UK – Approved Body (AB), AB Identifier - 2280

Japan – Recognized Certification Body (RCB), RCB Identifier - 210



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

2. DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft	31 st May 2021	Draft for comment
Draft #2	16 th June 2021	
Rev A	24 th July 2021	Initial Release

In the above table the latest report revision will replace all earlier versions.

3. TEST RESULT CERTIFICATE

Manufacturer: Hewlett Packard Enterprise Company 3333 Scott Blvd Santa Clara, California 95054 USA	Tested By: MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
Model: ASIN0304	Telephone: +1 925 462 0304
Equipment Type: Mobile & Portable Client Device	Fax: +1 925 462 0306
S/N's: Conducted: CNLSKYV00J Radiated: CNLSKYV00D	
Test Date(s): 19 th – 24 th May 2021	Website: www.micomlabs.com

STANDARD(S)	TEST RESULTS
FCC CFR 47 Part 15 Subpart C 15.247 (DTS) Bluetooth Low Energy (BLE)	EQUIPMENT COMPLIES

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.

Approved & Released for MiCOM Labs, Inc. by:

Graeme Grieve
Quality Manager MiCOM Labs, Inc.



Gordon Hurst
President & CEO MiCOM Labs, Inc.

4. REFERENCES AND MEASUREMENT UNCERTAINTY

4.1. Normative References

REF.	PUBLICATION	YEAR	TITLE
I	KDB 662911 D01 & D02	Oct 31 2013	Guidance for measurement of output emission of devices that employ single transmitter with multiple outputs or systems with multiple transmitters operating simultaneously in the same frequency band
II	KDB 558074 D01 v05r02	2nd April 2019	Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices operating under section 15.247 of the FCC Rules.
III	A2LA	5th October 2020	R105 - Requirement's When Making Reference to A2LA Accreditation Status
IV	ANSI C63.10	2013	American National Standard for Testing Unlicensed Wireless Devices
V	ANSI C63.4	2014	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
VI	CISPR 32	2015	Electromagnetic compatibility of multimedia equipment - Emission requirements
VII	ETSI TR 100 028	2001-12	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
VIII	FCC 47 CFR Part 15.247	2020	Radio Frequency Devices; Subpart C – Intentional Radiators
IX	ICES-003	Issue 7;October 15,2020	Information Technology Equipment (Including Digital Apparatus) – Limits and methods of measurement.
X	M 3003	Edition 3 Nov.2012	Expression of Uncertainty and Confidence in Measurements
XI	RSS-247 Issue 2	Feb 2017	Digital Transmission Systems (DTSs), Frequency Hopping System (FHSs) and Licence-Exempt Local Area Network (LE-LEN) Devices
XII	RSS-Gen Issue 5	2018	General Requirements for Compliance of Radio Apparatus. With Amendments 1: March 2019 and 2: Feb 2021.
XIII	FCC 47 CFR Part 2.1033	2020	FCC requirements and rules regarding photographs and test setup diagrams.
XIV	KDB 789033 D02 V02r01	14th December, 2017	Guidelines For Compliance Testing Of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E

4.2. Test and Uncertainty Procedure

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor $k = 2$, providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

5. PRODUCT DETAILS AND TEST CONFIGURATIONS

5.1. Technical Details

Details	Description
Purpose:	Test of the Hewlett Packard Enterprise Company UXI-G6C to FCC CFR 47 Part 15 Subpart C 15.247 (DTS), ISED RSS-247 Issue 2. Radio Frequency Devices; Subpart C – Intentional Radiators
Applicant:	Hewlett Packard Enterprise Company 3333 Scott Blvd Santa Clara California 95054 USA
Manufacturer:	Hewlett Packard Enterprise Company
Laboratory performing the tests:	MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
Test report reference number:	HPEN155-U5
Date EUT received:	27 th April 2021
Standard(s) applied:	FCC CFR 47 Part 15 Subpart C 15.247 (DTS) ISED RSS-247 Issue 2
Dates of test (from - to):	19 th – 24 th May 2021
No of Units Tested:	2 (1 Conducted, 1 Radiated)
Product Family Name:	Aruba User Experience Insight
Model(s):	ASIN0304, ASIN0303
Marketing Name:	UXI-G6C
Location for use:	Indoors
Declared Frequency Range(s):	2400 - 2483.5 MHz;
Type of Modulation:	GFSK
EUT Modes of Operation:	BLE: 2400 - 2483.5 MHz;
Declared Nominal Output Power (dBm):	+10 dBm
Rated Input Voltage and Current:	12Vdc, 1A
Operating Temperature Range:	0°C to + 40°C
ITU Emission Designator:	1M0G1D
Equipment Dimensions:	67.7 / 265.75 / 42.3 mm
Weight:	0.5 Kg
Hardware Rev:	DP2
Software Rev:	2.0.0.75

5.2. Scope Of Test Program

Hewlett Packard Enterprise Company ASIN0304

The scope of the test program was to test the Hewlett Packard Enterprise Company ASIN0304, UXI-G6C configurations in the frequency ranges 2400 - 2483.5 MHz; for compliance against the following specification:

FCC CFR 47 Part 15 Subpart C 15.247 (DTS)

Radio Frequency Devices; Subpart C – Intentional Radiators

ISED RSS-247 Issue 2

Digital Transmission Systems (DTSS), Frequency Hopping System (FHSs) and Licence-Exempt Local Area Network (LE-LEN) Devices

Model Tested: Model number ASIN0303 is same essential layout without LTE radios. ASIN0304 can be assumed to be worst case configuration. Per the manufacturer and unless otherwise noted, the ASIN0304 was tested as representative of the ASIN0303

5.3. Equipment Model(s) and Serial Number(s)

Type (EUT/ Support)	Equipment Description	Manufacturer	Model No.	Serial No.
EUT Conducted	Mobile & Portable Client Device	Hewlett Packard Enterprise	ASIN0304	Conducted: CNLSKYV00J
EUT Radiated	Mobile & Portable Client Device	Hewlett Packard Enterprise	ASIN0304	Radiated: CNLSKYV00D
Support	Power Supply (12V 1A)	APDI	WB-12G12R	--

5.4. Antenna Details

Type	Manufacturer	Model	Family	Gain (dBi)	BF Gain	Dir BW	X-Pol	Frequency Band (MHz)
integral	Aruba	BLE	PIFA	1.9	-	360	-	2400 - 2483.5
BF Gain - Beamforming Gain								
Dir BW - Directional BeamWidth								
X-Pol - Cross Polarization								

5.5. Cabling and I/O Ports

Port Type	Max Cable Length	# of Ports	Screened	Conn Type	Data Type	Bit Rate	Environment
dc Jack	<3m	1	No			N/A	Indoors
Ethernet PoE IN	>30m	1	No	RJ45	Digital	10, 100, 1000 MBits/s	Indoors
Micro USB	<3m	1	Yes				

5.6. Test Configurations

Results for the following configurations are provided in this report:

Operational Mode(s) (802.11a/b/g/n/ac)	Data Rate with Highest Power MBit/s	Channel Frequency (MHz)		
		Low	Mid	High
2400 - 2483.5 MHz				
BLE	1	2,402.00	2,440.00	2,480.00

5.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. NONE

5.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. NONE

6. TEST SUMMARY


List of Measurements

Test Header	Result	Data Link
6 dB & 99% Bandwidth	Complies	View Data
Conducted Output Power	Complies	View Data
Power Spectral Density	Complies	View Data
Emissions	Complies	-
(1) Conducted Emissions	Complies	-
(i) Conducted Spurious Emissions	Complies	View Data
(ii) Conducted Band-Edge Emissions	Complies	View Data
(2) Radiated Emissions	Complies	-
(i) TX Spurious & Restricted Band Emissions	Complies	View Data
(ii) Restricted Edge & Band-Edge Emissions	Complies	View Data
(3) Digital Emissions (0.03 - 1 GHz)	Complies, see MiCOM Labs Report HPEN155-G3	
(4) AC Wireline Emissions	Complies, see MiCOM Labs Report HPEN155-G3	

7. TEST EQUIPMENT CONFIGURATION(S)

7.1. Conducted RF

MiTest Automated Test System



A full system calibration was performed on the test station and any resulting system losses (or gains) were taken into account in the production of all final measurement data.




Asset#	Description	Manufacturer	Model#	Serial#	Calibration Due Date
#3 SA	MiTest Box to SA	Fairview Microwave	SCA1814-0101-72	#3 SA	4 Jun 2021
#3P1	EUT to MiTest box port 1	Fairview Microwave	SCA1814-0101-72	#3P1	4 Jun 2021
#3P2	EUT to MiTest box port 2	Fairview Microwave	SCA1814-0101-72	#3P2	4 Jun 2021
#3P3	EUT to MiTest box port 3	Fairview Microwave	SCA1814-0101-72	#3P3	4 Jun 2021
#3P4	EUT to MiTest box port 4	Fairview Microwave	SCA1812-0101-72	#3P4	4 Jun 2021
249	Thermocouple; Resistance Thermometer	Thermotronics	GR2105-02	9340 #2	30 Oct 2021
287	Rohde & Schwarz 40 GHz Receiver	Rhode & Schwarz	ESIB40	100201	8 Oct 2021
398	MiTest RF Conducted Test Software	MiCOM	MiTest ATS	Version 4.2.3.0	Not Required
405	DC Power Supply 0-60V	Agilent	6654A	MY4001826	Cal when used
408	USB to GPIB interface	National Instruments	GPIB-USB HS	14C0DE9	Not Required
440	USB Wideband Power Sensor	Boonton	55006	9178	22 Jun 2021
441	USB Wideband Power Sensor	Boonton	55006	9179	20 Jun 2021
442	USB Wideband Power Sensor	Boonton	55006	9181	19 Jun 2021
445	PoE Injector	D-Link	DPE-101GL	QTAH1E2000625	Not Required
461	Spectrum Analyzer	Agilent	E4440A	MY46185537	20 Jun 2021
510	Barometer/Thermometer	Control Company	68000-49	170871375	20 Dec 2021
515	MiTest Cloud Solutions RF Test Box	MiCOM	2nd Gen with DFS	515	4 Jun 2021
75	Environmental Chamber	Thermatron	SE-300-2-2	27946	20 Feb 2022


7.2. Radiated Emissions - 3m Chamber

The following tests were performed using the radiated test set-up shown in the diagram below. Radiated emissions above and below 1GHz.

Radiated Emissions Above 1GHz Test Setup



Radiated Emissions Below 1GHz Test Setup





Test Equipment Utilized


Asset#	Description	Manufacturer	Model#	Serial#	Calibration Due Date
170	Video System Controller for Semi Anechoic Chamber	Panasonic	WV-CU101	04R08507	Not Required
287	Rohde & Schwarz 40 GHz Receiver	Rhode & Schwarz	ESIB40	100201	8 Oct 2021
298	3M Radiated Emissions Chamber Maintenance Check	MiCOM	3M Chamber	298	26 Sep 2021
338	Sunol 30 to 3000 MHz Antenna	Sunol	JB3	A052907	4 Oct 2021
397	Amp 10 - 2500MHz	MiCOM Labs	Amp 10 - 2500 MHz	NA	9 Sep 2021
399	ETS 1-18 GHz Horn Antenna	ETS	3117	00154575	12 Sep 2021
406	Amplifier for Radiated Emissions	MiCOM Labs	40dB 1 to 18GHz Amp	0406	9 Sep 2021
410	Desktop Computer	Dell	Inspiron 620	WS38	Not Required
411	Mast/Turntable Controller	Sunol Sciences	SC98V	060199-1D	Not Required
412	USB to GPIB Interface	National Instruments	GPIB-USB HS	11B8DC2	Not Required
413	Mast Controller	Sunol Science	TWR95-4	030801-3	Not Required
415	Turntable Controller	Sunol Sciences	Turntable Controller	None	Not Required
447	MiTest Rad Emissions Test Software	MiCOM	Rad Emissions Test Software Version 1.0	447	Not Required
462	Schwarzbeck cable from Antenna to Amplifier.	Schwarzbeck	AK 9513	462	4 Sep 2021
463	Schwarzbeck cable from Amplifier to Bulkhead.	Schwarzbeck	AK 9513	463	4 Sep 2021
464	Schwarzbeck cable from Bulkhead to Receiver	Schwarzbeck	AK 9513	464	4 Sep 2021
466	Low Pass Filter DC-1500 MHz	Mini-Circuits	NLP-1750+	VUU10401438	4 Sep 2021
476	Low Pass dc-2200MHz filter	Mini Circuits	15542 NLP-2400+	VUU13801345	4 Sep 2021
480	Cable - Bulkhead to Amp	SRC Haverhill	157-3050360	480	4 Sep 2021
481	Cable - Bulkhead to Receiver	SRC Haverhill	151-3050787	481	4 Sep 2021
510	Barometer/Thermometer	Control Company	68000-49	170871375	20 Dec 2021
518	Cable - Amp to Antenna	SRC Haverhill	157-3051574	518	4 Sep 2021
CC05	Confidence Check	MiCOM	CC05	None	4 Sep 2021

8. MEASUREMENT AND PRESENTATION OF TEST DATA

The measurement and graphical data presented in this test report was generated automatically using state-of-the-art technology creating an easy-to-read report structure. Numerical measurement data is separated from supporting graphical data (plots) through hyperlinks. Numerical measurement data can be reviewed without scrolling through numerous graphical pages to arrive at the next data matrix.

Plots have been relegated into the Appendix 'Graphical Data'.

Test and report automation was performed by [MiTest](#). [MiTest](#) is an automated test system developed by MiCOM Labs. [MiTest](#) is the first cloud based modular test system enabling end-to-end automation of regulatory compliance testing for conducted RF testing.



The MiCOM Labs "[MiTest](#)" Automated Test System" (Patent Pending)

9. TEST RESULTS

9.1. 6 dB & 99% Bandwidth

Conducted Test Conditions for 6 dB and 99% Bandwidth			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	6 dB and 99 % Bandwidth	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (a)(2)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for 6 dB and 99% Bandwidth Measurement
The bandwidth at 6 dB and 99 % was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

Testing was performed under ambient conditions at nominal voltage. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits for 6 dB and 99% Bandwidth

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(2) Systems using digital modulation techniques may operate in the 902-928 MHz and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for 6 dB & 99% Bandwidth

Variant:	BLE	Duty Cycle (%):	61.6
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	GMH
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
	Port(s)							
MHz	a	b	c	d	Highest	Lowest	KHz	MHz
2402.0	0.690	--	--	--	0.690	0.690	500.00	-0.190
2440.0	0.697	--	--	--	0.697	0.697	500.00	-0.197
2480.0	0.693	--	--	--	0.693	0.693	500.00	-0.193

Test Frequency	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)			
	Port(s)							
MHz	a	b	c	d				
2402.0	1.043	--	--	--	1.043			
2440.0	1.043	--	--	--	1.043			
2480.0	1.044	--	--	--	1.044			

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

9.2. Conducted Output Power

Conducted Test Conditions for Fundamental Emission Output Power			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Output Power	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (b) & (c)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Fundamental Emission Output Power Measurement
 In the case of average power measurements an average power sensor was utilized.

For peak power measurements the spectrum analyzer built-in power function was used to integrate peak power over the 20 dB bandwidth.

Testing was performed under ambient conditions at nominal voltage only. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured, summed (Σ) and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.
 Supporting Information

Calculated Power = $A + G + Y + 10 \log (1/x)$ dBm

A = Total Power [$10^{\log_{10} (10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10})}$]

G = Antenna Gain

Y = Beamforming Gain

x = Duty Cycle (average power measurements only)

Limits for Fundamental Emission Output Power

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following for non-frequency hopping systems:

(3) For systems using digital modulation in the 902-928 MHz and 2400-2483.5 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(iii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

(2) In addition to the provisions in paragraphs (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400-2483.5

MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:

- (i) Different information must be transmitted to each receiver.
- (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
 - (A) The directional gain shall be calculated as the sum of $10 \log$ (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
 - (B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.
- (iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.
- (iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for Average Output Power

Variant:	BLE	Duty Cycle (%):	61.6
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	1.90
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	GMH
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Output Power (dBm)				Calculated Total Power Σ Port(s)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	dBm	dBm	dB	
2402.0	6.98	--	--	--	6.98	30.00	-23.02	10.00
2440.0	6.97	--	--	--	6.97	30.00	-23.03	10.00
2480.0	6.95	--	--	--	6.95	30.00	-23.05	10.00

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

The above Average Output Power was measured via a power sensor that returned a power measurement based on pulsed RF power. No Duty Cycling correction factor is required.

9.3. Power Spectral Density

Conducted Test Conditions for Power Spectral Density			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Power Spectral Density	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (e)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Power Spectral Density

The transmitter output was connected to a spectrum analyzer and the measured made in a 3 kHz resolution bandwidth using the analyzer auto-coupled sweep-time. A peak value was found over the full emission bandwidth and the spectrum downloaded for post processing purposes.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. The Peak Power Spectral Density is the highest level found across the emission bandwidth. With multiple antenna port measurements the numerical analyzer data from each port is summed (a) and a link to this additional graphic is provided.

Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Measure and sum the spectra across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The individual spectra are then summed mathematically in linear power units. Unlike in-band power measurements, in which the sum involves a single measured value (output power) from each output, measurements for compliance with PSD limits involve summing entire spectra across corresponding frequency bins on the various outputs. Consistency is maintained for any device with multiple transmitter outputs to be certain the individual outputs are all aligned with the same span and same number of points. In this instance, the linear power spectrum value within the first spectral bin of output 0 is summed with that in the first spectral bin of output 1, and the first spectral bin of output 2, and so on up to the Nth output to obtain the true value for the first frequency bin of the summed spectrum. The summed spectrum value for each frequency bin is computed in this fashion. These summed spectral values were post processed and the resulting numerical and graphical data presented.

NOTE:

It may be observed that the spectrum in some antenna port plots break the limit line however this in itself does NOT constitute a failure. In all cases a spectrum summation plot is provided in order to prove compliance. A failure occurs only after the summation of all spectrum plots have been summed and are found to be greater than the limit line.

Supporting Information

Calculated Power = $A + 10 \log (1/x)$ dBm

$A = \text{Total Power Spectral Density} [10 \log_{10} (10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10})]$

$x = \text{Duty Cycle}$

Limits Power Spectral Density

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for Power Spectral Density - Average

Variant:	BLE	Duty Cycle (%):	61.6
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	1.90
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	GMH
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Power Spectral Density				Amplitude Summation + DCCF (+2.1 dB)	Limit	Margin
	Port(s) (dBm/3KHz)						
MHz	a	b	c	d	dBm/3KHz	dBm/3KHz	dB
2402.0	-11.789	--	--	--	-9.706	8.0	-17.7
2440.0	-11.942	--	--	--	-9.859	8.0	-17.9
2480.0	-12.443	--	--	--	-10.360	8.0	-18.4

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

[DCCF - Duty Cycle Correction Factor](#)

Note: click the links in the above matrix to view the graphical image (plot).

9.4. Emissions

9.4.1. Conducted Emissions

9.4.1.1. Conducted Spurious Emissions

Conducted Test Conditions for Transmitter Conducted Spurious and Band-Edge Emissions			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Max Unwanted Emission Levels	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (d)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Transmitter Conducted Spurious and Band-Edge Emissions Measurement

Transmitter Conducted Spurious and Band-Edge emissions were measured at a limit of 30 dBc (average detector) or 20 dBc (peak detector) below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Measurements were made while EUT was operating in transmit mode of operation at the appropriate centre frequency closest to the band-edge. Emissions were maximized during the measurement and limits derived from the peak spectral power and drawn on each plot.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits Transmitter Conducted Spurious and Band-Edge Emissions

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for Conducted Spurious Emissions - Average

Variant:	BLE	Duty Cycle (%):	61.6
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable	Tested By:	GMH
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Frequency Range	Conducted Spurious Emissions - Average (dBm)							
		Port a		Port b		Port c		Port d	
MHz	MHz	SE	Limit	SE	Limit	SE	Limit	SE	Limit
2402.0	30.0 - 26000.0	-58.175	-50.15	--	--	--	--	--	--
2440.0	30.0 - 26000.0	-20.103	-50.10	--	--	--	--	--	--
2480.0	30.0 - 26000.0	-20.619	-50.62	--	--	--	--	--	--

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

9.4.1.2. Conducted Band-Edge Emissions

Conducted Test Conditions for Transmitter Conducted Spurious and Band-Edge Emissions			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Max Unwanted Emission Levels	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (d)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Transmitter Conducted Spurious and Band-Edge Emissions Measurement

Transmitter Conducted Spurious and Band-Edge emissions were measured at a limit of 30 dBc (average detector) or 20 dBc (peak detector) below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Measurements were made while EUT was operating in transmit mode of operation at the appropriate centre frequency closest to the band-edge. Emissions were maximized during the measurement and limits derived from the peak spectral power and drawn on each plot.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits Transmitter Conducted Spurious and Band-Edge Emissions

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for Conducted Low Band-Edge Emissions - Average

Variant:	BLE	Duty Cycle (%):	61.6
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	GMH
Engineering Test Notes:			

Test Measurement Results

Channel Frequency:	2402.0 MHz				
Band-Edge Frequency:	2400.0 MHz				
Test Frequency Range:	2350.0 - 2405.0 MHz				
Port(s)	Band-Edge Markers and Limit			Revised Limit	Margin
	M1 Amplitude (dBm)	Plot Limit (dBm)	M2 Frequency (MHz)	Amplitude (dBm)	M2A Frequency (MHz)
a	-58.77	-30.79	2401.20	--	--

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for Conducted High Band-Edge Emissions - Average

Variant:	BLE	Duty Cycle (%):	61.6
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	GMH
Engineering Test Notes:			

Test Measurement Results

Channel Frequency:	2480.0 MHz				
Band-Edge Frequency:	2483.5 MHz				
Test Frequency Range:	2475.0 - 2524.0 MHz				
Port(s)	Band-Edge Markers and Limit			Revised Limit	Margin
	M3 Amplitude (dBm)	Plot Limit (dBm)	M2 Frequency (MHz)	Amplitude (dBm)	M2A Frequency (MHz)
a	-62.74	-31.21	2480.60	--	--

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

9.4.2. Radiated Emissions

9.4.2.1. TX Spurious & Restricted Band Emissions

Radiated Test Conditions for Radiated Spurious and Band-Edge Emissions (Restricted Bands)			
Standard:	FCC CFR 47 Part 15 Subpart C 15.247 (DTS)	Ambient Temp. (°C):	20.0 - 24.5
Test Heading:	Radiated Spurious and Band-Edge Emissions	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.205, 15.209	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Radiated Spurious and Band-Edge Emissions (Restricted Bands)

Radiated emissions for restricted bands above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned. Measurements on any restricted band frequency or frequencies above 1 GHz are based on the use of measurement instrumentation employing peak and average detectors. All measurements were performed using a resolution bandwidth of 1 MHz.

Test configuration and setup for Radiated Spurious and Band-Edge Measurement were per the Radiated Test Set-up specified in this document.

Orientation testing of the EUT was performed and the EUT standing upright was determined to be the worst case for Spurious and Band Edge emissions with the integral antennas attached.

Limits for Restricted Bands

Peak emission: 74 dBuV/m

Average emission: 54 dBuV/m

Average Measurements were performed following ANSI C63.10 section 11.12.2.5.2 Trace averaging across on and off times of the EUT transmissions followed by a duty cycle correction.

RMS detector used, DCCF of $10\log(1/D)$ where D is the Duty Cycle.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where:

FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL - AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

Example:

Given receiver input reading of 51.5 dBmV; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength (FS) of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dBmV/m}$$

Conversion between dBmV/m (or dBmV) and mV/m (or mV) are as follows:

$$\text{Level (dBmV/m)} = 20 * \log(\text{level (mV/m)})$$

$$40 \text{ dBmV/m} = 100 \text{ mV/m}$$

$$48 \text{ dBmV/m} = 250 \text{ mV/m}$$

Restricted Bands of Operation (15.205)

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Frequency Band			
MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

(b) Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e) of this section, regardless of the field strength limits specified elsewhere in this subpart, the provisions of this section apply to emissions from any intentional radiator.

(d) The following devices are exempt from the requirements of this section:

- (1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a) of this section, the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a) of this section, and the fundamental emission is outside of the bands listed in paragraph (a) of this section more than 99% of the time the device is actively transmitting, without compensation for duty cycle.
- (2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.
- (3) Cable locating equipment operated pursuant to §15.213.
- (4) Any equipment operated under the provisions of §15.253, 15.255, and 15.256 in the frequency band 75-85 GHz, or §15.257 of this part.
- (5) Biomedical telemetry devices operating under the provisions of §15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.
- (6) Transmitters operating under the provisions of subparts D or F of this part.
- (7) Devices operated pursuant to §15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.
- (8) Devices operated in the 24.075-24.175 GHz band under §15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in §15.245(b).
- (9) Devices operated in the 24.0-24.25 GHz band under §15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in §15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of §15.245 shall not exceed the limits specified in §15.245(b).



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba BLE	Variant:	BLE
Antenna Gain (dBi):	1.90	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	61.6
Channel Frequency (MHz):	2402.00	Data Rate:	1.00 MBit/s
Power Setting:	8	Tested By:	JMH

Test Measurement Results

[Click here to view measurement data...](#)

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber.



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba BLE	Variant:	BLE
Antenna Gain (dBi):	1.90	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	61.6
Channel Frequency (MHz):	2440.00	Data Rate:	1.00 MBit/s
Power Setting:	8	Tested By:	JMH

Test Measurement Results

[Click here to view measurement data...](#)

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber.



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba BLE	Variant:	BLE
Antenna Gain (dBi):	1.90	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	61.6
Channel Frequency (MHz):	2480.00	Data Rate:	1.00 MBit/s
Power Setting:	8	Tested By:	JMH

Test Measurement Results

[Click here to view measurement data...](#)

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber.



Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

9.4.2.2. Restricted Edge & Band-Edge Emissions

Aruba BLE		Band-Edge Freq		Limit 74.0dB μ V/m		Limit 54.0dB μ V/m		Power Setting
Operational Mode	Operating Frequency (MHz)	MHz		dB μ V/m		dB μ V/m		
GFSK	2402.00	2390.00		49.65		36.23		8
GFSK	2480.00	2483.50		50.55		36.68		8

Equipment Configuration for Radiated - Lower Restricted Band-Edge Emissions

Antenna:	Aruba BLE	Variant:	BLE
Antenna Gain (dBi):	Not Applicable	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2402.00	Data Rate:	1.00 MBit/s
Power Setting:	8	Tested By:	JMH

Test Measurement Results

2310.00 - 2422.00 MHz													
Num	Frequency MHz	Raw dB μ V	Cable Loss dB	AF dB/m	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail	
#1	2378.91	15.74	2.01	31.90	49.65	Max Peak	Horizontal	153	22	74.0	-24.4	Pass	
#2	2385.74	4.36	2.01	31.94	38.31	Max Avg	Horizontal	153	22	54.0	-15.72	Pass	
#3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--	

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber. Avg Measurement includes DCCF of 2.08

Equipment Configuration for Radiated - Upper Restricted Band-Edge Emissions

Antenna:	Aruba BLE	Variant:	BLE
Antenna Gain (dBi):	1.90	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	61.6
Channel Frequency (MHz):	2480.00	Data Rate:	1.00 MBit/s
Power Setting:	8	Tested By:	JMH

Test Measurement Results

2452.00 - 2520.00 MHz													
Num	Frequency MHz	Raw dB μ V	Cable Loss dB	AF dB/m	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail	
#2	2497.38	16.19	2.04	32.32	50.55	Max Peak	Horizontal	153	22	74.0	-23.5	Pass	
#3	2502.97	4.39	2.05	32.32	38.76	Max Avg	Horizontal	153	22	54.0	-15.22	Pass	
#1	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--	

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber. Avg Measurement includes DCCF of 2.08




Title: Hewlett Packard Enterprise Company ASIN0304
To: FCC Part 15 Subpart C 15.247 (DTS), ISED 15-247 Issue 2
Serial #: HPEN155-U5 Rev A (BLE)

A. APPENDIX - GRAPHICAL IMAGES


A.1. Duty Cycle

BLE Duty Cycle



Return to matrix: [BLE Duty Cycle = 385.8/626.3 = 61.6% = 2.1 dB](#)

A.2. 6 dB & 99% Bandwidth




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = POS Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAXH	M1 : 2401.643 MHz : 1.675 dBm M2 : 2402.010 MHz : 7.646 dBm Delta1 : 690 KHz : 0.102 dB T1 : 2401.470 MHz : -5.758 dBm T2 : 2402.510 MHz : -5.685 dBm OBW : 1.043 MHz	Measured 6 dB Bandwidth: 0.690 MHz Limit: kHz Margin: #VALUE! MHz

[back to matrix](#)

6 dB & 99% BANDWIDTH



Variant: BLE, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = POS Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAXH	M1 : 2439.637 MHz : 1.991 dBm M2 : 2440.013 MHz : 7.936 dBm Delta1 : 697 KHz : 0.109 dB T1 : 2439.470 MHz : -5.420 dBm T2 : 2440.510 MHz : -5.508 dBm OBW : 1.043 MHz	Measured 6 dB Bandwidth: 0.697 MHz Limit: kHz Margin: #VALUE! MHz

[back to matrix](#)

6 dB & 99% BANDWIDTH




Variant: BLE, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = POS Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAXH	M1 : 2479.640 MHz : 1.364 dBm M2 : 2480.010 MHz : 7.356 dBm Delta1 : 693 KHz : 0.118 dB T1 : 2479.470 MHz : -6.015 dBm T2 : 2480.510 MHz : -6.030 dBm OBW : 1.044 MHz	Measured 6 dB Bandwidth: 0.693 MHz Limit: kHz Margin: #VALUE! MHz

[back to matrix](#)

A.3. Power Spectral Density




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.860 MHz : -11.789 dBm	Limit: ≤ 8.000 dBm

[back to matrix](#)

POWER SPECTRAL DENSITY - AVERAGE



Variant: BLE, Channel: 2402.00 MHz, SUM, Temp: 20, Voltage: 12 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.900 MHz : -11.789 dBm M1 + DCCF : 2401.900 MHz : -9.706 dBm Duty Cycle Correction Factor : +2.08 dB	Limit: ≤ 8.0 dBm Margin: -17.7 dB

[back to matrix](#)

POWER SPECTRAL DENSITY - AVERAGE




Variant: BLE, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2439.967 MHz : -11.942 dBm	Limit: ≤ 8.000 dBm

[back to matrix](#)

POWER SPECTRAL DENSITY - AVERAGE




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2440.000 MHz : -11.942 dBm M1 + DCCF : 2440.000 MHz : -9.859 dBm Duty Cycle Correction Factor : +2.08 dB	Limit: ≤ 8.0 dBm Margin: -17.9 dB

[back to matrix](#)

POWER SPECTRAL DENSITY - AVERAGE



Variant: BLE, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2479.969 MHz : -12.443 dBm	Limit: ≤ 8.000 dBm

[back to matrix](#)

POWER SPECTRAL DENSITY - AVERAGE



Variant: BLE, Channel: 2480.00 MHz, SUM, Temp: 20, Voltage: 12 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2480.000 MHz : -12.443 dBm M1 + DCCF : 2480.000 MHz : -10.360 dBm Duty Cycle Correction Factor : +2.08 dB	Limit: ≤ 8.0 dBm Margin: -18.4 dB

[back to matrix](#)

A.4. Emissions


A.4.1. Conducted Emissions

A.4.1.1. Conducted Spurious Emissions

CONDUCTED SPURIOUS EMISSIONS - AVERAGE



Variant: BLE, Channel: 2402.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2410.000 MHz : -20.150 dBm M2 : 13.620 GHz : -58.175 dBm	Limit: -50.15 dBm Margin: -8.02 dB

[back to matrix](#)

CONDUCTED SPURIOUS EMISSIONS - AVERAGE



Variant: BLE, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2450.000 MHz : -20.103 dBm M2 : 2450.000 MHz : -20.103 dBm	Limit: -50.10 dBm Margin: 30.00 dB

[back to matrix](#)

CONDUCTED SPURIOUS EMISSIONS - AVERAGE




Variant: BLE, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2500.000 MHz : -20.619 dBm M2 : 2500.000 MHz : -20.619 dBm	Limit: -50.62 dBm Margin: 30.00 dB

[back to matrix](#)

A.4.1.2. Conducted Band-Edge Emissions




Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -58.774 dBm M2 : 2401.240 MHz : -34.013 dBm M3 : 2401.980 MHz : -0.794 dBm	Channel Frequency: 2402.00 MHz

[back to matrix](#)

CONDUCTED HIGH BAND-EDGE EMISSIONS - AVERAGE



Variant: BLE, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 12 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = AVER Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2479.980 MHz : -1.206 dBm M2 : 2480.630 MHz : -22.848 dBm M3 : 2483.500 MHz : -62.739 dBm	Channel Frequency: 2480.00 MHz

[back to matrix](#)


A.4.2. Radiated Emissions

A.4.2.3. TX Spurious & Restricted Band Emissions



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: BLE, Test Freq: 2402.00 MHz, Antenna: Aruba BLE, Power Setting: 8, Duty Cycle (%):61.6




There are no emissions found within 6dB of the limit line.

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber.

[back to matrix](#)

TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: BLE, Test Freq: 2440.00 MHz, Antenna: Aruba BLE, Power Setting: 8, Duty Cycle (%):61.6



There are no emissions found within 6dB of the limit line.


Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber.

[back to matrix](#)



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: BLE, Test Freq: 2480.00 MHz, Antenna: Aruba BLE, Power Setting: 8, Duty Cycle (%): 61.6




There are no emissions found within 6dB of the limit line.

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber.

[back to matrix](#)

A.4.2.4. Restricted Edge & Band-Edge Emissions




2310.00 - 2422.00 MHz													
Num	Frequency MHz	Raw dB μ V	Cable Loss dB	AF dB/m	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail	
1	2378.91	15.74	2.01	31.90	49.65	Max Peak	Horizontal	153	22	74.0	-24.4	Pass	
2	2385.74	4.36	2.01	31.94	38.31	Max Avg	Horizontal	153	22	54.0	-15.72	Pass	
3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--	

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber. Avg Measurement includes DCCF of 2.08

[back to matrix](#)

RADIATED - UPPER RESTRICTED BAND-EDGE EMISSIONS

Variant: BLE, Test Freq: 2480.00 MHz, Antenna: Aruba BLE, Power Setting: 8, Duty Cycle (%):61.6



2452.00 - 2520.00 MHz													
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB/m	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail	
2	2497.38	16.19	2.04	32.32	50.55	Max Peak	Horizontal	153	22	74.0	-23.5	Pass	
3	2502.97	4.39	2.05	32.32	38.76	Max Avg	Horizontal	153	22	54.0	-15.22	Pass	
1	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--	

Test Notes: EUT powered by AC/DC ps. Connected to laptop outside chamber. Avg Measurement includes DCCF of 2.08

[back to matrix](#)



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com