

User's Manual

PM FBT T5 28

Application and performance specification

Electronic ballast for T5 28W

Description

Active power factor correction. $PF \geq 0.99$

Low harmonic distortion . $THD \leq 10\%$

Low lamp current crest factor. $CF \leq 1.6$

Warn (Rapid) start.

Long Life

De-active lamp protection

Model	Line Volts	Lamp type	Input watts	Nominal Lineamps	Power factor	Harmonic total	Crest factor
PMFBTT528	120V/60Hz	T528W	33W	0.28A	0.99	<10%	<1.6

Performance

Meets FCC Part 18 (Class A) for EMI
Non-consumer limits

Application:

Minimum starting temperature -18°C

Maximum ambient temperature 40°C

Maximum case temperature 75°C

Safety

UL listed

Physical parameters

Mounting length 226mm
(center to center)

Overall length 240mm

Weight 42mm

Height 30mm

This light device has been tested and found to comply with the limits for Consumer RF Lighting Device, pursuant to Part 18 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

1. Use only on 120 volt, 60 hertz.
2. Never disassemble or modify - any changes could void the user's authority to operate this device.
3. Not for use in totally enclosed fixtures.
4. Risk of electric shock - do not use where directly exposed to water.
5. This device is not intended for use with emergency exit fixtures or emergency exit lights.
6. This product could produce interference when used near a TV, radio, wireless remote control or maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30 MHz. If interference should occur, move the lamp away from the appliance a distance of three feet or more. Or, plug the lamp or the appliance into a different outlet.
7. To prevent burns, do not touch the bulb during operation or immediately after switching off.
8. Not for use with dimmers, electronic timer or photocell devices or occupancy sensor.

Warranty

Universal lighting technologies warrants to the purchaser that each electronics ballast will be marched with the lamp (T5 28W) and free from defects in material or workmanship for a period of 5 years from date of manufacture when properly installed and under normal condition of use.