

Report on the Radio Testing
For
Controlled Electronic Management Systems Limited
on
S700 Access Control Reader
Report no. TRA-032043-47-02A
25th January 2017

Report Number: TRA-032043-47-02A
Issue: A

REPORT ON THE RADIO TESTING OF A
Controlled Electronic Management Systems Limited
S700 Access Control Reader
WITH RESPECT TO SPECIFICATION
FCC 47CFR 15.209

TEST DATE: 5th - 9th January 2017

Tested by: D Winstanley

D Winstanley
Senior Radio Test Engineer

Approved by:

J Charters
Department Manager - Radio

Date: 25th January 2017

Disclaimers:

- [1] THIS DOCUMENT MAY BE REPRODUCED ONLY IN ITS ENTIRETY AND WITHOUT CHANGE
- [2] THE RESULTS CONTAINED IN THIS DOCUMENT RELATE ONLY TO THE ITEM(S) TESTED

RF914 4.0

1 Revision Record

<i>Issue Number</i>	<i>Issue Date</i>	<i>Revision History</i>
A	25th January 2017	Original

2 Summary

TEST REPORT NUMBER:	TRA-032043-47-02A
WORKS ORDER NUMBER	TRA-032043-11
PURPOSE OF TEST:	USA: Testing of radio frequency equipment per the relevant authorization procedure of chapter 47 of CFR (code of federal regulations) Part 2, subpart J..
TEST SPECIFICATION(S):	47CFR15.209
EQUIPMENT UNDER TEST (EUT):	S700 Access Control Reader
FCC IDENTIFIER:	QABS700V1-00
EUT SERIAL NUMBER:	#004
MANUFACTURER/AGENT:	Controlled Electronic Management Systems Limited
ADDRESS:	Mailpoint 1006 PO Box 3572 Stone ST15 9DX United Kingdom
CLIENT CONTACT:	Tim Harrison ☎ 9078 8027 ✉ tiharrison@tycoint.com
TEST DATE:	5th - 9th January 2017
TESTED BY:	D Winstanley Element

2.1 Test Summary

<i>Test Method and Description</i>	<i>Requirement Clause 47CFR15</i>	<i>Applicable to this equipment</i>	<i>Result / Note</i>
Radiated spurious emissions, below 30 MHz	15.209	☒	Pass
Radiated spurious emissions	15.209	☒	Pass
AC power line conducted emissions	15.207	☒	Pass
Occupied bandwidth	15.215(c)	☒	Pass
Field strength of fundamental	15.209	☒	Pass

Notes:

The results contained in this report relate only to the items tested, in the condition at time of test, and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only. Any modifications made are identified in Section 8 of this report.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 5.2 of this test report (Deviations from Test Standards).

3 Contents

1	Revision Record	3
2	Summary	4
2.1	Test Summary	5
3	Contents	6
4	Introduction	7
5	Test Specifications	8
5.1	Normative References	8
5.2	Deviations from Test Standards	8
6	Glossary of Terms	9
7	Equipment Under Test	10
7.1	EUT Identification	10
7.2	System Equipment	10
7.3	EUT Mode of Operation	10
7.3.1	Transmission	10
7.4	EUT Radio Parameters	10
7.4.1	General	10
7.5	EUT Description	10
8	Modifications	11
9	EUT Test Setup	11
9.1	Block Diagram	11
9.2	General Set-up Photograph	12
10	General Technical Parameters	13
10.1	Normal Conditions	13
10.2	Varying Test Conditions	13
11	Radiated emissions below 30 MHz	14
11.1	Definitions	14
11.2	Test Parameters	14
11.3	Test Limit	15
11.4	Test Method	15
11.5	Test Set-up Photograph	16
11.6	Test Equipment	16
11.7	Test Results	17
12	Radiated emissions	18
12.1	Definitions	18
12.2	Test Parameters	18
12.3	Test Limit	18
12.4	Test Method	19
12.5	Test Set-up Photograph	20
12.6	Test Equipment	20
12.7	Test Results	21
13	AC power-line conducted emissions	23
13.1	Definition	23
13.2	Test Parameters	23
13.3	Test Limit	23
13.4	Test Method	24
13.5	Test Set-up Photograph	24
13.6	Test Equipment	25
13.7	Test Results	25
14	Occupied Bandwidth	27
14.1	Definition	27
14.2	Test Parameters	27
14.3	Test Limit	28
14.4	Test Method	28
14.5	Test Equipment	28
14.6	Test Results	29
15	Transmitter output power (fundamental radiated emission)	31
15.1	Definition	31
15.2	Test Parameters	31
15.3	Test Limit	31
15.4	Test Method	32
15.5	Test Equipment	32
15.6	Test Results	32
16	Measurement Uncertainty	33
17	General SAR test reduction and exclusion guidance/RF Exposure	34

4 Introduction

This report TRA-032043-47-02A presents the results of the Radio testing on a Controlled Electronic Management Systems Limited, S700 Access Control Reader to specification 47CFR15 Radio Frequency Devices

The testing was carried out for Controlled Electronic Management Systems Limited by Element, at the address(es) detailed below.

☐	Element Hull Unit E South Orbital Trading Park Hedon Road Hull HU9 1NJ UK	☒	Element Skelmersdale Unit 1 Pendle Place Skelmersdale West Lancashire WN8 9PN UK
--------------------------	---	-------------------------------------	--

This report details the configuration of the equipment, the test methods used and any relevant modifications where appropriate.

All test and measurement equipment under the control of the laboratory and requiring calibration is subject to an established programme and procedures to control and maintain measurement standards. The quality management system meets the principles of ISO 9001, and has quality control procedures for monitoring the validity of tests undertaken. Records and sufficient detail are retained to establish an audit trail of calibration records relating to its test results for a defined period. Under control of the established calibration programme, key quantities or values of the test & measurement instrumentation are within specification and comply with the relevant traceable internationally recognised and appropriate standard specifications, which are UKAS calibrated as such where these properties have a significant effect on results. Participation in inter-laboratory comparisons and proficiency testing ensures satisfactory correlation of results conform to Elements own procedures, as well as statistical techniques for analysis of test data providing the appropriate confidence in measurements.

FCC Site Listing:

Element is accredited for the above sites under the US-EU MRA, Designation number UK0009.

ISED Registration Number(s):

Element Skelmersdale	3930B
Element Hull	3483A

The test site requirements of ANSI C63.4-2014 are met up to 1 GHz.

The test site SVSWR requirements of CISPR 16-1-4:2010 are met over the frequency range 1 GHz to 18 GHz.

5 Test Specifications

5.1 Normative References

- FCC 47 CFR Ch. I – Part 15 – Radio Frequency Devices.
- ANSI C63.10-2013 – American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
- ANSI C63.4-2014 – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

5.2 Deviations from Test Standards

There were no deviations from the test standard.

6 Glossary of Terms

§	denotes a section reference from the standard, not this document
AC	Alternating Current
ANSI	American National Standards Institute
BW	bandwidth
C	Celsius
CFR	Code of Federal Regulations
CW	Continuous Wave
dB	decibel
dBm	dB relative to 1 milliwatt
DC	Direct Current
DSSS	Direct Sequence Spread Spectrum
EIRP	Equivalent Isotropically Radiated Power
ERP	Effective Radiated Power
EUT	Equipment Under Test
FCC	Federal Communications Commission
FHSS	Frequency Hopping Spread Spectrum
Hz	hertz
IC	Industry Canada (nowISED)
ISED	Innovation, Science and Economic Development Canada
ITU	International Telecommunication Union
LBT	Listen Before Talk
m	metre
max	maximum
MIMO	Multiple Input and Multiple Output
min	minimum
MRA	Mutual Recognition Agreement
N/A	Not Applicable
PCB	Printed Circuit Board
PDF	Portable Document Format
Pt-mpt	Point-to-multipoint
Pt-pt	Point-to-point
RF	Radio Frequency
RH	Relative Humidity
RMS	Root Mean Square
Rx	receiver
s	second
SVSWR	Site Voltage Standing Wave Ratio
Tx	transmitter
UKAS	United Kingdom Accreditation Service
V	volt
W	watt
Ω	ohm

7 Equipment Under Test

7.1 EUT Identification

- Name: S700 Access Control Reader
- Serial Number: #004
- Model Number: S700 / DUAL TECH (125 kHz & 13.56 MHz)
- Software Revision: MCP V0.3.3 / KEYPAD V2.5.1
- Build Level / Revision Number: MCP – REV C // MAINBOARD – REV D // TOUCH PCB - REV D // IO PCB - REV C

7.2 System Equipment

Equipment listed below forms part of the overall test setup and is required for equipment functionality and/or monitoring during testing. The compliance levels achieved in this report relate only to the EUT and not items given in the following list.

	<i>Description</i>	<i>Make</i>	<i>Model</i>	<i>Serial Number</i>
1	Laptop	Dell	Latitude E5440	7F3KK12
2	Ethernet Switch	NETGEAR	FS105V2	1D52253X000C2
3	Door Simulator	CEM	Ver 1	N/A
4	Magnetic Lock	Generic	Generic	N/A

7.3 EUT Mode of Operation

7.3.1 Transmission

The mode of operation for Tx tests was as follows...

Test	Description of Operating Mode
All tests detailed in this report	EUT actively transmitting either waiting for a tag to be presented or reading a tag as required.

7.4 EUT Radio Parameters

7.4.1 General

Frequency of operation:	125 kHz & 13.56 MHz
Antenna:	Integral
Nominal Supply Voltage:	12 Vdc

7.5 EUT Description

The EUT is a Multifunction IP Access Terminal. It contains a 125 kHz and a 13.56 MHz RFID Reader which transmit alternately. This report covers the 125 kHz operation only.


8 Modifications

No modifications were performed during this assessment.

9 EUT Test Setup


9.1 Block Diagram

The following diagram shows basic EUT interconnections with cable type and cable lengths identified:



9.2 General Set-up Photograph

The following photograph shows basic EUT set-up:



10 General Technical Parameters

10.1 Normal Conditions

The E U T was tested under the normal environmental conditions of the test laboratory, except where otherwise stated. The normal power source applied was approx. 12 V dc from a battery.

10.2 Varying Test Conditions

Variation of temperature is required to ensure stability of the declared fundamental frequency. During frequency error testing the following variations were made:

	Category	Variation
☒	Standard	-20 to +50 C in 10 degree steps
☐	Extended	

Variation of supply voltage is required to ensure stability of the declared output power and frequency. During carrier power and frequency error testing the following variations were made:

	Category	Nominal	Variation
☐	Mains	110 V ac +/-2 %	85 % and 115 %
☒	Battery	New battery	N/A

11 Radiated emissions below 30 MHz

11.1 Definitions

Out-of-band emissions

Emissions on a frequency or frequencies immediately outside the necessary bandwidth which result from the modulation process, but exclude spurious emissions.

Spurious emissions

Emissions on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions.

Restricted bands

A frequency band in which intentional radiators are permitted to radiate only spurious emissions but not fundamental signals.

11.2 Test Parameters

Test Location:	Element Skelmersdale
Test Chamber:	Chamber 1
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.4
EUT Channels / Frequencies Measured:	125 kHz (13.56MHz Active)
Deviations From Standard:	None
Measurement Distance and Site	3m Alternative test sites (for preview) 10 m, OATS without ground plane (for Formals)
EUT Height:	0.8 m
Measurement Antenna and Height:	60 cm shielded loop; 1 m
Measurement BW:	9 kHz to 150 kHz: 200 Hz; 150 kHz to 30 MHz: 9 kHz
Measurement Detector:	9 kHz to 90 kHz and 110 kHz to 490 kHz: Average, RMS Other frequencies below 30 MHz: Quasi-peak.

Environmental Conditions (Normal Environment)

Temperature: 15 °C	+15 °C to +35 °C (as declared)
Humidity: 39 % RH	20 % RH to 75 % RH (as declared)

11.3 Test Limit

Emissions from license-exempt transmitters shall comply with the field strength limits shown in the table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

General Field Strength Limits for License-Exempt Transmitters at Frequencies Below 30 MHz

<i>Frequency, f (kHz)</i>	<i>Field Strength</i>	<i>Measurement Distance (m)</i>
9 to 490	2,400 / 377.f (μA/m) 2,400 / f (μV/m)	300
490 to 1,750	24,000 / 377.f (μA/m) 24,000 / f (μV/m)	30
1,750 to 30,000	30 (μV/m)	30

n.b. Devices operated pursuant to §15.225 / RSS-210 A2.6 are exempt from complying with the restricted band requirements for the 13.36–13.41 MHz band only.

11.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure i, the EUT fundamental frequency was maximised by rotating the EUT through 360°, in three orthogonal planes, and adjusting the measurement antenna azimuth.

Radiated electromagnetic emissions from the EUT are checked first by preview scans. Preview scans for all spectrum and modulation characteristics are checked, using a peak detector and where applicable worst-case determined for function, operation, orientation, etc. for both vertical and horizontal polarisations. Pre-scan plots are shown with a peak detector and 9 kHz RBW.

If the EUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.10 are followed. Alternatively, a layout closest to normal use (as declared by the provider) is employed, (see EUT setup photographs for more detail).

Emissions between 9 kHz and 30 MHz are measured using a calibrated 60cm active loop antenna. Pre-amplifiers and filters are used where required. Care is taken to ensure that test receiver resolution bandwidth, video bandwidth and detector type(s) meet the regulatory requirements.

Power values measured on the test receiver / analyzer are converted to field strength, FS, in μV/m at the regulatory distance, using:

$$FS = 10^{(PR - CF) / 20}$$

Where,


PR is the power recorded on the receiver / spectrum analyzer in dBμV and includes any cable loss, antenna factor and pre-amplifier gain;

CF is the distance extrapolation factor in dB (where measurement distance different to limit distance);


Per FCC 47CFR15.31(f)(2) / RSS-Gen 6.4, an extrapolation factor of 40 dB per decade was used for measurements at distances closer than specified.

This field strength value is then compared with the regulatory limit.

Figure i Test Setup




11.5 Test Set-up Photograph



11.6 Test Equipment

Equipment Type	Manufacturer	Equipment Description	Element No	Due For Calibration
ESR7	R&S	EMI Receiver	U456	03/09/2016
hfh2	R&S	Loop Antenna	L007	10/04/2017

11.7 Test Results



Emission Frequency (MHz)	Receiver Level (dBµV/m)	Measurement Distance (m)	Limit Distance (m)	Extrapolation Factor (dB)	Field Strength (µV/m)	Result
No Significant Emissions						PASS

12 Radiated emissions

12.1 Definitions

Out-of-band emissions

Emissions on a frequency or frequencies immediately outside the necessary bandwidth which result from the modulation process, but exclude spurious emissions.

Spurious emissions

Emissions on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions.

Restricted bands

A frequency band in which intentional radiators are permitted to radiate only spurious emissions but not fundamental signals.

12.2 Test Parameters

Test Location:	Element Skelmersdale
Test Chamber:	Radio Chamber
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.5
EUT Channels / Frequencies Measured:	125 kHz (13.56 MHz Active)
Deviations From Standard:	None
Measurement BW:	30 MHz to 1000 MHz: 120 kHz
Measurement Detector:	Quasi-peak

Environmental Conditions (Normal Environment)

Temperature: 22 °C	+15 °C to +35 °C (as declared)
Humidity: 24 % RH	20 % RH to 75 % RH (as declared)

12.3 Test Limit

Emissions from license-exempt transmitters shall comply with the field strength limits shown in the table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

General Field Strength Limits for License-Exempt Transmitters at Frequencies above 30 MHz

<i>Frequency (MHz)</i>	<i>Field Strength (μV/m at 3 m)</i>
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

12.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure ii, the emissions from the EUT were measured on a spectrum analyzer / EMI receiver.

Radiated electromagnetic emissions from the EUT are checked first by preview scans. Preview scans for all spectrum and modulation characteristics are checked, using a peak detector and where applicable worst-case determined for function, operation, orientation, etc. for both vertical and horizontal polarisations. Pre-scan plots are shown with a peak detector and 100 kHz RBW.

If the EUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.10 are followed. Alternatively, a layout closest to normal use (as declared by the provider) is employed, (see EUT setup photographs for more detail).

Emissions between 30 MHz and 1 GHz are measured using calibrated broadband antennas. Emissions above 1 GHz are characterized using standard gain horn antennas. Pre-amplifiers and filters are used where required. Care is taken to ensure that test receiver resolution bandwidth, video bandwidth and detector type(s) meet the regulatory requirements.

For both horizontal and vertical polarizations, the EUT is then rotated through 360 degrees in azimuth until the highest emission is detected. At the previously determined azimuth the test antenna is raised and lowered from 1 to 4 m in height until a maximum emission level is detected, this maximum value is recorded.

Power values measured on the test receiver / analyzer are converted to field strength, FS, in dBµV/m at the regulatory distance, using:

$$FS = PR + CL + AF - PA + DC - CF$$

Where,

PR is the power recorded on the receiver / spectrum analyzer in dBµV;

CL is the cable loss in dB;

AF is the test antenna factor in dB/m;


PA is the pre-amplifier gain in dB (where used);

DC is the duty correction factor in dB (where used, e.g. harmonics of pulsed fundamental);


CF is the distance factor in dB (where measurement distance is different to limit distance);

This field strength value is then compared with the regulatory limit.

Figure ii Test Setup




12.5 Test Set-up Photograph




12.6 Test Equipment

Equipment Type	Manufacturer	Equipment Description	Element No	Due For Calibration
CBL611/A	Chase	Bilog	U191	26/02/2017
ESVS10	R&S	Receiver	L352	14/07/2017

12.7 Test Results



Detector	Freq. (MHz)	Meas'd Emission (dBµV)	Cable Loss (dB)	Antenna Factor (dB/m)	Pre-amp Gain (dB)	Duty Cycle Corr'n (dB)	Distance Extrap'n Factor (dB)	Field Strength (dBµV/m)	Field Strength (µV/m)	Limit (µV/m)
QP	40.70	12.37	1.00	13.25	N/A	0.00	0.00	26.62	21.43	100
QP	54.25	20.58	1.20	6.78	N/A	0.00	0.00	28.56	26.79	100
QP	67.80	25.90	1.30	6.28	N/A	0.00	0.00	33.48	47.21	100
QP	81.35	22.51	1.30	7.87	N/A	0.00	0.00	31.68	38.37	100
QP	94.95	16.71	1.50	9.80	N/A	0.00	0.00	28.01	25.15	150
QP	108.50	26.67	1.59	11.15	N/A	0.00	0.00	39.41	93.43	150
QP	135.60	18.97	1.70	12.30	N/A	0.00	0.00	32.97	44.51	150
QP	162.75	12.96	1.80	10.53	N/A	0.00	0.00	25.29	18.39	150
QP	400.00	18.42	2.72	15.60	N/A	0.00	0.00	36.74	68.71	200
QP	425.00	12.41	2.88	16.05	N/A	0.00	0.00	31.34	36.90	200
QP	433.95	9.16	2.90	16.00	N/A	0.00	0.00	28.06	25.29	200
QP	450.00	15.17	2.90	16.50	N/A	0.00	0.00	34.57	53.52	200
QP	461.05	11.99	2.95	16.55	N/A	0.00	0.00	31.49	37.54	200
QP	475.00	10.06	3.01	16.90	N/A	0.00	0.00	29.97	31.51	200
QP	480.00	9.73	3.03	17.00	N/A	0.00	0.00	29.76	30.76	200
QP	488.20	12.28	3.07	17.30	N/A	0.00	0.00	32.65	42.90	200
QP	515.30	9.27	3.18	17.80	N/A	0.00	0.00	30.25	32.55	200
QP	542.45	6.78	3.20	19.55	N/A	0.00	0.00	29.53	29.96	200
QP	569.55	9.21	3.28	19.12	N/A	0.00	0.00	31.61	38.06	200
QP	596.65	5.32	3.30	19.10	N/A	0.00	0.00	27.72	24.32	200
QP	813.65	5.92	3.82	22.30	N/A	0.00	0.00	32.04	39.99	200



Date: 6.JAN.2017 13:21:17

13 AC power-line conducted emissions

13.1 Definition

Line-to-ground radio-noise voltage that is conducted from all of the EUT current-carrying power input terminals that are directly (or indirectly via separate transformers or power supplies) connected to a public power network.

13.2 Test Parameters

Test Location:	Element Skelmersdale
Test Chamber:	LF Lab (U404)
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.2
EUT Channels / Frequencies Measured:	125 kHz (13.56 MHz active)
Deviations From Standard:	None
Measurement BW:	10 kHz
Measurement Detectors:	Quasi-Peak and Average, RMS

Environmental Conditions (Normal Environment)

Temperature: 21 °C	+15 °C to +35 °C (as declared)
Humidity: 32 % RH	20 % RH to 75 % RH (as declared)

13.3 Test Limit

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz, shall not exceed the limits in Table 3.

Table 3 – AC Power Line Conducted Emission Limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-Peak	Average**
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

*The level decreases linearly with the logarithm of the frequency.

**A linear average detector is required.


13.4 Test Method

With the EUT setup in a screened room, as per section 9 of this report and connected as per Figure iii, the power line emissions were measured on a spectrum analyzer / EMI receiver.

AC power line conducted emissions from the EUT are checked first by preview scans with peak and average detectors covering both live and neutral lines. A spectrum analyzer is used to determine if any periodic emissions are present.

Formal measurements using the correct detector(s) and bandwidth are made on frequencies identified from the preview scans. Final measurements were performed with EUT set at its maximum duty in transmit and receive modes.

Figure iii Test Setup



13.5 Test Set-up Photograph




13.6 Test Equipment

Equipment Type	Manufacturer	Equipment Description	Element No	Due For Calibration
ESHS10	R&S	Receiver	U187	25/10/2017
ENV216	R&S	Lisn	U396	29/06/2017

13.7 Test Results

Conducted emissions on Mains 9kHz-30MHz ESHS10 + UH396



QuasiPeak Detector								
Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.195000	45.9	2000.0	10.000	On	N	9.6	18.0	63.8
0.235000	44.4	2000.0	10.000	On	N	9.6	17.8	62.3
0.270000	43.0	2000.0	10.000	On	N	9.6	18.1	61.1
0.365000	40.6	2000.0	10.000	On	L1	9.6	18.0	58.6
0.435000	39.2	2000.0	10.000	On	L1	9.6	18.0	57.2
0.565000	34.4	2000.0	10.000	On	L1	9.6	21.6	56.0
0.950000	22.0	2000.0	10.000	On	N	9.6	34.0	56.0
0.970000	22.4	2000.0	10.000	On	N	9.6	33.6	56.0
4.530000	0.7	2000.0	10.000	On	L1	9.7	55.3	56.0
13.345000	20.8	2000.0	10.000	On	L1	9.9	39.2	60.0
13.550000*	33.3	2000.0	10.000	On	L1	9.9	26.7	60.0
13.560000	62.1	2000.0	10.000	On	L1	9.9	-2.1	60.0
17.345000	17.2	2000.0	10.000	On	L1	9.9	42.8	60.0
17.795000	14.7	2000.0	10.000	On	L1	9.9	45.3	60.0
27.120000	36.1	2000.0	10.000	On	L1	10.0	23.9	60.0

QuasiPeak Detector Antenna Replaced with Load								
Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.560000	47.2	2000.0	10.000	On	L1	9.9	12.8	60.0

QuasiPeak Detector								
Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.180000	16.3	2000.0	10.000	On	N	9.6	38.2	54.5
0.220000	14.6	2000.0	10.000	On	N	9.6	38.3	52.8
0.305000	12.6	2000.0	10.000	On	L1	9.6	37.5	50.1
0.335000	11.4	2000.0	10.000	On	L1	9.6	37.9	49.3
0.440000	9.1	2000.0	10.000	On	L1	9.6	38.0	47.1
0.565000	5.6	2000.0	10.000	On	L1	9.6	40.4	46.0
0.950000	-1.1	2000.0	10.000	On	N	9.6	47.1	46.0
0.985000	-0.5	2000.0	10.000	On	N	9.6	46.5	46.0
2.995000	-1.4	2000.0	10.000	On	N	9.7	47.4	46.0
6.500000	9.8	2000.0	10.000	On	N	9.8	40.2	50.0
13.550000	18.1	2000.0	10.000	On	L1	9.9	31.9	50.0
13.560000	48.4	2000.0	10.000	On	L1	9.9	1.6	50.0
16.225000	20.7	2000.0	10.000	On	L1	9.9	29.4	50.0
17.695000	16.1	2000.0	10.000	On	L1	9.9	33.9	50.0
27.120000	23.2	2000.0	10.000	On	L1	10.0	26.8	50.0

14 Occupied Bandwidth

14.1 Definition

Occupied bandwidth

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to 0.5 % of the emitted power. This is also known as the 99 % *emission bandwidth*. For transmitters in which there are multiple carriers, contiguous or non-contiguous in frequency, the occupied bandwidth is to be the sum of the occupied bandwidths of the individual carriers.

20 dB bandwidth

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal.

14.2 Test Parameters

Test Location:	Element Skelmersdale
Test Chamber:	Radio Lab
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.9
EUT Channels / Frequencies Measured:	125 kHz
Deviations From Standard:	None
Measurement BW:	20 Hz
Spectrum Analyzer Video BW:	200 Hz
Measurement Span:	1 kHz
Measurement Detector:	Peak

Environmental Conditions (Normal Environment)

Temperature: 22 °C	+15 °C to +35 °C (as declared)
Humidity: 23 % RH	20 % RH to 75 % RH (as declared)
Supply: 12 V dc	12 V dc (as declared)

14.3 Test Limit

Federal Communications Commission:


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

14.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure iv, the bandwidth of the EUT was measured on a spectrum analyser.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each bandwidth.

Figure iv Test Setup




14.5 Test Equipment

Equipment Type	Manufacturer	Equipment Description	Element No	Due For Calibration
FSU50	R&S	Spectrum Analyser	U544	16/03/2017


14.6 Test Results

RSS-210.			
Channel Frequency (kHz)	F _L (kHz)	F _H (kHz)	99 % Bandwidth (Hz)
125.0	124.948717949	125.110576923	217.948



Date: 12.JAN.2017 17:38:47

15.215(c)			
Channel Frequency (kHz)	F _L (kHz)	F _H (kHz)	20 dB Bandwidth (Hz)
125	124.950320513	125.048076923	97.756



Date: 12.JAN.2017 17:34:26

15 Transmitter output power (fundamental radiated emission)

15.1 Definition

The RF power dissipated in the standard output termination when operating under the rated duty cycle selected by the applicant for approval.

15.2 Test Parameters

Test Location:	Element Skelmersdale
Test Chamber:	Radio Chamber
Test Antenna:	Active 60cm loop
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.3 / 6.4
EUT Channels / Frequencies Measured:	125 kHz
Deviations From Standard:	None
Measurement BW:	200 Hz
Measurement Detector:	Quasi-peak

Environmental Conditions (Normal Environment)

Temperature: 2 °C	+15 °C to +35 °C (as declared)
Humidity: 23 % RH	20 % RH to 75 % RH (as declared)

15.3 Test Limit

The field strength measured at 30 m shall not exceed the limits in the following table:

Field Strength Limits for License-Exempt Transmitters for Any Application

<i>Frequency range (MHz)</i>	<i>Field strength (μV/m)</i>	<i>Measurement Distance (m)</i>
0.09-0.490	2400/k(kHz)	300

15.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure v, the resolution bandwidth of the spectrum analyser was increased above the EUT occupied bandwidth and the peak emission data noted.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each bandwidth.

Power values measured on the test receiver / analyzer are converted to field strength, FS, in $\mu\text{V/m}$ at the regulatory distance, using:

$$FS = 10^{(PR - CF) / 20}$$

Where,

PR is the power recorded on the receiver / spectrum analyzer in $\text{dB}\mu\text{V}$ and includes any cable loss, antenna factor and pre-amplifier gain;


CF is the distance extrapolation factor in dB (where measurement distance different to limit distance);

Per FCC 47CFR15.31(f)(2) / RSS-Gen 6.4, an extrapolation factor of 40 dB per decade was used for measurements at distances closer than specified. Giving a factor of 80dB between 3 meters and 300 meters

Per FCC 47CFR15.31(f)(2) / RSS-Gen 6.4, an extrapolation factor of 21.9 dB was determined from measurements at 1 and 13 metres. Giving an extrapolation of 101.9 between 1 meters and 300 meters

This field strength value is then compared with the regulatory limit.

Figure v Test Setup



15.5 Test Equipment

Equipment Type	Manufacturer	Equipment Description	Element No	Due For Calibration
ESHS10	R&S	Receiver	U003	25/06/2017
hfh2	R&S	Loop Antenna	L007	10/04/2017

15.6 Test Results

Channel Frequency (kHz)	Receiver Level ($\text{dB}\mu\text{V/m}$)	Measurement Distance (m)	Limit Distance (m)	Extrapolation Factor (dB)	Field Strength ($\mu\text{V/m}$)	Result
125	85.3	1	300	101.9	0.148	PASS
125	63.4	3	300	80	0.148	PASS

16 Measurement Uncertainty

Calculated Measurement Uncertainties

All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95 % confidence:

[1] Radiated emissions below 30 MHz

Uncertainty in test result (9 kHz to 30 MHz) = **2.3 dB**

[2] Spurious emissions

Uncertainty in test result (30 MHz to 1 GHz) = **4.6 dB**

Uncertainty in test result (1 GHz to 18 GHz) = **4.7 dB**

[3] AC power line conducted emissions

Uncertainty in test result = **3.4 dB**

[4] Occupied bandwidth

Uncertainty in test result = **15.5 %**

[5] Maximum frequency error

Uncertainty in test result (Power Meter) = **0.113 ppm**

Uncertainty in test result (Spectrum Analyser) = **0.265 ppm**

17 General SAR test reduction and exclusion guidance/RF Exposure

Section 4.3 General SAR test reduction and exclusion guidance

For Standalone SAR exclusion consideration, when SAR Exclusion Threshold requirement in KDB 447498 is satisfied, standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.

The SAR Test Exclusion Threshold for frequency range below 100 MHz will be determined as follows.

$$\text{SAR Exclusion Threshold (SARET)} = (\text{Step 1} + \text{Step 2}) * \text{Step 3}$$

Step 1

$$NT = [(MP/TSD^A) * \sqrt{f_{\text{GHz}}}]$$

NT = Numeric Threshold (3.0 for 1-g SAR and 7.5 for 10-g SAR)

MP = Max Power of channel (mW) (including tune-up tolerance)

TSD^A = Min Test separation Distance or 50mm (whichever is lower) = 5mm (in this case)

We can transpose this formula to allow us to find the maximum power of a channel allowed and compare this to the measured maximum power.

$$= [(NT * TSD^A) / \sqrt{f_{\text{GHz}}}]$$

For Distances Greater than 50 mm Step 2 applies

Step 2

$$(TSD^B - 50\text{mm}) * 10$$

Where:

$$TSD^B = \text{Min Test separation Distance (mm)} = 50$$

Note: Step 2 doesn't apply here as the TSD^A is less than 50 mm

Step 3

- the power threshold at the corresponding test separation distance at 100 MHz in step 2 is multiplied by $[1 + \log(100/f_{\text{MHz}})]$ for test separation distances > 50 mm and < 200 mm
- the power threshold determined by the equation in steps 1 for 50 mm and 100 MHz is multiplied by $1/2$ for test separation distances ≤ 50 mm

$$\begin{aligned} \text{SARET} &= [(NT * TSD^A) / \sqrt{f_{\text{GHz}}}] * 1/2 \\ \text{SARET} &= [(3.0 * 50) / \sqrt{0.1}] * 1/2 \\ \text{SARET} &= 237.2 \text{ mW} \end{aligned}$$

Channel Frequency (kHz)	EIRP (mW)	SAR Exclusion Threshold (mW)	SAR Evaluation
125.0	6.57×10^{-6}	237.2	Not Required

Note: EIRP calculated from maximum radiated field strength.

Therefore standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.