




|                 |                |                   |          |
|-----------------|----------------|-------------------|----------|
| Channel         | 802.11n40 CH54 | Frequency         | 5270 MHz |
| Frequency Range | Above 1G       | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5107.5038   | 35.40            | 7.95        | 43.35          | 54.00          | 10.65       | 154         | 306       | AV       |
| 2   | 5107.9840   | 47.39            | 7.97        | 55.36          | 74.00          | 18.64       | 0           | 89        | PK       |
| 3   | 5150.0000   | 45.77            | 8.03        | 53.80          | 74.00          | 20.20       | 251         | 308       | PK       |
| 4   | 5150.0000   | 35.61            | 8.03        | 43.64          | 54.00          | 10.36       | 130         | 308       | AV       |
| 5   | 5268.8644   | 97.73            | 8.73        | 106.46         |                |             | 190         | 298       | PK       |
| 6   | 5271.2656   | 88.41            | 8.64        | 97.05          |                |             | 71          | 291       | AV       |
| 7   | 5350.0000   | 47.09            | 9.96        | 57.05          | 74.00          | 16.95       | 209         | 291       | PK       |
| 8   | 5350.0000   | 37.03            | 9.96        | 46.99          | 54.00          | 7.01        | 150         | 289       | AV       |
| 9   | 5378.8394   | 48.28            | 10.10       | 58.38          | 74.00          | 15.62       | 278         | 308       | PK       |
| 10  | 5378.8394   | 36.79            | 10.10       | 46.89          | 54.00          | 7.11        | 279         | 304       | AV       |
| 11  | 10540.0000  | 27.31            | 14.39       | 41.70          | 68.20          | 26.50       | 328         | 30        | PK       |
| 12  | 10540.0000  | 17.85            | 14.39       | 32.24          | 54.00          | 21.76       | 157         | 211       | AV       |
| 13  | 15810.0000  | 23.94            | 20.56       | 44.50          | 74.00          | 29.50       | 383         | 280       | PK       |
| 14  | 15810.0000  | 13.60            | 20.56       | 34.16          | 54.00          | 19.84       | 237         | 119       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]

|                 |             |                  |             |                   |                |             |             |           |          |
|-----------------|-------------|------------------|-------------|-------------------|----------------|-------------|-------------|-----------|----------|
| Channel         |             | 802.11n40 CH62   |             | Frequency         |                | 5310 MHz    |             |           |          |
| Frequency Range |             | Above 1G         |             | Detector Function |                | PK/AV       |             |           |          |
| Horizontal      |             |                  |             |                   |                |             |             |           |          |
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m]    | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5308.7244   | 78.16            | 9.16        | 87.32             |                |             | 377         | 152       | AV       |
| 2               | 5311.1256   | 86.19            | 9.19        | 95.38             |                |             | 262         | 152       | PK       |
| 3               | 5350.0000   | 34.25            | 9.96        | 44.21             | 54.00          | 9.79        | 371         | 78        | AV       |
| 4               | 5350.0000   | 46.20            | 9.96        | 56.16             | 74.00          | 17.84       | 242         | 233       | PK       |
| 5               | 5398.5293   | 34.66            | 10.03       | 44.69             | 54.00          | 9.31        | 328         | 104       | AV       |
| 6               | 5402.3712   | 46.61            | 10.09       | 56.70             | 74.00          | 17.30       | 152         | 138       | PK       |
| 7               | 10620.0000  | 26.64            | 14.27       | 40.91             | 74.00          | 33.09       | 352         | 3         | PK       |
| 8               | 10620.0000  | 17.50            | 14.27       | 31.77             | 54.00          | 22.23       | 340         | 350       | AV       |
| 9               | 15930.0000  | 22.81            | 21.20       | 44.01             | 74.00          | 29.99       | 130         | 155       | PK       |
| 10              | 15930.0000  | 13.28            | 21.20       | 34.48             | 54.00          | 19.52       | 301         | 1         | AV       |

FCC Part15C

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                |                   |          |
|-----------------|----------------|-------------------|----------|
| Channel         | 802.11n40 CH62 | Frequency         | 5310 MHz |
| Frequency Range | Above 1G       | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5312.0860   | 98.26            | 9.16        | 107.42         |                |             | 200         | 282       | PK       |
| 2   | 5312.5663   | 89.30            | 9.15        | 98.45          |                |             | 309         | 293       | AV       |
| 3   | 5350.0000   | 39.50            | 9.96        | 49.46          | 54.00          | 4.54        | 279         | 293       | AV       |
| 4   | 5350.0000   | 50.90            | 9.96        | 60.86          | 74.00          | 13.14       | 309         | 308       | PK       |
| 5   | 5370.6753   | 49.30            | 9.94        | 59.24          | 74.00          | 14.76       | 342         | 289       | PK       |
| 6   | 5373.0765   | 38.24            | 9.99        | 48.23          | 54.00          | 5.77        | 204         | 297       | AV       |
| 7   | 10620.0000  | 26.44            | 14.27       | 40.71          | 74.00          | 33.29       | 301         | 294       | PK       |
| 8   | 10620.0000  | 17.64            | 14.27       | 31.91          | 54.00          | 22.09       | 269         | 208       | AV       |
| 9   | 15930.0000  | 22.11            | 21.20       | 43.31          | 74.00          | 30.69       | 177         | 83        | PK       |
| 10  | 15930.0000  | 12.92            | 21.20       | 34.12          | 54.00          | 19.88       | 146         | 245       | AV       |




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                 |                   |          |
|-----------------|-----------------|-------------------|----------|
| Channel         | 802.11ac80 CH58 | Frequency         | 5290 MHz |
| Frequency Range | Above 1G        | Detector Function | PK/AV    |

## Horizontal

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5107.9840   | 47.19            | 7.97        | 55.16          | 74.00          | 18.84       | 212         | 218       | PK       |
| 2   | 5112.7864   | 34.67            | 7.99        | 42.66          | 54.00          | 11.34       | 207         | 270       | AV       |
| 3   | 5150.0000   | 44.68            | 8.03        | 52.71          | 74.00          | 21.29       | 111         | 182       | PK       |
| 4   | 5150.0000   | 34.20            | 8.03        | 42.23          | 54.00          | 11.77       | 54          | 329       | AV       |
| 5   | 5294.7974   | 72.08            | 8.72        | 80.80          |                |             | 284         | 152       | AV       |
| 6   | 5295.2776   | 80.86            | 8.73        | 89.59          |                |             | 275         | 150       | PK       |
| 7   | 5350.0000   | 44.86            | 9.96        | 54.82          | 74.00          | 19.18       | 384         | 359       | PK       |
| 8   | 5350.0000   | 34.26            | 9.96        | 44.22          | 54.00          | 9.78        | 26          | 270       | AV       |
| 9   | 5396.6083   | 34.73            | 10.03       | 44.76          | 54.00          | 9.24        | 167         | 161       | AV       |
| 10  | 5400.4502   | 46.88            | 10.03       | 56.91          | 74.00          | 17.09       | 0           | 32        | PK       |
| 11  | 10580.0000  | 27.02            | 14.11       | 41.13          | 68.20          | 27.07       | 263         | 244       | PK       |
| 12  | 10580.0000  | 17.56            | 14.11       | 31.67          | 54.00          | 22.33       | 324         | 99        | AV       |
| 13  | 15870.0000  | 22.65            | 20.81       | 43.46          | 74.00          | 30.54       | 331         | 23        | PK       |
| 14  | 15870.0000  | 13.73            | 20.81       | 34.54          | 54.00          | 19.46       | 351         | 175       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                 |                  |             |                   |                |             |             |           |          |
|-----------------|-----------------|------------------|-------------|-------------------|----------------|-------------|-------------|-----------|----------|
| Channel         | 802.11ac80 CH58 |                  |             | Frequency         | 5290 MHz       |             |             |           |          |
| Frequency Range | Above 1G        |                  |             | Detector Function | PK/AV          |             |             |           |          |
| Vertical        |                 |                  |             |                   |                |             |             |           |          |
| NO.             | Freq. [MHz]     | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m]    | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5115.1876       | 46.79            | 7.91        | 54.70             | 74.00          | 19.30       | 128         | 154       | PK       |
| 2               | 5132.9565       | 35.02            | 8.16        | 43.18             | 54.00          | 10.82       | 102         | 296       | AV       |
| 3               | 5150.0000       | 46.12            | 8.03        | 54.15             | 74.00          | 19.85       | 390         | 35        | PK       |
| 4               | 5150.0000       | 35.02            | 8.03        | 43.05             | 54.00          | 10.95       | 84          | 309       | AV       |
| 5               | 5292.3962       | 92.89            | 8.67        | 101.56            |                |             | 113         | 286       | PK       |
| 6               | 5293.3567       | 83.09            | 8.69        | 91.78             |                |             | 364         | 307       | AV       |
| 7               | 5350.0000       | 38.80            | 9.96        | 48.76             | 54.00          | 5.24        | 214         | 307       | AV       |
| 8               | 5350.0000       | 49.69            | 9.96        | 59.65             | 74.00          | 14.35       | 352         | 292       | PK       |
| 9               | 5371.6358       | 37.50            | 9.96        | 47.46             | 54.00          | 6.54        | 188         | 290       | AV       |
| 10              | 5386.0430       | 48.88            | 10.08       | 58.96             | 74.00          | 15.04       | 122         | 292       | PK       |
| 11              | 10580.0000      | 26.52            | 14.11       | 40.63             | 68.20          | 27.57       | 209         | 222       | PK       |
| 12              | 10580.0000      | 17.71            | 14.11       | 31.82             | 54.00          | 22.18       | 354         | 122       | AV       |
| 13              | 15870.0000      | 22.11            | 20.81       | 42.92             | 74.00          | 31.08       | 292         | 321       | PK       |
| 14              | 15870.0000      | 13.57            | 20.81       | 34.38             | 54.00          | 19.62       | 354         | 328       | AV       |

FCC Part15C

Level[dBμV/m]

Frequency[Hz]


Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                 |                   |          |
|-----------------|-----------------|-------------------|----------|
| Channel         | 802.11ax80 CH58 | Frequency         | 5290 MHz |
| Frequency Range | Above 1G        | Detector Function | PK/AV    |

## Horizontal

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5111.3457   | 47.19            | 8.03        | 55.22          | 74.00          | 18.78       | 211         | 132       | PK       |
| 2   | 5113.7469   | 34.64            | 7.96        | 42.60          | 54.00          | 11.40       | 177         | 157       | AV       |
| 3   | 5150.0000   | 45.41            | 8.03        | 53.44          | 74.00          | 20.56       | 243         | 172       | PK       |
| 4   | 5150.0000   | 34.17            | 8.03        | 42.20          | 54.00          | 11.80       | 93          | 185       | AV       |
| 5   | 5293.3567   | 80.88            | 8.69        | 89.57          |                |             | 35          | 155       | PK       |
| 6   | 5293.3567   | 70.37            | 8.69        | 79.06          |                |             | 267         | 153       | AV       |
| 7   | 5350.0000   | 45.38            | 9.96        | 55.34          | 74.00          | 18.66       | 29          | 130       | PK       |
| 8   | 5350.0000   | 34.16            | 9.96        | 44.12          | 54.00          | 9.88        | 27          | 359       | AV       |
| 9   | 5374.9975   | 34.75            | 10.02       | 44.77          | 54.00          | 9.23        | 253         | 132       | AV       |
| 10  | 5378.3592   | 46.51            | 10.09       | 56.60          | 74.00          | 17.40       | 360         | 37        | PK       |
| 11  | 10580.0000  | 26.57            | 14.11       | 40.68          | 68.20          | 27.52       | 102         | 49        | PK       |
| 12  | 10580.0000  | 17.66            | 14.11       | 31.77          | 54.00          | 22.23       | 119         | 212       | AV       |
| 13  | 15870.0000  | 22.59            | 20.81       | 43.40          | 74.00          | 30.60       | 307         | 129       | PK       |
| 14  | 15870.0000  | 13.47            | 20.81       | 34.28          | 54.00          | 19.72       | 181         | 236       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



| Channel         | 802.11ax80 CH58 | Frequency         | 5290 MHz    |                |                |             |             |           |          |
|-----------------|-----------------|-------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| Frequency Range | Above 1G        | Detector Function | PK/AV       |                |                |             |             |           |          |
| Vertical        |                 |                   |             |                |                |             |             |           |          |
| NO.             | Freq. [MHz]     | Reading [dBμV/m]  | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5071.9660       | 46.99             | 7.48        | 54.47          | 74.00          | 19.53       | 137         | 37        | PK       |
| 2               | 5110.3852       | 34.80             | 8.07        | 42.87          | 54.00          | 11.13       | 287         | 307       | AV       |
| 3               | 5150.0000       | 45.34             | 8.03        | 53.37          | 74.00          | 20.63       | 117         | 273       | PK       |
| 4               | 5150.0000       | 34.49             | 8.03        | 42.52          | 54.00          | 11.48       | 86          | 330       | AV       |
| 5               | 5291.4357       | 93.69             | 8.66        | 102.35         |                |             | 377         | 288       | PK       |
| 6               | 5292.8764       | 81.56             | 8.68        | 90.24          |                |             | 99          | 307       | AV       |
| 7               | 5350.0000       | 47.65             | 9.96        | 57.61          | 74.00          | 16.39       | 399         | 298       | PK       |
| 8               | 5350.0000       | 37.81             | 9.96        | 47.77          | 54.00          | 6.23        | 26          | 298       | AV       |
| 9               | 5365.3927       | 37.32             | 9.99        | 47.31          | 54.00          | 6.69        | 367         | 292       | AV       |
| 10              | 5366.3532       | 49.15             | 9.97        | 59.12          | 74.00          | 14.88       | 253         | 273       | PK       |
| 11              | 10580.0000      | 26.87             | 14.11       | 40.98          | 68.20          | 27.22       | 373         | 3         | PK       |
| 12              | 10580.0000      | 17.95             | 14.11       | 32.06          | 54.00          | 21.94       | 176         | 30        | AV       |
| 13              | 15870.0000      | 22.79             | 20.81       | 43.60          | 74.00          | 30.40       | 262         | 318       | PK       |
| 14              | 15870.0000      | 13.93             | 20.81       | 34.74          | 54.00          | 19.26       | 394         | 248       | AV       |

FCC Part15C

Level[dBμV/m]

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]




## 3.1.8 TEST RESULTS - Band 3 (5500-5720MHz):

### ABOVE 1GHz DATA

|                 |               |                   |             |                |                |             |             |           |          |
|-----------------|---------------|-------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| Channel         | 802.11a CH100 | Frequency         | 5500 MHz    |                |                |             |             |           |          |
| Frequency Range | Above 1G      | Detector Function | PK/AV       |                |                |             |             |           |          |
| Horizontal      |               |                   |             |                |                |             |             |           |          |
| NO.             | Freq. [MHz]   | Reading [dBμV/m]  | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5428.6643     | 46.62             | 9.84        | 56.46          | 74.00          | 17.54       | 314         | 206       | PK       |
| 2               | 5430.6653     | 34.54             | 9.85        | 44.39          | 54.00          | 9.61        | 387         | 286       | AV       |
| 3               | 5460.6803     | 45.97             | 9.99        | 55.96          | 68.30          | 12.34       | 395         | 299       | PK       |
| 4               | 5498.6994     | 80.39             | 9.16        | 89.55          |                |             | 185         | 320       | AV       |
| 5               | 5502.4512     | 88.68             | 9.34        | 98.02          |                |             | 375         | 307       | PK       |
| 6               | 11000.0000    | 26.20             | 14.83       | 41.03          | 74.00          | 32.97       | 240         | 121       | PK       |
| 7               | 11000.0000    | 16.68             | 14.83       | 31.51          | 54.00          | 22.49       | 265         | 226       | AV       |
| 8               | 16500.0000    | 20.78             | 23.16       | 43.94          | 68.20          | 24.26       | 318         | 310       | PK       |
| 9               | 16500.0000    | 11.65             | 23.16       | 34.81          | 54.00          | 19.19       | 165         | 1         | AV       |


FCC Part15 407



Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]







|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11a CH 120      |                |                   | Frequency         |                | 5600MHz        |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                |                   | Detector Function |                | PK/AV          |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11200.0000     | 26.21               | 15.10          | 41.31             | 74.00             | 32.69          | 150            | 290          | PK       |
| 2                                                                                                                                                                                                                                                            | 11200.0000     | 16.93               | 15.10          | 32.03             | 54.00             | 21.97          | 150            | 235          | AV       |
| 3                                                                                                                                                                                                                                                            | 16800.0000     | 20.51               | 24.83          | 45.34             | 68.20             | 22.86          | 150            | 105          | PK       |
| 4                                                                                                                                                                                                                                                            | 16800.0000     | 11.09               | 24.83          | 35.92             | 54.00             | 18.08          | 150            | 264          | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11200.0000     | 26.78               | 15.10          | 41.88             | 74.00             | 32.12          | 150            | 255          | PK       |
| 2                                                                                                                                                                                                                                                            | 11200.0000     | 17.52               | 15.10          | 32.62             | 54.00             | 21.38          | 150            | 166          | AV       |
| 3                                                                                                                                                                                                                                                            | 16800.0000     | 20.82               | 24.83          | 45.65             | 68.20             | 22.55          | 150            | 156          | PK       |
| 4                                                                                                                                                                                                                                                            | 16800.0000     | 12.11               | 24.83          | 36.94             | 54.00             | 17.06          | 150            | 156          | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m] |                |                     |                |                   |                   |                |                |              |          |



|                 |               |                   |             |                |                |             |             |           |          |
|-----------------|---------------|-------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| Channel         | 802.11a CH140 | Frequency         | 5700 MHz    |                |                |             |             |           |          |
| Frequency Range | Above 1G      | Detector Function | PK/AV       |                |                |             |             |           |          |
| Horizontal      |               |                   |             |                |                |             |             |           |          |
| NO.             | Freq. [MHz]   | Reading [dBμV/m]  | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5698.0740     | 90.34             | 8.79        | 99.13          |                |             | 372         | 318       | PK       |
| 2               | 5725.0000     | 45.07             | 8.89        | 53.96          | 68.30          | 14.34       | 339         | 186       | PK       |
| 3               | 5747.9490     | 49.79             | 8.93        | 58.72          | 68.30          | 9.58        | 251         | 114       | PK       |
| 4               | 11400.0000    | 16.31             | 15.09       | 31.40          | 54.00          | 22.60       | 150         | 86        | AV       |
| 5               | 11400.0000    | 25.62             | 15.09       | 40.71          | 74.00          | 33.29       | 150         | 165       | PK       |
| 6               | 17100.0000    | 10.93             | 25.93       | 36.86          | 54.00          | 17.14       | 150         | 264       | AV       |
| 7               | 17100.0000    | 21.10             | 25.93       | 47.03          | 68.20          | 21.17       | 150         | 178       | PK       |

FCC Part15 407

FCC Part15 407-PK

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |               |                   |          |
|-----------------|---------------|-------------------|----------|
| Channel         | 802.11a CH140 | Frequency         | 5700 MHz |
| Frequency Range | Above 1G      | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5698.5743   | 92.31            | 8.84        | 101.15         |                |             | 109         | 37        | PK       |
| 2   | 5725.0000   | 45.65            | 8.89        | 54.54          | 68.30          | 13.76       | 334         | 1         | PK       |
| 3   | 5740.7454   | 47.41            | 8.94        | 56.35          | 68.30          | 11.95       | 382         | 53        | PK       |
| 4   | 11400.0000  | 25.89            | 15.09       | 40.98          | 74.00          | 33.02       | 150         | 244       | PK       |
| 5   | 11400.0000  | 16.61            | 15.09       | 31.70          | 54.00          | 22.30       | 150         | 353       | AV       |
| 6   | 17100.0000  | 19.75            | 25.93       | 45.68          | 68.20          | 22.52       | 150         | 33        | PK       |
| 7   | 17100.0000  | 10.79            | 25.93       | 36.72          | 54.00          | 17.28       | 150         | 264       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11a CH 144      |                | Frequency         |                   | 5720MHz        |                |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                | Detector Function |                   | PK/AV          |                |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11440.0000     | 23.82               | 15.04          | 38.86             | 74.00             | 35.14          | 348            | 298          | PK       |
| 2                                                                                                                                                                                                                                                            | 11440.0000     | 16.46               | 15.04          | 31.50             | 54.00             | 22.50          | 323            | 205          | AV       |
| 3                                                                                                                                                                                                                                                            | 17160.0000     | 19.91               | 25.86          | 45.77             | 68.20             | 22.43          | 246            | 328          | PK       |
| 4                                                                                                                                                                                                                                                            | 17160.0000     | 12.03               | 25.86          | 37.89             | 54.00             | 16.11          | 245            | 301          | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11440.0000     | 24.17               | 15.04          | 39.21             | 74.00             | 34.79          | 376            | 302          | PK       |
| 2                                                                                                                                                                                                                                                            | 11440.0000     | 16.96               | 15.04          | 32.00             | 54.00             | 22.00          | 226            | 298          | AV       |
| 3                                                                                                                                                                                                                                                            | 17160.0000     | 20.00               | 25.86          | 45.86             | 68.20             | 22.34          | 270            | 349          | PK       |
| 4                                                                                                                                                                                                                                                            | 17160.0000     | 12.07               | 25.86          | 37.93             | 54.00             | 16.07          | 203            | 1            | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m] |                |                     |                |                   |                   |                |                |              |          |



|                 |                 |                  |                   |                |                |             |             |           |          |
|-----------------|-----------------|------------------|-------------------|----------------|----------------|-------------|-------------|-----------|----------|
| Channel         | 802.11n20 CH100 |                  | Frequency         |                | 5500 MHz       |             |             |           |          |
| Frequency Range | Above 1G        |                  | Detector Function |                | PK/AV          |             |             |           |          |
| Horizontal      |                 |                  |                   |                |                |             |             |           |          |
| NO.             | Freq. [MHz]     | Reading [dBμV/m] | Factor [dB]       | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5452.3012       | 46.28            | 9.78              | 56.06          | 74.00          | 17.94       | 371         | 211       | PK       |
| 2               | 5453.0515       | 35.12            | 9.80              | 44.92          | 54.00          | 9.08        | 151         | 150       | AV       |
| 3               | 5470.0000       | 45.45            | 9.94              | 55.39          | 68.30          | 12.91       | 342         | 245       | PK       |
| 4               | 5498.6994       | 89.11            | 9.16              | 98.27          |                |             | 333         | 145       | PK       |
| 5               | 5498.9495       | 80.92            | 9.17              | 90.09          |                |             | 290         | 145       | AV       |
| 6               | 11000.0000      | 25.70            | 14.83             | 40.53          | 74.00          | 33.47       | 134         | 37        | PK       |
| 7               | 11000.0000      | 17.78            | 14.83             | 32.61          | 54.00          | 21.39       | 270         | 272       | AV       |
| 8               | 16500.0000      | 21.72            | 23.16             | 44.88          | 68.20          | 23.32       | 153         | 268       | PK       |
| 9               | 16500.0000      | 11.75            | 23.16             | 34.91          | 54.00          | 19.09       | 165         | 90        | AV       |

FCC Part15 407

| Point | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-------|-------------|------------------|-------------|----------------|----------------|-------------|
| 1     | 5452.3012   | 46.28            | 9.78        | 56.06          | 74.00          | 17.94       |
| 2     | 5453.0515   | 35.12            | 9.80        | 44.92          | 54.00          | 9.08        |
| 3     | 5470.0000   | 45.45            | 9.94        | 55.39          | 68.30          | 12.91       |
| 4     | 5498.6994   | 89.11            | 9.16        | 98.27          |                |             |
| 5     | 5498.9495   | 80.92            | 9.17        | 90.09          |                |             |
| 6     | 11000.0000  | 25.70            | 14.83       | 40.53          | 74.00          | 33.47       |


Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



|                 |                 |                   |          |
|-----------------|-----------------|-------------------|----------|
| Channel         | 802.11n20 CH100 | Frequency         | 5500 MHz |
| Frequency Range | Above 1G        | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5432.1661   | 37.82            | 9.83        | 47.65          | 54.00          | 6.35        | 364         | 99        | AV       |
| 2   | 5438.2941   | 48.76            | 9.75        | 58.51          | 74.00          | 15.49       | 283         | 82        | PK       |
| 3   | 5470.0000   | 47.10            | 9.94        | 57.04          | 68.30          | 11.26       | 208         | 275       | PK       |
| 4   | 5498.3242   | 87.33            | 9.14        | 96.47          |                |             | 225         | 3         | AV       |
| 5   | 5498.4492   | 95.53            | 9.15        | 104.68         |                |             | 312         | 1         | PK       |
| 6   | 11000.0000  | 26.21            | 14.83       | 41.04          | 74.00          | 32.96       | 336         | 244       | PK       |
| 7   | 11000.0000  | 17.42            | 14.83       | 32.25          | 54.00          | 21.75       | 390         | 123       | AV       |
| 8   | 16500.0000  | 20.52            | 23.16       | 43.68          | 68.20          | 24.52       | 153         | 69        | PK       |
| 9   | 16500.0000  | 11.97            | 23.16       | 35.13          | 54.00          | 18.87       | 248         | 100       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
 2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
 4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11n20 CH 120    |                |                   | Frequency         |                | 5600MHz        |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                |                   | Detector Function |                | PK/AV          |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11200.0000     | 28.23               | 15.10          | 43.33             | 74.00             | 30.67          | 386            | 273          | PK       |
| 2                                                                                                                                                                                                                                                            | 11200.0000     | 17.03               | 15.10          | 32.13             | 54.00             | 21.87          | 339            | 273          | AV       |
| 3                                                                                                                                                                                                                                                            | 16800.0000     | 20.79               | 24.83          | 45.62             | 68.20             | 22.58          | 381            | 230          | PK       |
| 4                                                                                                                                                                                                                                                            | 16800.0000     | 11.58               | 24.83          | 36.41             | 54.00             | 17.59          | 335            | 276          | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11200.0000     | 28.27               | 15.10          | 43.37             | 74.00             | 30.63          | 229            | 151          | PK       |
| 2                                                                                                                                                                                                                                                            | 11200.0000     | 19.63               | 15.10          | 34.73             | 54.00             | 19.27          | 126            | 167          | AV       |
| 3                                                                                                                                                                                                                                                            | 16800.0000     | 21.05               | 24.83          | 45.88             | 68.20             | 22.32          | 400            | 184          | PK       |
| 4                                                                                                                                                                                                                                                            | 16800.0000     | 11.56               | 24.83          | 36.39             | 54.00             | 17.61          | 144            | 164          | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m] |                |                     |                |                   |                   |                |                |              |          |



|                 |                 |                  |             |                |                   |             |             |           |          |
|-----------------|-----------------|------------------|-------------|----------------|-------------------|-------------|-------------|-----------|----------|
| Channel         | 802.11n20 CH140 |                  |             |                | Frequency         | 5700 MHz    |             |           |          |
| Frequency Range | Above 1G        |                  |             |                | Detector Function | PK/AV       |             |           |          |
| Horizontal      |                 |                  |             |                |                   |             |             |           |          |
| NO.             | Freq. [MHz]     | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m]    | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5698.6743       | 89.28            | 8.84        | 98.12          |                   |             | 326         | 330       | PK       |
| 2               | 5725.0000       | 45.20            | 8.89        | 54.09          | 68.30             | 14.21       | 283         | 123       | PK       |
| 3               | 5744.3472       | 47.07            | 8.94        | 56.01          | 68.30             | 12.29       | 223         | 318       | PK       |
| 4               | 11400.0000      | 25.80            | 15.09       | 40.89          | 74.00             | 33.11       | 271         | 103       | PK       |
| 5               | 11400.0000      | 16.73            | 15.09       | 31.82          | 54.00             | 22.18       | 373         | 56        | AV       |
| 6               | 17100.0000      | 19.75            | 25.93       | 45.68          | 68.20             | 22.52       | 142         | 297       | PK       |
| 7               | 17100.0000      | 10.56            | 25.93       | 36.49          | 54.00             | 17.51       | 283         | 351       | AV       |

FCC Part15 407

FCC Part15 407-PK

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]

|                 |             |                  |             |                   |                |             |             |           |          |
|-----------------|-------------|------------------|-------------|-------------------|----------------|-------------|-------------|-----------|----------|
| Channel         |             | 802.11n20 CH140  |             | Frequency         |                | 5700 MHz    |             |           |          |
| Frequency Range |             | Above 1G         |             | Detector Function |                | PK/AV       |             |           |          |
| Vertical        |             |                  |             |                   |                |             |             |           |          |
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m]    | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5698.0740   | 92.33            | 8.79        | 101.12            |                |             | 315         | 1         | PK       |
| 2               | 5725.0000   | 45.87            | 8.89        | 54.76             | 68.30          | 13.54       | 202         | 358       | PK       |
| 3               | 5744.3972   | 47.88            | 8.94        | 56.82             | 68.30          | 11.48       | 262         | 1         | PK       |
| 4               | 11400.0000  | 28.39            | 15.09       | 43.48             | 74.00          | 30.52       | 114         | 282       | PK       |
| 5               | 11400.0000  | 18.63            | 15.09       | 33.72             | 54.00          | 20.28       | 380         | 278       | AV       |
| 6               | 17100.0000  | 19.80            | 25.93       | 45.73             | 68.20          | 22.47       | 385         | 23        | PK       |
| 7               | 17100.0000  | 10.41            | 25.93       | 36.34             | 54.00          | 17.66       | 263         | 255       | AV       |

FCC Part15 407

FCC Part15 407-PK

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]




|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11n20 CH 144    |                |                   | Frequency         |                | 5720MHz        |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                |                   | Detector Function |                | PK/AV          |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11440.0000     | 24.07               | 15.04          | 39.11             | 74.00             | 34.89          | 119            | 353          | PK       |
| 2                                                                                                                                                                                                                                                            | 11440.0000     | 16.65               | 15.04          | 31.69             | 54.00             | 22.31          | 207            | 138          | AV       |
| 3                                                                                                                                                                                                                                                            | 17160.0000     | 19.87               | 25.86          | 45.73             | 68.20             | 22.47          | 136            | 62           | PK       |
| 4                                                                                                                                                                                                                                                            | 17160.0000     | 12.21               | 25.86          | 38.07             | 54.00             | 15.93          | 301            | 62           | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11440.0000     | 27.32               | 15.04          | 42.36             | 74.00             | 31.64          | 363            | 205          | PK       |
| 2                                                                                                                                                                                                                                                            | 11440.0000     | 19.59               | 15.04          | 34.63             | 54.00             | 19.37          | 141            | 291          | AV       |
| 3                                                                                                                                                                                                                                                            | 17160.0000     | 19.35               | 25.86          | 45.21             | 68.20             | 22.99          | 171            | 239          | PK       |
| 4                                                                                                                                                                                                                                                            | 17160.0000     | 12.16               | 25.86          | 38.02             | 54.00             | 15.98          | 182            | 10           | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m] |                |                     |                |                   |                   |                |                |              |          |



|                 |                 |                   |          |
|-----------------|-----------------|-------------------|----------|
| Channel         | 802.11n40 CH102 | Frequency         | 5510 MHz |
| Frequency Range | Above 1G        | Detector Function | PK/AV    |

## Horizontal

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5452.3012   | 46.53            | 9.78        | 56.31          | 74.00          | 17.69       | 142         | 324       | PK       |
| 2   | 5456.3032   | 35.26            | 9.89        | 45.15          | 54.00          | 8.85        | 184         | 155       | AV       |
| 3   | 5470.0000   | 44.59            | 9.94        | 54.53          | 68.30          | 13.77       | 157         | 121       | PK       |
| 4   | 5511.0805   | 79.52            | 9.73        | 89.25          |                |             | 323         | 147       | AV       |
| 5   | 5512.4562   | 88.20            | 9.71        | 97.91          |                |             | 127         | 147       | PK       |
| 6   | 11020.0000  | 26.12            | 14.89       | 41.01          | 74.00          | 32.99       | 325         | 331       | PK       |
| 7   | 11020.0000  | 16.72            | 14.89       | 31.61          | 54.00          | 22.39       | 382         | 139       | AV       |
| 8   | 16530.0000  | 21.35            | 23.21       | 44.56          | 68.20          | 23.64       | 107         | 202       | PK       |
| 9   | 16530.0000  | 11.73            | 23.21       | 34.94          | 54.00          | 19.06       | 391         | 245       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]






|                 |                 |                   |          |
|-----------------|-----------------|-------------------|----------|
| Channel         | 802.11n40 CH102 | Frequency         | 5510 MHz |
| Frequency Range | Above 1G        | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5454.3022   | 37.16            | 9.83        | 46.99          | 54.00          | 7.01        | 194         | 295       | AV       |
| 2   | 5455.0525   | 48.48            | 9.85        | 58.33          | 74.00          | 15.67       | 108         | 304       | PK       |
| 3   | 5470.0000   | 47.62            | 9.94        | 57.56          | 68.30          | 10.74       | 286         | 329       | PK       |
| 4   | 5508.8294   | 94.22            | 9.69        | 103.91         |                |             | 200         | 359       | PK       |
| 5   | 5511.0805   | 86.18            | 9.73        | 95.91          |                |             | 271         | 3         | AV       |
| 6   | 11020.0000  | 26.25            | 14.89       | 41.14          | 74.00          | 32.86       | 353         | 212       | PK       |
| 7   | 11020.0000  | 17.51            | 14.89       | 32.40          | 54.00          | 21.60       | 116         | 26        | AV       |
| 8   | 16530.0000  | 21.53            | 23.21       | 44.74          | 68.20          | 23.46       | 108         | 56        | PK       |
| 9   | 16530.0000  | 11.50            | 23.21       | 34.71          | 54.00          | 19.29       | 257         | 129       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]




|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11n40 CH 126    |                |                   | Frequency         |                | 5630MHz        |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                |                   | Detector Function |                | PK/AV          |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11260.0000     | 25.89               | 14.87          | 40.76             | 74.00             | 33.24          | 250            | 105          | PK       |
| 2                                                                                                                                                                                                                                                            | 11260.0000     | 17.22               | 14.87          | 32.09             | 54.00             | 21.91          | 376            | 168          | AV       |
| 3                                                                                                                                                                                                                                                            | 16890.0000     | 20.08               | 25.27          | 45.35             | 68.20             | 22.85          | 249            | 105          | PK       |
| 4                                                                                                                                                                                                                                                            | 16890.0000     | 11.92               | 25.27          | 37.19             | 54.00             | 16.81          | 289            | 16           | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11260.0000     | 26.54               | 14.87          | 41.41             | 74.00             | 32.59          | 136            | 262          | PK       |
| 2                                                                                                                                                                                                                                                            | 11260.0000     | 18.39               | 14.87          | 33.26             | 54.00             | 20.74          | 381            | 146          | AV       |
| 3                                                                                                                                                                                                                                                            | 16890.0000     | 21.47               | 25.27          | 46.74             | 68.20             | 21.46          | 225            | 302          | PK       |
| 4                                                                                                                                                                                                                                                            | 16890.0000     | 11.73               | 25.27          | 37.00             | 54.00             | 17.00          | 335            | 146          | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m] |                |                     |                |                   |                   |                |                |              |          |



|                 |             |                  |             |                |                   |             |             |           |          |
|-----------------|-------------|------------------|-------------|----------------|-------------------|-------------|-------------|-----------|----------|
| Channel         |             | 802.11n40 CH134  |             |                | Frequency         |             | 5670 MHz    |           |          |
| Frequency Range |             | Above 1G         |             |                | Detector Function |             | PK/AV       |           |          |
| Horizontal      |             |                  |             |                |                   |             |             |           |          |
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m]    | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5672.3112   | 88.69            | 9.18        | 97.87          |                   |             | 364         | 335       | PK       |
| 2               | 5725.0000   | 45.57            | 8.89        | 54.46          | 68.30             | 13.84       | 293         | 19        | PK       |
| 3               | 5746.6983   | 48.18            | 8.93        | 57.11          | 68.30             | 11.19       | 367         | 347       | PK       |
| 4               | 11340.0000  | 26.51            | 14.88       | 41.39          | 74.00             | 32.61       | 150         | 36        | PK       |
| 5               | 11340.0000  | 17.13            | 14.88       | 32.01          | 54.00             | 21.99       | 150         | 291       | AV       |
| 6               | 17010.0000  | 20.37            | 26.15       | 46.52          | 68.20             | 21.68       | 150         | 230       | PK       |
| 7               | 17010.0000  | 10.85            | 26.15       | 37.00          | 54.00             | 17.00       | 150         | 33        | AV       |

FCC Part15 407



FCC Part15 407-PK

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]



|                 |                 |                   |          |
|-----------------|-----------------|-------------------|----------|
| Channel         | 802.11n40 CH134 | Frequency         | 5670 MHz |
| Frequency Range | Above 1G        | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5672.4112   | 91.25            | 9.17        | 100.42         |                |             | 156         | 17        | PK       |
| 2   | 5725.0000   | 45.07            | 8.89        | 53.96          | 68.30          | 14.34       | 265         | 234       | PK       |
| 3   | 5748.6493   | 47.18            | 8.93        | 56.11          | 68.30          | 12.19       | 163         | 1         | PK       |
| 4   | 11340.0000  | 27.67            | 14.88       | 42.55          | 74.00          | 31.45       | 366         | 215       | PK       |
| 5   | 11340.0000  | 16.55            | 14.88       | 31.43          | 54.00          | 22.57       | 157         | 118       | AV       |
| 6   | 17010.0000  | 20.26            | 26.15       | 46.41          | 68.20          | 21.79       | 102         | 313       | PK       |
| 7   | 17010.0000  | 11.33            | 26.15       | 37.48          | 54.00          | 16.52       | 373         | 111       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]




|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11n40 CH 142    |                |                   | Frequency         |                | 5710MHz        |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                |                   | Detector Function |                | PK/AV          |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11420.0000     | 25.50               | 15.13          | 40.63             | 74.00             | 33.37          | 217            | 189          | PK       |
| 2                                                                                                                                                                                                                                                            | 11420.0000     | 16.76               | 15.13          | 31.89             | 54.00             | 22.11          | 236            | 189          | AV       |
| 3                                                                                                                                                                                                                                                            | 17130.0000     | 18.99               | 26.05          | 45.04             | 68.20             | 23.16          | 172            | 104          | PK       |
| 4                                                                                                                                                                                                                                                            | 17130.0000     | 12.15               | 26.05          | 38.20             | 54.00             | 15.80          | 249            | 327          | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11420.0000     | 26.22               | 15.13          | 41.35             | 74.00             | 32.65          | 374            | 284          | PK       |
| 2                                                                                                                                                                                                                                                            | 11420.0000     | 19.48               | 15.13          | 34.61             | 54.00             | 19.39          | 382            | 232          | AV       |
| 3                                                                                                                                                                                                                                                            | 17130.0000     | 19.25               | 26.05          | 45.30             | 68.20             | 22.90          | 233            | 351          | PK       |
| 4                                                                                                                                                                                                                                                            | 17130.0000     | 11.46               | 26.05          | 37.51             | 54.00             | 16.49          | 320            | 157          | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m] |                |                     |                |                   |                   |                |                |              |          |



|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ac80 CH106 | Frequency         | 5530 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

## Horizontal

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5451.8009   | 46.57            | 9.76        | 56.33          | 74.00          | 17.67       | 172         | 63        | PK       |
| 2   | 5454.3022   | 35.09            | 9.83        | 44.92          | 54.00          | 9.08        | 183         | 149       | AV       |
| 3   | 5470.0000   | 44.87            | 9.94        | 54.81          | 68.30          | 13.49       | 281         | 37        | PK       |
| 4   | 5533.2166   | 83.84            | 8.96        | 92.80          |                |             | 207         | 153       | PK       |
| 5   | 5533.5918   | 74.53            | 8.96        | 83.49          |                |             | 121         | 153       | AV       |
| 6   | 11060.0000  | 25.77            | 15.05       | 40.82          | 74.00          | 33.18       | 195         | 6         | PK       |
| 7   | 11060.0000  | 16.78            | 15.05       | 31.83          | 54.00          | 22.17       | 101         | 338       | AV       |
| 8   | 16590.0000  | 21.86            | 23.82       | 45.68          | 68.20          | 22.52       | 212         | 209       | PK       |
| 9   | 16590.0000  | 11.62            | 23.82       | 35.44          | 54.00          | 18.56       | 197         | 315       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]






|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ac80 CH106 | Frequency         | 5530 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5453.4267   | 38.03            | 9.81        | 47.84          | 54.00          | 6.16        | 111         | 308       | AV       |
| 2   | 5453.6768   | 51.49            | 9.81        | 61.30          | 74.00          | 12.70       | 118         | 304       | PK       |
| 3   | 5470.0000   | 49.51            | 9.94        | 59.45          | 68.30          | 8.85        | 169         | 304       | PK       |
| 4   | 5532.2161   | 90.47            | 8.94        | 99.41          |                |             | 35          | 10        | PK       |
| 5   | 5533.3417   | 81.49            | 8.96        | 90.45          |                |             | 202         | 5         | AV       |
| 6   | 11060.0000  | 26.06            | 15.05       | 41.11          | 74.00          | 32.89       | 109         | 143       | PK       |
| 7   | 11060.0000  | 16.83            | 15.05       | 31.88          | 54.00          | 22.12       | 203         | 242       | AV       |
| 8   | 16590.0000  | 21.30            | 23.82       | 45.12          | 68.20          | 23.08       | 347         | 229       | PK       |
| 9   | 16590.0000  | 12.25            | 23.82       | 36.07          | 54.00          | 17.93       | 235         | 352       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ac80 CH122 | Frequency         | 5610 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

### Horizontal

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5613.0315   | 83.73            | 9.02        | 92.75          |                |             | 196         | 322       | PK       |
| 2   | 5725.0000   | 45.32            | 8.89        | 54.21          | 68.30          | 14.09       | 148         | 3         | PK       |
| 3   | 5744.9975   | 47.18            | 8.94        | 56.12          | 68.30          | 12.18       | 282         | 206       | PK       |
| 4   | 11220.0000  | 26.33            | 15.03       | 41.36          | 74.00          | 32.64       | 315         | 43        | PK       |
| 5   | 11220.0000  | 16.88            | 15.03       | 31.91          | 54.00          | 22.09       | 211         | 53        | AV       |
| 6   | 16830.0000  | 21.23            | 24.89       | 46.12          | 68.20          | 22.08       | 389         | 3         | PK       |
| 7   | 16830.0000  | 11.08            | 24.89       | 35.97          | 54.00          | 18.03       | 155         | 63        | AV       |




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ac80 CH122 | Frequency         | 5610 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

### Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5614.3322   | 89.63            | 9.01        | 98.64          |                |             | 154         | 5         | PK       |
| 2   | 5725.0000   | 45.49            | 8.89        | 54.38          | 68.30          | 13.92       | 173         | 260       | PK       |
| 3   | 5734.9925   | 47.39            | 8.81        | 56.20          | 68.30          | 12.10       | 215         | 25        | PK       |
| 4   | 11220.0000  | 26.06            | 15.03       | 41.09          | 74.00          | 32.91       | 199         | 150       | PK       |
| 5   | 11220.0000  | 16.67            | 15.03       | 31.70          | 54.00          | 22.30       | 263         | 43        | AV       |
| 6   | 16830.0000  | 20.71            | 24.89       | 45.60          | 68.20          | 22.60       | 383         | 163       | PK       |
| 7   | 16830.0000  | 11.18            | 24.89       | 36.07          | 54.00          | 17.93       | 250         | 332       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]




|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11ac80 CH 138   |                |                   | Frequency         |                | 5690MHz        |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                |                   | Detector Function |                | PK/AV          |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11380.0000     | 25.77               | 14.99          | 40.76             | 74.00             | 33.24          | 194            | 46           | PK       |
| 2                                                                                                                                                                                                                                                            | 11380.0000     | 17.90               | 14.99          | 32.89             | 54.00             | 21.11          | 384            | 184          | AV       |
| 3                                                                                                                                                                                                                                                            | 17070.0000     | 19.31               | 26.26          | 45.57             | 68.20             | 22.63          | 290            | 13           | PK       |
| 4                                                                                                                                                                                                                                                            | 17070.0000     | 12.48               | 26.26          | 38.74             | 54.00             | 15.26          | 399            | 13           | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11380.0000     | 26.56               | 14.99          | 41.55             | 74.00             | 32.45          | 319            | 218          | PK       |
| 2                                                                                                                                                                                                                                                            | 11380.0000     | 18.77               | 14.99          | 33.76             | 54.00             | 20.24          | 191            | 43           | AV       |
| 3                                                                                                                                                                                                                                                            | 17070.0000     | 20.01               | 26.26          | 46.27             | 68.20             | 21.93          | 323            | 158          | PK       |
| 4                                                                                                                                                                                                                                                            | 17070.0000     | 12.36               | 26.26          | 38.62             | 54.00             | 15.38          | 376            | 6            | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m] |                |                     |                |                   |                   |                |                |              |          |



|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ax80 CH106 | Frequency         | 5530 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

## Horizontal

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5435.7929   | 46.67            | 9.78        | 56.45          | 74.00          | 17.55       | 369         | 41        | PK       |
| 2   | 5453.6768   | 35.02            | 9.81        | 44.83          | 54.00          | 9.17        | 371         | 320       | AV       |
| 3   | 5470.0000   | 44.64            | 9.94        | 54.58          | 68.30          | 13.72       | 261         | 160       | PK       |
| 4   | 5535.8429   | 73.22            | 9.01        | 82.23          |                |             | 104         | 151       | AV       |
| 5   | 5536.0930   | 84.12            | 9.01        | 93.13          |                |             | 153         | 147       | PK       |
| 6   | 11060.0000  | 26.80            | 15.05       | 41.85          | 74.00          | 32.15       | 393         | 172       | PK       |
| 7   | 11060.0000  | 16.49            | 15.05       | 31.54          | 54.00          | 22.46       | 227         | 302       | AV       |
| 8   | 16590.0000  | 21.65            | 23.82       | 45.47          | 68.20          | 22.73       | 313         | 106       | PK       |
| 9   | 16590.0000  | 11.85            | 23.82       | 35.67          | 54.00          | 18.33       | 341         | 72        | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ax80 CH106 | Frequency         | 5530 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5453.6768   | 37.39            | 9.81        | 47.20          | 54.00          | 6.80        | 191         | 304       | AV       |
| 2   | 5454.0520   | 49.18            | 9.83        | 59.01          | 74.00          | 14.99       | 299         | 313       | PK       |
| 3   | 5470.0000   | 47.62            | 9.94        | 57.56          | 68.30          | 10.74       | 284         | 292       | PK       |
| 4   | 5534.9675   | 79.77            | 8.99        | 88.76          |                |             | 171         | 1         | AV       |
| 5   | 5538.5943   | 90.25            | 9.06        | 99.31          |                |             | 125         | 10        | PK       |
| 6   | 11060.0000  | 25.47            | 15.05       | 40.52          | 74.00          | 33.48       | 300         | 50        | PK       |
| 7   | 11060.0000  | 16.93            | 15.05       | 31.98          | 54.00          | 22.02       | 349         | 56        | AV       |
| 8   | 16590.0000  | 20.92            | 23.82       | 44.74          | 68.20          | 23.46       | 299         | 53        | PK       |
| 9   | 16590.0000  | 12.05            | 23.82       | 35.87          | 54.00          | 18.13       | 308         | 210       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]






|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ax80 CH122 | Frequency         | 5610 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

## Horizontal

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5598.9245   | 84.23            | 8.86        | 93.09          |                |             | 350         | 326       | PK       |
| 2   | 5725.0000   | 45.19            | 8.89        | 54.08          | 68.30          | 14.22       | 180         | 302       | PK       |
| 3   | 5736.4932   | 46.66            | 8.85        | 55.51          | 68.30          | 12.79       | 242         | 34        | PK       |
| 4   | 11220.0000  | 25.91            | 15.03       | 40.94          | 74.00          | 33.06       | 255         | 76        | PK       |
| 5   | 11220.0000  | 16.81            | 15.03       | 31.84          | 54.00          | 22.16       | 345         | 252       | AV       |
| 6   | 16830.0000  | 21.96            | 24.89       | 46.85          | 68.20          | 21.35       | 173         | 186       | PK       |
| 7   | 16830.0000  | 11.88            | 24.89       | 36.77          | 54.00          | 17.23       | 235         | 30        | AV       |




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                  |                   |          |
|-----------------|------------------|-------------------|----------|
| Channel         | 802.11ax80 CH122 | Frequency         | 5610 MHz |
| Frequency Range | Above 1G         | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5605.1276   | 89.97            | 8.94        | 98.91          |                |             | 140         | 17        | PK       |
| 2   | 5725.0000   | 45.60            | 8.89        | 54.49          | 68.30          | 13.81       | 390         | 101       | PK       |
| 3   | 5733.4917   | 47.19            | 8.77        | 55.96          | 68.30          | 12.34       | 379         | 359       | PK       |
| 4   | 11220.0000  | 26.40            | 15.03       | 41.43          | 74.00          | 32.57       | 101         | 305       | PK       |
| 5   | 11220.0000  | 16.83            | 15.03       | 31.86          | 54.00          | 22.14       | 171         | 26        | AV       |
| 6   | 16830.0000  | 19.86            | 24.89       | 44.75          | 68.20          | 23.45       | 133         | 182       | PK       |
| 7   | 16830.0000  | 12.01            | 24.89       | 36.90          | 54.00          | 17.10       | 372         | 226       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11ax80 CH 138   |                |                   | Frequency         |                | 5690MHz        |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                |                   | Detector Function |                | PK/AV          |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11380.0000     | 24.49               | 14.99          | 39.48             | 74.00             | 34.52          | 105            | 26           | PK       |
| 2                                                                                                                                                                                                                                                            | 11380.0000     | 17.60               | 14.99          | 32.59             | 54.00             | 21.41          | 367            | 49           | AV       |
| 3                                                                                                                                                                                                                                                            | 17070.0000     | 20.12               | 26.26          | 46.38             | 68.20             | 21.82          | 279            | 306          | PK       |
| 4                                                                                                                                                                                                                                                            | 17070.0000     | 11.94               | 26.26          | 38.20             | 54.00             | 15.80          | 118            | 23           | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11380.0000     | 25.88               | 14.99          | 40.87             | 74.00             | 33.13          | 190            | 139          | PK       |
| 2                                                                                                                                                                                                                                                            | 11380.0000     | 17.39               | 14.99          | 32.38             | 54.00             | 21.62          | 187            | 80           | AV       |
| 3                                                                                                                                                                                                                                                            | 17070.0000     | 19.46               | 26.26          | 45.72             | 68.20             | 22.48          | 319            | 299          | PK       |
| 4                                                                                                                                                                                                                                                            | 17070.0000     | 13.07               | 26.26          | 39.33             | 54.00             | 14.67          | 296            | 299          | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m] |                |                     |                |                   |                   |                |                |              |          |






|                 |               |                   |          |
|-----------------|---------------|-------------------|----------|
| Channel         | 802.11a CH149 | Frequency         | 5745 MHz |
| Frequency Range | Above 1G      | Detector Function | PK/AV    |

## Vertical

| NO. | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
|-----|-------------|------------------|-------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 5613.8819   | 47.03            | 9.02        | 56.05          | 68.20          | 12.15       | 235         | 251       | PK       |
| 2   | 5747.0735   | 90.66            | 8.93        | 99.59          |                |             | 230         | 288       | PK       |
| 3   | 5972.5613   | 50.59            | 10.00       | 60.59          | 68.20          | 7.61        | 134         | 200       | PK       |
| 4   | 11490.0000  | 24.49            | 15.04       | 39.53          | 74.00          | 34.47       | 292         | 249       | PK       |
| 5   | 11490.0000  | 17.30            | 15.04       | 32.34          | 54.00          | 21.66       | 322         | 249       | AV       |
| 6   | 17235.0000  | 19.65            | 25.53       | 45.18          | 68.20          | 23.02       | 304         | 72        | PK       |
| 7   | 17235.0000  | 12.19            | 25.53       | 37.72          | 54.00          | 16.28       | 336         | 126       | AV       |



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                                                                                                                                                                                                                                                              |                |                     |                |                   |                   |                |                |              |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------|----------------|-------------------|-------------------|----------------|----------------|--------------|----------|
| Channel                                                                                                                                                                                                                                                      |                | 802.11a CH 157      |                | Frequency         |                   | 5785MHz        |                |              |          |
| Frequency Range                                                                                                                                                                                                                                              |                | Above 1G            |                | Detector Function |                   | PK/AV          |                |              |          |
| Horizontal                                                                                                                                                                                                                                                   |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Detector |
| 1                                                                                                                                                                                                                                                            | 11570.0000     | 25.40               | 15.34          | 40.74             | 74.00             | 33.26          | 219            | 142          | PK       |
| 2                                                                                                                                                                                                                                                            | 11570.0000     | 18.51               | 15.34          | 33.85             | 54.00             | 20.15          | 152            | 93           | AV       |
| 3                                                                                                                                                                                                                                                            | 17355.0000     | 19.35               | 26.30          | 45.65             | 68.20             | 22.55          | 337            | 99           | PK       |
| 4                                                                                                                                                                                                                                                            | 17355.0000     | 13.31               | 26.30          | 39.61             | 54.00             | 14.39          | 202            | 122          | AV       |
| Vertical                                                                                                                                                                                                                                                     |                |                     |                |                   |                   |                |                |              |          |
| NO.                                                                                                                                                                                                                                                          | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Factor<br>[dB] | Level<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Remark   |
| 1                                                                                                                                                                                                                                                            | 11570.0000     | 26.13               | 15.34          | 41.47             | 74.00             | 32.53          | 251            | 189          | PK       |
| 2                                                                                                                                                                                                                                                            | 11570.0000     | 18.33               | 15.34          | 33.67             | 54.00             | 20.33          | 136            | 66           | AV       |
| 3                                                                                                                                                                                                                                                            | 17355.0000     | 19.16               | 26.30          | 45.46             | 68.20             | 22.74          | 222            | 295          | PK       |
| 4                                                                                                                                                                                                                                                            | 17355.0000     | 12.52               | 26.30          | 38.82             | 54.00             | 15.18          | 167            | 216          | AV       |
| Remark: 1. The emission levels of other frequencies were greater than 20dB margin.<br>2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).<br>3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).<br>4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m] |                |                     |                |                   |                   |                |                |              |          |





|                 |               |                  |             |                   |                |             |             |           |          |
|-----------------|---------------|------------------|-------------|-------------------|----------------|-------------|-------------|-----------|----------|
| Channel         | 802.11a CH165 |                  |             | Frequency         | 5825 MHz       |             |             |           |          |
| Frequency Range | Above 1G      |                  |             | Detector Function | PK/AV          |             |             |           |          |
| Horizontal      |               |                  |             |                   |                |             |             |           |          |
| NO.             | Freq. [MHz]   | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m]    | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5639.0195     | 48.21            | 8.49        | 56.70             | 68.20          | 11.50       | 203         | 194       | PK       |
| 2               | 5826.0505     | 92.46            | 8.78        | 101.24            |                |             | 198         | 296       | PK       |
| 3               | 5971.8109     | 52.18            | 10.01       | 62.19             | 68.20          | 6.01        | 125         | 264       | PK       |
| 4               | 11650.0000    | 25.27            | 15.21       | 40.48             | 74.00          | 33.52       | 358         | 188       | PK       |
| 5               | 11650.0000    | 18.26            | 15.21       | 33.47             | 54.00          | 20.53       | 270         | 351       | AV       |
| 6               | 17475.0000    | 19.31            | 26.05       | 45.36             | 68.20          | 22.84       | 274         | 357       | PK       |
| 7               | 17475.0000    | 10.96            | 26.05       | 37.01             | 54.00          | 16.99       | 156         | 202       | AV       |

FCC Part15 407

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |             |                  |             |                   |                |             |             |           |          |
|-----------------|-------------|------------------|-------------|-------------------|----------------|-------------|-------------|-----------|----------|
| Channel         |             | 802.11a CH165    |             | Frequency         |                | 5825 MHz    |             |           |          |
| Frequency Range |             | Above 1G         |             | Detector Function |                | PK/AV       |             |           |          |
| Vertical        |             |                  |             |                   |                |             |             |           |          |
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m]    | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5633.9545   | 47.02            | 8.81        | 55.83             | 68.20          | 12.37       | 209         | 80        | PK       |
| 2               | 5725.0000   | 45.76            | 8.89        | 54.65             | 68.20          | 67.55       | 176         | 358       | PK       |
| 3               | 5823.2366   | 98.28            | 8.82        | 107.10            |                |             | 102         | 1         | PK       |
| 4               | 11650.0000  | 24.62            | 15.21       | 39.83             | 74.00          | 34.17       | 161         | 33        | PK       |
| 5               | 11650.0000  | 18.49            | 15.21       | 33.70             | 54.00          | 20.30       | 138         | 105       | AV       |
| 6               | 17475.0000  | 18.30            | 26.05       | 44.35             | 68.20          | 23.85       | 166         | 13        | PK       |
| 7               | 17475.0000  | 11.44            | 26.05       | 37.49             | 54.00          | 16.51       | 362         | 252       | AV       |

FCC Part15 407

Frequency[Hz]

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV/m) + Factor (dB).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



|                 |                 |                  |             |                   |                |             |             |           |          |
|-----------------|-----------------|------------------|-------------|-------------------|----------------|-------------|-------------|-----------|----------|
| Channel         | 802.11n20 CH149 |                  |             | Frequency         | 5745 MHz       |             |             |           |          |
| Frequency Range | Above 1G        |                  |             | Detector Function | PK/AV          |             |             |           |          |
| Horizontal      |                 |                  |             |                   |                |             |             |           |          |
| NO.             | Freq. [MHz]     | Reading [dBμV/m] | Factor [dB] | Level [dBμV/m]    | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector |
| 1               | 5636.7684       | 48.45            | 8.63        | 57.08             | 68.20          | 11.12       | 168         | 202       | PK       |
| 2               | 5746.6983       | 88.95            | 8.93        | 97.88             |                |             | 397         | 239       | PK       |
| 3               | 5933.5418       | 47.28            | 10.61       | 57.89             | 68.20          | 10.31       | 232         | 308       | PK       |
| 4               | 11490.0000      | 24.70            | 15.04       | 39.74             | 74.00          | 34.26       | 255         | 229       | PK       |
| 5               | 11490.0000      | 17.96            | 15.04       | 33.00             | 54.00          | 21.00       | 283         | 358       | AV       |
| 6               | 17235.0000      | 19.48            | 25.53       | 45.01             | 68.20          | 23.19       | 326         | 140       | PK       |
| 7               | 17235.0000      | 12.80            | 25.53       | 38.33             | 54.00          | 15.67       | 169         | 110       | AV       |

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.  
2. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).  
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]