

# THRU Lab & Engineering.

477-6, Hager-Ri, Yoju-Up, Yoju-Gun  
Kyunggi-Do, 469-803, Korea  
T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

## Test Report

Product Name: Watch Pager(Receiver)

FCCID: QBT-LT2005W

**Applicant:**  
**Lee Technology Korea Co., Ltd.**

3<sup>rd</sup> FL #499-2 Sang 3-dong, Wonmi-gu,  
Bucheon-city, Kyungki-do,  
KOREA

**Date Receipt:** 07/11/2007

**Date Tested:** 07/12/2007

APPLICANT: Lee Technology Korea Co., Ltd.  
FCCID #: QBT-LT2005W  
REPORT #:THRU-707001

COVER SHEET

# THRU Lab & Engineering.

477-6, Hager-Ri, Yaju-Up, Yaju-Gun  
Kyunggi-Do, 469-803, Korea  
T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID: QBT-LT2005W

## TABLE OF CONTENTS FOR A RECEIVER REPORT

PAGE 1.....TEST EQUIPMENT LIST

PAGE 2.....TEST PROCEDURE

PAGE 3-6.....RADIATED EMISSIONS TEST DATA

PAGE 7-9....POWERLINE CONDUCTED EMISSIONS

APPLICANT: Lee Technology Korea Co., Ltd.  
FCCID #: QBT-LT2005W  
REPORT #:THRU-707001

TABLE OF CONTENTS

# THRU Lab & Engineering.

477-6, Hager-Ri, Yoju-Up, Yoju-Gun

Kyunggi-Do, 469-803, Korea

T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

## EMC Equipment List

No	Description	Manufacturer	Model No.	Serial No.	Due Cal.
1	Test Receiver	Rohde & Schwarz	ESHS 10	825832/014	2007.08.25
2	Test Receiver	Rohde & Schwarz	ESVS 10	826008/014	2008.06.12
3	Spectrum Analyzer	Hewlett Packard	8566B	2311A02394	2008.06.13
4	Spectrum Display	Hewlett Packard	85662A	2542A12429	2008.06.13
5	Quasi-peak Adapter	Hewlett Packard	85650A	2521A00887	2008.06.13
6	RF Preselector	Hewlett Packard	85685A	2648A00504	2008.06.13
7	Preamplifier	Hewlett Packard	8449B	3008A00375	2007.04.23
8	Preamplifier	Hewlett Packard	8447F	3113A05367	2007.05.09
9	Preamplifier	Hewlett Packard	8447F	2805A02570	2008.05.28
10	Preamplifier	A.H. Systems	PAM-0118	164	2008.05.08
11	Biconical Antenna	Eaton Corp.	94455-1	0977	2008.04.01
12	Biconical Antenna	EMCO	3104C	9111-2468	2008.06.07
13	Log Periodic Antenna	EMCO	3146	2051	2008.05.11
14	Horn Antenna	A.H. Systems	SAS-571	414	2008.03.17
15	Loop Antenna	Rohde & Schwarz	HFH2-Z2.335.4711.52	826532/006	2009.01.31
16	Dipole Antenna	Rohde & Schwarz	VHAP	574	2007.12.12
17	Dipole Antenna	Rohde & Schwarz	VHAP	575	2007.12.12
18	Dipole Antenna	Rohde & Schwarz	UHAP	546	2007.12.12
19	Dipole Antenna	Rohde & Schwarz	UHAP	547	2007.12.12
20	Signal Generator	Rohde & Schwarz	SMX	825459/030	2007.06.15
21	Spectrum Monitor	Rohde & Schwarz	EZM	862304/007	None
22	Panorama Monitor	Rohde & Schwarz	EPN	883707/207	None
23	Spectrum Analyzer	Advantest Corp.	R3261C	61720208	2008.06.12
24	LISN	EMCO	3825/2	9111-1912	2007.12.12
25	LISN	Kyoritsu	KNW-242	8-923-2	2008.05.23
26	Plotter	Hewlett Packard	7475A	2210A02802	None
27	Modulation Analyzer	Hewlett Packard	8901B	3438A05094	2008.05.25
28	Waveform Generator	Hewlett Packard	33120A	US3400119 0	2008.05.21
29	Audio analyzer	Hewlett Packard	8903B	3011A12915	2008.05.21
30	Temperature & Humidity Chamber	TABAI EZPEC CORP.	MC711P	112000492	2006.08.27
31	Antenna Mast	EMCO	1070-3	9109-1617	None

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID #: QBT-LT2005W

REPORT #:THRU-707001

# THRU Lab & Engineering.

477-6, Hager-Ri, Yaju-Up, Yaju-Gun

Kyunggi-Do, 469-803, Korea

T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

32	Turn Table	EMCO	1080-1,2	9203-1762	None
33	Positioning Controller	EMCO	1090	9111-1054	
34	Antenna Power Supply	Rohde & Schwarz	HZ-9	920127	None
35	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	881052	None
36	Coaxial Take-up Reel	EMCO	100817	9109-1684	None

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID #: QBT-LT2005W

REPORT #:THRU-707001

2 of 7

# THRU Lab & Engineering.

477-6, Hager-Ri, Yaju-Up, Yaju-Gun

Kyunggi-Do, 469-803, Korea

T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

## TEST PROCEDURE

**GENERAL:** This report shall NOT be reproduced except in full without the written approval of of THRU &ENGINEERING. Shielded interface cables were used in all cases except for cables connecting to the telephone line and the power cords. A test program was run which simulated a normal data transmission on a network.

**RADIATION INTERFERENCE:** The test procedure used was ANSI STANDARD C63.4-2003 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 28.5°C with a humidity of 60%.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

**Example:**

$$\begin{array}{ll} \text{Freq (MHz) METER READING + ACF = FS} \\ 33 \quad 20 \text{ dBuV} + 10.36 \text{ dB} = 30.36 \text{ dBuV/m @ 3m} \end{array}$$

**ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES:** The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-2003 10.1.7 with the EUT 40 cm from the vertical ground wall.

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID #: QBT-LT2005W

REPORT #:THRU-707001

# THRU Lab & Engineering.

477-6, Hager-Ri, Yoju-Up, Yoju-Gun

Kyunggi-Do, 469-803, Korea

T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID: QBT-LT2005W

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.109, 15.33(b)(3)

REQUIREMENTS:	30 to 88 MHz:	40.0 dBuV/M @ 3 METERS
	88 to 216 MHz:	43.5 dBuV/M
	216 to 960 MHz:	46.0 dBuV/M
	ABOVE 960 MHz:	54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

## TEST DATA:

\* Tuning Frequency : 450.3250MHz

No	Emission Frequency (MHz)	Meter Reading dBuV/m	Ant. Polarity	Correction Factor dB	Cable Loss dB	Field Strength (dBuV/m)	Margin (dBuv)	Limit (dBuv/m)
1	46.24	10.2	V	11.6	1.0	22.8	-17.2	40.0
2	71.12	10.1	H	5.8	1.2	17.1	-22.9	40.0
3	80.46	9.6	V	8.2	1.3	19.1	-20.9	40.0
4	125.40	9.4	H	11.8	1.9	23.1	-20.4	43.5
5	154.50	7.9	V	16.9	2.1	27.0	-16.5	43.5
6	194.30	8.6	H	14.7	2.5	25.7	-17.8	43.5
7	216.20	9.4	H	10.7	2.7	22.8	-23.2	46.0
8	372.50	8.6	H	15.0	4.0	27.6	-18.4	46.0
9	513.00	5.2	V	17.9	5.0	28.1	-17.9	46.0
10	694.50	5.5	H	21.3	6.2	33.0	-13.0	46.0
11	730.00	4.2	H	21.2	6.4	31.8	-14.2	46.0
12	857.00	5.2	H	23.2	7.1	35.5	-10.5	46.0
13	879.50	4.3	V	23.6	7.2	35.1	-10.9	46.0
14	875.85							46.0
15	900.42							46.0
16	923.00							46.0

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB.

TEST PROCEDURE: ANSI STANDARD C63.4-2003 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Pre-selector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an appropriate antenna - see the test equipment list. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: Kyoung Moon Choi

DATE: 07/12/2007

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID #: QBT-LT2005W

REPORT #:THRU-707001

# THRU Lab & Engineering.

477-6, Hager-Ri, Yoju-Up, Yoju-Gun

Kyunggi-Do, 469-803, Korea

T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID: QBT-LT2005W

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.109, 15.33(b)(3)

REQUIREMENTS:	30 to 88 MHz:	40.0 dBuV/M @ 3 METERS
	88 to 216 MHz:	43.5 dBuV/M
	216 to 960 MHz:	46.0 dBuV/M
	ABOVE 960 MHz:	54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

## TEST DATA:

\* Tuning Frequency : 457.5750MHz

No	Emission Frequency (MHz)	Meter Reading dBuV/m	Ant. Polarity	Correction Factor dB	Cable Loss dB	Field Strength (dBuV/m)	Margin (dBuv)	Limit (dBuv/m)
1	45.78	12.7	H	11.7	1.0	25.4	-14.6	40.0
2	66.13	12.0	H	6.2	1.2	19.4	-20.6	40.0
3	80.46	9.8	V	8.2	1.3	19.3	-20.7	40.0
4	117.50	10.5	V	10.9	1.8	23.2	-20.3	43.5
5	125.70	9.7	H	11.9	1.9	23.5	-20.0	43.5
6	194.20	8.3	H	14.6	2.5	25.4	-18.1	43.5
7	344.30	8.9	V	15.3	3.8	28.0	-18.0	46.0
8	429.20	7.4	H	15.9	4.4	27.7	-18.3	46.0
9	487.70	8.1	V	18.7	4.8	31.6	-14.4	46.0
10	508.50	8.1	H	18.0	5.0	31.0	-15.0	46.0
11	616.00	7.5	H	20.1	5.7	33.3	-12.7	46.0
12	706.50	8.4	H	21.4	6.2	36.0	-10.0	46.0
13	852.00	5.6	V	23.1	7.0	35.7	-10.3	46.0
14	872.35							46.0
15	925.55							46.0
16	955.15							46.0

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB.

TEST PROCEDURE: ANSI STANDARD C63.4-2003 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Pre-selector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an appropriate antenna - see the test equipment list. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: Kyoung Moon Choi

DATE: 07/12/2007

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID #: QBT-LT2005W

REPORT #:THRU-707001

# THRU Lab & Engineering.

477-6, Hager-Ri, Yoju-Up, Yoju-Gun

Kyunggi-Do, 469-803, Korea

T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID: QBT-LT2005W

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.109, 15.33(b)(3)

REQUIREMENTS:	30 to 88 MHz:	40.0 dBuV/M @ 3 METERS
	88 to 216 MHz:	43.5 dBuV/M
	216 to 960 MHz:	46.0 dBuV/M
	ABOVE 960 MHz:	54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

## TEST DATA:

\* Tuning Frequency : 467.8000MHz

No	Emission Frequency (MHz)	Meter Reading dBuV/m	Ant. Polarity	Correction Factor dB	Cable Loss dB	Field Strength (dBuV/m)	Margin (dBuv)	Limit (dBuv/m)
1	49.72	13.2	V	11.0	1.0	25.2	-14.8	40.0
2	68.13	12.4	H	5.8	1.2	19.4	-20.6	40.0
3	133.00	10.2	V	13.4	2.0	25.6	-17.9	43.5
4	143.00	10.1	H	15.6	2.0	27.7	-15.8	43.5
5	194.50	10.5	H	14.7	2.5	27.7	-15.8	43.5
6	276.50	7.4	V	16.2	3.3	26.9	-19.1	46.0
7	415.90	9.1	H	15.6	4.3	29.1	-16.9	46.0
8	483.80	5.6	V	18.9	4.8	29.3	-16.7	46.0
9	573.50	10.2	H	18.5	5.4	34.1	-11.9	46.0
10	627.50	7.5	V	20.6	5.7	33.8	-12.2	46.0
11	718.00	5.6	H	21.3	6.3	33.2	-12.8	46.0
12	857.00	4.9	H	23.2	7.1	35.2	-10.8	46.0
13	885.00	5.0	H	23.6	7.2	35.8	-10.2	46.0
14	892.80							46.0
15	917.64							46.0
16	972.03							54.0

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB.

TEST PROCEDURE: ANSI STANDARD C63.4-2003 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Pre-selector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an appropriate antenna - see the test equipment list. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: Kyoung Moon Choi

DATE: 07/12/2007

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID #: QBT-LT2005W

REPORT #:THRU-707001

# THRU Lab & Engineering.

477-6, Hager-Ri, Yaju-Up, Yaju-Gun  
Kyunggi-Do, 469-803, Korea  
T820318835092F820318835169 email [thrukang@kornet.net](mailto:thrukang@kornet.net)

**APPLICANT:** Lee Technology Korea Co., Ltd.

**MODEL #:** QBT-LT2005W

**NAME OF TEST:** POWER LINE CONDUCTED INTERFERENCE

**RULES PART NO.:** 15.107

<b>REQUIREMENTS:</b>	<b>QUASI-PEAK</b>	<b>AVERAGE</b>
.15 - 0.5 MHz	66-56 dBuV	56-46 dBuV
0.5 - 5.0	56	46
5.0 - 30.	60	50

**TEST PROCEDURE:** ANSI STANDARD C63.4-2003. The spectrum was scanned from .15 to 30 MHz.

**TEST DATA:**

THE HIGHEST EMISSION READ FOR LINE 1 WAS 18.5dBuV @ 0.161MHz

THE HIGHEST EMISSION READ FOR LINE 2 WAS 21.1dBuV @ 0.420MHz

THE GRAPHS ON THE FOLLOWING PAGE REPRESENT THE EMISSIONS TAKEN FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

**PERFORMED BY:** Kyoung Moon Choi

**DATE:** 07/12/2007

## “Not Applicable”

APPLICANT: Lee Technology Korea Co., Ltd.

FCCID #: QBT-LT2005W

REPORT #:THRU-707001

7 of 7