



# FCC TEST REPORT (BLUETOOTH LE)

**REPORT NO.:** RF141013D01-3

**MODEL NO.:** AM30

**FCC ID:** QCIAM30

**RECEIVED:** Oct. 13, 2014

**TESTED:** Oct. 30 ~ Dec. 15, 2014

**ISSUED:** Dec. 23, 2014

**APPLICANT:** SMART Technologies Inc.

**ADDRESS:** 3636 Research Road NW Calgary, AB T2L 1Y1  
CANADA

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist.,  
New Taipei City, Taiwan ( R.O.C. )

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



## Table of Contents

|   |    |
|---|----|
| RELEASE CONTROL RECORD .....  | 4  |
| 1. CERTIFICATION.....   | 5  |
| 2. SUMMARY OF TEST RESULTS .....                                    | 6  |
| 2.1 MEASUREMENT UNCERTAINTY.....                                    | 6  |
| 3. GENERAL INFORMATION .....  | 7  |
| 3.1 GENERAL DESCRIPTION OF EUT .....                                | 7  |
| 3.2 DESCRIPTION OF TEST MODES .....                                 | 8  |
| 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....        | 9  |
| 3.3 DUTY CYCLE OF TEST SIGNAL .....                                 | 11 |
| 3.4 DESCRIPTION OF SUPPORT UNITS .....                              | 12 |
| 3.4.1 CONFIGURATION OF SYSTEM UNDER TEST.....                       | 13 |
| 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS.....                   | 14 |
| 4. TEST TYPES AND RESULTS .....                                     | 15 |
| 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT .....                | 15 |
| 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE<br>MEASUREMENT ..... | 15 |
| 4.1.2 TEST INSTRUMENTS .....  | 16 |
| 4.1.3 TEST PROCEDURES .....   | 17 |
| 4.1.4 DEVIATION FROM TEST STANDARD.....                             | 17 |
| 4.1.5 TEST SETUP.....   | 18 |
| 4.1.6 EUT OPERATING CONDITIONS .....                                | 18 |
| 4.1.7 TEST RESULTS .....  | 19 |
| 4.2 CONDUCTED EMISSION MEASUREMENT .....                            | 23 |
| 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....                | 23 |
| 4.2.2 TEST INSTRUMENTS .....  | 23 |
| 4.2.3 TEST PROCEDURES .....   | 24 |
| 4.2.4 DEVIATION FROM TEST STANDARD.....                             | 24 |
| 4.2.5 TEST SETUP.....   | 24 |
| 4.2.6 EUT OPERATING CONDITIONS .....                                | 24 |
| 4.2.7 TEST RESULTS .....  | 25 |
| 4.3 6dB BANDWIDTH MEASUREMENT .....                                 | 27 |
| 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....                     | 27 |
| 4.3.2 TEST SETUP .....  | 27 |
| 4.3.3 TEST INSTRUMENTS .....  | 27 |
| 4.3.4 TEST PROCEDURE.....   | 27 |
| 4.3.5 DEVIATION FROM TEST STANDARD.....                             | 27 |
| 4.3.6 EUT OPERATING CONDITIONS .....                                | 27 |
| 4.3.7 TEST RESULTS .....  | 28 |
| 4.4 CONDUCTED OUTPUT POWER.....                                     | 29 |
| 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....             | 29 |
| 4.4.2 TEST SETUP .....  | 29 |
| 4.4.3 TEST INSTRUMENTS.....   | 29 |



A D T

|  |    |
|--|----|
| 4.4.4 TEST PROCEDURES .....  | 29 |
| 4.4.5 DEVIATION FROM TEST STANDARD .....   | 29 |
| 4.4.6 EUT OPERATING CONDITIONS .....   | 29 |
| 4.4.7 TEST RESULTS .....   | 30 |
| 4.5 POWER SPECTRAL DENSITY MEASUREMENT .....   | 31 |
| 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....                                       | 31 |
| 4.5.2 TEST SETUP .....   | 31 |
| 4.5.3 TEST INSTRUMENTS .....   | 31 |
| 4.5.4 TEST PROCEDURE .....   | 31 |
| 4.5.5 DEVIATION FROM TEST STANDARD .....   | 31 |
| 4.5.6 EUT OPERATING CONDITION .....  | 31 |
| 4.5.7 TEST RESULTS .....   | 32 |
| 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....   | 33 |
| 4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....                               | 33 |
| 4.6.2 TEST SETUP .....   | 33 |
| 4.6.3 TEST INSTRUMENTS .....   | 33 |
| 4.6.4 TEST PROCEDURE .....   | 33 |
| 4.6.5 DEVIATION FROM TEST STANDARD .....   | 34 |
| 4.6.6 EUT OPERATING CONDITION .....  | 34 |
| 4.6.7 TEST RESULTS .....   | 34 |
| 5. PHOTOGRAPHS OF THE TEST CONFIGURATION .....   | 36 |
| 6. INFORMATION ON THE TESTING LABORATORIES .....   | 37 |
| 7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING<br>CHANGES TO THE EUT BY THE LAB ..... | 38 |



A D T

## RELEASE CONTROL RECORD

| ISSUE NO.     | REASON FOR CHANGE | DATE ISSUED   |
|---------------|-------------------|---------------|
| RF141013D01-3 | Original release  | Dec. 23, 2014 |



A D T

## 1. CERTIFICATION

**PRODUCT:** PC Device

**BRAND NAME:** SMART

**MODEL NO.:** AM30

**APPLICANT:** SMART Technologies Inc.

**TESTED:** Oct. 30 ~ Dec. 15, 2014

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS:** FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Annie Chang , **DATE:** Dec. 23, 2014  
( Annie Chang / Supervisor )

**APPROVED BY :** Rex Lai , **DATE:** Dec. 23, 2014  
( Rex Lai / Assistant Manager )



A D T

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C |                             |        |   |
|--|-----------------------------|--------|---|
| STANDARD SECTION                         | TEST TYPE                   | RESULT | REMARK  |
| 15.207                                   | AC Power Conducted Emission | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -11.24dB at 0.17997MHz. |
| 15.205 & 15.209                          | Radiated Emissions          | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -6.6dB at 35.53MHz.     |
| 15.247(d)                                | Band Edge Measurement       | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -13.5dB at 2400.00MHz.  |
| 15.247(d)                                | Antenna Port Emission       | PASS   | Meet the requirement of limit.  |
| 15.247(a)(2)                             | 6dB bandwidth               | PASS   | Meet the requirement of limit.  |
| 15.247(b)                                | Conducted power             | PASS   | Meet the requirement of limit.  |
| 15.247(e)                                | Power Spectral Density      | PASS   | Meet the requirement of limit.  |
| 15.203                                   | Antenna Requirement         | PASS   | No antenna connector is used.   |

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Measurement         | Frequency    | Uncertainty |
|---------------------|--------------|-------------|
| Conducted emissions | 150kHz~30MHz | 3.43 dB     |
| Radiated emissions  | 30MHz ~ 1GHz | 4.00 dB     |
|                     | Above 1GHz   | 3.36 dB     |



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                            |                                  |
|----------------------------|----------------------------------|
| <b>EUT</b>                 | PC Device                        |
| <b>MODEL NO.</b>           | AM30                             |
| <b>POWER SUPPLY</b>        | 19Vdc, 5A                        |
| <b>MODULATION TYPE</b>     | GFSK                             |
| <b>TRANSFER RATE</b>       | 1Mbit/sec.                       |
| <b>NUMBER OF CHANNEL</b>   | 40                               |
| <b>OPERATING FREQUENCY</b> | 2402-2480MHz                     |
| <b>MAX. OUTPUT POWER</b>   | 1.6mW                            |
| <b>ANTENNA TYPE</b>        | Dipole antenna with 2.18dBi gain |
| <b>ANTENNA CONNECTOR</b>   | N/A                              |
| <b>I/O PORTS</b>           | Refer to user's manual           |
| <b>DATA CABLE</b>          | N/A                              |
| <b>ACCESSORY DEVICES</b>   | N/A                              |

**NOTE:**

1. The EUT was configured with the following key components:

| <b>Component</b> | <b>Brand</b> | <b>Model No.</b> | <b>Spec.</b>                                |
|------------------|--------------|------------------|---|
| Processor        | Qualcomm     | APQ8074AC        | 4 cores /2.45GHz                            |
| RAM              | Samsung      | K3QF7F70DM-QGCF  | 3GB LPDDR3 SDRAM                            |
| Flash Storage    | Toshiba      | THGBMBG6D1KBAIL  | 8GB   |
| Wi-Fi/BT Chip    | Qualcomm     | WCN3680          | Dual -band 2.4GHz and 5GHz<br>WLAN / BT 4.0 |

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

### 3.2 DESCRIPTION OF TEST MODES

40 channels are provided to this EUT:

| CHANNEL | FREQ.<br>(MHz) | CHANNEL | FREQ.<br>(MHz) | CHANNEL | FREQ.<br>(MHz) | CHANNEL | FREQ.<br>(MHz) |
|---------|----------------|---------|----------------|---------|----------------|---------|----------------|
| 0       | 2402           | 10      | 2422           | 20      | 2442           | 30      | 2462           |
| 1       | 2404           | 11      | 2424           | 21      | 2444           | 31      | 2464           |
| 2       | 2406           | 12      | 2426           | 22      | 2446           | 32      | 2466           |
| 3       | 2408           | 13      | 2428           | 23      | 2448           | 33      | 2468           |
| 4       | 2410           | 14      | 2430           | 24      | 2450           | 34      | 2470           |
| 5       | 2412           | 15      | 2432           | 25      | 2452           | 35      | 2472           |
| 6       | 2414           | 16      | 2434           | 26      | 2454           | 36      | 2474           |
| 7       | 2416           | 17      | 2436           | 27      | 2456           | 37      | 2476           |
| 8       | 2418           | 18      | 2438           | 28      | 2458           | 38      | 2478           |
| 9       | 2420           | 19      | 2440           | 29      | 2460           | 39      | 2480           |

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

| EUT<br>CONFIGURE<br>MODE | APPLICABLE TO |         |         |      |    | DESCRIPTION |
|--------------------------|---------------|---------|---------|------|----|-------------|
|                          | PLC           | RE < 1G | RE ≥ 1G | APCM | OB |             |
| -                        | √             | √       | √       | √    | √  | -           |

Where **PLC**: Power Line Conducted Emission      **RE < 1G**: Radiated Emission below 1GHz  
**RE ≥ 1G**: Radiated Emission above 1GHz      **APCM**: Antenna Port Conducted Measurement  
**OB**: Conducted Out-Band Emission Measurement

#### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE<br>MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE |
|-----------------------|-------------------|----------------|-----------------|
| -                     | 0 to 39           | 19             | GFSK            |

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE<br>MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE |
|-----------------------|-------------------|----------------|-----------------|
| -                     | 0 to 39           | 0, 19, 39      | GFSK            |

#### POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE<br>MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE |
|-----------------------|-------------------|----------------|-----------------|
| -                     | 0 to 39           | 19             | GFSK            |



A D T

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE |
|--------------------|-------------------|----------------|-----------------|
| -                  | 0 to 39           | 0, 19, 39      | GFSK            |

**CONDUCTED OUT-BAND EMISSION MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE |
|--------------------|-------------------|----------------|-----------------|
| -                  | 0 to 39           | 0, 19, 39      | GFSK            |


**TEST CONDITION:**

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER  | TESTED BY |
|---------------|--------------------------|--------------|-----------|
| RE<1G         | 26deg. C, 73% RH         | 120Vac, 60Hz | Aaron You |
| RE≥1G         | 21deg. C, 79% RH         | 120Vac, 60Hz | Aaron You |
| PLC           | 21deg. C, 73% RH         | 120Vac, 60Hz | Aaron You |
| APCM          | 20deg. C, 70% RH         | 120Vac, 60Hz | Saxon Lee |
| OB            | 20deg. C, 70% RH         | 120Vac, 60Hz | Saxon Lee |

### 3.3 DUTY CYCLE OF TEST SIGNAL

Duty cycle of test signal is < 98%

Duty cycle =  $0.377/0.626 = 0.602$ , Duty factor =  $10 * \log(1/0.602) = 2.20$





A D T

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT         | BRAND     | MODEL NO.  | SERIAL NO.               | FCC ID           |
|-----|-----------------|-----------|------------|--------------------------|------------------|
| 1   | Mechanical tool | N/A       | N/A        | N/A                      | N/A              |
| 2   | ADAPTER         | FPS       | FSP120-AAB | N/A                      | N/A              |
| 3   | LCD MONITOR     | DELL      | U2410      | CN082WXD728<br>720CC0KDL | FCC DoC Approved |
| 4   | USB KEYBOARD    | BTC       | 5200U      | G09302046353             | E5XKB5122U       |
| 5   | USB Mouse       | Microsoft | 1113       | 9170515772226            | FCC DoC Approved |


| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS                                |
|-----|--|
| 1   | N/A  |
| 2   | DC cable (1.5m)  |
| 3   | 1.8m shielded HDMI cable   |
| 4   | 1.5 m braid shielded wire, terminated with USB connector via drain wire, w/o core. |
| 5   | 1.5 m braid shielded wire, terminated with USB connector via drain wire, w/o core. |

**NOTE:** 1. All power cords of the above support units are non shielded (1.8m).


2. The support units 1-2 were provided by client.

### 3.4.1 CONFIGURATION OF SYSTEM UNDER TEST

For Conduction test only:



For Other tests except for Conduction test:





A D T

### 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**

**558074 D01 DTS Meas Guidance v03r02**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

**NOTE:** The product has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



## 4. TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| FREQUENCIES (MHz) | FIELD STRENGTH (microvolts/meter) | MEASUREMENT DISTANCE (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>u</sub>V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

## 4.1.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER        | MODEL NO.                | SERIAL NO.     | CALIBRATED DATE | CALIBRATED UNTIL |
|-----------------------------------|--------------------------|----------------|-----------------|------------------|
| HP Preamplifier                   | 8447D                    | 2432A03504     | Feb. 26, 2014   | Feb. 25, 2015    |
| HP Preamplifier                   | 8449B                    | 3008A01201     | Feb. 26, 2014   | Feb. 25, 2015    |
| MITEQ Preamplifier                | AMF-6F-260400-3 3-8P     | 892164         | Mar. 01, 2014   | Feb. 28, 2015    |
| Agilent Spectrum                  | E4446A                   | MY51100050     | Oct. 24, 2014   | Oct. 23, 2015    |
| Agilent TEST RECEIVER             | N9038A                   | MY51210129     | Jan. 18, 2014   | Jan. 17, 2015    |
| Schwarzbeck Antenna               | VULB 9168                | 139            | Feb. 24, 2014   | Feb. 23, 2015    |
| Schwarzbeck Antenna               | VHBA 9123                | 480            | May 29, 2013    | May 28, 2015     |
| Schwarzbeck Horn Antenna          | BBHA-9170                | 212            | Aug. 26, 2014   | Aug. 25, 2015    |
| Schwarzbeck Horn Antenna          | BBHA 9120-D1             | D130           | Aug. 26, 2014   | Aug. 25, 2015    |
| ADT. Turn Table                   | TT100                    | 0306           | NA              | NA               |
| ADT. Tower                        | AT100                    | 0306           | NA              | NA               |
| Software                          | ADT_Radiated_V7.6.15.9.4 | NA             | NA              | NA               |
| SUHNER RF cable                   | SF104                    | CABLE-CH6      | Aug. 15, 2014   | Aug. 14, 2015    |
| SUHNER RF cable                   | SF102                    | Cable-CH8-3.6m | Aug. 15, 2014   | Aug. 14, 2015    |
| EMCO Horn Antenna                 | 3115                     | 00028257       | Aug. 28, 2014   | Aug. 27, 2015    |
| ROHDE & SCHWARZ Spectrum Analyzer | FSV40                    | 101042         | Sep. 29, 2014   | Sep. 28, 2015    |
| Anritsu Power Sensor              | MA2411B                  | 0738404        | Apr. 21, 2014   | Apr. 20, 2015    |
| Anritsu Power Meter               | ML2495A                  | 0842014        | Apr. 21, 2014   | Apr. 20, 2015    |

**NOTE:**

1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Chamber No. 6.
4. The Industry Canada Reference No. IC 7450E-6.
5. The FCC Site Registration No. is 447212.



A D T

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

#### 4.1.5 TEST SETUP

Frequency range 30MHz~1GHz



Frequency range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.



A D T

## 4.1.7 TEST RESULTS

### ABOVE 1GHz DATA

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 0 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | 2390.00        | 51.8 PK                       | 74.0              | -22.2          | 1.00 H                   | 311                        | 55.96                  | -4.20                          |
| 2   | 2390.00        | 38.4 AV                       | 54.0              | -15.7          | 1.00 H                   | 311                        | 42.55                  | -4.20                          |
| 3   | #2400.00       | 60.9 PK                       | 74.2              | -13.3          | 1.00 H                   | 311                        | 65.05                  | -4.14                          |
| 4   | #2400.00       | 48.6 AV                       | 70.4              | -21.8          | 1.00 H                   | 311                        | 52.69                  | -4.14                          |
| 5   | *2402.00       | 94.2 PK                       |                   |                | 1.00 H                   | 311                        | 98.35                  | -4.13                          |
| 6   | *2402.00       | 90.4 AV                       |                   |                | 1.00 H                   | 311                        | 94.52                  | -4.13                          |
| 7   | 4804.00        | 44.9 PK                       | 74.0              | -29.1          | 1.21 H                   | 227                        | 42.51                  | 2.35                           |
| 8   | 4804.00        | 32.6 AV                       | 54.0              | -21.5          | 1.21 H                   | 227                        | 30.20                  | 2.35                           |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | 2390.00        | 52.2 PK                       | 74.0              | -21.8          | 1.00 V                   | 330                        | 56.36                  | -4.20                          |
| 2   | 2390.00        | 38.5 AV                       | 54.0              | -15.5          | 1.00 V                   | 330                        | 42.71                  | -4.20                          |
| 3   | #2400.00       | 64.7 PK                       | 78.2              | -13.5          | 1.00 V                   | 330                        | 68.88                  | -4.14                          |
| 4   | #2400.00       | 52.1 AV                       | 73.9              | -21.8          | 1.00 V                   | 330                        | 56.24                  | -4.14                          |
| 5   | *2402.00       | 98.2 PK                       |                   |                | 1.00 V                   | 330                        | 102.32                 | -4.13                          |
| 6   | *2402.00       | 93.9 AV                       |                   |                | 1.00 V                   | 330                        | 98.02                  | -4.13                          |
| 7   | 4804.00        | 45.4 PK                       | 74.0              | -28.6          | 1.05 V                   | 293                        | 43.08                  | 2.35                           |
| 8   | 4804.00        | 33.7 AV                       | 54.0              | -20.3          | 1.05 V                   | 293                        | 31.31                  | 2.35                           |

### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 19 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | *2440.00       | 92.6 PK                       |                   |                | 1.11 H                   | 285                        | 96.55                  | -3.95                          |
| 2   | *2440.00       | 88.6 AV                       |                   |                | 1.11 H                   | 285                        | 92.56                  | -3.95                          |
| 3   | 4880.00        | 45.1 PK                       | 74.0              | -28.9          | 1.02 H                   | 253                        | 42.65                  | 2.46                           |
| 4   | 4880.00        | 32.7 AV                       | 54.0              | -21.4          | 1.02 H                   | 253                        | 30.19                  | 2.46                           |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | *2440.00       | 96.2 PK                       |                   |                | 1.74 V                   | 273                        | 100.16                 | -3.95                          |
| 2   | *2440.00       | 92.1 AV                       |                   |                | 1.74 V                   | 273                        | 96.07                  | -3.95                          |
| 3   | 4880.00        | 45.3 PK                       | 74.0              | -28.7          | 1.00 V                   | 126                        | 42.88                  | 2.46                           |
| 4   | 4880.00        | 33.6 AV                       | 54.0              | -20.4          | 1.00 V                   | 126                        | 31.15                  | 2.46                           |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 39 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | *2480.00       | 92.7 PK                       |                   |                | 1.09 H                   | 285                        | 96.50                  | -3.78                          |
| 2   | *2480.00       | 88.7 AV                       |                   |                | 1.09 H                   | 285                        | 92.47                  | -3.78                          |
| 3   | 2483.50        | 51.4 PK                       | 74.0              | -22.7          | 1.09 H                   | 285                        | 55.12                  | -3.77                          |
| 4   | 2483.50        | 38.4 AV                       | 54.0              | -15.6          | 1.09 H                   | 285                        | 42.20                  | -3.77                          |
| 5   | 4960.00        | 45.3 PK                       | 74.0              | -28.7          | 1.02 H                   | 230                        | 42.71                  | 2.59                           |
| 6   | 4960.00        | 33.0 AV                       | 54.0              | -21.0          | 1.02 H                   | 230                        | 30.38                  | 2.59                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | *2480.00       | 96.4 PK                       |                   |                | 1.69 V                   | 272                        | 100.18                 | -3.78                          |
| 2   | *2480.00       | 92.3 AV                       |                   |                | 1.69 V                   | 272                        | 96.03                  | -3.78                          |
| 3   | 2483.50        | 51.7 PK                       | 74.0              | -22.4          | 1.69 V                   | 272                        | 55.42                  | -3.77                          |
| 4   | 2483.50        | 38.5 AV                       | 54.0              | -15.5          | 1.69 V                   | 272                        | 42.28                  | -3.77                          |
| 5   | 4960.00        | 45.8 PK                       | 74.0              | -28.2          | 1.15 V                   | 193                        | 43.24                  | 2.59                           |
| 6   | 4960.00        | 33.7 AV                       | 54.0              | -20.3          | 1.15 V                   | 193                        | 31.08                  | 2.59                           |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

## BELOW 1GHZ WORST-CASE DATA

|                 |               |                      |                 |
|-----------------|---------------|----------------------|-----------------|
| CHANNEL         | TX Channel 19 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz  |                      |                 |

## ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 34.46          | 29.7 QP                       | 40.0              | -10.4          | 2.75 H                   | 258                        | 44.82                  | -15.17                         |
| 2   | 178.46         | 19.6 QP                       | 43.5              | -24.0          | 2.61 H                   | 240                        | 34.20                  | -14.65                         |
| 3   | 265.71         | 25.8 QP                       | 46.0              | -20.2          | 1.73 H                   | 34                         | 39.02                  | -13.23                         |
| 4   | 327.35         | 30.3 QP                       | 46.0              | -15.7          | 2.04 H                   | 49                         | 41.78                  | -11.44                         |
| 5   | 370.03         | 31.5 QP                       | 46.0              | -14.5          | 2.20 H                   | 266                        | 42.13                  | -10.64                         |
| 6   | 749.98         | 27.8 QP                       | 46.0              | -18.2          | 1.07 H                   | 247                        | 31.51                  | -3.68                          |

## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 35.53          | 33.4 QP                       | 40.0              | -6.6           | 1.26 V                   | 34                         | 48.55                  | -15.12                         |
| 2   | 79.47          | 24.1 QP                       | 40.0              | -15.9          | 1.13 V                   | 360                        | 42.19                  | -18.05                         |
| 3   | 116.38         | 24.5 QP                       | 43.5              | -19.0          | 1.00 V                   | 242                        | 40.78                  | -16.30                         |
| 4   | 178.12         | 26.4 QP                       | 43.5              | -17.1          | 1.00 V                   | 244                        | 41.00                  | -14.63                         |
| 5   | 326.38         | 25.7 QP                       | 46.0              | -20.3          | 1.00 V                   | 111                        | 37.14                  | -11.44                         |
| 6   | 749.98         | 27.9 QP                       | 46.0              | -18.2          | 2.51 V                   | 171                        | 31.53                  | -3.68                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dB $\mu$ V) |          |
|-----------------------------|------------------------------|----------|
|                             | Quasi-peak                   | Average  |
| 0.15 ~ 0.5                  | 66 to 56                     | 56 to 46 |
| 0.5 ~ 5                     | 56                           | 46       |
| 5 ~ 30                      | 60                           | 50       |

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 TEST INSTRUMENTS

| Description & Manufacturer                                       | Model No.       | Serial No.   | Cal. Date     | Cal. Due      |
|--|-----------------|--------------|---------------|---------------|
| ROHDE & SCHWARZ<br>TEST RECEIVER                                 | ESCS 30         | 100276       | Apr. 18, 2014 | Apr. 17, 2015 |
| ROHDE & SCHWARZ<br>Artificial Mains Network<br>(for EUT)         | ENV216          | 101197       | Apr. 18, 2014 | Apr. 17, 2015 |
| LISN With Adapter<br>(for EUT)                                   | AD10            | C10Ada-002   | Apr. 18, 2014 | Apr. 17, 2015 |
| ROHDE & SCHWARZ<br>Artificial Mains Network<br>(for peripherals) | ESH3-Z5         | 100218       | Nov. 25, 2014 | Nov. 24, 2015 |
| SCHWARZBECK<br>Artificial Mains Network<br>(For EUT)             | NNLK8129        | 8129229      | May 08, 2014  | May 07, 2015  |
| Software   | ADT_Cond_V7.3.7 | NA           | NA            | NA            |
| RF cable (JYEBAO)  | 5D-FB           | Cable-C10.01 | Feb. 18, 2014 | Feb. 17, 2015 |
| SUHNER Terminator<br>(For ROHDE & SCHWARZ<br>LISN)               | 65BNC-5001      | E1-011484    | May 27, 2014  | May 26, 2015  |
| ROHDE & SCHWARZ<br>Artificial Mains Network<br>(For TV EUT)      | ESH3-Z5         | 100220       | Nov. 20, 2014 | Nov. 19, 2015 |
| LISN With Adapter<br>(for TV EUT)                                | 100220          | N/A          | Nov. 20, 2014 | Nov. 19, 2015 |

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in Shielded Room No. 10.  
3. The VCCI Site Registration No. C-1852.

#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



**Note: Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under transmission condition continuously at specific channel frequency.
- b. EUT sent messages to monitor and monitor displayed it on screen.

## 4.2.7 TEST RESULTS


### CONDUCTED WORST-CASE DATA :

| PHASE |  | Line 1 |  | 6dB BANDWIDTH |  | 9kHz |  |
|-------|--|--------|--|---------------|--|------|--|
|-------|--|--------|--|---------------|--|------|--|

| No | Frequency<br>(MHz) | Correction<br>Factor<br>(dB) | Reading Value<br>(dBuV) |       | Emission Level<br>(dBuV) |       | Limit<br>(dBuV) |       | Margin<br>(dB) |        |
|----|--------------------|------------------------------|-------------------------|-------|--------------------------|-------|-----------------|-------|----------------|--------|
|    |                    |                              | Q.P.                    | AV.   | Q.P.                     | AV.   | Q.P.            | AV.   | Q.P.           | AV.    |
| 1  | 0.17997            | 9.66                         | 42.51                   | 33.58 | 52.17                    | 43.24 | 64.49           | 54.49 | -12.31         | -11.24 |
| 2  | 0.23984            | 9.66                         | 34.08                   | 24.00 | 43.74                    | 33.66 | 62.10           | 52.10 | -18.36         | -18.44 |
| 3  | 0.35958            | 9.67                         | 32.84                   | 25.61 | 42.51                    | 35.28 | 58.74           | 48.74 | -16.23         | -13.46 |
| 4  | 0.59930            | 9.68                         | 21.67                   | 19.19 | 31.35                    | 28.87 | 56.00           | 46.00 | -24.65         | -17.13 |
| 5  | 1.37500            | 9.69                         | 20.94                   | 16.32 | 30.63                    | 26.01 | 56.00           | 46.00 | -25.37         | -19.99 |
| 6  | 4.05469            | 9.73                         | 19.04                   | 6.50  | 28.77                    | 16.23 | 56.00           | 46.00 | -27.23         | -29.77 |
| 7  | 18.78125           | 9.95                         | 19.86                   | 12.69 | 29.81                    | 22.64 | 60.00           | 50.00 | -30.19         | -27.36 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|              |        |                      |      |
|--------------|--------|----------------------|------|
| <b>PHASE</b> | Line 2 | <b>6dB BANDWIDTH</b> | 9kHz |
|--------------|--------|----------------------|------|

| No | Frequency<br>(MHz) | Correction<br>Factor<br>(dB) | Phase Of Power : Neutral (N) |       |                          |       |                 |       |                |        |
|----|--------------------|------------------------------|------------------------------|-------|--------------------------|-------|-----------------|-------|----------------|--------|
|    |                    |                              | Reading Value<br>(dBuV)      |       | Emission Level<br>(dBuV) |       | Limit<br>(dBuV) |       | Margin<br>(dB) |        |
|    |                    |                              | Q.P.                         | AV.   | Q.P.                     | AV.   | Q.P.            | AV.   | Q.P.           | AV.    |
| 1  | 0.18125            | 9.67                         | 43.11                        | 32.93 | 52.78                    | 42.60 | 64.43           | 54.43 | -11.65         | -11.83 |
| 2  | 0.23984            | 9.67                         | 34.96                        | 24.22 | 44.63                    | 33.89 | 62.10           | 52.10 | -17.47         | -18.21 |
| 3  | 0.35703            | 9.68                         | 32.66                        | 25.27 | 42.34                    | 34.95 | 58.80           | 48.80 | -16.46         | -13.85 |
| 4  | 1.42969            | 9.69                         | 20.41                        | 15.86 | 30.10                    | 25.55 | 56.00           | 46.00 | -25.90         | -20.45 |
| 5  | 4.10938            | 9.74                         | 18.59                        | 8.27  | 28.33                    | 18.01 | 56.00           | 46.00 | -27.67         | -27.99 |
| 6  | 18.67969           | 9.97                         | 18.94                        | 11.45 | 28.91                    | 21.42 | 60.00           | 50.00 | -31.09         | -28.58 |

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




## 4.3 6dB BANDWIDTH MEASUREMENT

### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 4.3.2 TEST SETUP



### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.3.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

#### 4.3.7 TEST RESULTS

| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) | MINIMUM LIMIT (MHz) | PASS / FAIL |
|---------|-------------------------|---------------------|---------------------|-------------|
| 0       | 2402                    | 0.69                | 0.5                 | PASS        |
| 19      | 2440                    | 0.69                | 0.5                 | PASS        |
| 39      | 2480                    | 0.69                | 0.5                 | PASS        |




## 4.4 CONDUCTED OUTPUT POWER

### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

### 4.4.2 TEST SETUP



### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 TEST PROCEDURES

A peak / average power sensor were used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the power level.

### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



A D T

## 4.4.7 TEST RESULTS

### FOR PEAK POWER

| CHANNEL | FREQUENCY (MHz) | PEAK POWER (dBm) | PEAK POWER (mW) | LIMIT (dBm) | PASS/FAIL |
|---------|-----------------|------------------|-----------------|-------------|-----------|
| 0       | 2402            | 1.33             | 1.4             | 30          | PASS      |
| 19      | 2440            | 1.95             | 1.6             | 30          | PASS      |
| 39      | 2480            | 1.32             | 1.4             | 30          | PASS      |

### FOR AVERAGE POWER

| CHANNEL | FREQUENCY (MHz) | AVERAGE POWER (dBm) |
|---------|-----------------|---------------------|
| 0       | 2402            | 1.11                |
| 19      | 2440            | 1.71                |
| 39      | 2480            | 1.12                |




A D T

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- a. Set the RBW = 3 kHz, VBW = 10 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITION


Same as Item 4.3.6



A D T

## 4.5.7 TEST RESULTS

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 0       | 2402           | -23.83            | 8                   | PASS          |
| 19      | 2440           | -23.47            | 8                   | PASS          |
| 39      | 2480           | -25.50            | 8                   | PASS          |






## 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

### 4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 TEST PROCEDURE

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



A D T

## MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

## 4.6.5 DEVIATION FROM TEST STANDARD





No deviation.

## 4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

## 4.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

**CH 0**

**CH 19**

**CH 39**

**CH 0 Band edge**




A D T

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## 7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---