

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-18N-RWD-003

AGR No. : A18OA-159

Applicant : Woosim Systems Inc.

Address : 60, Sandan-ro 388beon-gil, Galsan-myeon, Hongseong-gun, Chungcheongnam-do,
Korea

Manufacturer : Woosim Systems Inc.

Address : 60, Sandan-ro 388beon-gil, Galsan-myeon, Hongseong-gun, Chungcheongnam-do,
Korea

Type of Equipment : Mobile Printer

FCC ID. : QDDWSP-MC350

Model Name : WSP-MC350

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : October 12, 2018

Date of issue : November 06, 2018

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:



Jae-Ho Lee / Chief Engineer
ONETECH Corp.

Approved by:



Keun-Young, Choi / Vice President
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6
4.1 EUT DESCRIPTION.....	6
4.2 CALCULATED MPE SAFE DISTANCE.....	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-18N-RWD-003	November 06, 2018	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : Woosim Systems Inc.
 Address : 60, Sandan-ro 388beon-gil, Galsan-myeon, Hongseong-gun, Chungcheongnam-do, Korea
 Contact Person : Moo Seung Lim / Manager
 Telephone No. : +82-41-339-3726
 FCC ID : QDDWSP-MC350
 Model Name : WSP-MC350
 Brand Name : -
 Serial Number : N/A
 Date : November 06, 2018

EQUIPMENT CLASS	<i>DSS – PART 15 SPREAD SPECTRUM TRANSMITTER</i>
E.U.T. DESCRIPTION	Mobile Printer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The Woosim Systems Inc., Model WSP-MC350 (referred to as the EUT in this report) is a Mobile Printer. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Mobile Printer	
Operating Frequency	2 402 MHz ~ 2 480 MHz	
RF Output Power	1 Mbps	4.65 dBm
	2 Mbps	2.68 dBm
	3 Mbps	2.77 dBm
Number of Channel	79 Channels	
Modulation Type	GFSK for 1 Mbps, $\pi/4$ -DQPSK for 2 Mbps, 8-DPSK for 3Mbps	
Antenna Type	Printed Monopole Antenna	
Antenna Gain	-3 dBi	
List of each Osc. or crystal Freq.(Freq. $\geq$ 1 MHz)	26 MHz	
Rated Supply Voltage	DC 7.4 V	

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 EUT Description

Kind of EUT	Mobile Printer	
Operating Frequency Band	☐ Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz ☐ WLAN: 2 412 MHz ~ 2 462 MHz ☐ WLAN: 5 180 MHz ~ 5 240 MHz ☐ WLAN: 5 745 MHz ~ 5 825 MHz ☒ Bluetooth: 2 402 MHz ~ 2 480 MHz ☐ Bluetooth BLE: 2 402 MHz ~ 2 480 MHz	
MAX. RF OUTPUT POWER	1 Mbps	4.65 dBm
	2 Mbps	2.68 dBm
	3 Mbps	2.77 dBm
Antenna Gain	-3 dBi	
Exposure Evaluation Applied	☐ MPE ☐ SAR ☒ N/A	

4.2 Calculated MPE Safe Distance

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

$$[(\text{Max. Power of channel, including tune-up tolerance, mW})/(\text{Mim. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3$$

$$= (2.92/5) \times \sqrt{2.480} = 0.92$$

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and are excluded from SAR Test.

	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
1 Mbps	2 480	4.15 ± 0.5	4.65	2.92	5	0.92
2 Mbps	2 480	2.18 ± 0.5	2.68	1.85	5	0.58
3 Mbps	2 480	2.27 ± 0.5	2.77	1.89	5	0.60



Tested by: Ha-Ram, Lee / Assistant Manager