



8DPSK

2 402 MHz


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 384.50 ¹⁾	V	45.60	27.10	-30.39	-	42.31	74.00	31.69
4 805.48 ¹⁾	H	54.60	32.33	-46.12	-	40.81	74.00	33.19
7 206.20	V	55.20	37.11	-44.31	-	48.00	74.00	26.00
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



Horizontal/Vertical for 1 GHz ~ 3.5 GHz




Horizontal/Vertical for 3.5 GHz ~ 18 GHz




2 441 MHz

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
4 846.08 ¹⁾	H	55.70	32.58	-45.94	-	42.34	74.00	31.66
7 323.17 ¹⁾	V	55.80	37.01	-44.29	-	48.52	74.00	25.48
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

Horizontal/Vertical for 1 GHz ~ 3.5 GHz




Horizontal/Vertical for 3.5 GHz ~ 18 GHz




2 480 MHz


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 483.56 ¹⁾	H	49.10	27.70	-30.24	-	46.56	74.00	27.44
4 956.77 ¹⁾	V	54.20	32.81	-45.44	-	41.57	74.00	32.43
7 446.90 ¹⁾	V	52.60	36.81	-44.08	-	45.33	74.00	28.67
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



Horizontal/Vertical for 1 GHz ~ 3.5 GHz




Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Test results (Above 18 GHz) – Worst Case : GFSK_2 402 MHz

Horizontal/Vertical for 18 GHz ~ 26.5 GHz




Note: The Worst case was based on the lowest margin condition considering Harmonic and Spurious Emission.


Simultaneous condition

Case 1 : 802.11n HT40 (2 422 MHz) + BT_BDR(DH-1)(2 402 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
4 801.13 ¹⁾	H	52.50	32.21	-43.85	-	40.86	74.00	33.14
4 838.35 ¹⁾	H	53.10	32.43	-43.68	-	41.85	74.00	32.15
7 206.20	H	55.20	36.72	-41.32	-	50.60	74.00	23.40
7 359.90 ¹⁾	H	51.30	36.46	-41.34	-	46.42	74.00	27.58
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



Horizontal/Vertical for 3.5 GHz ~ 18 GHz





Horizontal/Vertical for 18 GHz ~ 26.5 GHz




Case 2 : 802.11n HT40 (5 240 MHz) + BT_BDR(DH-1)(2 402 MHz)


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
4 826.15 ¹⁾	V	53.70	32.36	-43.73	-	42.33	74.00	31.67
7 205.72	V	51.40	36.72	-40.93	-	47.19	74.00	26.81
10 491.27	V	48.66	38.50	-42.06	-	45.10	68.20	23.10
15 719.37 ¹⁾	V	63.10	38.10	-39.59	-	61.61	74.00	12.39
Average Data								
15 719.37 ¹⁾	V	52.05	38.10	-39.59	0.33	50.89	54.00	3.11




Horizontal/Vertical for 3.5 GHz ~ 18 GHz




Horizontal/Vertical for 5 GHz ~ 6.5 GHz



Horizontal/Vertical for 6.5 GHz ~ 18 GHz




Horizontal/Vertical for 18 GHz ~ 26.5 GHz



7.7. Conducted Spurious Emission

Test setup



Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operation, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation specified in §15.209(a) is not required. In addition, radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limit : 20 dBc

Test procedure

ANSI C63.10-2013 - Section 6.10.4, 7.8.8

Test settings

▪ Band-edge

- 1) Span : Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation
- 2) Reference level : As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log(\text{OBW}/\text{RBW})]$ below the reference level.
- 3) Attenuation: Auto (at least 10 dB preferred)
- 4) Sweep time = Coupled
- 5) RBW : 100 kHz
- 6) VBW : 300 kHz
- 7) Detector : Peak
- 8) Trace : Max hold


▪ Spurious emissions

- 1) Span : 30 MHz to 10 times the operating frequency in GHz
- 2) RBW : 100 kHz
- 3) VBW : 300 kHz
- 4) Sweep time : Coupled
- 5) Detector : Peak


Test results

GFSK


Conducted band-edge / Low ch




Conducted spurious / Low ch.



Conducted band-edge / High ch.




Conducted spurious / Mid ch.



Conducted band-edge / Hopping ch.




Conducted spurious / High ch.




8DPSK


Conducted band-edge / Low ch




Conducted spurious / Low ch.




Conducted band-edge / High ch.




Conducted spurious / Mid ch.



Conducted band-edge / Hopping ch.




Conducted spurious / High ch.



7.8. AC Conducted Emission

Test setup



Limit


According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity — Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

Test results -Worst case: GFSK_2 480 MHz



Final Result

--- N_A Phase ---										
No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.27579	38.2	27.2	10.1	48.3	37.3	60.9	50.9	12.6	13.6
2	0.40388	32.6	14.2	10.3	42.9	24.5	57.8	47.8	14.9	23.3
3	0.55064	33.5	21.1	10.3	43.8	31.4	56.0	46.0	12.2	14.6
4	0.70235	30.2	17.2	10.1	40.3	27.3	56.0	46.0	15.7	18.7
5	2.12639	17.3	3.6	10.0	27.3	13.6	56.0	46.0	28.7	32.4
6	3.36134	22.3	6.6	10.0	32.3	16.6	56.0	46.0	23.7	29.4

--- L1_A Phase ---										
No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.28076	34.3	23.0	10.1	44.4	33.1	60.8	50.8	16.4	17.7
2	0.4048	28.3	11.6	10.3	38.6	21.9	57.8	47.8	19.2	25.9
3	0.55188	29.3	18.7	10.3	39.6	29.0	56.0	46.0	16.4	17.0
4	0.68775	27.4	15.3	10.2	37.6	25.5	56.0	46.0	18.4	20.5
5	0.96327	25.7	10.7	10.1	35.8	20.8	56.0	46.0	20.2	25.2
6	3.56019	22.8	7.3	10.0	32.8	17.3	56.0	46.0	23.2	28.7

8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV30	100732	24.07.03
DC Power Supply	AGILENT	E3632A	MY40008800	24.07.03
Attenuator	API Inmet	40AH2W-10	18	25.04.30
Power Sensor	R&S	NRP-Z81	1137.9009.02-106223-bB	25.04.24
Power Divider	Aeroflex/ Weinschel, Inc	1580-1	PE430	24.07.04
Bluetooth Tester	TESCOM	TC-3000C	3000C000270	24.07.04
Attenuator	HUBER+SUHNER	6610_SK-50-1/199_NE	ATT01	24.10.16
Signal Generator	R&S	SMB100A	176206	25.01.18
PSA Spectrum Analyzer	Agilent	E4440A	MY44303500	24.07.04
Amplifier	SONOMA INSTRUMENT	310N	421910	24.10.12
Bilog Antenna	Teseq GmbH	CBL 6112D	61521	24.11.17
Loop Antenna	R&S	HFH2-Z2	100355	24.08.10
Signal Generator	R&S	SMB100A	176206	25.01.18
Controller	INNCO SYSTEMS	CO3000	1441/54370322/ P	-
Antenna Mast	INNCO SYSTEMS	MA4640-XP-ET	-	-
Turn Device	INNCO SYSTEMS	DS1200-S-1t	-	-
Spectrum Analyzer	R&S	FSVA40	101575	24.06.19
Broadband PreAmplifier	SCHWARZBECK	BBV9718D	57	25.01.19
Low Noise Amplifier	TESTEK	TK-PA18H	220124-L	24.10.12
Low Noise Amplifier	TESTEK	TK-PA1840H	220133-L	24.10.17
Horn Antenna	SCHWARZBECK	BBHA9120D	2763	24.10.18
Horn Antenna	SCHWARZBECK	BBHA9170	1267	24.10.16
High Pass Filter	Wainwright Instruments GmbH	WHKX12-2805-3000-18000-40SS	SN58	24.10.16
High Pass Filter	QOTANA TECHNOLOGIES	DBHF0508004000A	23041800061	24.07.10
TWO-LINE V - NETWORK	R&S	ENV216	101358	24.09.27
EMI TEST RECEIVER	R&S	ESCI3	101408	24.08.18

End of test report