

System / software:	SARA2 / 2.3 VPM	Input Power Drift:	
Date / Time:	2/18/2005 11:18:46 AM	DUT Battery Model/No:	
Filename:	Byst5mmch6_3d.txt	Probe Serial Number:	0123
Ambient Temperature:	22.0°C	Liquid Simulant:	2450
Device Under Test:	Broadcom PPT	Relative Permittivity:	51.86
Relative Humidity:	50%	Conductivity:	1.912
Phantom S/No:	HeadBox_spout.csv	Liquid Temperature:	22.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-77.00 mm
DUT Position:	bystander 5mm	Max SAR Z-axis Location:	-161.00 mm
Antenna Configuration:	integral	Max E Field:	17.01 V/m
Test Frequency:	2437MHz	SAR 1g:	0.420 W/kg
Air Factors:	346 / 318 / 386	SAR 10g:	0.212 W/kg
Conversion Factors:	0.705 / 0.705 / 0.705	SAR Start:	0.092 W/kg
Type of Modulation:		SAR End:	0.092 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-0.04 dB
Diode Compression Factors (V*200):	19 / 19 / 19	Probe battery last changed:	2/3/05
Input Power Level:	max	Extrapolation:	poly4

