



**FCC CFR47 CERTIFICATION
CLASS II PERMISSIVE CHANGE
TEST REPORT**

FOR

BROADCOM 802.11ag WIRELESS LAN PCI-E MINI CARD

MODEL NUMBER: BCM94311MCAG

FCC ID: QDS-BRCM1019

REPORT NUMBER: 05U3891-1B

ISSUE DATE: FEBRUARY 06, 2006

Prepared for
**BROADCOM CORP.
190 MATHILDA PLACE
SUNNYVALE, CA 94086, USA**

Prepared by
**COMPLIANCE ENGINEERING SERVICES, INC.
d.b.a.
COMPLIANCE CERTIFICATION SERVICES
561F MONTEREY ROAD,
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888**



LAB CODE:200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
A	01/23/06	Initial Issue	Thu
B	02/06/06	Revised Section 8.1.1 6dB Bandwidth Table	Thu

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY.....	5
3. CROSS REFERENCE TO OTHER REPORTS ON THIS PRODUCT.....	5
4. FACILITIES AND ACCREDITATION.....	5
5. CALIBRATION AND UNCERTAINTY.....	5
5.1. MEASURING INSTRUMENT CALIBRATION.....	5
5.2. MEASUREMENT UNCERTAINTY.....	5
6. EQUIPMENT UNDER TEST.....	6
6.1. DESCRIPTION OF EUT.....	6
6.2. CLASS II PERMISSIVE CHANGE DESCRIPTION.....	6
6.3. MAXIMUM OUTPUT POWER.....	6
6.4. DESCRIPTION OF AVAILABLE ANTENNAS	6
6.5. SOFTWARE AND FIRMWARE.....	6
6.6. WORST-CASE CONFIGURATION AND MODE.....	7
6.7. DESCRIPTION OF TEST SETUP.....	8
7. TEST AND MEASUREMENT EQUIPMENT.....	10
8. LIMITS AND RESULTS.....	11
8.1. CHANNEL TESTS FOR THE 5725 TO 5850 MHz BAND.....	11
8.1.1. 6 dB BANDWIDTH	11
8.1.2. 99% BANDWIDTH.....	15
8.1.3. PEAK OUTPUT POWER.....	19
8.1.4. MAXIMUM PERMISSIBLE EXPOSURE	24
8.1.5. AVERAGE POWER	27
8.1.6. PEAK POWER SPECTRAL DENSITY	28
8.1.7. CONDUCTED SPURIOUS EMISSIONS.....	32
8.2. RADIATED EMISSIONS	39
8.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS.....	39
8.2.2. TRANSMITTER ABOVE 1 GHz FOR 5725 TO 5850 MHz BAND.....	42
8.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz.....	43
8.3. POWERLINE CONDUCTED EMISSIONS	47
9. SETUP PHOTOS.....	51

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: BROADCOM CORP.
190 MATHILDA PLACE
SUNNYVALE, CA 94086, USA

EUT DESCRIPTION: BROADCOM 802.11ag WIRELESS LAN PCI-E MINI CARD

MODEL: BCM94311MCAG

SERIAL NUMBER: 1039517

DATE TESTED: December 20, 2005 to January 09, 2006

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED


Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Note: The 802.11ag 5.8 GHz DTS Band is applicable to this report; another 5.2 GHz UNII band of operation is in separate report.

Approved & Released For CCS By:

Tested By:



THU CHAN
EMC SUPERVISOR
COMPLIANCE CERTIFICATION SERVICES

VIEN TRAN
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. CROSS REFERENCE TO OTHER REPORTS ON THIS PRODUCT

Other FCC reports applicable to this product include CCS 05U3891-2.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

5. CALIBRATION AND UNCERTAINTY

5.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

5.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

6. EQUIPMENT UNDER TEST

6.1. DESCRIPTION OF EUT

The EUT is an 802.11a/g transceiver WLAN module, operating in the DTS 5725-5850 MHz band.

6.2. CLASS II PERMISSIVE CHANGE DESCRIPTION

The EUT was originally tested and reported under CCS project no.: 05U3487-1B and granted by TCB on August 03, 2005, with a peak antenna gain of 5.7 dBi in frequency range 5725 – 5850 MHz. The major change filed under this application is:

1. Changing of 5GHz PA with a PIFA Stamped metal antenna of 6.2dBi maximum gain at the 5725 – 5850 MHz same as a previous project no: 05U3830.

So, all the tests were performed at 5GHz band only under the report.

6.3. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

5725 to 5850 MHz Authorized Band

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5745 - 5825	802.11a	23.65	231.74

6.4. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PIFA Stamped metal antenna manufactured by Hitachi Cable, Ltd., which has a maximum gain of 6.2dBi at 5 GHz band

6.5. SOFTWARE AND FIRMWARE

The EUT driver software installed in the host support equipment during testing was BCM94311, version. 3.100.53.0

The test utility software used during testing was wl_tools.

6.6. WORST-CASE CONFIGURATION AND MODE

The worst-case channel is determined as the channel with the highest output power. The highest measured output powers were at 5825 MHz for 11a.

The worst-case data rate for these channels is determined to be 6 Mb/s for 11a mode based on previous experience with WLAN product design architectures.

WORSRT-CASE POWER AND BIT RATE SETTING

802.11a - 5.8 GHz

CHANNEL	149	157	165
(MHz)	5745	5785	5825
Band Edge (dBm)	17	17	17
Emission (dBm)	17	17	17
Peak Power / PSD (dBm)	17	17	17
Bit Rate (Mbps)	54 Mbps for Peak reading & 6 Mbps for Average reading		

Powers are the same for both Band Edge & Emission

6.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	HP	Pavilion dv4030us	CNE52005T6	DoC
AC Adapter	HP	PPP0009S	CT 57BC30AU4RO0L0	DoC
Extended Card	ADEXELEC	PEX1-MINI	01/01/1900	N/A


I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC Power	1	AC power	Unshielded	1.5 m	N/A
2	DC Power	1	DC Power	Unshielded	1.5 m	N/A

TEST SETUP

The EUT is installed in a host laptop computer via a card bus-to-mini PCI adapter / extension board during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
EMI Test Receiver	R & S	ESHS 20	827129/006	10/22/2006
Site A Line Stabilizer / Conditioner	Tripplite	LC-1800a	A0051681	CNR
LISN, 10 kHz ~ 30 MHz	FCC	LISN-50/250-25-2	2023	08/30/2006
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	8379443	10/21/2006
Spectrum Analyzer	HP	E4446A	US42510266	08/25/2006
Antenna, Horn 1 ~ 18 GHz	EMCO	3117	29310	09/12/2006
Antenna, Horn 18 ~ 26 GHz	ARA	SWH-28	1007	06/02/2006
Antenna, Horn 26 ~ 40 GHz	ARA	MWH-2640/B	1029	12/03/2006
Preamplifier, 1 ~ 26.5 GHz	HP	8449B	3008A00369	08/17/2006
PreAmplifier 26-40 GHz	MITEQ	NSP4000-SP2	924343	06/01/2006
Peak Power Meter	Agilent	E4416A	GB41291160	11/07/2006
Peak / Average Power Sensor	Agilent	E9327A	US40440755	11/07/2006
RF Filter Section	HP	85420E	3705A00256	11/21/2006
EMI Receiver, 9 kHz ~ 2.9 GHz	HP	8542E	3942A00286	11/21/2006
Bilog Antenna 30MHz---- 2Ghz	Sunol Sciences	JB1 Antenna	A121003	12/22/2006
7.6 GHz High Pass Filter	Micro Tronics	HPM13350	1	N/A
5.75 - 5.8 Reject Filter	Micro Tronics	BRC13192	2	N/A

8. LIMITS AND RESULTS

8.1. CHANNEL TESTS FOR THE 5725 TO 5850 MHz BAND

8.1.1. 6 dB BANDWIDTH

LIMIT

§15.247 (a) (2) For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.


RESULTS


No non-compliance noted:


802.11a Mode

Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	5745	16580	500	16080
Middle	5785	16580	500	16080
High	5825	16580	500	16080

6 DB BANDWIDTH (802.11a MODE)







8.1.2. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.


RESULTS


No non-compliance noted:


802.11a Mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	5745	16.5912
Middle	5785	16.5755
High	5825	16.5521

99% BANDWIDTH (802.11a MODE)







8.1.3. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz , and 5725-5850 MHz bands: 1 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.247 (b) (4) (ii) Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.

RESULTS


The maximum antenna gain is 6.2 dBi for other than fixed, point-to-point operations, therefore the limit is 30 dBm.


No non-compliance noted:


802.11a Mode

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	5745	23.57	30	-6.43
Middle	5785	23.59	30	-6.41
High	5825	23.65	30	-6.35

OUTPUT POWER (802.11a MODE)







8.1.4. MAXIMUM PERMISSIBLE EXPOSURE

LIMITS

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations and rearranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{((30 * P * G) / (3770 * S))}$$

Changing to units of Power to mW and Distance to cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = 100 * d \text{ (m)}$$

yields

$$d = 100 * \sqrt{((30 * (P / 1000) * G) / (3770 * S))}$$

$$d = 0.282 * \sqrt{(P * G / S)}$$

where

d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm²

Substituting the logarithmic form of power and gain using:

$$P \text{ (mW)} = 10^{(P \text{ (dBm)} / 10)} \text{ and}$$

$$G \text{ (numeric)} = 10^{(G \text{ (dBi)} / 10)}$$

yields

$$d = 0.282 * 10^{((P + G) / 20)} / \sqrt{S}$$

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm²

Rearranging terms to calculate the power density at a specific distance yields

$$S = 0.0795 * 10^{((P + G) / 10)} / (d^2)$$

LIMITS

From §1.1310 Table 1 (B), the maximum value of $S = 1.0 \text{ mW/cm}^2$

RESULTS

No non-compliance noted: (MPE distance equals 20 cm)

Mode	MPE Distance (cm)	Output Power (dBm)	Antenna Gain (dBi)	Power Density (mW/cm²)
802.11a	20.0	23.65	6.20	0.19

NOTE: For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.

8.1.5. AVERAGE POWER

AVERAGE POWER LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

No non-compliance noted:

The cable assembly insertion loss of 12.1 dB (including 10 dB pad and 2.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

802.11a Mode

Channel	Frequency (MHz)	Average Power (dBm)
Low	5745	17.33
Middle	5785	17.21
High	5825	17.10

8.1.6. PEAK POWER SPECTRAL DENSITY

LIMIT

§15.247 (d) For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer, the maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer using RBW = 3 kHz and VBW > 3 kHz, sweep time = span / 3 kHz, and video averaging is turned off. The PPSD is the highest level found across the emission in any 3 kHz band.


RESULTS


No non-compliance noted:


802.11a Mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	5745	-8.65	8	-16.65
Middle	5785	-5.93	8	-13.93
High	5825	-5.60	8	-13.60

PEAK POWER SPECTRAL DENSITY (802.11a MODE)







8.1.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS


No non-compliance noted:


SPURIOUS EMISSIONS, LOW CHANNEL (802.11a MODE)







SPURIOUS EMISSIONS, MID CHANNEL (802.11a MODE)





SPURIOUS EMISSIONS, HIGH CHANNEL (802.11a MODE)





8.2. RADIATED EMISSIONS

8.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each 5 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


8.2.2. TRANSMITTER ABOVE 1 GHz FOR 5725 TO 5850 MHz BAND

HARMONICS AND SPURIOUS EMISSIONS (802.11a MODE)

12/16/05 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site															
Test Engr: Vien Tran Project #:05U3891 Company:Broadcom EUT Descrip.:802.11 ag WLAN PCI-EMini Card EUT M/N:BCM94311MCAG Test Target:FCC 15.247 Mode Oper:TX, 5.8GHz															
Test Equipment:															
Horn 1-18GHz T73; S/N: 6717 @3m		Pre-amplifier 1-26GHz T34 HP 8449B		Pre-amplifier 26-40GHz		Horn > 18GHz T39-T88 ARA 18-40GHz & Mixer > 40GHz		Limit FCC 15.205							
Hi Frequency Cables															
2 foot cable		3 foot cable Vien 187215002		12 foot cable Vien 197209005		HPF HPF_7.6GHz		Reject Filter R_001		<u>Peak Measurements</u> RBW=VBW=1MHz <u>Average Measurements</u> RBW=1MHz ; VBW=10Hz					
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Filtr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
Low Ch, 5745MHz Average=17dBm															
11.490	3.0	51.7	37.7	38.3	4.8	-32.5	0.0	0.7	63.0	49.0	74	54	-11.0	-5.0	V
11.490	3.0	49.8	35.4	38.3	4.8	-32.5	0.0	0.7	61.1	46.7	74	54	-12.9	-7.3	H
Mid Ch, 5785MHz Average=17dBm															
11.570	3.0	49.8	37.7	38.3	4.8	-32.5	0.0	0.7	61.1	49.0	74	54	-12.9	-5.0	V
11.570	3.0	46.6	36.2	38.3	4.8	-32.5	0.0	0.7	57.9	47.5	74	54	-16.1	-6.5	H
High Ch, 5825MHz Average=17dBm															
11.650	3.0	50.7	36.9	38.4	4.8	-32.5	0.0	0.7	62.0	48.2	74	54	-12.0	-5.8	V
11.650	3.0	53.8	38.7	38.4	4.8	-32.5	0.0	0.7	65.1	50.0	74	54	-8.9	-4.0	H
Note: No other emissions were detected above the system noise floor.															
f	Measurement Frequency					Amp	Preamp Gain					Avg Lim	Average Field Strength Limit		
Dist	Distance to Antenna					D Corr	Distance Correct to 3 meters					Pk Lim	Peak Field Strength Limit		
Read	Analyzer Reading					Avg	Average Field Strength @ 3 m					Avg Mar	Margin vs. Average Limit		
AF	Antenna Factor					Peak	Calculated Peak Field Strength					Pk Mar	Margin vs. Peak Limit		
CL	Cable Loss					HPF	High Pass Filter								

8.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



HORIZONTAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	216.240	39.80	0.00	39.80	46.00	-6.20	Peak
2	315.180	42.20	0.00	42.20	46.00	-3.80	Peak
3	402.480	41.66	0.00	41.66	46.00	-4.34	Peak
4	432.550	39.53	0.00	39.53	46.00	-6.47	Peak
5	633.340	41.40	0.00	41.40	46.00	-4.60	Peak
6	785.630	42.86	0.00	42.86	46.00	-3.14	Peak

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)


VERTICAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 17 File#: 3891.emi

Date: 12-19-2005 Time: 12:08:32



(Audix ATC)

Trace:

Ref Trace:

Condition: FCC CLASS-B VERTICAL

Test Operator: : Vien Tran

Project #: : 05u3891

Company: : Broacom

EUT: : 802.11ag Wireless LAN PCI-E Mini Card

Model No.: : BCM94311MCAG

Configuration: : EUT, Laptop, & Extended Card

Mode of operation: Tx 5 GHz_Worst Case

Target of Test : FCC B

VERTICAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	201.690	36.33	0.00	36.33	43.50	-7.17	Peak
2	315.180	34.62	0.00	34.62	46.00	-11.38	Peak
3	402.480	43.03	0.00	43.03	46.00	-2.97	Peak
4	431.580	44.45	0.00	44.45	46.00	-1.55	Peak
5	633.340	39.27	0.00	39.27	46.00	-6.73	Peak
6	785.630	42.31	0.00	42.31	46.00	-3.69	QP
7	785.630	44.99	0.00	44.99	46.00	-1.01	Peak

8.3. POWERLINE CONDUCTED EMISSIONS

LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

No non-compliance noted:


6 WORST EMISSIONS

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq.	Reading			Closs	Limit	FCC_B	Margin		Remark
(MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	(dB)	QP	AV	QP (dB)	AV (dB)	L1 / L2
0.15	51.52	--	--	0.00	66.00	56.00	-14.48	-4.48	L1
0.22	45.34	--	--	0.00	62.82	52.82	-17.48	-7.48	L1
4.43	31.60	--	--	0.00	56.00	46.00	-24.40	-14.40	L1
0.16	51.18	--	--	0.00	65.46	55.46	-14.28	-4.28	L2
0.33	39.90	--	--	0.00	59.45	49.45	-19.55	-9.55	L2
0.92	34.62	--	--	0.00	56.00	46.00	-21.38	-11.38	L2
6 Worst Data									

LINE 1 RESULTS

Compliance Certification Services
 561F Monterey Road
 Morgan Hill, CA 95037
 Tel: (408) 463-0885
 Fax: (408) 463-0888

Data#: 7 File#: Lc3891.emi Date: 12-19-2005 Time: 14:02:58



(Auxiliary ATC)

Trace:


Ref Trace:

Condition: CISPR CLASS-B
 Test Operator : Vien Tran
 Project # : 05U3891
 Company : Broadcom
 EUT Description: 802.11 ag Wireless LAN PCI-E Mini Card
 Model : BCM94311MCAG
 EUT Config : EUT on Extended Car/ Laptop
 : AC Adapter
 Mode Of Oper : Tx 5 GHz Worst Case
 Target : FCC Class B
 Power Source : 115Vac, 60Hz
 : L1: Peak (Black)

LINE 2 RESULTS

Compliance Certification Services
 561F Monterey Road
 Morgan Hill, CA 95037
 Tel: (408) 463-0885
 Fax: (408) 463-0888

Data#: 14 File#: Lc3891.emi Date: 12-19-2005 Time: 14:26:12



(Auxiliary ATC)


Trace:

Ref Trace:

Condition: CISPR CLASS-B
 Test Operator : Vien Tran
 Project # : 05U3891
 Company : Broadcom
 EUT Description: 802.11 ag Wireless LAN PCI-E Mini Card
 Model : BCM94311MCAG
 EUT Config : EUT on Extended Car/ Laptop
 : AC Adapter
 Mode Of Oper : Tx 5 GHz Worst Case
 Target : FCC Class B
 Power Source : 115Vac, 60Hz
 : L2: Peak (Black)

9. SETUP PHOTOS

ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP




RADIATED RF MEASUREMENT SET UP

RADIATED FRONT PHOTO




RADIATED BACK PHOTO



RADIATED SIDE PHOTO



POWERLINE CONDUCTED EMISSIONS MEASUREMENT SETUP



LINE CONDUCTED BACK PHOTO



END OF REPORT