



**FCC CFR47 CERTIFICATION
CLASS II PERMISSIVE CHANGE
TEST REPORT**

FOR

**BROADCOM 802.11ag /DRAFT 802.11n
WIRELESS LAN PCI-E MINI CARD**

MODEL NUMBER: BCM94321MC

FCC ID: QDS-BRCM1022

REPORT NUMBER: 07U10822-1

ISSUE DATE: JANUARY 29, 2007

Prepared for
**BROADCOM CORP.
190 MATHILDA PLACE
SUNNYVALE, CA 94086, USA**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**

NVLAP[®]

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue	Revisions	Revised By
--	1/29/07	Initial Issue	Thu

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY.....	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	5
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	5
5. EQUIPMENT UNDER TEST.....	6
5.1. <i>DESCRIPTION OF EUT</i>	6
5.2. <i>CLASS II PERMISSIVE CHANGE DESCRIPTION</i>	6
5.3. <i>MAXIMUM OUTPUT POWER</i>	6
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS.....</i>	6
5.5. <i>SOFTWARE AND FIRMWARE</i>	7
5.6. <i>CONFIGURATION AND MODE</i>	7
5.7. <i>DESCRIPTION OF TEST SETUP</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. LIMITS AND RESULTS	11
7.1. <i>CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND</i>	11
7.1.1. 6 dB BANDWIDTH	11
7.1.2. 99% BANDWIDTH.....	13
7.1.3. PEAK OUTPUT POWER	15
7.1.4. MAXIMUM PERMISSIBLE EXPOSURE.....	18
7.1.5. AVERAGE POWER.....	21
7.1.6. PEAK POWER SPECTRAL DENSITY	22
7.1.7. CONDUCTED SPURIOUS EMISSIONS.....	24
7.2. <i>RADIATED EMISSIONS.....</i>	27
7.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS	27
7.2.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND	30
7.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz	40
7.3. <i>POWERLINE CONDUCTED EMISSIONS</i>	42
8. SETUP PHOTOS	46

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: BROADCOM CORP.
190 MATHILDA PLACE
SUNNYVALE, CA 94086, USA

EUT DESCRIPTION: BROADCOM 802.11 AG /DRAFT 802.11n WIRELESS LAN PCI-E MINI CARD

MODEL: BCM94321MC

SERIAL NUMBER: 817

DATE TESTED: DECEMBER 07, 2006 to JANUARY 23, 2007

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



THU CHAN
EMC SUPERVISOR
COMPLIANCE CERTIFICATION SERVICES

Tested By:



VIEN TRAN
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is an 802.11n MIMO transceiver chipset. The chipset is installed on a Mini PCI-E card, model number BCM94321MC.

The radio module is manufactured by Broadcom Corp.

5.2. CLASS II PERMISSIVE CHANGE DESCRIPTION

The EUT was originally tested and reported under CCS project no. 06U10233-1C and granted by TCB with antennas below:

- Hitachi, HMT-05 / HFT17-DL17 Model, PIFA Stamped Metal Antenna: 3.9dBi @ 2.4GHz.
- Foxconn, 820-2032, PCB Antenna: 2.15dBi @ 2.4GHz.
- Phycomp, 4313 33401250 (left), 4313 3402250 (right), PCB Antenna: 2.2dBi @ 2.4GHz.

The major change filed under this application is increasing the output power of channel 11 (2462 MHz), 11b legacy mode, from 17.5dBm to 19dBm. The Hitachi antenna with 3.9dBi gain and Foxconn antenna with 2.15dBi gain were using for testing to cover for all worst case antenna gains. The full testing was performed only for channel 11 @ b-mode.

5.3. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

2400 to 2483.5 MHz Authorized Band

Frequency (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2462	802.11b	21.8	153.46

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

The EUT has 2 Tx/Rx antennas that are automatically selected for use as per the MCS index and STF mode selections. And the EUT was tested with three different antennas as described below:

- Hitachi, HMT-05 / HFT17-DL17 Model, PIFA Stamped Metal Antenna: 3.9dBi @ 2.4GHz, 3.9dBi @ 5.15GHz, 5.6dBi @ 5.35GHz, & 5.8dBi @ 5.725GHz.
- Foxconn, 820-2032, PCB Antenna: 2.15dBi @ 2.4GHz, 7.44dBi @ 5.15GHz, 6.25dBi @ 5.35GHz, & 5.79dBi @ 5.850GHz.
- Phycomp, 4313 33401250 (left), 4313 3402250 (right), PCB Antenna: 2.2dBi @ 2.4GHz & 3.9dBi @ 5GHz.

5.5. SOFTWARE AND FIRMWARE

The EUT was tested in the following manner:

- “epi_ttcp.exe” was used to transmit UDP packets to a broadcast IP address (192.168.66.255) – i.e. no ACK required. This test mode sends a continuous packetized data stream with duty cycles that vary dependant upon data rate/MCS Index selected.
- “wl ampdu” and “frameburst” were enabled to ensure worst case data packet transfer and duty cycle.
- Worst case packet length have also been used to ensure max duty cycle

5.6. CONFIGURATION AND MODE

Operating modes were changed directly in software with no other changes to the set up. Power levels were verified across all the MCS Index at the start of test and as required throughout testing.

Prior to each test a power meter was used to tune the gated average power within a Tx packet. The channel gates on the meter were set to ensure that, at the time of recording, only packet power was captured without including duty cycle off time.

Power was tuned for different modes, channels and antennas based on the power tuning table contained in the Operational Description submitted under the same filing.

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT


PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop PC	Dell	Inspiron 0000	CN-901014-70166-57K-01JT	DOC
AC Adapter	Dell	PA-1600-06D1	F9710	DOC

I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	AC	Unshielded	1.2 m	N/A
2	DC	1	DC	Unshielded	1.2 m	N/A

TEST SETUP

The EUT is installed in a host laptop computer via Express card to MiniPCI-E adapter boards during the tests. Test software exercised the radio card.

SETUP DIAGRAM

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
Spectrum Analyzer 3 Hz ~ 44 GHz	Agilent / HP	E4446A	US42510266	10/19/2007
Antenna, Horn 1 ~ 18 GHz	EMCO	3115	2238	4/22/2007
Preamplifier, 1 ~ 26.5 GHz	Agilent / HP	8449B	3008A00561	10/3/2007
LISN, 10 kHz ~ 30 MHz	FCC	LISN-50/250-25-2	2023	8/30/2007
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	8379443	8/30/2007
EMI Test Receiver	R & S	ESHS 20	827129/006	11/3/2007
AC Power Source, 10 kVA	ACS	AFC-10K-AFC-2	J1568	CNR
EMI Receiver, 9 kHz ~ 2.9 GHz	Agilent / HP	8542E	3942A00286	2/4/2007
RF Filter Section	Agilent / HP	85420E	3705A00256	2/4/2007
Antenna, Bilog 30 MHz ~ 2 Ghz	Sunol Sciences	JB1	A121003	3/3/2007
4.0 High Pass Filter	Micro Tronics	HPM13351	3	N/A
2.0 - 4.2 GHz Combiner	Mini-Circuits	ZA4PD-4	SF380100518	N/A
Peak Power Meter	Agilent / HP	E4416A	GB41291160	12/2/2007
4.0 GHz High Pass Filter	Micro Tronics	HPM13351	3	N/A
2.4 - 2.5 Reject Filter	Micro Tronics	BRM50702	3	N/A

7. LIMITS AND RESULTS

7.1. CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND

7.1.1. 6 dB BANDWIDTH

LIMIT

§15.247 (a) (2) For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

No non-compliance noted:

802.11b Mode

Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
High	2462	10170	500	9670

6 dB BANDWIDTH (802.11b MODE)

7.1.2. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

No non-compliance noted:

802.11b Mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
High	2462	13.054

99% BANDWIDTH (802.11b MODE)

7.1.3. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz , and 5725-5850 MHz bands: 1 watt.

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz , and 5725-5850 MHz bands: 1 watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

§15.247 (b) (4) (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.

The test is performed in accordance with FCC document “Measurement of Digital Transmission Systems Operating under Section 15.247”, March 23, 2005. The transmitter operates continuously therefore Power Output Option 2, Method # 1 is used.


RESULTS

The maximum antenna gain is 3.9 dBi for other than fixed, point-to-point operations, therefore the limit is 30 dBm.

No non-compliance noted:

802.11b Mode

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
High	2462	21.86	30	-8.14

OUTPUT POWER (802.11b MODE)

7.1.4. MAXIMUM PERMISSIBLE EXPOSURE

LIMITS

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations and rearranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{(30 * P * G) / (3770 * S)}$$

Changing to units of Power to mW and Distance to cm, using:

$$P (\text{mW}) = P (\text{W}) / 1000 \text{ and}$$

$$d (\text{cm}) = 100 * d (\text{m})$$

yields

$$d = 100 * \sqrt{(30 * (P / 1000) * G) / (3770 * S)}$$

$$d = 0.282 * \sqrt{(P * G / S)}$$

where

d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm^2

Substituting the logarithmic form of power and gain using:

$$P (\text{mW}) = 10^{(P (\text{dBm}) / 10)} \text{ and}$$

$$G (\text{numeric}) = 10^{(G (\text{dBi}) / 10)}$$

yields

$$d = 0.282 * 10^{((P + G) / 20)} / \sqrt{S}$$

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm^2

Rearranging terms to calculate the power density at a specific distance yields

$$S = 0.0795 * 10^{((P + G) / 10)} / (d^2)$$

LIMITS

From §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm²

RESULTS

Mode	MPE Distance (cm)	Output Power (dBm)	Antenna Gain (dBi)	Power Density (mW/cm ²)
802.11b	20.0	21.86	3.90	0.07

NOTE: For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.

7.1.5. AVERAGE POWER

AVERAGE POWER LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

No non-compliance noted:

The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

802.11b Mode

Channel	Frequency (MHz)	Power (dBm)
High	2462	19.18

7.1.6. PEAK POWER SPECTRAL DENSITY

LIMIT

§15.247 (d) For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer, the maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer using RBW = 3 kHz and VBW > 3 kHz, sweep time = span / 3 kHz, and video averaging is turned off. The PPSD is the highest level found across the emission in any 3 kHz band.

RESULTS

No non-compliance noted:

802.11b Mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
High	2462	-3.04	8	-11.04

PEAK POWER SPECTRAL DENSITY (802.11b MODE)

7.1.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS

No non-compliance noted:

SPURIOUS EMISSIONS, HIGH CHANNEL (802.11b MODE)



7.2. RADIATED EMISSIONS

7.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each 5 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


7.2.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND


HITACHI ANTENNA

RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS (b MODE)

High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site															
Company: Broadcom Date: 01/15/2007 Test Engineer: Vien Tran Configuration: EUT & Hitachi (Dell) Antenna Mode Of Operation: Tx 11b Legacy Mode															
<u>Test Equipment:</u>															
Horn 1-18GHz			Pre-amplifier 1-26GHz			Pre-amplifier 26-40GHz			Horn > 18GHz			Limit			
T73; S/N: 6717 @3m			T34 HP 8449B									FCC 15.205			
Hi Frequency Cables															
2 foot cable			3 foot cable			12 foot cable			HPF			Reject Filter			
Vien 177079005						Vien 197209005			HPF_4.0GHz						
Peak Measurements RBW=VBW=1MHz Average Measurements RBW=1MHz ; VBW=10Hz															
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF	CL	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
CH 11, 2462 MHz															
4.924	3.0	54.49	50.64	33.8	2.8	-34.8	0.0	0.6	56.9	53.1	74	54	-17.1	-0.9	V
7.386	3.0	44.49	34.63	35.6	3.3	-34.1	0.0	0.6	50.0	40.1	74	54	-24.0	-13.9	V
12.310	3.0	42.01	30.25	38.5	4.4	-32.5	0.0	0.9	53.3	41.6	74	54	-20.7	-12.4	V
4.924	3.0	52.50	50.81	33.8	2.8	-34.8	0.0	0.6	55.0	53.3	74	54	-19.0	-0.7	H
7.386	3.0	45.33	36.50	35.6	3.3	-34.1	0.0	0.6	50.8	42.0	74	54	-23.2	-12.0	H
12.310	3.0	45.24	36.27	38.5	4.4	-32.5	0.0	0.9	56.6	47.6	74	54	-17.4	-6.4	H
f Measurement Frequency Dist Distance to Antenna Read Analyzer Reading AF Antenna Factor CL Cable Loss															
Amp Preamp Gain D Corr Distance Correct to 3 meters Avg Average Field Strength @ 3 m Peak Calculated Peak Field Strength HPF High Pass Filter															
Avg Lim Average Field Strength Limit Pk Lim Peak Field Strength Limit Avg Mar Margin vs. Average Limit Pk Mar Margin vs. Peak Limit															

FOXCONN ANTENNA**RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, HORIZONTAL)**



RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, VERTICAL)



HARMONICS AND SPURIOUS EMISSIONS (b MODE)

High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site															
Company: Broadcom Date: 01/15/2007 Test Engineer: Vien Tran Configuration: EUT & Foxconn (Apple PCB) Antenna Mode Of Operation: Tx 11b Legacy Mode															
<u>Test Equipment:</u>															
Horn 1-18GHz			Pre-amplifier 1-26GHz			Pre-amplifier 26-40GHz			Horn > 18GHz			Limit			
T73; S/N: 6717 @3m			T34 HP 8449B									FCC 15.205			
Hi Frequency Cables															
2 foot cable			3 foot cable			12 foot cable			HPF			Reject Filter			
Vien 177079005						Vien 197209005			HPF_4.0GHz						
Peak Measurements RBW=VBW=1MHz Average Measurements RBW=1MHz ; VBW=10Hz															
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF	CL	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
CH 11, 2462 MHz															
4.924	3.0	50.60	46.80	33.4	3.1	-36.5	0.0	0.6	51.2	47.4	74	54	-22.8	-6.6	V
7.386	3.0	50.40	45.90	35.0	4.2	-36.2	0.0	0.6	54.0	49.5	74	54	-20.0	-4.5	V
12.310	3.0	45.70	37.80	37.6	4.9	-35.4	0.0	0.9	53.7	45.8	74	54	-20.3	-8.2	V
4.924	3.0	50.00	46.60	33.4	3.1	-36.5	0.0	0.6	50.6	47.2	74	54	-23.4	-6.8	H
7.386	3.0	46.20	38.80	35.0	4.2	-36.2	0.0	0.6	49.8	42.4	74	54	-24.2	-11.6	H
12.310	3.0	43.70	34.60	37.6	4.9	-35.4	0.0	0.9	51.7	42.6	74	54	-22.3	-11.4	H
f Measurement Frequency Dist Distance to Antenna Read Analyzer Reading AF Antenna Factor CL Cable Loss															
Amp Preamp Gain D Corr Distance Correct to 3 meters Avg Average Field Strength @ 3 m Peak Calculated Peak Field Strength HPF High Pass Filter															
Avg Lim Average Field Strength Limit Pk Lim Peak Field Strength Limit Avg Mar Margin vs. Average Limit Pk Mar Margin vs. Peak Limit															

7.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

HORIZONTAL



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 6 File#: 06U10708.EMI Date: 01-03-2007 Time: 13:41:11
Audix ATC

Condition: FCC CLASS-B HORIZONTAL
Test Operator: : William Zhuang
Company: : Broadcom
Project #: : 06U10708
Configuration: : EUT/ Laptop
Mode of Operation: TX 2.4GHz band, Worst Case
Target: : FCC Class B

Page: 1

Freq	Read			Limit		Over	
	Level	Factor	Level	Line	Limit	Remark	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	31.940	9.59	19.94	29.53	40.00	-10.47	Peak
2	104.690	19.02	12.38	31.40	43.50	-12.10	Peak
3	148.340	20.57	14.33	34.89	43.50	-8.61	Peak
4	172.590	21.41	13.31	34.72	43.50	-8.78	Peak
5	205.570	25.96	13.71	39.67	43.50	-3.83	Peak
6	218.180	26.46	12.51	38.97	46.00	-7.03	Peak
7	247.280	24.32	13.75	38.06	46.00	-7.94	Peak
8	407.330	25.15	18.21	43.36	46.00	-2.64	Peak
9	761.380	21.52	24.02	45.54	46.00	-0.46	Peak
10	904.940	17.26	25.99	43.25	46.00	-2.75	Peak

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)

VERTICAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 8 File#: 06U10708.EMI Date: 01-03-2007 Time: 13:48:44
Audix ATC

Condition: FCC CLASS-B VERTICAL
Test Operator: : William Zhuang
Company: : Broadcom
Project #: : 06U10708
Configuration: : EUT/ Laptop
Mode of Operation: : TX 2.4GHz band, Worst Case
Target: : FCC Class B

Page: 1

Freq	Read		Limit	Over	Limit	Remark
	Level	Factor				
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	128.940	18.97	15.15	34.12	43.50	-9.38 Peak
2	206.540	21.13	13.61	34.74	43.50	-8.76 Peak
3	407.330	20.12	18.21	38.33	46.00	-7.67 Peak
4	521.790	17.69	20.55	38.24	46.00	-7.76 Peak
5	707.060	14.92	23.20	38.12	46.00	-7.88 Peak
6	904.940	14.59	25.99	40.58	46.00	-5.42 Peak

7.3. POWERLINE CONDUCTED EMISSIONS

LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


Line conducted data is recorded for both NEUTRAL and HOT lines.


RESULTS

No non-compliance noted:

6 WORST EMISSIONS


CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq. (MHz)	Reading			Closs (dB)	Limit	FCC_B	Margin		Remark
	PK(dBuV)	QP (dBuV)	AV (dBuV)				QP (dB)	AV (dB)	
0.17	51.37	--	38.56	0.00	65.16	55.16	-13.79	-16.60	L1
0.24	43.92	--	29.86	0.00	62.17	52.17	-18.25	-22.31	L1
3.95	36.12	--	24.00	0.00	56.00	46.00	-19.88	-22.00	L1
0.18	52.27	--	40.72	0.00	64.49	54.49	-12.22	-13.77	L2
0.24	43.92	--	35.37	0.00	62.17	52.17	-18.25	-16.80	L2
4.10	36.12	--	26.99	0.00	56.00	46.00	-19.88	-19.01	L2
6 Worst Data									

LINE 1 RESULTS

LINE 2 RESULTS

8. SETUP PHOTOS

ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP




RADIATED RF MEASUREMENT SETUP

RADIATED FRONT PHOTO



RADIATED BACK PHOTO



RADIATED SIDE PHOTO



POWERLINE CONDUCTED EMISSIONS MEASUREMENT SETUP

LINE CONDUCTED FRONT PHOTO



LINE CONDUCTED BACK PHOTO



END OF REPORT