



**FCC 47 CFR PART 15 SUBPART C AND ANSI C63.4:2003**  
**TEST REPORT (Class II Permissive Change Report)**

For

**802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD**

**Model : BCM94313HMG2L**

**Trade Name : Broadcom**

**Issued for**

**BROADCOM CORPORATION**

**190 MATHILDA PLACE SUNNYVALE, CA 94086, U.S.A.**

**Issued by**

**Compliance Certification Services Inc.**  
**Hsinchu Lab.**

**NO. 989-1 Wen Shan Rd., Shang Shan Village,  
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C**  
TEL: +886-3-5921698  
FAX: +886-3-5921108

**<http://www.ccsrf.com>  
E-Mail : [service@ccsrf.com](mailto:service@ccsrf.com)**

**Issued Date: March 03, 2012**



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.



## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	03/03/2012	Initial Issue	All Page 35	Kelly Tsai

**TABLE OF CONTENTS**

<b>TITLE</b>	<b>PAGE NO.</b>
<b>1. TEST REPORT CERTIFICATION</b>	<b>4</b>
<b>2. EUT DESCRIPTION</b>	<b>5</b>
<b>3. DESCRIPTION OF CLASS II CHANGE</b>	<b>6</b>
<b>4. DESCRIPTION OF TEST MODES</b>	<b>6</b>
<b>5. TEST METHODOLOGY</b>	<b>6</b>
<b>6. FACILITIES AND ACCREDITATION</b>	<b>7</b>
6.1 FACILITIES	7
6.2 ACCREDITATIONS	7
6.3 MEASUREMENT UNCERTAINTY	8
<b>7. SETUP OF EQUIPMENT UNDER TEST</b>	<b>9</b>
<b>8. FCC PART 15.247 REQUIREMENTS</b>	<b>10</b>
8.1 MAXIMUM PEAK OUTPUT POWER	10-15
8.2 RADIATED EMISSION	16-34
<b>APPENDIX SETUP PHOTOS</b>	<b>35</b>



## 1. TEST REPORT CERTIFICATION

**Applicant** : BROADCOM CORPORATION  
**Address** : 190 MATHILDA PLACE SUNNYVALE, CA 94086, U.S.A.  
**Equipment Under Test** : 802.11g/DRAFT 802.11n WIRELESS LAN PCI-E  
MINICARD  
**Model** : BCM94313HMG2L  
**Trade Name** : Broadcom  
**Tested Date** : February 14 ~ February 29, 2012

APPLICABLE STANDARD	
Standard	Test Result
FCC Part 15 Subpart C AND ANSI C63.4:2003	PASS

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

*Approved by:*

Rex Liao  
Deputy Section Manager

*Reviewed by:*

Jacky Chen  
Deputy Section Manager



## 2. EUT DESCRIPTION

<b>Product Name</b>	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD
<b>Model Number</b>	BCM94313HMG2L
<b>Identify Number</b>	T111230116
<b>Received Date</b>	February 14, 2012
<b>Frequency Range</b>	IEEE 802.11b/g : 2412MHz~2462MHz
<b>Transmit Power</b>	IEEE 802.11b : 21.10dBm (0.1288 W) IEEE 802.11g : 25.75dBm (0.3758 W)
<b>Channel Spacing</b>	IEEE 802.11b/g : 5MHz
<b>Channel Number</b>	IEEE 802.11b/g : 11 Channels
<b>Transmit Data Rate</b>	IEEE 802.11b : 11, 5.5, 2, 1 Mbps IEEE 802.11g : 54, 48, 36, 24, 18, 12, 9, 6 Mbps
<b>Type of Modulation</b>	IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g : OFDM (64QAM, 16QAM, QPSK, BPSK)
<b>Frequency Selection</b>	by software / firmware
<b>Antenna Type</b>	PIFA Antenna , Antenna Gain :1.73 dBi
<b>DC Power Cord Type</b>	Non-shielded cable 1.8m (Non-detachable)
<b>Test Voltage</b>	120Vac, 60Hz
<b>Power Rating</b>	20Vdc, 4.5A (From Power Adapter)
<b>I/O Port</b>	USB 2.0 Port × 2, RJ-45 Port × 1, HDMI Port × 1, USB 3.0 Port × 2, Audio In Port × 1, Audio Out Port × 1, SD Card Port × 1, VGA Port × 1, Power Port × 1

### Power Adapter :

No.	Manufacturer	Model No.	Power Input	Power Output
1	lenovo	ADP-90DD B	100-240Vac, 50/60Hz, 1.5A	20Vdc, 4.5A

### Remark :

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. For more details, please refer to the User's manual of the EUT.
3. This submittal(s) (test report) is intended for FCC ID: QDS-BRCM1050I filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



### **3. DESCRIPTION OF CLASS II CHANGE**

The major change filed under this application is:

The operation frequency is 2412MHz~2462MHz.

Add portable Condition compliance to the grant so that the module may be used in qualified host PC(s) and implementation of module-notebook authentication.

Product name: Notebook Computer

Brand name: lenovo

Model: 20151, 2616, Lenovo IdeaPad Z485

The Above model numbers have the same specifications.

### **4. DESCRIPTION OF TEST MODES**

The EUT is an 802.11b/g transceiver in 802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MIMICARD form factor. The EUT is  $1 \times 1$  spatial device. The antenna configuration is one TX antenna (Chain 1) and two RX antennas (Diversity), as there are two PIFA antennas.

#### **Radiated Emission Test (Below 1 GHz)**

TX Mode

#### **Conducted / Radiated Emission Test (Above 1 GHz)**

##### **IEEE 802.11b, 802.11g, 802.11n HT20 mode**

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode : 1Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11g mode : 6Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11n HT20 mode : Covered by the worst case 802.11g Mode Legacy testing.

### **5. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with ANSI C63.4: 2003 and FCC CFR 47, 15.207, 15.209 and 15.247.



## 6. FACILITIES AND ACCREDITATION

### 6.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

NO. 989-1 Wen Shan Rd., Shang Shan Village,  
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C

The sites are constructed in conformance with the requirements of ANSI C63.4:2003 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4, CISPR 16-1-5.

### 6.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

**Taiwan**      TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>Canada</b>	INDUSTRY CANADA
<b>Japan</b>	VCCI
<b>Taiwan</b>	BSMI
<b>USA</b>	FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>



## 6.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.5189
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 2.5164
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 2.4967
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 2.7655

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2006, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than  $U_{CISPR}$  which is 3.6dB and 5.2dB respectively. CCS values (called  $U_{Lab}$  in CISPR 16-4-2) is less than  $U_{CISPR}$  as shown in the table above. Therefore, MU need not be considered for compliance.



## 7. SETUP OF EQUIPMENT UNDER TEST

### SUPPORT EQUIPMENT

N/A

### SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

### EUT OPERATING CONDITION

#### **Tx Mode**

1. Setup all computers like the setup diagram.

2. Select the following settings.

3. net stop wlansvc

timeout 1

net start wlansvc

timeout 4

wl out

wl up

wl antdiv 0

wl txant 0

wl mpc 0

wl frameburst 1

wl down

wl ampdu 1

wl country ALL

wl band b

wl up

wl chanspec -c 1 -b 2 -w 20 -s 0

timeout 4

wl wsec 0

timeout 4

wl join testb imode adhoc

timeout 4

wl legacylink

timeout 6

wl nrate -r 1

wl cck\_txbw 2

wl txpwr1 -o -q 75

timeout 4

epi\_ttcp -tsuHfm -l 8760 -n 10000000 192.168.66.255

4. Run Tx Test software.

5. All of the functions are under run.

6. Start test.



## 8. FCC PART 15.247 REQUIREMENTS

### 8.1 MAXIMUM PEAK OUTPUT POWER

#### LIMITS

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4407B	US41443108	08/09/2012

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### TEST SETUP



#### TEST PROCEDURE

1. The spectrum shall be set as follows :

Span : 1.5 times channel integration bandwidth.

RBW : 1MHz

VBW : 3MHz

Detector : Peak

Sweep : Single trace

2. Compute the combined power of all signal responses contained in the trace by covering all the data points.

3. The peak output power is the channel power integrated over 26dB bandwidth.

**TEST RESULTS****IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	19.47	0.0885	30	1	PASS
Middle	2437	21.10	0.1288	30	1	PASS
High	2462	15.80	0.0380	30	1	PASS

**Remark:**


1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.


**IEEE 802.11g Mode**


Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	23.63	0.2307	30	1	PASS
Middle	2437	25.75	0.3758	30	1	PASS
High	2462	17.18	0.0522	30	1	PASS


**Remark:**

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.

MAXIMUM PEAK OUTPUT POWER









## 8.2 RADIATED EMISSION

### LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

**Remark:**

1. <sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
2. <sup>2</sup> Above 38.6

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

**Remark:** \*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

## TEST EQUIPMENT

### Radiated Emission / 966Chamber\_B

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/19/2012
EMI Receiver	ROHDE & SCHWARZ	ESCS 30	826547/004	10/27/2012
Broadband Hybrid Bi-Log Antenna	Sunol Sciences	JB1	A100209-4	10/05/2012
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078733	12/06/2012
Horn Antenna	COM-POWER	AH-840	03077	12/06/2012
Pre-Amplifier	Agilent	8447D	2944A10052	07/19/2012
Pre-Amplifier	Agilent	8449B	3008A01916	09/18/2012
LOOP Antenna	EMCO	6502	8905-2356	06/10/2012
Notch Filters Band Reject	Micro-Tronics	BRM05702-01	026	N.C.R


**Remark:** 1. Each piece of equipment is scheduled for calibration once a year.  
2. N.C.R = No Calibration Request.




## TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from below 1GHz.

### 9kHz ~ 30MHz




### 30MHz ~ 1GHz





The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



## **TEST PROCEDURE**

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

### ***Remark :***

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.



## TEST RESULTS

### **Below 1 GHz (9kHz ~ 30MHz)**

No emission found between lowest internal used/generated frequency to 30MHz.

### **Below 1 GHz (30MHz ~ 1GHz)**

<b>Product Name</b>	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD	<b>Test By</b>	Leon Cheng
<b>Test Model</b>	BCM94313HMG2L	<b>Test Date</b>	2012/02/24
<b>Test Mode</b>	IEEE 802.11b TX / CH Middle (worst case)	<b>Temp. &amp; Humidity</b>	21°C, 58%

<b>966 Chamber_B at 3Meter / Horizontal</b>						
Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Remark
231.76	44.30	-14.33	29.96	46.00	-16.04	Peak
251.16	42.12	-13.54	28.58	46.00	-17.42	Peak
351.07	38.17	-10.82	27.35	46.00	-18.65	Peak
454.86	36.21	-9.10	27.12	46.00	-18.88	Peak
785.63	34.24	-3.99	30.25	46.00	-15.75	Peak
797.27	39.39	-3.76	35.63	46.00	-10.37	Peak

<b>966 Chamber_B at 3Meter / Vertical</b>						
Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Remark
30.00	35.27	-6.10	29.17	40.00	-10.83	Peak
231.76	43.86	-14.33	29.52	46.00	-16.48	Peak
379.20	35.96	-10.34	25.62	46.00	-20.38	Peak
447.10	36.03	-9.24	26.80	46.00	-19.20	Peak
524.70	36.38	-8.08	28.30	46.00	-17.70	Peak
800.18	37.70	-3.71	33.99	46.00	-12.01	Peak

#### **Remark:**

1. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
2. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – PreAmp.Gain (dB)
4. Result (dB $\mu$ V/m) = Reading (dB $\mu$ V) + Correction Factor (dB/m)
5. Margin (dB) = Remark result (dB $\mu$ V/m) - Quasi-peak limit (dB $\mu$ V/m).



## TX Above 1 GHz

Product Name	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD	Test By	Leon Cheng
Test Model	BCM94313HMG2L	Test Date	2012/02/21
Test Mode	IEEE 802.11b TX / CH Low	Temp. & Humidity	19°C, 62%

## 966 Chamber\_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1488.00	53.96	---	-2.31	51.66	---	74.00	54.00	-2.34	Peak
1682.00	53.91	---	-0.64	53.27	---	74.00	54.00	-0.73	Peak
3990.00	44.49	---	6.98	51.47	---	74.00	54.00	-2.53	Peak
4980.00	39.48	---	9.87	49.35	---	74.00	54.00	-4.65	Peak
5685.00	39.86	---	11.14	51.01	---	74.00	54.00	-2.99	Peak

## 966 Chamber\_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1234.00	55.07	---	-3.13	51.94	---	74.00	54.00	-2.06	Peak
1504.00	54.37	---	-2.23	52.14	---	74.00	54.00	-1.86	Peak
3990.00	44.29	---	6.98	51.27	---	74.00	54.00	-2.73	Peak
4830.00	40.68	---	9.50	50.18	---	74.00	54.00	-3.82	Peak
5730.00	39.68	---	11.24	50.91	---	74.00	54.00	-3.09	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD	<b>Test By</b>	Leon Cheng
<b>Test Model</b>	BCM94313HMG2L	<b>Test Date</b>	2012/02/21
<b>Test Mode</b>	IEEE 802.11b TX / CH Middle	<b>Temp. &amp; Humidity</b>	19°C, 62%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1310.00	53.91	---	-2.88	51.03	---	74.00	54.00	-2.97	Peak
1392.00	54.72	---	-2.62	52.10	---	74.00	54.00	-1.90	Peak
3990.00	43.97	---	6.98	50.95	---	74.00	54.00	-3.05	Peak
5640.00	39.62	---	11.05	50.67	---	74.00	54.00	-3.33	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1100.00	55.21	---	-3.56	51.65	---	74.00	54.00	-2.35	Peak
1316.00	54.38	---	-2.86	51.52	---	74.00	54.00	-2.48	Peak
3195.00	46.08	---	5.62	51.70	---	74.00	54.00	-2.30	Peak
3990.00	43.30	---	6.98	50.28	---	74.00	54.00	-3.72	Peak
4875.00	40.09	---	9.61	49.70	---	74.00	54.00	-4.30	Peak
5850.00	39.10	---	11.49	50.59	---	74.00	54.00	-3.41	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD	<b>Test By</b>	Leon Cheng
<b>Test Model</b>	BCM94313HMG2L	<b>Test Date</b>	2012/02/21
<b>Test Mode</b>	IEEE 802.11b TX / CH High	<b>Temp. &amp; Humidity</b>	19°C, 62%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1120.00	55.17	---	-3.49	51.68	---	74.00	54.00	-2.32	Peak
1280.00	54.12	---	-2.98	51.14	---	74.00	54.00	-2.86	Peak
3990.00	45.33	---	6.98	52.31	---	74.00	54.00	-1.69	Peak
4920.00	41.86	---	9.72	51.58	---	74.00	54.00	-2.42	Peak
5985.00	39.26	---	11.78	51.04	---	74.00	54.00	-2.96	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1158.00	55.53	---	-3.37	52.15	---	74.00	54.00	-1.85	Peak
1330.00	54.31	---	-2.82	51.49	---	74.00	54.00	-2.51	Peak
3195.00	46.39	---	5.62	52.01	---	74.00	54.00	-1.99	Peak
3990.00	44.46	---	6.98	51.44	---	74.00	54.00	-2.56	Peak
4920.00	42.02	---	9.72	51.75	---	74.00	54.00	-2.25	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD	<b>Test By</b>	Leon Cheng
<b>Test Model</b>	BCM94313HMG2L	<b>Test Date</b>	2012/02/21
<b>Test Mode</b>	IEEE 802.11g TX / CH Low	<b>Temp. &amp; Humidity</b>	19°C, 62%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1330.00	54.35	---	-2.82	51.53	---	74.00	54.00	-2.47	Peak
1504.00	54.55	---	-2.23	52.32	---	74.00	54.00	-1.68	Peak
3990.00	43.66	---	6.98	50.63	---	74.00	54.00	-3.37	Peak
4980.00	40.87	---	9.87	50.74	---	74.00	54.00	-3.26	Peak
966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1156.00	54.77	---	-3.38	51.39	---	74.00	54.00	-2.61	Peak
1424.00	54.25	---	-2.51	51.74	---	74.00	54.00	-2.26	Peak
3195.00	45.33	---	5.62	50.95	---	74.00	54.00	-3.05	Peak
4005.00	43.85	---	7.02	50.86	---	74.00	54.00	-3.14	Peak
4830.00	39.64	---	9.50	49.14	---	74.00	54.00	-4.86	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

5. Result = Reading + Correction Factor

Margin = Result - Limit

Remark Peak = Result(PK) - Limit(AV)

Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD	<b>Test By</b>	Leon Cheng
<b>Test Model</b>	BCM94313HMG2L	<b>Test Date</b>	2012/02/21
<b>Test Mode</b>	IEEE 802.11g TX / CH Middle	<b>Temp. &amp; Humidity</b>	19°C, 62%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1300.00	54.74	---	-2.91	51.83	---	74.00	54.00	-2.17	Peak
1538.00	53.68	---	-1.93	51.75	---	74.00	54.00	-2.25	Peak
3990.00	43.91	---	6.98	50.89	---	74.00	54.00	-3.11	Peak
4920.00	39.91	---	9.72	49.63	---	74.00	54.00	-4.37	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1300.00	54.36	---	-2.91	51.45	---	74.00	54.00	-2.55	Peak
1384.00	53.78	---	-2.64	51.13	---	74.00	54.00	-2.87	Peak
4005.00	42.93	---	7.02	49.95	---	74.00	54.00	-4.05	Peak
4260.00	40.99	---	7.88	48.87	---	74.00	54.00	-5.13	Peak
4920.00	38.56	---	9.72	48.29	---	74.00	54.00	-5.71	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	802.11g/DRAFT 802.11n WIRELESS LAN PCI-E MINICARD	<b>Test By</b>	Leon Cheng
<b>Test Model</b>	BCM94313HMG2L	<b>Test Date</b>	2012/02/21
<b>Test Mode</b>	IEEE 802.11g TX / CH High	<b>Temp. &amp; Humidity</b>	19°C, 62%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1414.00	54.79	---	-2.55	52.24	---	74.00	54.00	-1.76	Peak
1614.00	53.09	---	-1.25	51.84	---	74.00	54.00	-2.16	Peak
3990.00	43.72	---	6.98	50.70	---	74.00	54.00	-3.30	Peak
4935.00	38.88	---	9.76	48.64	---	74.00	54.00	-5.36	Peak
966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1248.00	54.96	---	-3.08	51.88	---	74.00	54.00	-2.12	Peak
1530.00	53.93	---	-2.00	51.93	---	74.00	54.00	-2.07	Peak
3195.00	44.21	---	5.62	49.83	---	74.00	54.00	-4.17	Peak
3990.00	44.59	---	6.98	51.57	---	74.00	54.00	-2.43	Peak
4935.00	39.04	---	9.76	48.80	---	74.00	54.00	-5.20	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor

Margin = Result - Limit

Remark Peak = Result(PK) - Limit(AV)


Remark AVG = Result(AV) - Limit(AV)



## Restricted Band Edges


## Detector Mode : Peak

## Polarity : Horizontal



## Detector Mode : Average


## Polarity : Horizontal






## Detector Mode : Peak

## Polarity : Vertical



## Detector Mode : Average


## Polarity : Vertical






## Detector Mode : Peak



## Polarity : Horizontal



## Detector Mode : Average

## Polarity : Horizontal




**Detector Mode : Peak****Polarity : Vertical****Detector Mode : Average****Polarity : Vertical**




## Detector Mode : Peak



## Polarity : Horizontal






## Detector Mode : Average

## Polarity : Horizontal



**Detector Mode : Peak****Polarity : Vertical****Detector Mode : Average****Polarity : Vertical**

**Detector Mode : Peak****Polarity : Horizontal****Detector Mode : Average****Polarity : Horizontal**

**Detector Mode : Peak****Polarity : Vertical****Detector Mode : Average****Polarity : Vertical**