



EMC Test Data

Client:	Broadcom	Job Number:	J84866
Model:	BCM943142HM 802.11bgn (20 and 40MHz SISO only + BT 4.0)	T-Log Number:	T84936
Contact:	Anne Liang	Account Manager:	Sheareen Washington
Standard:	FCC 15.247, 15.E, RSS-210	Class:	N/A

Maximum Permissible Exposure

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 10/28/2011

Test Engineer: Mark Hill

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m^2), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	Yes
Power Density at 20cm (mW/cm^2)	0.04

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	Broadcom	Job Number:	J84866
Model:	BCM943142HM 802.11bgn (20 and 40MHz SISO only + BT 4.0)	T-Log Number:	T84936
		Account Manager:	Sheareen Washington
Contact:	Anne Liang		
Standard:	FCC 15.247, 15.E, RSS-210	Class:	N/A

Use: General

Antenna: 3.9dBi

802.11b - Worse case operating mode

Freq. MHz	EUT Power		Cable Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm^2	MPE Limit at 20 cm mW/cm^2
	dBm	mW*						
2412	18.7	74.1	0	3.9	18.7	181.97	0.036	1.000
2437	19.1	81.3	0	3.9	19.1	199.53	0.040	1.000
2462	18.1	64.6	0	3.9	18.1	158.49	0.032	1.000

For the cases where S > the MPE Limit

Freq. MHz	S @ 20 cm mW/cm^2	MPE Limit mW/cm^2	Distance where S <= MPE Limit
2412	0.036	1.000	3.8cm
2437	0.040	1.000	4.0cm
2462	0.032	1.000	3.6cm