



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

Application No. : LN023446(8)

Client : Kid Galaxy INC.
Tower 2, Unit 425B Manchester,
150 Dow Street, NH03101, U. S. A.

Sample Description : One(1) item of submitted sample stated to be:

Sample Description	Model no.
Jumbo Go Go	40215
Go Go Auto	10422, 10421, 10436, 10437, 10438, 10460, 10414, 10709, 10710, 10711, 10712, 10471, 10472, 10433, 10435, 10415, 10410, 10402, 10403, 10420

Radio Frequency : 49.860MHz Transmitter

Rating : 1 x 9V size battery

No. of submitted sample : Two (2) piece (s)

Date Received : 25 Jul 2011.

Test Period : 01 Aug 2011 to 02 Aug 2011.

Test Requested : FCC Part 15 Permissive Change

Test Method : 47 CFR Part 15 (10-1-09 Edition)
ANSI C63.4 - 2009

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C.

Remark : All twenty one models are the same in circuitry, components and construction.
Therefore, model 40215 was chosen to be the representative of the test sample.
The difference between the tested model and the declared model(s) is/are the
model name, model number and color.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____

Page 1 of 11

Mr. WONG Lap-pong, Andrew
Assistant Manager
Electrical Division

FCC ID: QEA-E003-49T

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
1.4	Measurement Uncertainty	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conducted Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	10
5.1	Bandwidth	10
5.2	Duty cycle	10
5.3	Transmission time	10
6	Appendices	11

FCC ID: QEA-E003-49T

Page 2 of 11



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for Jumbo Go Go. It operates at 49.860MHz and the oscillation of radio control is generated by a crystal. The EUT is powered by 1 x 9V szie battery. There is a button on the EUT. When the button is passed, the EUT will transmit radio control signal to the receiver.

The antenna is permanently attached in EUT and the radio output power is unable to adjust.

The brief circuit description is listed as follows:

- X1, Q3 and its associated circuit act as oscillator.
- Q4 and its associated circuit act as amplifier.
- Q1, Q2 and its associated circuit act as encoder.

FCC ID: QEA-E003-49T

Page 3 of 11



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2009. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC ID: QEA-E003-49T

Page 4 of 11



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
EMI Test Receiver	R&S	ESCI	100152	16 Mar 2012
Broadband Antenna	Schaffner	CBL6112B	2718	31 Oct 2012
Coaxial Cable	Schaffner	RG 213/U	N/A	30 May 2013
Coaxial Cable	Suhner	RG 214/U	N/A	30 May 2013

1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U _{lab})
30MHz ~ 200MHz (Horizontal)	4.63dB
30MHz ~ 200MHz (Vertical)	4.64dB
200MHz ~1000MHz (Horizontal)	4.65dB
200MHz ~1000MHz (Vertical)	4.64dB

Conducted emissions

Frequency	Uncertainty (U _{lab})
150kHz ~ 30MHz	3.04dB



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

“#” means emissions appearing within the restricted bands shall follow the requirement of section 15.205.

The frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

Parameter	Recorded value
Ambient temperature:	24 °C
Relative humidity:	56 %

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V)	Antenna Factor and Cable Loss (dB/m)	Average Factor (dB)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
49.860	V	58.5	12.6	- 5.4	65.7	80.0	- 14.3
99.721	V	8.8	9.9	-	18.7	43.5	- 24.8
148.582	H	6.8	12.9	-	19.7	43.5	- 23.8
199.443	H	6.5	11.5	-	18.0	43.5	- 25.5
249.299	H	10.5	11.0	-	21.5	46.0	- 24.5
#299.160	H	8.5	14.9	-	23.4	46.0	- 22.6
349.021	H	8.6	15.9	-	24.5	46.0	- 21.5
398.882	H	10.4	15.9	-	26.3	46.0	- 19.7
448.738	H	7.7	18.8	-	26.5	46.0	- 19.5
498.602	H	10.0	18.8	-	28.8	46.0	- 17.2

FCC ID: QEA-E003-49T

Page 7 of 11



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2009. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10 kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26dB below the carrier level. It meets the requirement of Section 15.235(b).

5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 1.03 ms

Effective period of the cycle = 0.55 ms

Duty Cycle = 0.55ms / 1.03ms
= 0.534

Therefore, the average factor is found by $20 \log_{10} 0.534 = -5.4 \text{dB}$

5.3 Transmission time

Not Applicable



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AN0043022(0)

Date : 05 Aug 2011

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label/Location	1	page
A5.	Bandwidth Plot	1	page
A6.	Average Factor	1	page
A7.	Block Diagram	1	page
A8.	Schematics Diagram	1	page
A9.	User Manual	1	page
A10.	Operation Description	1	page

***** End of Report *****

FCC ID: QEA-E003-49T

Page 11 of 11