


SK TECH CO., LTD.

Page 1 of 14

Certificate of Compliance

Test Report No.:	SKTOS-02062		
NVLAP CODE :	200220-0		
Applicant:	MagicEyes Digital Company		
Applicant Address:	501, A-ONE Plaza, 269-6, Seohyeon-Dong, Bundang-Gu, Seongnam, Kyeonggi-Do, Korea		
Product:	PDA		
FCC ID:	QENMKIVKI	Model No.:	MKIVKI
Receipt No.:	SKE20020228-126	Date of receipt:	Feb. 28, 2002
Date of Issue:	June 12, 2002		
Testing location:	SK TECH CO., LTD. 820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea		
Test Standards:	ANSI C63.4 / 2000		
Rule Parts:	FCC part 15 Subpart B		
Equipment Class :	Class B Digital Device Peripheral		
Test Result:	The above mentioned product has been tested and passed.		

Prepared by: Y.H.Kang

Tested by: Y.B.Kim/Engineer

Approved by: K.S.Kim/Manager
& Chief Engineer

Signature

Date

Signature

Date

Signature

Date

Other Aspects :

Abbreviations :

· OK, Pass = passed · Fail = failed · N/A = not applicable

- This test report is not permitted to copy partly without our permission.
- This test result is dependent on only equipment to be used.
- This test result is based on a single evaluation of one sample of the above mentioned.
- This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government.
- We certify that this test report has been based on the measurement standards that is traceable to the national or International standards.

NVLAP Lab. Code: 200220-0



» » **Contents** « «

Contents	2
List of Tables	2
List of Figures	2
List of Photographs	2
Buyer Model No.	3
1. General	4
2. Test Site	4
2.1 Location	4
2.2 List of Test and Measurement Instruments	5
2.3 Test Date	5
2.4 Test Environment	5
3. Description of the tested samples	6
3.1 Rating and Physical Characteristics	6
3.2 Submitted Documents	6
4. Measurement Conditions	7
4.1 Modes of Operation	7
4.2 List of Peripherals	7
4.3 Type of Used cables	8
4.4 Test Setup	8
4.5 Uncertainty	8
5. EMISSION Test	9
5.1 Conducted Emissions	9
5.2 Radiated Emissions	13

» **List of Tables**

Table 1	List of test and measurement Equipment	5
Table 2	Test Data, Conducted Emissions	12
Table 3	Test Data, Radiated Emissions	14

» **List of Figures**

Figure 1	Spectral Diagram, LINE-PE	10
Figure 2	Spectral Diagram, Neutral-PE	11



1. General

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. All measurements reported herein were performed by SK Tech Co., Ltd. and were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. Test Site

SK TECH Co., Ltd.

2.1 Location

820-2, Wolmoon Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea

The test site is in compliance with ISO/IEC 17025 for general requirements for the competence of testing and calibration laboratories.

This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200220-0 and DATech for DAR-Registration No.:TTI-P-G155/97-10



2.2 List of Test and Measurement Instruments

Table 1 : List of Test and Measurement Equipment

- **Conducted Disturbance**

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESHS10	862970/019	02.2003
Artificial Mains Network	ESH3-Z5	834549/001	10.2002
EMI Receiver	ESHS10	835871/002	10.2002
Artificial Mains Network	ESH3-Z5	836679/018	10.2002
Conducted Cable	N/A	N/A	N/A

- **Radiated Disturbance**

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESVS 10	825120/013	02.2003
EMI Receiver	ESVS 10	834468/008	11.2002
Spectrum Analyzer	R3361A	11730187	06.2002
Amplifier	8447F	3113A05153	06.2003
Log Periodic Antenna	UHALP9107	1819	02.2003
Biconical Antenna	BBA9106	91031626	02.2003
Antenna Mast	5907	N/A	N/A
Antenna & Turntable controller	5906	N/A	N/A
Amp & Receiver connection cables	N/A	N/A	N/A
50Ω Switcher	MP59B	6100214538	N/A

2.3 Test Date

Date of Application : Feb. 28, 2002
 Date of Test : Mar. 06, 2002



SK TECH CO., LTD.

Page 5 of 14

2.4 Test Environment

See each test item's description.



3. Description of the tested samples

The EUT is PDA.

3.1 Rating and Physical Characteristics

Main Body		
Item	Spec	Remark
Processor	MMSP-1	48MHz
Memory	16Mb SDRAM x 2	
	64MB Nand Flash	Expandable to 256MB
Power	5.2V 2A	
Battery	Li-ion Rechargeable	1800mAh
Battery Hours	5 Hours @ Audio + Video	14 Hours @ Audio only
Display	2.5 inch Color TFT LCD with Back Light	
Interface	USB, Serial, IrDA	
Camera	CMOS Image Sensor, VGA resolution	
Size	94.3mm x 71mm x 23.4mm	24.8mm at Battery
Weight	157g	165g with Camera Module
Buttons	Power, Volume Up/Down, Mode, Record	
	Navigation, Enter, Home, Menu, Select	

3.2 Submitted Documents

N/A



4. Measurement Conditions

Operating of EUT voltage is 5.2V DC supplied by the adaptor which is structural element for EUT.

(Adaptor Input Voltage : AC 120V, 60Hz)

4.1 Modes of Operation

The EUT was in the following operation mode during all testing;

The EUT is connected with PC.

All tested in mode. (MP3 Player, Video Camera)

4.2 List of Peripherals

Description	Manufacturer	Model Name	Serial No.	FCC ID
PC	LG-IBM	W8S	202KI10585	N/A
Monitor	Comtec	CT-151B	N/A	DoC
Keyboard	JING MOLD	LKB-0107	20101342	N/A
Mouse	Kye Systems	P801	01030680	N/A
Printer	H.P	2225C	324512493	N/A
Adapter 1 (for EUT)	Sae Yang	SY-0004	N/A	N/A
Adapter 2 (for Monitor)	L.S.E	LSE9802B1240	A10142102041	N/A
Adapter 3 (for Printer)	Dream Electronic	DR-05600U	N/A	N/A



4.3 Type of Used Cables

Description	Length	Type of shield	Manufacturer	Remark
AC/DC Adapter cable	1.8m	Non-shield	None	For EUT
AC/DC Adapter cable	1.8m	Non-shield	None	For Monitor
USB cable	1.8m	Non-shield	None	For EUT
Earphone cable	1.6m	Non-shield	None	
PC Power cable	1.8m	Non-shield	None	
Keyboard interface cable	1.5m	Non-shield	None	
Mouse interface cable	1.5m	Non-shield	None	
Printer power cable	1.8m	Non-shield	None	
Printer interface cable	1.2m	Shield	None	
VGA cable	1.5m	Shield	None	

4.4 Test Setup

The test setup photographs showed the external supply connections and interfaces.

4.5 Uncertainty

1) Radiated disturbance

$$U_c \text{ (Combined standard Uncertainty)} = \pm 1.9 \text{ dB}$$

$$\text{Expanded uncertainty } U = K U_c$$

$$K = 2$$

$$\therefore U = \pm 3.8 \text{ dB}$$

2) Conducted disturbance

$$U_c = \pm 0.88 \text{ dB}$$

$$U = K U_c = 2 \times U_c = \pm 1.8 \text{ dB}$$



5. EMISSION Test

5.1 Conducted Emissions

Result:**Pass**

The line-conducted facility is located inside a 2.0M x 3.6M x 7.2M shielded enclosure.

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 604-05.

A 1m x 1.5m wooden table 80cm. high is placed 40cm. away from the vertical wall and 1.5m away from the side wall of the shielded room. ROHDE & SCHWARZ Model ESH3-Z5 (10kHz-30MHz) 50ohm/50 uH Line-Impedance Stabilization Networks(LISNs) are bonded to the shielded room. The EUT is powered from the ROHDE & SCHWARZ LISN and the support equipment is powered from the ROHDE & SCHWARZ LISN. Power to the LISNs are filtered by a high-current high-insertion loss Lindgren enclosures power line filters (100dB 14kHz-10GHz).

The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure.

All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2".

If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the ROHDE & SCHWARZ LISN.

All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 450kHz to 30MHz with 100msec. sweep time.

The frequency producing the maximum level was reexamined using EMI/field Intensity Meter (ESHS 10) and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode.

The bandwidth of the receiver was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.


Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; if applicable; whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of conducted test.

Each EME reported was calibrated using self-calibrating mode.

**SK TECH CO., LTD.**

Page 10 of 14

Figure 1 : Spectral Diagram, LINE - PE

**SK TECH CO., LTD.**

Page 11 of 14


Figure 2 : Spectral Diagram, NEUTRAL – PE



Table 2: Test Data, Conducted Emissions

Frequency (MHz)	(1)Reading (dB μ V)	Line	(2)C/F (dB)	(3)C/L (dB)	(4)Actual (dB μ V)	(5)Limit (dB μ V)	(6)Margin (dB)
3.850	44.06	A	0.2	0.4	44.66	48.0	3.34
3.920	45.28	A	0.2	0.4	45.88	48.0	2.12
4.050	45.16	A	0.2	0.4	45.76	48.0	2.24
4.100	44.05	A	0.2	0.4	44.65	48.0	3.35
4.120	44.09	A	0.2	0.4	44.69	48.0	3.31
4.180	45.29	A	0.2	0.4	45.89	48.0	2.11
4.260	44.12	A	0.2	0.4	44.72	48.0	3.28
4.330	44.16	A	0.2	0.4	44.76	48.0	3.24
0.560	42.49	B	0.2	0.1	42.79	48.0	5.21
3.860	41.80	B	0.2	0.4	42.40	48.0	5.60
3.950	41.62	B	0.2	0.4	42.22	48.0	5.78
4.010	41.51	B	0.2	0.4	42.11	48.0	5.89
4.050	42.52	B	0.2	0.4	43.12	48.0	4.88
4.140	44.64	B	0.2	0.4	45.24	48.0	2.76
4.190	44.66	B	0.2	0.4	45.26	48.0	2.74
4.250	44.97	B	0.2	0.4	45.57	48.0	2.43
4.280	42.56	B	0.2	0.4	43.16	48.0	4.84

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emissions are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. Line A = LINE-PE, Line B = NEUTRAL-PE
6. C/F = Correction Factor
7. C/L = Cable Loss

◆ Margin Calculation

$$(6)\text{Margin} = (5)\text{Limit} - (4)\text{Actual}$$

$$[(4)\text{Actual} = (1)\text{Reading} + (2)\text{C/F} + (3)\text{C/L}]$$



5.2 Radiated Emissions

Result :**Pass**

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME.

Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found.

The spectrum was scanned from 30 to 300 MHz using biconical antenna and from 300 to 1000 MHz using log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using SCHWARZBECK dipole antennas. The test equipment was placed on a wooden table situated on a 4x4 meter area adjacent to the measurement area. Turntable was to protect from weather in the dome that made with FRP.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter(ESVS 10) and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table.

The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed, and/or support equipment, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of radiated emission test.

Each EME reported was calibrated using self-calibrating mode.


Table 3 : Test Data, Radiated Emissions

Frequency (MHz)	Pol.	Height [m]	Angle [°]	(1) Reading (dB μ V)	(2) AFCL (dB/m)	(3) Actual (dB μ V/m)	(4) Limit (dB μ V/m)	(5) Margin (dB)
144.10	H	3.8	253	20.6	16.8	37.4	43.5	6.1
290.60	V	1.5	239	10.3	21.7	32.0	46.0	14.0
433.00	V	1.0	305	12.3	21.7	34.0	46.0	12.0

Table. Radiated Measurements at 3-meters

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emission are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. AFCL = Antenna factor and cable loss
6. H = Horizontal, V = Vertical Polarization

◆ Margin Calculation

$$\begin{aligned}
 (5) \text{Margin} &= (4) \text{Limit} - (3) \text{Actual} \\
 (3) \text{Actual} &= (1) \text{Reading} + (2) \text{AFCL}
 \end{aligned}$$