



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC Part 22 & 24 Certification

**Applicant Name:**

SmartSynch Inc.  
4400 Old Canton Road, Suite 300  
Jackson, MS 39211  
USA

**Date of Testing:**

November 23 - 24, 2009

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

0911232145.QHC

**FCC ID:****QHC-OPENWAY20****APPLICANT:****SMARTSYNCH INC.****Application Type:** Certification**FCC Classification:** PCS Licensed Transmitter (PCB)**FCC Rule Part(s):** §2; §22(H), §24(E)**EUT Type:** Smartmeter**Model(s):** SSI Openway 2.0**Tx Frequency Range:** 824.20 - 848.80MHz (Cell. GSM) / 1850.20 - 1909.80MHz (PCS GSM)**Max. RF Output Power:** 32.45 dBm (1.758 W) Conducted (Cell. GSM)

30.05 dBm (1.012 W) Conducted (PCS GSM)

**Emission Designator(s):** 243KGXW (Cellular GSM), 247KGXW (PCS GSM)**Test Device Serial No.:** *identical prototype* [S/N: 6JF060901025, 6JF060901029]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant Conditions:** Power output listed is conducted for Part 22 and Part 24.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
\_\_\_\_\_  
Randy Ortanez  
President


FCC ID: QHC-OPENWAY20	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 1 of 33

## T A B L E   O F   C O N T E N T S

---


FCC PART 22 & 24 MEASUREMENT REPORT.....	3
1.0    INTRODUCTION .....	4
1.1    SCOPE .....	4
1.2    TESTING FACILITY.....	4
2.0    PRODUCT INFORMATION.....	5
2.1    EQUIPMENT DESCRIPTION .....	5
2.2    EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....	5
2.3    LABELING REQUIREMENTS.....	5
3.0    DESCRIPTION OF TESTS .....	6
3.1    MEASUREMENT PROCEDURE .....	6
3.2    OCCUPIED BANDWIDTH EMISSION LIMITS .....	6
3.3    CELLULAR - BASE FREQUENCY BLOCKS.....	6
3.4    CELLULAR - MOBILE FREQUENCY BLOCKS.....	7
3.5    PCS - BASE FREQUENCY BLOCKS.....	7
3.6    PCS - MOBILE FREQUENCY BLOCKS .....	7
3.7    SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	7
3.8    RADIATED SPURIOUS AND HARMONIC EMISSIONS .....	8
3.9    PEAK-AVERAGE RATIO.....	8
3.10    FREQUENCY STABILITY / TEMPERATURE VARIATION .....	8
4.0    TEST EQUIPMENT CALIBRATION DATA .....	9
5.0    SAMPLE CALCULATIONS .....	10
6.0    TEST RESULTS.....	11
6.1    SUMMARY.....	11
6.2    TRANSMITTER CONDUCTED OUTPUT POWER .....	12
6.3    CELLULAR GSM RADIATED MEASUREMENTS .....	13
6.4    PCS GSM RADIATED MEASUREMENTS .....	16
6.5    CELLULAR GSM FREQUENCY STABILITY MEASUREMENTS.....	19
6.6    PCS GSM FREQUENCY STABILITY MEASUREMENTS.....	21
7.0    PLOTS OF EMISSIONS.....	23
8.0    CONCLUSION.....	33

FCC ID: QHC-OPENWAY20	 FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 2 of 33



# MEASUREMENT REPORT

## FCC Part 22 & 24



### §2.1033 General Information

**APPLICANT:** SmartSynch Inc.  
**APPLICANT ADDRESS:** 4400 Old Canton Road, Suite 300  
**Jackson, MS 39211**  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22(H), §24(E)  
**BASE MODEL:** SSI Openway 2.0  
**FCC ID:** QHC-OPENWAY20  
**FCC CLASSIFICATION:** PCS Licensed Transmitter (PCB)  
**EMISSION DESIGNATOR(S):** 243KGXW (Cellular GSM), 247KGXW (PCS GSM)  
**MODE:** GSM/GPRS  
**FREQUENCY TOLERANCE:** ±0.00025 % (2.5 ppm)  
**Test Device Serial No.:** 6JF060901025,  Production  Pre-Production  Engineering 6JF060901029  
**DATE(S) OF TEST:** November 23 - 24, 2009  
**TEST REPORT S/N:** 0911232145.QHC

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: QHC-OPENWAY20	PCTEST <sup>®</sup> ENGINEERING LABORATORY, INC.		FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 3 of 33

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

### 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity are, the Baltimore-Washington Intert'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.		FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 4 of 33

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **SmartSynch Smartmeter** FCC ID: QHC-OPENWAY20. The EUT consisted of the following component(s):

Trade Name / Base Model	FCC ID	Description
SmartSynch / Model: SSI Openway 2.0	QHC-OPENWAY20	Smartmeter

Table 2-1. EUT Equipment Description

### 2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

*This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).


Please see attachment for FCC ID label and label location.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 5 of 33

## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (See Figure 3-1). The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This power level was recorded using a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded with the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



**Figure 3-1. Diagram of 3-meter outdoor test range**


Deviation from Measurement Procedure.....None

### 3.2 Occupied Bandwidth Emission Limits

§2.1049, 22.917(a), 24.238(a)

- On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

### 3.3 Cellular - Base Frequency Blocks



**BLOCK 1: 869 – 880 MHz (A\* Low + A)**


**BLOCK 2: 880 – 890 MHz (B)**

**BLOCK 3: 890 – 891.5 MHz (A\* High)**

**BLOCK 4: 891.5 – 894 MHz (B\*)**

FCC ID: QHC-OPENWAY20	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 6 of 33

### 3.4 Cellular - Mobile Frequency Blocks




**BLOCK 1:** 824 – 835 MHz (A\* Low + A)

**BLOCK 2:** 835 – 845 MHz (B)

**BLOCK 3:** 845 – 846.5 MHz (A\* High)

**BLOCK 4:** 846.5 – 849 MHz (B\*)

### 3.5 PCS - Base Frequency Blocks



**BLOCK 1:** 1930 – 1945 MHz (A)

**BLOCK 2:** 1945 – 1950 MHz (D)


**BLOCK 3:** 1950 – 1965 MHz (B)

**BLOCK 4:** 1965 – 1970 MHz (E)

**BLOCK 5:** 1970 – 1975 MHz (F)

**BLOCK 6:** 1975 – 1990 MHz (C)

### 3.6 PCS - Mobile Frequency Blocks



**BLOCK 1:** 1850 – 1865 MHz (A)

**BLOCK 2:** 1865 – 1870 MHz (D)

**BLOCK 3:** 1870 – 1885 MHz (B)

**BLOCK 4:** 1885 – 1890 MHz (E)

**BLOCK 5:** 1890 – 1895 MHz (F)

**BLOCK 6:** 1895 – 1910 MHz (C)

### 3.7 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a), 24.238(a)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 7 of 33

### 3.8 Radiated Spurious and Harmonic Emissions

§2.1053, 22.917(a), 24.238(a)

Spurious and harmonic radiated emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This level is then measured with a broadband average power meter. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive average power meter reading. This spurious level is recorded with the power meter. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.

### 3.9 Peak-Average Ratio

§24.232(d)

A peak to average ratio measurement is performed at the conducted port of the EUT. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the peak to average ratio of the EUT in a bandwidth greater than the emission bandwidth. Both traces are displayed in the analyzers' zero span mode while triggering on a pulse. The largest deviation is measured to determine the peak to average ratio.

### 3.10 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235

The frequency stability of the transmitter is measured by:

- Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.*

#### Time Period and Procedure:

- The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 8 of 33

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	263-10dB	(DC-18GHz) 10 dB Attenuator	N/A		N/A	N/A
-	No.165	(30MHz - 1000MHz) RG58 Coax Cable	N/A		N/A	N/A
-	No.166	(1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167	(100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Agilent	11713A	Attenuation/Switch Driver	12/4/2008	Annual	12/4/2009	3439A02645
Agilent	8449B	(1-26.5GHz) Pre-Amplifier	12/4/2008	Annual	12/4/2009	3008A00985
Agilent	8495A	(0-70dB) DC-4GHz Attenuator	N/A		N/A	N/A
Agilent	85650A	Quasi-Peak Adapter	12/4/2008	Annual	12/4/2009	3303A01872
Agilent	8566B	(100Hz-22GHz) Spectrum Analyzer	12/5/2008	Annual	12/5/2009	3638A08713
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/25/2009	Biennial	3/25/2011	MY45470194
Agilent	N9020A	MXA Signal Analyzer	10/22/2009	Annual	10/22/2010	US46470561
Anritsu	ML2495A	Power Meter	10/12/2009	Annual	10/12/2010	941001
Emco	3115	Horn Antenna (1-18GHz)	10/14/2009	Biennial	10/14/2011	9704-5182
Espec	ESX-2CA	Environmental Chamber	3/30/2009	Annual	3/30/2010	17620
MiniCircuits	VHF-1300+	High Pass Filter	N/A		N/A	30716
MiniCircuits	VHF-3100+	High Pass Filter	N/A		N/A	30721
Pasternack	PE2208-6	Bidirectional Coupler	N/A		N/A	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	9/11/2009	Annual	9/11/2010	836371/0079
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Rx	7/17/2009	Biennial	7/17/2011	9105-2404
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Tx	7/17/2009	Biennial	7/17/2011	9105-2403
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	5/14/2009	Biennial	5/14/2011	A050307

Table 4-1. Test Equipment

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 <b>SmartSync</b>	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 9 of 33

## 5.0 SAMPLE CALCULATIONS

### Emission Designator

**Emission Designator = 250KGXW**

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

### Spurious Radiated Emission - PCS Band

**Example: Channel 512 PCS Mode 2<sup>nd</sup> Harmonic (3700.40 MHz)**

The average receive power meter reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the power meter. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

FCC ID: QHC-OPENWAY20	 PCTEST <sup>®</sup> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 10 of 33

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: SmartSync Inc.  
 FCC ID: QHC-OPENWAY20  
 FCC Classification: PCS Licensed Transmitter (PCB)  
 Mode(s): GSM/GPRS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
<b>TRANSMITTER MODE (TX)</b>					
2.1049, 22.917(a), 24.238(a)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 22.917(a), 24.238(a)	Band Edge / Conducted Spurious Emissions	< 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.0
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.0
2.1046	Transmitter Conducted Output Power	N/A		PASS	Section 6.2
2.1053, 22.917(a), 24.238(a)	Undesirable Emissions	< 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions	RADIATED	PASS	Sections 6.3, 6.4
2.1055, 22.355, 24.235	Frequency Stability	< 2.5 ppm		PASS	Sections 6.5, 6.6

Table 6-1. Summary of Test Results

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 11 of 33

## 6.2 Transmitter Conducted Output Power

### §2.1046

A base station simulator (Rhode and Schwartz Model: CMU200) was used to establish communication with the **SmartSynch Smartmeter FCC ID: QHC-OPENWAY20**. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active. The GPRS conducted powers are reported below.

Band	Channel	GPRS			
		Uplink / Downlink Slots Used	Conducted Power	Uplink / Downlink Slots Used	Conducted Power
		[dBm]		[dBm]	
Cellular	128	1/1	32.39	2/1	32.26
	190	1/1	32.45	2/1	32.35
	251	1/1	32.39	2/1	32.31
PCS	512	1/1	29.94	2/1	29.87
	661	1/1	30.05	2/1	29.99
	810	1/1	29.93	2/1	29.84

Table 6-2. Transmitter Conducted Output Power Measurements




Figure 6-1. GSM/GPRS Conducted Power Test Setup Diagram

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 <b>SmartSynch</b>	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 12 of 33

### 6.3 Cellular GSM Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  -13.00 dBm

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBD)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
1648.40	-42.03	6.08	-35.95	H	-22.9
2472.60	-34.91	6.53	-28.38	H	-15.4
3296.80	-52.73	6.87	-45.86	H	-32.9
4121.00	-56.41	7.21	-49.21	H	-36.2
4945.20	-56.49	8.37	-48.11	H	-35.1

Table 6-3. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active. This unit was tested while powered by an AC power source.

FCC ID: QHC-OPENWAY20		FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 13 of 33

## Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  -13.00 dBm

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBD)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
1673.20	-37.39	6.09	-31.30	H	-18.3
2509.80	-49.96	6.55	-43.41	H	-30.4
3346.40	-56.04	6.89	-49.15	H	-36.1
4183.00	-57.84	7.43	-50.41	H	-37.4
5019.60	-54.93	8.35	-46.58	H	-33.6

Table 6-4. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active. This unit was tested while powered by an AC power source.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 <b>Reviewed by:</b> Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 14 of 33

## Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  -13.00 dBm

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
1697.60	-37.20	6.09	-31.11	H	-18.1
2546.40	-44.09	6.57	-37.52	H	-24.5
3395.20	-55.26	6.91	-48.35	H	-35.3
4244.00	-58.37	7.65	-50.72	H	-37.7
5092.80	-54.54	8.33	-46.21	H	-33.2

Table 6-5. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active. This unit was tested while powered by an AC power source.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 <b>SmartSync</b>	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 15 of 33

## 6.4 PCS GSM Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  -13.00 dBm

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
3700.40	-58.71	9.02	-49.69	H	-36.7
5550.60	-55.18	10.40	-44.78	H	-31.8
7400.80	-52.86	10.50	-42.36	H	-29.4
9251.00	-85.05	11.85	-73.20	H	-60.2
11101.20	-82.59	12.76	-69.83	H	-56.8

Table 6-6. Radiated Spurious Data (PCS GSM Mode – Ch. 512)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active. This unit was tested while powered by an AC power source.

FCC ID: QHC-OPENWAY20		FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 16 of 33

## PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  -13.00 dBm

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
3760.00	-58.12	8.99	-49.13	H	-36.1
5640.00	-55.88	10.40	-45.48	H	-32.5
7520.00	-56.03	10.62	-45.41	H	-32.4
9400.00	-84.87	11.70	-73.17	H	-60.2
11280.00	-81.79	12.69	-69.10	H	-56.1

Table 6-7. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active. This unit was tested while powered by an AC power source.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 17 of 33

## PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  -13.00 dBm

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
3819.60	-57.64	8.97	-48.67	H	-35.7
5729.40	-55.92	10.40	-45.52	H	-32.5
7639.20	-56.40	10.71	-45.69	H	-32.7
9549.00	-84.71	11.64	-73.07	H	-60.1
11458.80	-80.99	12.62	-68.38	H	-55.4

Table 6-8. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GPRS mode while transmitting with one slot active. This unit was tested while powered by an AC power source.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 <b>SmartSync</b>	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 18 of 33

## 6.5 Cellular GSM Frequency Stability Measurements

§2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 190

REFERENCE VOLTAGE: 120 VAC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (VAC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	120.00	+ 20 (Ref)	836,600,005	5	0.000001
100 %		- 30	836,600,010	10	0.000001
100 %		- 20	836,599,988	-12	-0.000001
100 %		- 10	836,599,982	-18	-0.000002
100 %		0	836,599,987	-13	-0.000002
100 %		+ 10	836,599,981	-19	-0.000002
100 %		+ 20	836,599,983	-17	-0.000002
100 %		+ 30	836,599,994	-6	-0.000001
100 %		+ 40	836,600,010	10	0.000001
100 %		+ 50	836,599,993	-7	-0.000001
115 %	138.00	+ 20	836,599,980	-20	-0.000002
85%	102.00	+ 20	836,599,986	-14	-0.000002

Table 6-9. Frequency Stability Data (Cellular GSM Mode – Ch. 190)

FCC ID: QHC-OPENWAY20	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 SmartSync	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 19 of 33

## Cellular GSM Frequency Stability Measurements (Cont'd)

§2.1055, 22.355; RSS-132 (4.3)



Plot 6-1. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)

FCC ID: QHC-OPENWAY20		FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 20 of 33

## 6.6 PCS GSM Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 120 VAC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (VAC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	120.00	+ 20 (Ref)	1,880,000,009	9	0.000000
100 %		- 30	1,879,999,992	-8	0.000000
100 %		- 20	1,880,000,010	10	0.000001
100 %		- 10	1,879,999,979	-21	-0.000001
100 %		0	1,879,999,994	-6	0.000000
100 %		+ 10	1,880,000,019	19	0.000001
100 %		+ 20	1,879,999,990	-10	-0.000001
100 %		+ 30	1,880,000,010	10	0.000001
100 %		+ 40	1,879,999,989	-11	-0.000001
100 %		+ 50	1,880,000,013	13	0.000001
115 %	138.00	+ 20	1,880,000,020	20	0.000001
BATT. ENDPOINT	102.00	+ 20	1,880,000,021	21	0.000001

Table 6-10. Frequency Stability Data (PCS GSM Mode – Ch. 661)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 21 of 33

## PCS GSM Frequency Stability Measurements (Cont'd)


§2.1055, 24.235; RSS-133 (6.3)




Plot 6-2. Frequency Stability Graph (PCS GSM Mode – Ch. 661)

FCC ID: QHC-OPENWAY20		FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 22 of 33

## 7.0 PLOTS OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-2. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 23 of 33




Plot 7-3. Band Edge Plot (Cellular GSM Mode – Ch. 128)




Plot 7-4. Conducted Spurious (Cellular GSM Mode – Ch. 190)

FCC ID: QHC-OPENWAY20	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 24 of 33




Plot 7-5. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)




Plot 7-6. Occupied Bandwidth Plot (Cellular GSM Mode – Ch. 190)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> <sup>®</sup> ENGINEERING LABORATORY, INC.			FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter			




Plot 7-7. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)




Plot 7-8. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)

FCC ID: QHC-OPENWAY20	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 26 of 33




Plot 7-9. Band Edge Plot (Cellular GSM Mode – Ch. 251)




Plot 7-10. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 27 of 33




Plot 7-11. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-12. Band Edge Plot (PCS GSM Mode – Ch. 512)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 28 of 33



Plot 7-13. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-14. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 29 of 33




Plot 7-15. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)




Plot 7-16. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 30 of 33




Plot 7-17. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)



Plot 7-18. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 31 of 33



Plot 7-19. Band Edge Plot (PCS GSM Mode – Ch. 810)

FCC ID: QHC-OPENWAY20	<b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter	Page 32 of 33

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **SmartSynch Smartmeter** **FCC ID: QHC-OPENWAY20** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

FCC ID: QHC-OPENWAY20	 <b>PCTEST</b> <sup>®</sup> ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/GPRS MEASUREMENT REPORT (CERTIFICATION)	 SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0911232145.QHC	Test Dates: November 23 - 24, 2009	EUT Type: Smartmeter		Page 33 of 33