

COMMSCOPE TECHNOLOGIES, LLC

MPE CALCULATION TEST REPORT

SCOPE OF WORK

MPE Calculation – Added 80 MHz to n77 C Band with 5G W/ RP5200 Host

REPORT NUMBER

105852007BOX-001MPE

ISSUE DATE

08/23/2024

[REVISED DATE]

Original Issue

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. October 2022

© 2022 INTERTEK



MPE CALCULATION TEST REPORT (FULL COMPLIANCE)

Report Number: 105852007BOX-001MPE
Project Number: G105852007

Report Issue Date: 08/23/2024

Model(s) Tested: n77 C Band with 5G W/ RP5200 Host, W/
80 MHz Bandwidth

Model(s) Partially Tested: None

Model(s) Not Tested but declared equivalent by the client: None

Standards: FCC Part 1.1310: 04/23 Limits for Maximum Permissible Exposure (MPE)
(General Population / Uncontrolled Exposure)

Tested by:

Intertek
70 Codman Hill Road
Boxborough, MA 01719
USA

Client:

CommScope Technologies, LLC
900 Chelmsford St.
Lowell, MA 01851
USA

Report prepared by Reviewer



Vathana Ven / Sr. EMC Staff Engineer

Report reviewed by Reviewer



Kouma Sinn / Sr. EMC Staff Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Table of Contents

1	<i>Introduction and Conclusion</i>	4
2	<i>Test Summary</i>	4
3	<i>Client Information</i>	5
4	<i>Description of Equipment Under Test and Variant Models</i>	5
5	<i>FCC MPE Limits</i>	7
6	<i>Revision History</i>	9

1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

2 Test Summary

Section	Test full name	Result
3	Client Information	--
4	Description of Equipment Under Test and Variant Models	--
5	FCC MPE Calculation FCC Part 1.1310: 08/23 (General Population / Uncontrolled Exposure)	Pass
6	Revision History	--

3 Client Information

This EUT was tested at the request of:

Client: CommScope Technologies, LLC
900 Chelmsford St.
Lowell, MA 01851
USA

Contact: Julie Lee
Telephone: (978) 250-2678
Fax: None
Email: Julie.Lee@commscope.com

4 Description of Equipment Under Test and Variant Models

Manufacturer: CommScope Technologies, LLC
900 Chelmsford St.
Lowell, MA 01851
USA

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
n77 C Band with 5G W/ RP5200 Host base station	CommScope Technologies LLC	n77 C Band	TJBSAC23440073

Receive Date:	07/25/2024
Received Condition:	Good
Type:	Production

Description of Equipment Under Test (provided by client)	
n77 C Band with 5G W/ RP5200 Host base station with 80 MHz bandwidth added.	

Radio Characteristics	
Frequency Band(s)	3740-3940 MHz
Modulation Type(s)	TM1.1, TM3.1, TM3.1a, TM3.3
Maximum Output Power	2.21 Watt (Worst-case EIRP)
Test Channels	Low – 3740 MHz, Mid – 3840 MHz, High – 3940 MHz
Occupied Bandwidth	77.921 MHz (Worst-case)
MIMO Information (# of Transmit and Receive antenna ports)	Four Antenna Ports
Equipment Type	Plug-in Radio Module
Antenna Type and Gain	Detachable Antenna: +4 dBi (as provided by the client. Intertek takes no responsibility for the accuracy of this information. Actual antenna gain will be determined at the time of licensing)

Variant Models:

The following variant models were not tested as part of this evaluation and are not eligible for certification; but have been identified by the manufacturer as being electrically identical models, depopulated models, or with reasonable similarity to the model(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

None

5 FCC MPE Calculation

5.1 Limits

§ 1.1310: The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

Part 1.1310 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

5.2 Test Procedure

An MPE evaluation was performed in order to show that the device was compliant with the general population exposure limits from FCC §2.1091. The maximum power density was calculated for each transmitter band at a separation distance of 20cm using the maximum declared output power including tune up tolerance.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$\text{ConductedPower}_{\text{mW}} = 10^{\text{ConductedPower(dBm)/10}}$$

$$\text{PowerDensity} = \frac{\text{ConductedPower}_{\text{mW}} \times \text{Ant.Gain}}{4\pi \times (20_{\text{cm}})^2}$$

5.3 Results:

The calculated maximum power density at 20 cm distance was equal to or less than the required Maximum Permissible Exposure (MPE) for General Population / Uncontrolled Exposure environment. The sample was found to comply.

		Port 1	Port 2	Port 3	Port 4	dBm, mW	dB _i	dBm, mW	mW/cm ²	mW/cm ²	mW/cm ²
TM1.1	Low	22.79	24.06	23.39	23.35	29.44	4.00	33.44	0.440	1.00	-0.560
	3720 MHz	190.11	254.68	218.27	216.27	879.34		2208.79			
	Mid	23.11	23.06	23.17	23.31	29.18		33.18	0.414	1.00	-0.586
	3840 MHz	204.64	202.30	207.49	214.29	828.73		2081.67			
	High	22.77	22.62	22.83	22.63	28.73	4.00	32.73	0.374	1.00	-0.626
	3960 MHz	189.23	182.81	191.87	183.23	747.14		1876.74			
	Low	22.53	23.86	23.86	23.27	29.43		33.43	0.439	1.00	-0.561
	3720 MHz	179.06	243.22	243.22	212.32	877.83		2205.00			
TM3.1	Mid	22.95	22.79	22.88	23.25	28.99	4.00	32.99	0.396	1.00	-0.604
	3840 MHz	197.24	190.11	194.09	211.35	792.79		1991.39			
	High	22.76	22.52	22.75	22.67	28.70		32.70	0.370	1.00	-0.630
	3960 MHz	188.80	178.65	188.36	184.93	740.74		1860.65			
	Low	22.81	22.79	23.43	22.12	28.83	4.00	32.83	0.382	1.00	-0.618
TM3.1a	3720 MHz	190.99	190.11	220.29	162.93	764.32		1919.87			
	Mid	22.79	22.70	22.54	22.43	28.64	4.00	32.64	0.365	1.00	-0.635
	3840 MHz	190.11	186.21	179.47	174.98	730.77		1835.62			
	High	22.12	22.31	22.16	22.18	28.21	4.00	32.21	0.331	1.00	-0.669
	3960 MHz	162.93	170.22	164.44	165.20	662.78		1664.83			
TM3.3	Low	22.79	22.54	23.24	22.00	28.69	4.00	32.69	0.369	1.00	-0.631
	3720 MHz	190.11	179.47	210.86	158.49	738.93		1856.12			
	Mid	22.81	22.48	22.49	22.55	28.61		32.61	0.363	1.00	-0.637
	3840 MHz	190.99	177.01	177.42	179.89	725.30		1821.88			
	High	22.23	22.35	22.24	22.44	28.34	4.00	32.34	0.341	1.00	-0.659
	3960 MHz	167.11	171.79	167.49	175.39	681.78		1712.56			

Notes: The EIRP power used for MPE calculation was taken from Report # 105852007BOX-001.

6 Revision History

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	08/23/2024	105852007BOX-001MPE	VFV	KPS	Original Issue