

Test report No:
NIE: 60088RAN.003A2

Assessment report

RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091 ISED RSS-102 Issue 5:2015

Identification of item tested	Wireless Module
Trademark	Cinterion ALAS5-AM
Model and /or type reference	ALAS5-AM
Other identification of the product	FCC IC: QIPALAS5-AM IC: 7830A-ALAS5AM HW version: Rev. 1.1.4b SW version: Rev. 00.052
Features	2G, 3G and 4G
Manufacturer	GEMALTO M2M GMBH Werinherstr. 81 81541 Munich, Germany
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) IEEE Std C95.3™ -2002 (R2008). IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields With Respect to Human Exposure to Such Fields, 100 kHz–300 GHz
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2020-03-04
Report template No	FAN36_01

Index

- Competences and guarantees3
- General conditions3
- Data provided by the client.....3
- Identification of the client.....3
- Document history3
- General description of the device under evaluation4
- Maximum Antenna Gain determination for RF Exposure compliance.....5
- Appendix A: FCC RF Exposure information8
 - FCC RF Exposure evaluation9
 - FCC MPE Evaluation10
 - FCC EIRP Limits10
- Appendix B: ISED RF Exposure information11
 - ISED RF Exposure evaluation for mobile devices.....12
 - ISED MPE Evaluation13
 - ISED EIRP Limits13

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This assessment report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies.

Data provided by the client

The device under evaluation consists of a Cinterion ALAS5-AM wireless module supporting 2G, 3G and 4G cellular technologies.

DEKRA Testing and Certification, S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

GEMALTO M2M GMBH
Werinherstr. 81
81541 Munich, Germany

Document history

Report number	Date	Description
60088RAN.003	2019-07-11	First release
60088RAN.003A1	2019-08-13	Second release. Corrected maximum gain values for GPRS mode according to the FCC & ISED EIRP limits. Updated RSS-130 standard from Issue 1 to Issue 2.
60088RAN.003A2	2020-03-04	Third release. Corrected frequency range of WCDMA Band V.

General description of the device under evaluation

The device under evaluation consists of a Cinterion ALAS5-AM wireless module supporting 2G, 3G and 4G cellular technologies.

As the equipment under evaluation is a module, a conservative evaluation distance of 20 cm has been used to perform the assessment.

The equipment specifications declared by the manufacturer for each supported feature are:

Technology / Mode	Band	Frequency (MHz)	Maximum Conducted Output Power RMS Burst (Incl. Tune-Up) (dBm)	Duty Cycle (%)	Average Conducted Power (dBm)
GSM	850	824 - 849	34.00	12.50	24.97
GPRS 1TX	850	824 - 849	34.00	12.50	24.97
GPRS 2TX	850	824 - 849	34.00	25.00	27.98
GPRS 3TX	850	824 - 849	34.00	37.50	29.74
GPRS 4TX	850	824 - 849	34.00	50.00	30.99
EGPRS 1TX	850	824 - 849	29.00	12.50	19.97
EGPRS 2TX	850	824 - 849	29.00	25.00	22.98
EGPRS 3TX	850	824 - 849	29.00	37.50	24.74
EGPRS 4TX	850	824 - 849	29.00	50.00	25.99
GSM	1900	1850 - 1910	32.00	12.50	22.97
GPRS 1TX	1900	1850 - 1910	32.00	12.50	22.97
GPRS 2TX	1900	1850 - 1910	32.00	25.00	25.98
GPRS 3TX	1900	1850 - 1910	32.00	37.50	27.74
GPRS 4TX	1900	1850 - 1910	32.00	50.00	28.99
EGPRS 1TX	1900	1850 - 1910	28.00	12.50	18.97
EGPRS 2TX	1900	1850 - 1910	28.00	25.00	21.98
EGPRS 3TX	1900	1850 - 1910	28.00	37.50	23.74
EGPRS 4TX	1900	1850 - 1910	28.00	50.00	24.99
UMTS	II	1850 - 1910	26.00	100.00	26.00
UMTS	IV	1710 - 1755	26.00	100.00	26.00
UMTS	V	824 - 849	26.00	100.00	26.00
LTE	2	1850 - 1910	25.00	100.00	25.00
LTE	4	1710 - 1755	25.00	100.00	25.00
LTE	5	824 - 849	25.00	100.00	25.00
LTE	7	2500 - 2570	25.00	100.00	25.00
LTE	12	699 - 716	25.00	100.00	25.00
LTE	13	777 - 787	25.00	100.00	25.00
LTE	66	1710 - 1780	25.00	100.00	25.00

Table 1: Equipment specifications

Maximum Antenna Gain determination for RF Exposure compliance

Summary of maximum antenna gain values:

Maximum antenna gain for mobile operation to comply with MPE and EIRP limits (see Appendix A and B) shall not exceed the following values:

Technology / Mode	Band	Frequency (MHz)	Maximum Gain to comply with:			Maximum Gain (dBi)
			FCC MPE Limits (dBi)	ISED MPE Limits (dBi)	FCC/ISED EIRP Limits (dBi)	
GSM/GPRS	850	824 - 849	3.4	0.1	6.6	0.1
GSM/GPRS	1900	1850 - 1910	8.0	4.5	1.0	1.0
UMTS	II	1850 - 1910	11.0	7.5	7.0	7.0
UMTS	IV	1710 - 1755	11.0	7.2	4.0	4.0
UMTS	V	824 - 849	8.4	5.1	14.6	5.1
LTE	2	1850 - 1910	12.0	8.5	8.0	8.0
LTE	4	1710 - 1755	12.0	8.2	5.0	5.0
LTE	5	824 - 849	9.4	6.1	15.6	6.1
LTE	7	2500 - 2570	12.0	9.4	8.0	8.0
LTE	12	699 - 716	8.6	5.6	11.9	5.6
LTE	13	777 - 787	9.1	5.9	11.9	5.9
LTE	66	1710 - 1780	12.0	8.2	5.0	5.0

Table 2: Maximum Antenna Gain values

Maximum Gain to meet FCC Radiofrequency radiation exposure limits:

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Power density (mW/cm ²)	FCC General Population Limit (mW/cm ²)	Verdict	Maximum Gain to meet FCC MPE Limits (dBi)
GSM/GPRS	850	824 - 849	20.0	0.25	0.5	Pass	3.4
GSM/GPRS	1900	1850 - 1910	20.0	0.16	1.0	Pass	8.0
UMTS	II	1850 - 1910	20.0	0.08	1.0	Pass	11.0
UMTS	IV	1710 - 1755	20.0	0.08	1.0	Pass	11.0
UMTS	V	824 - 849	20.0	0.08	0.5	Pass	8.4
LTE	2	1850 - 1910	20.0	0.06	1.0	Pass	12.0
LTE	4	1710 - 1755	20.0	0.06	1.0	Pass	12.0
LTE	5	824 - 849	20.0	0.06	0.5	Pass	9.4
LTE	7	2500 - 2570	20.0	0.06	1.0	Pass	12.0
LTE	12	699 - 716	20.0	0.06	0.5	Pass	8.6
LTE	13	777 - 787	20.0	0.06	0.5	Pass	9.1
LTE	66	1710 - 1780	20.0	0.06	1.0	Pass	12.0

Table 3: Maximum Antenna Gain values based on MPE limits

Maximum Gain to meet ISED Radiofrequency radiation exposure limits:

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Power density (W/m ²)	ISED General Public Limit (W/m ²)	Verdict	Maximum Gain to meet ISED MPE Limits (dBi)
GSM/GPRS	850	824 - 849	20.0	2.50	2.6	Pass	0.1
GSM/GPRS	1900	1850 - 1910	20.0	1.58	4.5	Pass	4.5
UMTS	II	1850 - 1910	20.0	0.79	4.5	Pass	7.5
UMTS	IV	1710 - 1755	20.0	0.79	4.2	Pass	7.2
UMTS	V	824 - 849	20.0	0.79	2.6	Pass	5.1
LTE	2	1850 - 1910	20.0	0.63	4.5	Pass	8.5
LTE	4	1710 - 1755	20.0	0.63	4.2	Pass	8.2
LTE	5	824 - 849	20.0	0.63	2.6	Pass	6.1
LTE	7	2500 - 2570	20.0	0.63	5.5	Pass	9.4
LTE	12	699 - 716	20.0	0.63	2.3	Pass	5.6
LTE	13	777 - 787	20.0	0.63	2.5	Pass	5.9
LTE	66	1710 - 1780	20.0	0.63	4.2	Pass	8.2

Table 4: Maximum Antenna Gain values based on RF Exposure limits

Maximum Gain to meet FCC & ISSED EIRP limits:

Technology / Mode	Band	Frequency (MHz)	Maximum Conducted Output Power RMS Burst (Incl. Tune-Up) (dBm)	EIRP Limits (dBm)	Maximum Gain to meet EIRP Limits (dBi)
GSM/GPRS	850	824 - 849	34.0	40.6	6.6
GSM/GPRS	1900	1850 - 1910	32.0	33.0	1.0
UMTS	II	1850 - 1910	26.0	33.0	7.0
UMTS	IV	1710 - 1755	26.0	30.0	4.0
UMTS	V	824 - 849	26.0	40.6	14.6
LTE	2	1850 - 1910	25.0	33.0	8.0
LTE	4	1710 - 1755	25.0	30.0	5.0
LTE	5	824 - 849	25.0	40.6	15.6
LTE	7	2500 - 2570	25.0	33.0	8.0
LTE	12	699 - 716	25.0	36.9	11.9
LTE	13	777 - 787	25.0	36.9	11.9
LTE	66	1710 - 1780	25.0	30.0	5.0

Table 5: Maximum Antenna Gain values based on EIRP limits

Appendix A: FCC RF Exposure information

FCC RF Exposure evaluation

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	* 100	6
3.0–30	1842/f	4.89/f	* 900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500			f/300	6
1,500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* 100	30
1.34–30	824/f	2.19/f	* 180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500			f/1500	30
1,500–100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{\max}[mW]}{4\pi R[cm]^2}$$

$$\text{Maximum gain to meet the MPE limit: } G_{\max}[dBi] = (10 * \log[S[mW/cm^2] * 4\pi R[cm]^2] - P_{\max}[dBm])$$

Where:

S = power density

$P_{\max}$ = power input to the antenna

R = distance to the center of radiation of the antenna (evaluation distance)

$G_{\max}$ = power gain of the antenna in the direction of interest relative to an isotropic radiator

FCC EIRP Limits

Maximum FCC EIRP limits are stated into FCC 47 CFR §22.913, FCC 47 CFR §24.232 and FCC 47 CFR §22.50 standards, these limits are frequency-dependent and are shown in the following table:

Standard	Frequency Band	Technology & Band	EIRP limit (W)	EIRP limit (dBm)
FCC 47 CFR §27.50 (c)	700	LTE 12	4.92	36.92
FCC 47 CFR §27.50 (b)	700	LTE 13	4.92	36.92
FCC 47 CFR §22.913	850	GSM 850, UMTS V, LTE 5	11.48	40.6
FCC 47 CFR §27.50 (d)	1700	WCDMA IV, LTE 4/66	1.0	30.0
FCC 47 CFR §24.232	1900	GSM 1900, UMTS II, LTE 2	2.0	33.0
FCC 47 CFR §27.50 (h) (2)	2600	LTE 7	2.0	33.0

Appendix B: ISED RF Exposure information

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph "4. Exposure Limits", Industry of Canada has adopted the RF field strength limits established in Health Canada's RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public
(Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/ $f^{1.2}$
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

Table 6: RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²³	170	180	-	Instantaneous*
0.1-10	-	1.6/ f	-	6**
1.29-10	193/ $f^{0.5}$	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ $f^{0.25}$	0.3444/ $f^{0.25}$	44.72/ $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	9.40 x 10 ⁻⁴ $f^{0.5}$	3.33 x 10 ⁻⁴ f	616000/ $f^{1.2}$
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

ISED MPE Evaluation

Each supported transmission technology will be evaluated to determine if it is in compliance with RSS-102 Issue 5, RF Field Strength Limits for devices used by the General Public.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[W/m^2] = \frac{P_{\max}[W]}{4\pi R[m]^2}$$

$$\text{Maximum gain to meet the RSS -102 limit: } G_{\max}[dBi] = (10 * \log[S[W/m^2] * 4\pi R[m]^2) + 30 - P_{\max}[dBm]$$

Where:

S = power density

$P_{\max}$ = power input to the antenna

R = distance to the center of radiation of the antenna (evaluation distance)

$G_{\max}$ = power gain of the antenna in the direction of interest relative to an isotropic radiator

ISED EIRP Limits

Maximum ISED EIRP limits are stated into RSS-130 Issue 2, RSS-132 Issue 3, RSS-133 Issue 6, RSS-139 Issue 3 and RSS-199 Issue 3. These limits are frequency-dependent and are shown in the following table:

Standard	Frequency Band	Technology & Band	EIRP limit (W)	EIRP limit (dBm)
RSS-130 Issue 2	700	LTE 12/13	4.92	36.92
RSS-132 Issue 3	850	GSM 850, UMTS V, LTE 5	11.5	40.6
RSS-139. Issue 3	1700	WCDMA IV, LTE 4/66	1.0	30.0
RSS-133 Issue 6	1900	GSM 1900, UMTS II, LTE 2	2.0	33.0
RSS-199 Issue 3	2600	LTE 7	2.0	33.0