

10493-AAA	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.14	68.93	17.44	1.99	80.0	± 9.6 %
		Y	3.43	67.18	16.34		80.0	
		Z	4.17	70.14	18.51		80.0	
10494-AAA	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.05	75.19	19.25	1.99	80.0	± 9.6 %
		Y	3.54	71.12	17.58		80.0	
		Z	6.21	80.26	21.94		80.0	
10495-AAA	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.16	69.77	17.74	1.99	80.0	± 9.6 %
		Y	3.39	67.63	16.56		80.0	
		Z	4.24	71.24	18.96		80.0	
10496-AAA	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.21	69.35	17.61	1.99	80.0	± 9.6 %
		Y	3.47	67.41	16.52		80.0	
		Z	4.25	70.59	18.72		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.80	70.81	15.55	1.99	80.0	± 9.6 %
		Y	1.12	61.02	9.43		80.0	
		Z	8.49	87.13	21.57		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.12	64.40	11.96	1.99	80.0	± 9.6 %
		Y	1.22	60.00	7.90		80.0	
		Z	2.34	66.73	13.07		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.08	63.91	11.60	1.99	80.0	± 9.6 %
		Y	1.24	60.00	7.76		80.0	
		Z	2.18	65.53	12.38		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.29	75.80	19.32	1.99	80.0	± 9.6 %
		Y	2.69	70.50	16.68		80.0	
		Z	6.80	85.39	23.56		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.69	70.47	17.19	1.99	80.0	± 9.6 %
		Y	2.68	67.14	14.90		80.0	
		Z	4.30	74.37	19.32		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.74	70.21	17.06	1.99	80.0	± 9.6 %
		Y	2.72	66.99	14.78		80.0	
		Z	4.30	73.88	19.06		80.0	
10503-AAA	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.45	75.33	19.39	1.99	80.0	± 9.6 %
		Y	2.96	70.75	17.34		80.0	
		Z	5.89	81.99	22.70		80.0	
10504-AAA	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.78	70.07	17.61	1.99	80.0	± 9.6 %
		Y	2.95	67.61	16.07		80.0	
		Z	4.03	72.50	19.24		80.0	
10505-AAA	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.85	69.73	17.51	1.99	80.0	± 9.6 %
		Y	3.05	67.50	16.04		80.0	
		Z	4.04	71.89	19.00		80.0	
10506-AAA	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.99	74.98	19.16	1.99	80.0	± 9.6 %
		Y	3.51	70.98	17.51		80.0	
		Z	6.10	79.97	21.82		80.0	
10507-AAA	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.14	69.70	17.69	1.99	80.0	± 9.6 %
		Y	3.37	67.57	16.53		80.0	
		Z	4.22	71.16	18.92		80.0	

10508-AAA	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.19	69.27	17.57	1.99	80.0	± 9.6 %
		Y	3.46	67.35	16.48		80.0	
		Z	4.23	70.50	18.67		80.0	
10509-AAA	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.01	72.76	18.36	1.99	80.0	± 9.6 %
		Y	3.88	69.93	17.15		80.0	
		Z	5.50	75.60	20.16		80.0	
10510-AAA	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.60	69.25	17.58	1.99	80.0	± 9.6 %
		Y	3.87	67.44	16.63		80.0	
		Z	4.58	70.12	18.50		80.0	
10511-AAA	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.62	68.88	17.49	1.99	80.0	± 9.6 %
		Y	3.93	67.23	16.59		80.0	
		Z	4.58	69.61	18.33		80.0	
10512-AAA	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	5.53	75.04	19.02	1.99	80.0	± 9.6 %
		Y	4.01	71.29	17.52		80.0	
		Z	6.61	79.40	21.39		80.0	
10513-AAA	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.53	69.77	17.76	1.99	80.0	± 9.6 %
		Y	3.75	67.65	16.71		80.0	
		Z	4.55	70.81	18.79		80.0	
10514-AAA	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.49	69.17	17.60	1.99	80.0	± 9.6 %
		Y	3.78	67.28	16.62		80.0	
		Z	4.47	70.01	18.51		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	1.06	65.13	16.67	0.00	150.0	± 9.6 %
		Y	0.99	63.18	14.66		150.0	
		Z	1.10	66.46	17.84		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	2.53	99.73	30.26	0.00	150.0	± 9.6 %
		Y	0.60	69.53	16.99		150.0	
		Z	100.00	178.66	51.01		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	1.01	69.54	18.69	0.00	150.0	± 9.6 %
		Y	0.83	64.94	15.24		150.0	
		Z	1.16	73.22	21.01		150.0	
10518-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.76	67.04	16.66	0.00	150.0	± 9.6 %
		Y	4.49	66.77	16.17		150.0	
		Z	4.75	67.24	16.91		150.0	
10519-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.99	67.33	16.79	0.00	150.0	± 9.6 %
		Y	4.67	66.98	16.28		150.0	
		Z	4.96	67.51	17.03		150.0	
10520-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.84	67.34	16.74	0.00	150.0	± 9.6 %
		Y	4.52	66.93	16.20		150.0	
		Z	4.82	67.53	16.99		150.0	
10521-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.77	67.37	16.74	0.00	150.0	± 9.6 %
		Y	4.45	66.93	16.19		150.0	
		Z	4.75	67.56	16.99		150.0	
10522-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.81	67.29	16.74	0.00	150.0	± 9.6 %
		Y	4.52	67.04	16.28		150.0	
		Z	4.80	67.54	17.03		150.0	

10523-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.69	67.24	16.63	0.00	150.0	± 9.6 %
		Y	4.41	66.93	16.15		150.0	
		Z	4.67	67.46	16.90		150.0	
10524-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.77	67.27	16.74	0.00	150.0	± 9.6 %
		Y	4.46	66.96	16.25		150.0	
		Z	4.75	67.50	17.02		150.0	
10525-AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.72	66.31	16.34	0.00	150.0	± 9.6 %
		Y	4.46	66.03	15.85		150.0	
		Z	4.72	66.53	16.60		150.0	
10526-AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.93	66.73	16.48	0.00	150.0	± 9.6 %
		Y	4.61	66.37	15.99		150.0	
		Z	4.92	66.95	16.75		150.0	
10527-AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.85	66.73	16.45	0.00	150.0	± 9.6 %
		Y	4.54	66.33	15.93		150.0	
		Z	4.84	66.94	16.72		150.0	
10528-AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.87	66.75	16.48	0.00	150.0	± 9.6 %
		Y	4.55	66.34	15.96		150.0	
		Z	4.86	66.96	16.75		150.0	
10529-AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.87	66.75	16.48	0.00	150.0	± 9.6 %
		Y	4.55	66.34	15.96		150.0	
		Z	4.86	66.96	16.75		150.0	
10531-AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.89	66.92	16.52	0.00	150.0	± 9.6 %
		Y	4.53	66.42	15.96		150.0	
		Z	4.87	67.13	16.79		150.0	
10532-AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.74	66.81	16.48	0.00	150.0	± 9.6 %
		Y	4.40	66.28	15.89		150.0	
		Z	4.72	67.01	16.75		150.0	
10533-AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.88	66.77	16.46	0.00	150.0	± 9.6 %
		Y	4.56	66.40	15.96		150.0	
		Z	4.87	66.99	16.73		150.0	
10534-AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	5.37	66.84	16.48	0.00	150.0	± 9.6 %
		Y	5.09	66.42	16.02		150.0	
		Z	5.37	66.98	16.71		150.0	
10535-AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	5.45	66.98	16.53	0.00	150.0	± 9.6 %
		Y	5.15	66.59	16.09		150.0	
		Z	5.44	67.13	16.77		150.0	
10536-AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	5.32	67.00	16.53	0.00	150.0	± 9.6 %
		Y	5.03	66.55	16.05		150.0	
		Z	5.31	67.15	16.77		150.0	
10537-AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	5.38	66.96	16.51	0.00	150.0	± 9.6 %
		Y	5.08	66.51	16.04		150.0	
		Z	5.38	67.11	16.75		150.0	
10538-AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	5.49	67.02	16.58	0.00	150.0	± 9.6 %
		Y	5.16	66.52	16.08		150.0	
		Z	5.48	67.15	16.81		150.0	
10540-AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	5.39	66.97	16.57	0.00	150.0	± 9.6 %
		Y	5.09	66.51	16.09		150.0	
		Z	5.39	67.12	16.81		150.0	

10541-AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	5.38	66.89	16.53	0.00	150.0	± 9.6 %
		Y	5.07	66.41	16.03		150.0	
		Z	5.36	66.99	16.74		150.0	
10542-AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.52	66.89	16.54	0.00	150.0	± 9.6 %
		Y	5.23	66.49	16.09		150.0	
		Z	5.51	67.03	16.77		150.0	
10543-AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.61	66.89	16.55	0.00	150.0	± 9.6 %
		Y	5.29	66.51	16.12		150.0	
		Z	5.59	67.03	16.78		150.0	
10544-AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.64	66.92	16.44	0.00	150.0	± 9.6 %
		Y	5.41	66.54	16.01		150.0	
		Z	5.65	67.02	16.65		150.0	
10545-AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.86	67.33	16.58	0.00	150.0	± 9.6 %
		Y	5.59	66.92	16.16		150.0	
		Z	5.88	67.51	16.83		150.0	
10546-AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.75	67.23	16.55	0.00	150.0	± 9.6 %
		Y	5.46	66.71	16.07		150.0	
		Z	5.75	67.34	16.77		150.0	
10547-AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.84	67.29	16.57	0.00	150.0	± 9.6 %
		Y	5.53	66.76	16.08		150.0	
		Z	5.84	67.40	16.79		150.0	
10548-AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	6.17	68.41	17.09	0.00	150.0	± 9.6 %
		Y	5.72	67.50	16.43		150.0	
		Z	6.26	68.82	17.45		150.0	
10550-AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.77	67.16	16.53	0.00	150.0	± 9.6 %
		Y	5.49	66.75	16.10		150.0	
		Z	5.77	67.28	16.75		150.0	
10551-AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.79	67.28	16.55	0.00	150.0	± 9.6 %
		Y	5.49	66.77	16.07		150.0	
		Z	5.78	67.36	16.75		150.0	
10552-AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.68	67.03	16.44	0.00	150.0	± 9.6 %
		Y	5.42	66.62	16.00		150.0	
		Z	5.68	67.11	16.64		150.0	
10553-AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.78	67.06	16.48	0.00	150.0	± 9.6 %
		Y	5.50	66.63	16.04		150.0	
		Z	5.77	67.15	16.68		150.0	
10554-AAA	IEEE 1602.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	6.04	67.29	16.52	0.00	150.0	± 9.6 %
		Y	5.82	66.89	16.10		150.0	
		Z	6.06	67.39	16.73		150.0	
10555-AAA	IEEE 1602.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	6.21	67.65	16.67	0.00	150.0	± 9.6 %
		Y	5.93	67.16	16.21		150.0	
		Z	6.22	67.74	16.87		150.0	
10556-AAA	IEEE 1602.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	6.21	67.64	16.66	0.00	150.0	± 9.6 %
		Y	5.95	67.21	16.23		150.0	
		Z	6.23	67.76	16.88		150.0	
10557-AAA	IEEE 1602.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	6.20	67.62	16.67	0.00	150.0	± 9.6 %
		Y	5.92	67.12	16.21		150.0	
		Z	6.21	67.70	16.87		150.0	

10558-AAA	IEEE 1602.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	6.27	67.82	16.78	0.00	150.0	± 9.6 %
		Y	5.96	67.26	16.30		150.0	
		Z	6.27	67.91	16.99		150.0	
10560-AAA	IEEE 1602.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	6.25	67.63	16.73	0.00	150.0	± 9.6 %
		Y	5.96	67.13	16.27		150.0	
		Z	6.25	67.69	16.91		150.0	
10561-AAA	IEEE 1602.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	6.16	67.59	16.74	0.00	150.0	± 9.6 %
		Y	5.89	67.10	16.28		150.0	
		Z	6.17	67.67	16.94		150.0	
10562-AAA	IEEE 1602.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	6.34	68.10	17.00	0.00	150.0	± 9.6 %
		Y	5.98	67.40	16.44		150.0	
		Z	6.35	68.23	17.22		150.0	
10563-AAA	IEEE 1602.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	6.63	68.49	17.13	0.00	150.0	± 9.6 %
		Y	6.09	67.36	16.38		150.0	
		Z	6.75	68.92	17.50		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	5.08	67.05	16.75	0.46	150.0	± 9.6 %
		Y	4.82	66.83	16.32		150.0	
		Z	5.06	67.23	16.99		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	5.35	67.57	17.09	0.46	150.0	± 9.6 %
		Y	5.03	67.25	16.63		150.0	
		Z	5.32	67.73	17.33		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	5.18	67.44	16.92	0.46	150.0	± 9.6 %
		Y	4.87	67.09	16.44		150.0	
		Z	5.16	67.61	17.17		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	5.21	67.88	17.30	0.46	150.0	± 9.6 %
		Y	4.89	67.46	16.79		150.0	
		Z	5.19	68.06	17.56		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	5.07	67.08	16.62	0.46	150.0	± 9.6 %
		Y	4.78	66.88	16.22		150.0	
		Z	5.05	67.30	16.89		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	5.14	67.88	17.31	0.46	150.0	± 9.6 %
		Y	4.86	67.58	16.86		150.0	
		Z	5.14	68.11	17.60		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	5.20	67.72	17.25	0.46	150.0	± 9.6 %
		Y	4.89	67.43	16.80		150.0	
		Z	5.17	67.92	17.51		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.26	66.11	17.07	0.46	130.0	± 9.6 %
		Y	1.14	63.86	15.15		130.0	
		Z	1.28	67.12	18.23		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.29	66.92	17.55	0.46	130.0	± 9.6 %
		Y	1.15	64.34	15.47		130.0	
		Z	1.31	68.09	18.81		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	100.00	155.25	42.39	0.46	130.0	± 9.6 %
		Y	1.23	77.62	20.43		130.0	
		Z	100.00	169.07	48.13		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.74	76.95	22.36	0.46	130.0	± 9.6 %
		Y	1.18	68.91	17.90		130.0	
		Z	2.01	81.76	25.27		130.0	

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.84	66.74	16.72	0.46	130.0	± 9.6 %
		Y	4.58	66.55	16.30		130.0	
		Z	4.83	66.98	17.03		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.87	66.92	16.80	0.46	130.0	± 9.6 %
		Y	4.61	66.72	16.37		130.0	
		Z	4.86	67.16	17.11		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	5.11	67.27	16.98	0.46	130.0	± 9.6 %
		Y	4.80	66.99	16.53		130.0	
		Z	5.10	67.50	17.29		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	5.01	67.48	17.11	0.46	130.0	± 9.6 %
		Y	4.70	67.13	16.62		130.0	
		Z	5.00	67.72	17.43		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.77	66.76	16.41	0.46	130.0	± 9.6 %
		Y	4.46	66.41	15.94		130.0	
		Z	4.75	66.97	16.71		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.81	66.70	16.38	0.46	130.0	± 9.6 %
		Y	4.51	66.47	15.97		130.0	
		Z	4.79	66.95	16.70		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.91	67.56	17.06	0.46	130.0	± 9.6 %
		Y	4.59	67.16	16.57		130.0	
		Z	4.90	67.80	17.39		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.72	66.48	16.18	0.46	130.0	± 9.6 %
		Y	4.40	66.18	15.74		130.0	
		Z	4.70	66.70	16.49		130.0	
10583-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.84	66.74	16.72	0.46	130.0	± 9.6 %
		Y	4.58	66.55	16.30		130.0	
		Z	4.83	66.98	17.03		130.0	
10584-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.87	66.92	16.80	0.46	130.0	± 9.6 %
		Y	4.61	66.72	16.37		130.0	
		Z	4.86	67.16	17.11		130.0	
10585-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	5.11	67.27	16.98	0.46	130.0	± 9.6 %
		Y	4.80	66.99	16.53		130.0	
		Z	5.10	67.50	17.29		130.0	
10586-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	5.01	67.48	17.11	0.46	130.0	± 9.6 %
		Y	4.70	67.13	16.62		130.0	
		Z	5.00	67.72	17.43		130.0	
10587-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.77	66.76	16.41	0.46	130.0	± 9.6 %
		Y	4.46	66.41	15.94		130.0	
		Z	4.75	66.97	16.71		130.0	
10588-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.81	66.70	16.38	0.46	130.0	± 9.6 %
		Y	4.51	66.47	15.97		130.0	
		Z	4.79	66.95	16.70		130.0	
10589-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.91	67.56	17.06	0.46	130.0	± 9.6 %
		Y	4.59	67.16	16.57		130.0	
		Z	4.90	67.80	17.39		130.0	
10590-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.72	66.48	16.18	0.46	130.0	± 9.6 %
		Y	4.40	66.18	15.74		130.0	
		Z	4.70	66.70	16.49		130.0	

10591-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.99	66.80	16.82	0.46	130.0	± 9.6 %
		Y	4.74	66.62	16.41		130.0	
		Z	4.98	67.02	17.11		130.0	
10592-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	5.17	67.16	16.94	0.46	130.0	± 9.6 %
		Y	4.88	66.94	16.54		130.0	
		Z	5.16	67.39	17.24		130.0	
10593-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	5.10	67.12	16.85	0.46	130.0	± 9.6 %
		Y	4.80	66.84	16.41		130.0	
		Z	5.09	67.33	17.15		130.0	
10594-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	5.15	67.27	16.99	0.46	130.0	± 9.6 %
		Y	4.85	67.00	16.57		130.0	
		Z	5.14	67.49	17.30		130.0	
10595-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	5.13	67.24	16.90	0.46	130.0	± 9.6 %
		Y	4.82	66.96	16.47		130.0	
		Z	5.11	67.46	17.20		130.0	
10596-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	5.06	67.22	16.89	0.46	130.0	± 9.6 %
		Y	4.75	66.95	16.47		130.0	
		Z	5.05	67.46	17.20		130.0	
10597-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	5.01	67.17	16.80	0.46	130.0	± 9.6 %
		Y	4.70	66.84	16.34		130.0	
		Z	5.00	67.39	17.11		130.0	
10598-AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	5.00	67.47	17.10	0.46	130.0	± 9.6 %
		Y	4.69	67.05	16.59		130.0	
		Z	4.99	67.69	17.41		130.0	
10599-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.66	67.41	16.99	0.46	130.0	± 9.6 %
		Y	5.39	67.09	16.60		130.0	
		Z	5.67	67.62	17.29		130.0	
10600-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.89	68.08	17.29	0.46	130.0	± 9.6 %
		Y	5.50	67.45	16.76		130.0	
		Z	5.90	68.31	17.60		130.0	
10601-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.73	67.68	17.10	0.46	130.0	± 9.6 %
		Y	5.41	67.26	16.68		130.0	
		Z	5.73	67.90	17.41		130.0	
10602-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.82	67.68	17.02	0.46	130.0	± 9.6 %
		Y	5.53	67.38	16.66		130.0	
		Z	5.81	67.85	17.30		130.0	
10603-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.94	68.10	17.36	0.46	130.0	± 9.6 %
		Y	5.58	67.60	16.90		130.0	
		Z	5.90	68.16	17.58		130.0	
10604-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.67	67.39	17.00	0.46	130.0	± 9.6 %
		Y	5.45	67.23	16.70		130.0	
		Z	5.67	67.57	17.29		130.0	
10605-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.78	67.67	17.13	0.46	130.0	± 9.6 %
		Y	5.51	67.41	16.79		130.0	
		Z	5.80	67.92	17.45		130.0	
10606-AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.55	67.14	16.74	0.46	130.0	± 9.6 %
		Y	5.26	66.74	16.32		130.0	
		Z	5.54	67.28	17.00		130.0	

10607-AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.83	66.14	16.45	0.46	130.0	± 9.6 %
		Y	4.58	65.94	16.04		130.0	
		Z	4.83	66.41	16.78		130.0	
10608-AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	5.05	66.59	16.62	0.46	130.0	± 9.6 %
		Y	4.75	66.32	16.20		130.0	
		Z	5.05	66.86	16.95		130.0	
10609-AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.94	66.46	16.48	0.46	130.0	± 9.6 %
		Y	4.64	66.17	16.03		130.0	
		Z	4.94	66.73	16.81		130.0	
10610-AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.99	66.63	16.64	0.46	130.0	± 9.6 %
		Y	4.69	66.32	16.19		130.0	
		Z	4.99	66.91	16.97		130.0	
10611-AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.92	66.46	16.50	0.46	130.0	± 9.6 %
		Y	4.60	66.12	16.04		130.0	
		Z	4.91	66.72	16.83		130.0	
10612-AAA	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.93	66.59	16.52	0.46	130.0	± 9.6 %
		Y	4.61	66.27	16.08		130.0	
		Z	4.93	66.89	16.87		130.0	
10613-AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.94	66.52	16.43	0.46	130.0	± 9.6 %
		Y	4.61	66.14	15.96		130.0	
		Z	4.94	66.79	16.76		130.0	
10614-AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.88	66.76	16.70	0.46	130.0	± 9.6 %
		Y	4.56	66.32	16.18		130.0	
		Z	4.88	67.02	17.03		130.0	
10615-AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.91	66.23	16.24	0.46	130.0	± 9.6 %
		Y	4.60	65.97	15.82		130.0	
		Z	4.91	66.50	16.57		130.0	
10616-AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.49	66.72	16.63	0.46	130.0	± 9.6 %
		Y	5.22	66.38	16.23		130.0	
		Z	5.50	66.93	16.93		130.0	
10617-AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.55	66.83	16.65	0.46	130.0	± 9.6 %
		Y	5.28	66.55	16.29		130.0	
		Z	5.56	67.04	16.95		130.0	
10618-AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.45	66.92	16.72	0.46	130.0	± 9.6 %
		Y	5.17	66.56	16.31		130.0	
		Z	5.46	67.15	17.03		130.0	
10619-AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.46	66.70	16.54	0.46	130.0	± 9.6 %
		Y	5.18	66.36	16.15		130.0	
		Z	5.48	66.94	16.86		130.0	
10620-AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.59	66.83	16.65	0.46	130.0	± 9.6 %
		Y	5.27	66.40	16.21		130.0	
		Z	5.59	67.03	16.95		130.0	
10621-AAA	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.57	66.92	16.82	0.46	130.0	± 9.6 %
		Y	5.28	66.53	16.40		130.0	
		Z	5.57	67.09	17.10		130.0	
10622-AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.56	67.02	16.86	0.46	130.0	± 9.6 %
		Y	5.29	66.70	16.48		130.0	
		Z	5.58	67.26	17.18		130.0	

10623-AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	5.45	66.61	16.54	0.46	130.0	± 9.6 %
		Y	5.17	66.23	16.12		130.0	
		Z	5.45	66.76	16.80		130.0	
10624-AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.63	66.74	16.66	0.46	130.0	± 9.6 %
		Y	5.36	66.43	16.28		130.0	
		Z	5.65	66.97	16.97		130.0	
10625-AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	6.03	67.75	17.21	0.46	130.0	± 9.6 %
		Y	5.64	67.15	16.69		130.0	
		Z	6.14	68.26	17.65		130.0	
10626-AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.74	66.74	16.55	0.46	130.0	± 9.6 %
		Y	5.53	66.45	16.20		130.0	
		Z	5.76	66.91	16.83		130.0	
10627-AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	6.00	67.29	16.77	0.46	130.0	± 9.6 %
		Y	5.75	66.97	16.42		130.0	
		Z	6.06	67.58	17.12		130.0	
10628-AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.81	66.92	16.53	0.46	130.0	± 9.6 %
		Y	5.54	66.50	16.12		130.0	
		Z	5.83	67.10	16.81		130.0	
10629-AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.91	67.00	16.56	0.46	130.0	± 9.6 %
		Y	5.62	66.56	16.15		130.0	
		Z	5.92	67.15	16.83		130.0	
10630-AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	6.49	68.87	17.48	0.46	130.0	± 9.6 %
		Y	5.94	67.73	16.74		130.0	
		Z	6.64	69.43	17.95		130.0	
10631-AAA	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	6.36	68.62	17.56	0.46	130.0	± 9.6 %
		Y	5.90	67.70	16.90		130.0	
		Z	6.40	68.89	17.89		130.0	
10632-AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.99	67.43	16.99	0.46	130.0	± 9.6 %
		Y	5.72	67.04	16.59		130.0	
		Z	6.02	67.63	17.28		130.0	
10633-AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.93	67.24	16.72	0.46	130.0	± 9.6 %
		Y	5.61	66.69	16.25		130.0	
		Z	5.92	67.32	16.95		130.0	
10634-AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.91	67.22	16.78	0.46	130.0	± 9.6 %
		Y	5.60	66.71	16.32		130.0	
		Z	5.89	67.30	17.01		130.0	
10635-AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.77	66.46	16.12	0.46	130.0	± 9.6 %
		Y	5.48	66.06	15.73		130.0	
		Z	5.76	66.58	16.37		130.0	
10636-AAA	IEEE 1602.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	6.15	67.13	16.64	0.46	130.0	± 9.6 %
		Y	5.94	66.81	16.29		130.0	
		Z	6.19	67.31	16.92		130.0	
10637-AAA	IEEE 1602.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.33	67.56	16.83	0.46	130.0	± 9.6 %
		Y	6.08	67.17	16.45		130.0	
		Z	6.37	67.74	17.11		130.0	
10638-AAA	IEEE 1602.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.32	67.49	16.77	0.46	130.0	± 9.6 %
		Y	6.09	67.16	16.42		130.0	
		Z	6.37	67.71	17.07		130.0	

10639-AAA	IEEE 1602.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	6.33	67.54	16.85	0.46	130.0	± 9.6 %
		Y	6.06	67.09	16.43		130.0	
		Z	6.36	67.69	17.11		130.0	
10640-AAA	IEEE 1602.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	6.36	67.62	16.82	0.46	130.0	± 9.6 %
		Y	6.06	67.09	16.38		130.0	
		Z	6.39	67.78	17.09		130.0	
10641-AAA	IEEE 1602.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.35	67.32	16.69	0.46	130.0	± 9.6 %
		Y	6.12	67.03	16.36		130.0	
		Z	6.37	67.48	16.96		130.0	
10642-AAA	IEEE 1602.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.43	67.70	17.06	0.46	130.0	± 9.6 %
		Y	6.15	67.26	16.64		130.0	
		Z	6.44	67.83	17.30		130.0	
10643-AAA	IEEE 1602.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	6.25	67.35	16.78	0.46	130.0	± 9.6 %
		Y	5.99	66.96	16.39		130.0	
		Z	6.27	67.50	17.04		130.0	
10644-AAA	IEEE 1602.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	6.50	68.09	17.17	0.46	130.0	± 9.6 %
		Y	6.12	67.35	16.61		130.0	
		Z	6.53	68.27	17.44		130.0	
10645-AAA	IEEE 1602.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.79	68.49	17.30	0.46	130.0	± 9.6 %
		Y	6.27	67.44	16.61		130.0	
		Z	6.99	69.13	17.81		130.0	

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)



Client

Auden

Certificate No: Z15-97104

CALIBRATION CERTIFICATE

Object

ES3DV3 - SN:3071

Calibration Procedure(s)

FD-Z11-2-004-01

Calibration Procedures for Dosimetric E-field Probes

Calibration date:

September 28, 2015

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22 ± 3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	01-Jul-15 (CTTL, No.J15X04256)	Jun-16
Power sensor NRP-Z91	101547	01-Jul-15 (CTTL, No.J15X04256)	Jun-16
Power sensor NRP-Z91	101548	01-Jul-15 (CTTL, No.J15X04256)	Jun-16
Reference10dBAttenuator	18N50W-10dB	13-Mar-14(TMC,No.JZ14-1103)	Mar-16
Reference20dBAttenuator	18N50W-20dB	13-Mar-14(TMC,No.JZ14-1104)	Mar-16
Reference Probe EX3DV4	SN 7307	27-Feb-15(SPEAG,No.EX3-7307_Feb15)	Feb-16
DAE4	SN 771	27-Jan-15(SPEAG, No.DAE4-771_Jan15)	Jan -16
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGeneratorMG3700A	6201052605	01-Jul-15 (CTTL, No.J15X04255)	Jun-16
Network Analyzer E5071C	MY46110673	03-Feb-15 (CTTL, No.J15X00728)	Feb-16

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Qi Dianyuan	SAR Project Leader	
Approved by:	Lu Bingsong	Deputy Director of the laboratory	

Issued: September 30, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: ctl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A,B,C,D	modulation dependent linearization parameters
Polarization Φ	Φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i $\theta=0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}:** Assessed for E-field polarization $\theta=0$ ($f \leq 900\text{MHz}$ in TEM-cell; $f > 1800\text{MHz}$: waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}:** DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}; A,B,C** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800\text{MHz}$) and inside waveguide using analytical field distributions based on power measurements for $f > 800\text{MHz}$. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from $\pm 50\text{MHz}$ to $\pm 100\text{MHz}$.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle:** The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN: 3071

Calibrated: September 28, 2015

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)