



Maximum Permissible Exposure (MPE) Estimation for E169/E169G

1 Introduction

HUAWEI E169/E169G HSDPA/UMTS/EDGE/GPRS/GSM dual mode 4 BAND USB Stick is subscriber equipment in the UMTS/GSM system. The WCDMA frequency is Band I and Band VIII. The GSM/GPRS/EDGE frequency band includes GSM850, EGSM900, DCS1800 and PCS1900, E169/E169G implements such functions as RF signal receiving/transmitting, HSDPA/WCDMA and EDGE/GPRS/GSM protocol processing, data service etc. Externally it provides USB interface (to connect to the notebook etc.), USIM card interface and antenna interface. E169/E169G has an internal antenna as default.

E169G is the USB stick which changes some component from E169.

The PCB and antenna are the same.

The differences between E169 and E169G are:

1. E169 support WCDMA band 8. E169G do not support and clear the WCDMA 900M component on the PCB.
2. E169 supports TF card and external antenna. E169G do not supports the external interface and the TF interface.

There are 3 kind of external color for both of them. They are silver, white and black.

2 Limits and Guidelines on Exposure to Electromagnetic Fields

According to the FCC Part 2.1091, we know: mobile device (transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitters radiating structure(s) and the body of the user or nearby persons). And the Cellular radiotelephone service and PCS services are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if they operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more. The radiated power of 850M/1900M for E169/E169G is 2W/1W, so for E169/E169G only the 850M band is need to be subjected to routine the environmental evaluation for RF exposure.

Uncontrolled limits are used for general public. General population/uncontrolled exposure apply in situations is which the general public may be exposed, or in which persons that



are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure. The exposure levels can be expressed in terms of power density, electric field strength, or magnetic field strength, as averaged over 30 minutes for the general public and 6 minutes for trained personnel. The exposure criterion is frequency dependent, and a chart covering the range from 3 kHz to 100 GHz can be found in NCRP No.86 (references IEEE C95.1-1999).

Below are the limits.

| Limits for Occupational/Controlled Exposure | | | |
|--|--|--|--|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm²) |
| 0.003-0.1 | 614 | 163 | (100)* |
| 0.1-3.0 | 614 | 16.3/f | (100)* |
| 3.0-30 | 1842/f | 16.3/f | (900/f ²)* |
| 30-100 | 61.4 | 16.3/f | 1.0 |
| 100-300 | 61.4 | 0.163 | 1.0 |
| 300-3000 | -- | -- | f/300 |
| 3000-15,000 | -- | -- | 10 |
| 15,000-100,000 | -- | -- | 10 |

| Limits for General Population/Uncontrolled Exposure | | | |
|--|--|--|--|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm²) |
| 0.003-0.1 | 614 | 163 | (100)* |
| 0.1-1.34 | 614 | 16.3/f | (100)* |
| 1.34-3.0 | 823.8/f | 16.3/f | (180/f ²)* |
| 3.0-30 | 823.8/f | 16.3/f | ((180/f ²))* |
| 30-100 | 27.5 | 158.3 / f1.668 | 0.2 |
| 100-300 | 27.5 | 0.0729 | 0.2 |
| 300-3000 | -- | -- | f/1500 |
| 3000-15,000 | -- | -- | f/1500 |
| 15,000-100,000 | -- | -- | 10 |

Power density S [mW/cm²] for controlled area at 850 MHz , (TX: 824MHz – 849MHz)

$$S = \frac{f(\text{MHz})}{300} = \frac{824}{300} = 2.75 \text{ mW/cm}^2$$

Power density S [mW/cm²] for uncontrolled area at 850 MHz



$$S = \frac{f(MHz)}{1500} = \frac{824}{1500} = 0.55 \text{ mW/cm}^2$$

$$S = 0.55 \text{ mW/cm}^2 = 5.5 \text{ W/m}^2 \text{ for uncontrolled exposure}$$

Reference levels are provided for exposure assessment to determine whether the basic restrictions on exposure of humans to electromagnetic fields are exceeded. The basic restrictions on exposure to electromagnetic fields are based directly on established health effects and biological considerations.

3 Location of EUT

The EUT uses one monopole antenna. The source of the radiation is mounted on terminal; generally the direction of the antenna position is uprightness tabletop. The highest level of emission would be expected in close vicinity of the antenna and in line of sight to the antenna.

4 Prediction of the Exposure to Electromagnetic Fields

Calculations can be made on a site by site basis to ensure the power density is below the limits given above, or guidelines can be done beforehand to ensure the minimum distances from the antenna is maintained through the site planning. The calculations are based on FCC OET 65 Appendix B.

4.1 Calculation of the Safe Distance

Below method describes a theoretical approach to calculate possible exposure to electromagnetic radiation around a base station transceiver antenna. Precise statements are basically only possible either with measurements or complex calculations considering the complexity of the environment (e.g. soil conditions, near buildings and other obstacles) which causes reflections, scattering of electromagnetic fields.

The maximum output power (given in EIRP) of a base station is usually limited by license conditions of the network operator.

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation. The calculations are based on FCC OET 65 Appendix B.

$$S = \frac{P(W) * G_{numeric}}{4 * r^2(m) * \pi}$$

Whereas:



P = Maximum output power in W of the site

G numeric = Numeric gain of the antenna relative to isotropic antenna

R = distance between the antenna and the point of exposure in meters

4.2 Technical Description E169/E169G

Technical Specification:

| | |
|-----------------------------------|--|
| Output power: | 2W (33 dBm) for GSM850MHz |
| Transmitter frequency band | GSM850 |
| Number of antenna ports: | 1 |
| Frequency range: | 850M : Uplink:824 M~849M ; Downlink:869 M~894M |
| Gain: | <1dBi (GSM850) |
| Mechanical specification (Height) | 19.2mm for GSM850 |

4.3 Estimation of compliance boundary for indoor antenna

GSM 850M:

For the final determination of the compliance boundary the model for far-field calculation is used since this overestimates the field strength in the near-field region. Thus the calculated compliance boundary should be rather more conservative and on the safe side.

For EUT the following compliance boundary is calculated:

Power at antenna connector BTS: **32.54 dBm**

Antenna-cable attenuation: **0 dB**

Input power to antenna: **32.54 dBm (1.76W)**

Antenna gain: **1 dBi (1.26)**

Compliance boundary

For GSM 850MHz band:

When r=20cm

$$S = \frac{P(W) * G_{numeric}}{4 * r^2(m) * \pi}$$



$$S = \frac{1.76 * 1.26}{4 * 0.2^2 * \pi} = 4.41 \text{ W/m}^2 < 5.5 \text{ W/m}^2$$

The S at the position which is 20cm far from the EUT is smaller than the uncontrolled exposure limit line. So the EUT also complies with the Limits for Occupational/Controlled Exposure.