



# FCC Test Report

**Product Name: HSPA+ USB Stick**

**Model Number: E353s-6**

**Report No: SYBH(Z-RF)011052011-2002**  
**FCC ID: QISE353S-6**

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

## Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



|                  |                               |
|------------------|-------------------------------|
| REGULATION       | FCC CFR47 Part 2: Subpart J;  |
|                  | FCC CFR47 Part 24: Subpart E; |
|                  |                               |
|                  |                               |
|                  |                               |
|                  |                               |
|                  |                               |
|                  |                               |
| START OF TEST    | APr.26, 2011                  |
| END OF TEST      | Apr.29, 2011                  |
|                  |                               |
| Final Judgement: | Pass                          |

Approved By      May.06, 2011      Chenxiaohong      Chen Xiaohong  
Date      Name      Signature

Reviewed By      May.06, 2011      Xuguangyi      Xuguangyi  
Date      Name      Signature

Operator      May.06, 2011      Zhangting      Zhang Ting  
Date      Name      Signature



## Contents

|          |                                                              |           |
|----------|--------------------------------------------------------------|-----------|
| <b>1</b> | <b><u>Summary</u></b>                                        | <b>5</b>  |
| <b>2</b> | <b><u>Product Description</u></b>                            | <b>6</b>  |
| 2.1      | PRODUCTION INFORMATION                                       | 6         |
| 2.2      | MODIFICATION INFORMATION                                     | 6         |
| <b>3</b> | <b><u>Test Site Description</u></b>                          | <b>7</b>  |
| 3.1      | TESTING PERIOD                                               | 7         |
| 3.2      | GENERAL SET UP DESCRIPTION                                   | 7         |
| <b>4</b> | <b><u>Product Description</u></b>                            | <b>8</b>  |
| 4.1      | TECHNICAL CHARACTERISTICS                                    | 8         |
| 4.2      | EUT IDENTIFICATION LIST                                      | 10        |
| <b>5</b> | <b><u>Main Test Instruments</u></b>                          | <b>11</b> |
| <b>6</b> | <b><u>Transmitter Measurements</u></b>                       | <b>12</b> |
| 6.1      | EFFECTIVE ISOTROPICALLY RADIATED POWER OF TRANSMITTER (EIRP) | 12        |
| 6.2      | CONDUCTED POWER OF TRANSMITTER                               | 17        |
| 6.3      | MODULATION CHARACTERISTICS                                   | 19        |
| 6.4      | OCCUPIED BANDWIDTH                                           | 21        |
| 6.5      | BAND EDGES COMPLIANCE                                        | 24        |
| 6.6      | SPURIOUS EMISSION AT ANTENNA TERMINAL                        | 26        |
| 6.7      | FREQUENCY STABILITY                                          | 29        |
| <b>7</b> | <b><u>System Measurement Uncertainty</u></b>                 | <b>33</b> |
| <b>8</b> | <b><u>Appendices</u></b>                                     | <b>34</b> |

## 1 Summary

The table below summarizes the measurements and results for the EUT. Detailed results and descriptions are shown in the following pages.

Table 1 Summary of results

| FCC Measurement Specification | FCC Limits Part(s) | Description                             | Result     |
|-------------------------------|--------------------|-----------------------------------------|------------|
| 2.1046                        | 24.232             | Effective Radiated Power of Transmitter | PASS       |
| 2.1046                        | 24.232             | Conducted Power of Transmitter          | PASS       |
| 2.1047                        | /                  | Modulation Characteristics              | PASS       |
| 2.1049                        | /                  | Occupied Bandwidth                      | PASS       |
| 2.1051                        | 24.238             | Band Edges Compliance                   | PASS       |
| 2.1051                        | 24.238             | Spurious Emission at Antenna Terminal   | PASS       |
| 2.1055                        | 24.235             | Frequency Stability                     | PASS       |
| 2.1053                        | 24.238             | Radiated Spurious Emissions             | (See Note) |

Note: The Radiated Spurious Emissions' test results are shown in the EMC report.



## 2 Product Description

### 2.1 Production Information

#### 2.1.1 General Description

E353s-6 HSPA+/WCDMA/EDGE/GPRS/GSM dual mode USB Stick is subscriber equipment in the UMTS/GSM system. E353s-6 implement such functions as RF signal receiving/transmitting, HSPA+/WCDMA and EDGE/GPRS/GSM protocol processing, data service etc. Externally it provides USB interface (to connect to the notebook etc.), USIM card interface and Micro SD card interface. E353s-6 has an internal antenna as default.

**Note: Only tests for WCDMA Band II and GSM/GPRS/EDGE 1900MHz (PCS) band were included in this report for the requirement of FCC part 2 & 24.**

#### 2.1.2 Support function and Service

The EUT support the function and service as follows:

Table 2 Service and Test mode List

| Service Name   | Characteristic   | Corresponding Test Mode | Note     |
|----------------|------------------|-------------------------|----------|
| Voice and data | Modulation: GMSK | TM1                     | GPRS/GSM |
| Data           | Modulation: 8PSK | TM2                     | EDGE     |
| Data           | Modulation: QPSK | TM3                     | WCDMA    |
| Data           | Modulation: QPSK | TM4                     | HSDPA    |
| Data           | Modulation: QPSK | TM5                     | HSUPA    |

Note: \* The specified GPRS test conditions & settings are defined in 3GPP TS51.010 V5.4.0 and the EDGE test conditions & settings are defined in 3GPP TS51.010 V5.4.0.  
The specified WCDMA test conditions & settings are defined in 3GPP TS 34.121 V7.3.0.

### 2.2 Modification Information

For original equipment, following table is not application.

Table 3 Modification Information

| Model Number   | Board/Module | Original Version | New Version | Modify Information |
|----------------|--------------|------------------|-------------|--------------------|
| Not applicable |              |                  |             |                    |
|                |              |                  |             |                    |
|                |              |                  |             |                    |

### **3 Test Site Description**

The test site of:

***Huawei Technologies Co. Ltd.  
P.O. Box 518129  
Huawei base, Bantian,  
Longgang District, Shenzhen, China***

#### **3.1 Testing Period**

The test have been performed during the period of

**Apr.26, 2011 – Apr.29, 2011**

#### **3.2 General Set up Description**

**TM1:** GPRS/GSM Mode with GMSK Modulation

**TM2:** EDGE Mode with 8PSK Modulation

**TM3:** WCDMA Mode with QPSK Modulation

**TM4:** HSDPA Mode with QPSK Modulation

**TM5:** HSUPA Mode with QPSK Modulation

## 4 Product Description

### 4.1 Technical Characteristics

#### 4.1.1 Frequency Range

Table 4 Frequency Range

|                |                  |
|----------------|------------------|
| Uplink band:   | 1850 to 1910 MHz |
| Downlink band: | 1930 to 1990 MHz |

#### 4.1.2 Channel Spacing / Separation

Table 5 Channel Spacing / Separation

|                  | EDGE/GPRS/GSM | UMTS/HSPA |
|------------------|---------------|-----------|
| Channel Raster   | 200 kHz       | 200 kHz   |
| Channel spacing: | 200 kHz       | 5 MHz     |

#### 4.1.3 Type of Emission

Table 6 Type of Emission

|                       | GPRS/GSM | EDGE    | UMTS/HSPA |
|-----------------------|----------|---------|-----------|
| Emission Designation: | 300kGXW  | 300KG7W | 5M00F9W   |

According to CFR 47 (FCC) part 2, subpart C, section 2.201 and 2.202

#### 4.1.4 Environmental Requirements

Table 7 Environmental Requirements

|                      |          |
|----------------------|----------|
| Minimum temperature: | - 10 °C  |
| Maximum temperature: | + 55 °C  |
| Relative Humidity:   | 5%-95%RH |

#### 4.1.5 Power Source

Table 8 Power Source

|                     |                    |
|---------------------|--------------------|
| AC voltage nominal: | ~ 120 V            |
| AC voltage range    | ~ 100 V to ~ 240 V |
| AC current maximal: | 650mA              |

#### 4.1.6 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (9).

Please reference the document Tune-up Procedure in TCF.

#### 4.1.7 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8).

The voltage and current in the final RF stage is:

Table 9 Applied DC Voltages and Currents

|          |                                                                       |
|----------|-----------------------------------------------------------------------|
| Voltage: | == +2.8V                                                              |
| Current: | 100mA According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8) |



## 4.2 EUT Identification List

### 4.2.1 Board Information

Table 10 Board Information

|                  |              |  |
|------------------|--------------|--|
| HSPA+ USB Stick  |              |  |
| E353s-6          |              |  |
| Board and Module |              |  |
| Serial number    | IMEI         |  |
| G3N2A11141200097 | 357260011271 |  |

### 4.2.2 FCC Identification

Grantee Code: QIS  
Product Code: E353S-6  
FCC Identification: QISE353S-6

## 5 Main Test Instruments

Table 11 Main Test Equipments

| Equipment Description                | Manufacturer | Model                   | Serial Number | Calibrated until |
|--------------------------------------|--------------|-------------------------|---------------|------------------|
| Power supply                         | KEITHLEY     | 2303                    | 1288003       | Sep.27,2011      |
| Universal Radio Communication Tester | R&S          | CMU200                  | 105822        | Oct.24.2011      |
| Universal Radio Communication Tester | Agilent      | E5515C                  | MY50260239    | Aug.04,2011      |
| Spectrum Analyzer                    | Agilent      | E4440A                  | MY49420179    | Apr.24,2012      |
| Signal Analyzer                      | R&S          | FSQ31                   | 200021        | Sep.27,2011      |
| Temperature Chamber                  | ESPEC        | MW3030                  | 611403        | May.12,2011      |
| Signal Generator                     | R&S          | SMR40                   | 100325        | May.12,2011      |
| Vector Signal Generator              | R&S          | SMU200A                 | 104162        | Sep.07,2011      |
| Spectrum Analyzer                    | R&S          | FSU26                   | EG26725       | Mar.07,2012      |
| Tunable Dipole                       | Schwarzbeck  | D69250-UHAP/D69250-VHAP | 919/1009      | Dec.13.2011      |
| Tunable Dipole                       | Schwarzbeck  | D69250-UHAP/D69250-VHAP | 979/917       | Dec.13.2011      |
| Horn Antenna                         | R & S        | HF906                   | 359287/005    | May.07, 2011     |
| Horn Antenna                         | R & S        | HF906                   | 359287/006    | April.27, 2012   |
| Broadband Antenna                    | SCHAFFNER    | CBL 6112B               | 2536          | Sep.21, 2011     |
| Broadband Antenna                    | SCHAFFNER    | CBL 6112B               | 2941          | Jun.11, 2011     |
| Horn Antenna                         | ETS-LINDGREN | 3160                    | 60008         | Sep.20.2011      |
| Horn Antenna                         | ETS-LINDGREN | 3160                    | 60006         | Oct.27.2011      |
| Test receiver                        | R&S          | ESU26                   | 36090302083   | Jun.24.2011      |

## 6 Transmitter Measurements

### 6.1 Effective Isotropically Radiated Power of Transmitter (EIRP)

#### 6.1.1 Test Conditions

Table 12 Test Conditions

|                      |                                                    |
|----------------------|----------------------------------------------------|
| Preconditioning:     | 0.5 hour                                           |
| Measured at:         | enclosure                                          |
| Ambient temperature: | 25 °C                                              |
| Relative humidity:   | 55%                                                |
| Test Configurations: | TM1/TM2/TM3/TM4/TM5 at frequency Bottom,Middle,Top |

#### 6.1.2 Test Specifications and Limits

##### 6.1.2.1 Specification

CFR 47 (FCC) part 2.1046 and part 24.232

##### 6.1.2.2 Supporting Standards

Table 13 Supporting Standards:

|                       |                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI/TIA-603-C:2004   | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards                                                             |
| 3GPP TS51.010 V5.4.0  | Digital cellular telecommunications system;<br>Mobile Station (MS) conformance specification;                                                   |
| 3GPP TS 34.121 V7.3.0 | Universal Mobile Telecommunications System (UMTS);<br>User Equipment (UE) conformance specification;<br>Radio transmission and reception (FDD); |

##### 6.1.2.3 Limits

Compliance with part 24.232, in no any case may the peak power of a mobile station transmitter exceed 2 W. And calculate longitude EIRP by following formula: $EIRP(dBm) = 10 \cdot \log(EIRP \text{ in mwatts})$ .  
 $EIRP(dBm) = ERP(dBm) + 2.15dB$ .

Table 14 Limits

|                              |           |
|------------------------------|-----------|
| Maximum Output Power (Watts) | < 2 Watts |
| Maximum Output Power (dBm)   | < 33 dBm  |


#### 6.1.3 Test Method and Setup

- For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, EIRP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the wireless communication tester CMU200 via the air interface. The band is set as PCS1900M and WCDMA1900.
- Test the Radiated maximum output power by the CMU200 received from test antenna.

- (c) Use substitution method to verify the maximum output power. The EUT is substituted by a horn antenna. The horn is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step (b) on CMU200, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.

## Test setup

### Step 1: Pre-test



### Step 2: Substitution method to verify the maximum EIRP




Figure 1. Test Set-up

NOTE: Effective Isotropic radiated power (EIRP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave horn antennas.  
There is a constant difference of 2.15 dB between EIRP and ERP.  
 $EIRP (dBm) = ERP (dBm) + 2.15$  (ITU-R Recommendation SM.329-10).  
EIRP was measured using 1 host.

## 6.1.4 Measurement Results

### 6.1.4.1 Pre-test Results

For HSDPA test mode, there are 4 sub-test for different configuration. For the sub-test 1, The channel is Middle range.

| Sub-test | c     | d     | d (SF) | c/d   | HS (Note1, Note 2) | CM (dB) (Note 3) | MPR (dB) (Note 3) | Test result |
|----------|-------|-------|--------|-------|--------------------|------------------|-------------------|-------------|
| 1        | 2/15  | 15/15 | 64     | 2/15  | 4/15               | 0.0              | 0.0               | 22.15       |
| 2        | 12/15 | 15/15 | 64     | 12/15 | 24/15              | 1.0              | 0.0               | 21.42       |
| 3        | 15/15 | 8/15  | 64     | 15/8  | 30/15              | 1.5              | 0.5               | 21.34       |
| 4        | 15/15 | 4/15  | 64     | 15/4  | 30/15              | 1.5              | 0.5               | 21.40       |

For the following test, the TM4 was used for HSDPA.

For HSUPA test mode, there are 5 sub-test for different configuration. For the sub-test 1, The channel is Middle range.

| Sub-test | $\beta c/\beta d$ | $\beta HS$ | $\beta ec$ | $\beta ed$         | $\beta ed$ (SF) | $\beta ed$ (Codes) | CM (dB) | MPR (dB) | Test result |
|----------|-------------------|------------|------------|--------------------|-----------------|--------------------|---------|----------|-------------|
| 1        | 11/15             | 16/15      | 16/15      | 448/75             | 4               | 1                  | 1.0     | 0.0      | 21.41       |
| 2        | 6/15              | 12/15      | 12/15      | 94/75              | 4               | 1                  | 3.0     | 2.0      | 19.51       |
| 3        | 15/9              | 30/15      | 30/15      | $\beta ed1: 47/15$ | 4               | 2                  | 2.0     | 1.0      | 20.42       |
| 4        | 2/15              | 2/15       | 2/15       | 56/75              | 4               | 1                  | 3.0     | 2.0      | 19.82       |
| 5        | 15/15             | 24/15      | 24/15      | 224/25             | 4               | 1                  | 1.0     | 0.0      | 21.41       |

For the following test, the TM5 was used for HSUPA.

Table 15 Measurement Results

|                 |                          | RF Output Power (EIRP)      |       |                           |       |                             |       |
|-----------------|--------------------------|-----------------------------|-------|---------------------------|-------|-----------------------------|-------|
| TEST CONDITIONS |                          | Channel512(B)<br>1850.2MHz  |       | Channel661 (M)<br>1880MHz |       | Channel810(T)<br>1909.8MHz  |       |
|                 |                          | dBm                         |       | dBm                       |       | dBm                         |       |
|                 |                          | Measured                    | Limit | Measured                  | Limit | Measured                    | Limit |
| TM1             | T <sub>nom</sub> (25 °C) | 30.68                       | 33    | 30.76                     | 33    | 30.79                       | 33    |
|                 | V <sub>nom</sub> (3.7V)  |                             |       |                           |       |                             |       |
| TM2             | T <sub>nom</sub> (25 °C) | 26.25                       | 33    | 26.38                     | 33    | 26.39                       | 33    |
|                 | V <sub>nom</sub> (3.7V)  |                             |       |                           |       |                             |       |
|                 |                          |                             |       |                           |       |                             |       |
| TEST CONDITIONS |                          | Channel9262(B)<br>1852.4MHz |       | Channel9400(M)<br>1880MHz |       | Channel9538(T)<br>1907.6MHz |       |

|     |                                                     | dBm      |       | dBm      |       | dBm      |       |
|-----|-----------------------------------------------------|----------|-------|----------|-------|----------|-------|
|     |                                                     | Measured | Limit | Measured | Limit | Measured | Limit |
| TM3 | T <sub>nom</sub> (25 °C)<br>V <sub>nom</sub> (3.7V) | 23.82    | 33    | 23.69    | 33    | 23.52    | 33    |
| TM4 | T <sub>nom</sub> (25 °C)<br>V <sub>nom</sub> (3.7V) | 23.74    | 33    | 23.65    | 33    | 23.33    | 33    |
| TM5 | T <sub>nom</sub> (25 °C)<br>V <sub>nom</sub> (3.7V) | 22.80    | 33    | 22.96    | 33    | 22.87    | 33    |

#### 6.1.4.2 Substitution Results

Table 16 Substitution Results

| Test Mode | Freq. [MHz] | Meas. Level [dBm] | Substitution Antenna Type | SGP [dBm] | Substitution Gain [dBi] | Cable Loss [dB] | Substitution Level (EIRP) [dBm] | Limit [dBm] | Result |
|-----------|-------------|-------------------|---------------------------|-----------|-------------------------|-----------------|---------------------------------|-------------|--------|
| TM1       | 1850.2      | 30.68             | Horn Ant.                 | 27.12     | 4.5                     | 1.0             | 30.62                           | 33          | Pass   |
| TM1       | 1880.0      | 30.76             | Horn Ant.                 | 27.23     | 4.5                     | 1.0             | 30.73                           | 33          | Pass   |
| TM1       | 1909.8      | 30.79             | Horn Ant.                 | 26.95     | 4.8                     | 1.0             | 30.75                           | 33          | Pass   |
| TM2       | 1850.2      | 26.25             | Horn Ant.                 | 22.78     | 4.5                     | 1.0             | 26.28                           | 33          | Pass   |
| TM2       | 1880.0      | 26.38             | Horn Ant.                 | 22.83     | 4.5                     | 1.0             | 26.33                           | 33          | Pass   |
| TM2       | 1909.8      | 26.39             | Horn Ant.                 | 22.49     | 4.8                     | 1.0             | 26.29                           | 33          | Pass   |
| TM3       | 1852.4      | 23.82             | Horn Ant.                 | 20.37     | 4.5                     | 1.0             | 23.87                           | 33          | Pass   |
| TM3       | 1880.0      | 23.69             | Horn Ant.                 | 20.11     | 4.5                     | 1.0             | 23.61                           | 33          | Pass   |
| TM3       | 1907.6      | 23.52             | Horn Ant.                 | 19.75     | 4.8                     | 1.0             | 23.55                           | 33          | Pass   |
| TM4       | 1852.4      | 23.74             | Horn Ant.                 | 20.25     | 4.5                     | 1.0             | 23.75                           | 33          | Pass   |
| TM4       | 1880.0      | 23.65             | Horn Ant.                 | 20.11     | 4.5                     | 1.0             | 23.61                           | 33          | Pass   |
| TM4       | 1907.6      | 23.33             | Horn Ant.                 | 19.52     | 4.8                     | 1.0             | 23.32                           | 33          | Pass   |
| TM5       | 1852.4      | 22.80             | Horn Ant.                 | 19.31     | 4.5                     | 1.0             | 22.81                           | 33          | Pass   |
| TM5       | 1880.0      | 22.96             | Horn Ant.                 | 19.42     | 4.5                     | 1.0             | 22.92                           | 33          | Pass   |
| TM5       | 1907.6      | 22.87             | Horn Ant.                 | 19.02     | 4.8                     | 1.0             | 22.82                           | 33          | Pass   |

Note: a, For get the EIRP (Efficient Isotropic Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{EIRP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$

NOTE: SGP- Signal Generator Level

b, RBW=10kHz, VBW=300kHz, and integrated by the instrument to 200kHz for TM1 and TM2 and 5M for TM3 , TM4,TM5.



## 6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.



## 6.2 Conducted Power of Transmitter

### 6.2.1 Test Conditions

Table 17 Test Conditions

|                      |                                                    |
|----------------------|----------------------------------------------------|
| Preconditioning:     | 0.5 hour                                           |
| Measured at:         | Antenna connector                                  |
| Ambient temperature: | 25 °C                                              |
| Relative humidity:   | 52 %                                               |
| Test Configurations: | TM1/TM2/TM3/TM4/TM5 at frequency Bottom,Middle,Top |

### 6.2.2 Test Specifications and Limits

#### 6.2.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 24 subpart E

#### 6.2.2.2 Supporting Standards

Table 18 Supporting Standards:

|                       |                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI/TIA-603-C:2004   | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards                                                       |
| 3GPP TS51.010 V5.4.0  | Digital cellular telecommunications system; Mobile Station (MS) conformance specification;                                                |
| 3GPP TS 34.121 V7.3.0 | Universal Mobile Telecommunications System (UMTS); User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

#### 6.2.2.3 Limits

Compliance with part 24.232, in no any case may the peak power of a mobile station transmitter exceed 2 W. The calculated longitude EIRP by following formula:

$$\text{EIRP (dBm)} = 10 * \log (\text{EIRP}_{\text{in mWatts}}).$$

And for conducted power, we can use Antenna Gain to calculate the limit. So the conducted power:

$$\begin{aligned} P_{\text{cod}}(\text{dBm}) &= \text{EIRP}(\text{dBm}) - \text{Gain}(\text{dBi}). \\ \text{and Gain (dBi)} &= \text{Gain}(\text{dBd}) + 2.15\text{dB} \end{aligned}$$

Table 19 Limits

|                                      |                  |
|--------------------------------------|------------------|
| Maximum Output Power (Watts)         | < 2 Watts(33dBm) |
| Antenna Gain(dBi):                   | 1.44             |
| Maximum Conducted Output Power (dBm) | < 31.56dBm       |

### 6.2.3 Test Method and Setup

(a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, Conducted maximum power shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the wireless communication tester CMU200 via the antenna connector. The band is set as PCS and WCDMA1900M.

(b) Test the Conducted maximum output power by the CMU200.

#### Test setup




Figure 2. Test Set-up

### 6.2.4 Measurement Results

Table 20 Measurement Results

|                 |                             | RF Output Power(Conducted)  |       |                           |       |                             |       |
|-----------------|-----------------------------|-----------------------------|-------|---------------------------|-------|-----------------------------|-------|
| TEST CONDITIONS |                             | Channel512(B)<br>1850.2MHz  |       | Channel661 (M)<br>1880MHz |       | Channel810(T)<br>1909.8MHz  |       |
|                 |                             | dBm                         |       | dBm                       |       | dBm                         |       |
|                 |                             | Measured                    | Limit | Measured                  | Limit | Measured                    | Limit |
| TM1             | Tnom (25 °C)<br>Vnom (3.7V) | 29.24                       | 31.56 | 29.32                     | 31.56 | 29.35                       | 31.56 |
| TM2             | Tnom (25 °C)<br>Vnom (3.7V) | 24.81                       | 31.56 | 24.94                     | 31.56 | 24.95                       | 31.56 |
| TEST CONDITIONS |                             | Channel9262(B)<br>1852.4MHz |       | Channel9400(M)<br>1880MHz |       | Channel9538(T)<br>1907.6MHz |       |
|                 |                             | dBm                         |       | dBm                       |       | dBm                         |       |
|                 |                             | Measured                    | Limit | Measured                  | Limit | Measured                    | Limit |
| TM3             | Tnom (25 °C)<br>Vnom (3.7V) | 22.38                       | 31.56 | 22.25                     | 31.56 | 22.08                       | 31.56 |
| TM4             | Tnom (25 °C)<br>Vnom (3.7V) | 22.30                       | 31.56 | 22.21                     | 31.56 | 21.89                       | 31.56 |
| TM5             | Tnom (25 °C)<br>Vnom (3.7V) | 21.36                       | 31.56 | 21.52                     | 31.56 | 21.43                       | 31.56 |

### 6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause

## 6.3 Modulation Characteristics

### 6.3.1 Test Conditions

Table 21 Test Conditions

|                      |                                 |
|----------------------|---------------------------------|
| Preconditioning:     | 0.5 hour                        |
| Measured at:         | Antenna connector               |
| Ambient temperature: | 25 °C                           |
| Relative humidity:   | 52 %                            |
| Test Configurations: | TM1/TM2/TM3 at frequency Middle |

### 6.3.2 Test Specifications and Limits

#### 6.3.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 24 subpart E

#### 6.3.2.2 Supporting Standards

Table 22 Supporting Standards:

|                       |                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI/TIA-603-C:2004   | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards                                                             |
| 3GPP TS51.010 V5.4.0  | Digital cellular telecommunications system;<br>Mobile Station (MS) conformance specification;                                                   |
| 3GPP TS 34.121 V7.3.0 | Universal Mobile Telecommunications System (UMTS);<br>User Equipment (UE) conformance specification;<br>Radio transmission and reception (FDD); |

#### 6.3.2.3 Limits

No specific modulation characteristics requirement limits in part 2.1047 and part 24 subpart E.

Table 23 Limits

|        |                |
|--------|----------------|
| Limits | Not applicable |
|--------|----------------|

### 6.3.3 Test Method and Setup

Connect the EUT to Universal Radio Communication Tester CMU200 via the antenna connector. The frequency band is set as PCS and WCDMA1900M. The EUT's output is matched with 50  $\Omega$  load, test method was according to 3GPP TS 51.010 and TS 34.121. The waveform quality and constellation of the EUT was tested.

#### Test setup




Figure 3. Test Set-up

### 6.3.4 Measurement Results

Table 24 Measurement Results

|                          |                         | Modulation Characteristic  |                     |
|--------------------------|-------------------------|----------------------------|---------------------|
| TEST CONDITIONS          |                         | Channel 661(M)<br>1880MHz  |                     |
|                          |                         | Measured                   |                     |
|                          |                         | TM1                        | TM2                 |
| T <sub>nom</sub> (25 °C) | V <sub>nom</sub> (3.7V) | Refer to Appendix A        | Refer to Appendix A |
|                          |                         |                            |                     |
|                          |                         | Modulation Characteristic  |                     |
| TEST CONDITIONS          |                         | Channel 9400(M)<br>1880MHz |                     |
|                          |                         | Measured                   |                     |
|                          |                         | TM3                        |                     |
| T <sub>nom</sub> (25 °C) | V <sub>nom</sub> (3.7V) | Refer to Appendix A        |                     |

### 6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
For the measurement results refer to Appendix A.

## 6.4 Occupied Bandwidth

### 6.4.1 Test Conditions

Table 25 Test Conditions

|                      |                                            |
|----------------------|--------------------------------------------|
| Preconditioning:     | 0.5 hour                                   |
| Measured at:         | Antenna connector                          |
| Ambient temperature: | 25 °C                                      |
| Relative humidity:   | 55 %                                       |
| Test Configurations: | TM1/TM2/TM3 at frequency Bottom,Middle,Top |

### 6.4.2 Test Specifications and Limits

#### 6.4.2.1 Specification

CFR 47 (FCC) part 2.1049 and part 24 subpart E

#### 6.4.2.2 Supporting Standards

Table 26 Supporting Standards:

|                       |                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI/TIA-603-C:2004   | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards                                                             |
| 3GPP TS51.010 V5.4.0  | Digital cellular telecommunications system;<br>Mobile Station (MS) conformance specification;                                                   |
| 3GPP TS 34.121 V7.3.0 | Universal Mobile Telecommunications System (UMTS);<br>User Equipment (UE) conformance specification;<br>Radio transmission and reception (FDD); |

#### 6.4.2.3 Limits

No specific occupied bandwidth requirement in part 24 subpart E, but the occupied bandwidth was defined in part 2.1049: the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Table 27 Limits

|                               |                        |
|-------------------------------|------------------------|
| Upper /lower frequency limits | 0.5% of the mean power |
|-------------------------------|------------------------|

### 6.4.3 Test Method and Setup

The EUT was connected to the wireless spectrum analyzer R&S FSQ31 via the one RF connector. The band class is set as PCS and WCDMA1900M. The EUT was controlled to transmit maximum power. Measure and record the occupied bandwidth of the EUT by the R&S FSQ31.

The OBW, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

Refer to 47CFR part2.1049 section (g)&(h).

(g) Transmitter in which the modulating base band comprises not more than three independent channels - when modulated by the full complement of signals for which the transmitter is rated. The level of modulation for each channel should be set to that prescribed in rule parts applicable to the services for which the transmitter is intended. If specific modulation levels are not set forth in the rules, the tests should provide the manufacturer's maximum rated condition.

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudorandom generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at discretion of the user.

For TM1/TM2 following RBW and VBW are employed:

Measurement bandwidth (RBW): 3 kHz (Resolution bandwidth)

Video bandwidth (VBW): 10 kHz

For TM3 system following RBW and VBW are employed:

Measurement bandwidth (RBW): 50 kHz (Resolution bandwidth)

Video bandwidth (VBW): 500 kHz

## Test Set-up




Figure 4. Test Set-up

## 6.4.4 Measurement Results

Table 28 Measurement Results

| TEST CONDITIONS   |     | Occupied Bandwidth          |        |                           |        |                             |        |
|-------------------|-----|-----------------------------|--------|---------------------------|--------|-----------------------------|--------|
|                   |     | Channel512 (B)<br>1850.2MHz |        | Channel661 (M)<br>1880MHz |        | Channel810 (T)<br>1909.8MHz |        |
|                   |     | Measured<br>(kHz)           |        | Measured<br>(kHz)         |        | Measured<br>(kHz)           |        |
|                   |     | TM1                         | TM2    | TM1                       | TM2    | TM1                         | TM2    |
| $T_{nom}$ (25 °C) | 99% | 243.59                      | 254.81 | 243.59                    | 251.60 | 246.79                      | 256.41 |
| $V_{nom}$ (3.7V)  |     |                             |        |                           |        |                             |        |
|                   |     | Occupied Bandwidth          |        |                           |        |                             |        |



| TEST CONDITIONS                                     |     | Channel9262(B)<br>1852.4MHz | Channel9400(M)<br>1880MHz | Channel9538 (T)<br>1907.6MHz |
|-----------------------------------------------------|-----|-----------------------------|---------------------------|------------------------------|
|                                                     |     | Measured<br>(MHz)           | Measured<br>(MHz)         | Measured<br>(MHz)            |
|                                                     |     | TM3                         | TM3                       | TM3                          |
| T <sub>nom</sub> (25 °C)<br>V <sub>nom</sub> (3.7V) | 99% | 4.15                        | 4.15                      | 4.18                         |

## 6.4.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
For the measurement results refer to appendix B.

## 6.5 Band Edges Compliance

### 6.5.1 Test Conditions

Table 29 Test Conditions

|                      |                                     |
|----------------------|-------------------------------------|
| Preconditioning:     | 0.5 hour                            |
| Measured at:         | Antenna connector                   |
| Ambient temperature: | 25°C                                |
| Relative humidity:   | 55 %                                |
| Test Configurations: | TM1/TM2/TM3 at frequency Bottom,Top |

### 6.5.2 Test Specifications and Limits

#### 6.5.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 24.238

#### 6.5.2.2 Supporting Standards

Table 30 Supporting Standards:

|                       |                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI/TIA-603-C:2004   | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards                                                             |
| 3GPP TS51.010 V5.4.0  | Digital cellular telecommunications system;<br>Mobile Station (MS) conformance specification;                                                   |
| 3GPP TS 34.121 V7.3.0 | Universal Mobile Telecommunications System (UMTS);<br>User Equipment (UE) conformance specification;<br>Radio transmission and reception (FDD); |

#### 6.5.2.3 Limits

Compliance with part 24.238, all spurious emission must be attenuated below the transmitter power by at least  $43 + 10 \log_{10} P$  (W) . (Whereas P is the rated power of the EUT).

Table 31 Limits

|                       | TM1                                     | TM2                                       | TM3                                        |
|-----------------------|-----------------------------------------|-------------------------------------------|--------------------------------------------|
| Rated Power:          | 30 dBm                                  | 26 dBm                                    | 24 dBm                                     |
| Required attenuation: | $43 + 10 \log(1) = 43$ , 30 dBm - 43 dB | $43 + 10 \log(0.4) = 39$ , 26 dBm - 39 dB | $43 + 10 \log(0.25) = 37$ , 24 dBm - 37 dB |
| Absolute level        | - 13 dBm                                | - 13 dBm                                  | - 13 dBm                                   |

### 6.5.3 Test Method and Setup

The EUT was connected to the wireless spectrum analyzer R&S FSQ31 via the one RF connector, the band class is set as PCS and WCDMA1900M. The EUT was controlled to transmit maximum power. Measure and record band edges compliance of the EUT by the R&S FSQ31.

The limit is -13dBm.

For TM1/TM2 following RBW and VBW are employed:

Measurement bandwidth (RBW): 3 kHz (Resolution bandwidth)

Video bandwidth (VBW): 10 kHz

For TM3 system following RBW and VBW are employed:

Measurement bandwidth (RBW): 50 kHz (Resolution bandwidth)

Video bandwidth (VBW): 500 kHz

## Test Set-up




Figure 5. Test Set-up

## 6.5.4 Measurement Results

Table 32 Measurement Results outside Band Edges

| Band | Frequency of Band edges [MHz]       | Channel Number | Test Mode | Spurious Level measured [dBm] | FCC limit | Result |
|------|-------------------------------------|----------------|-----------|-------------------------------|-----------|--------|
| PCS  | $T_{nom}$ (25 °C), $V_{nom}$ (3.7V) |                |           |                               |           |        |
|      | 1850.2                              | 512            | TM1       | <-13 (See appendix C)         | - 13 dBm  | Pass   |
|      | 1909.8                              | 810            | TM1       | <-13 (See appendix C)         | - 13 dBm  | Pass   |
|      | 1850.2                              | 512            | TM2       | <-13 (See appendix C)         | - 13 dBm  | Pass   |
|      | 1909.8                              | 810            | TM2       | <-13 (See appendix C)         | - 13 dBm  | Pass   |
|      | 1852.4                              | 9262           | TM3       | <-13 (See appendix C)         | - 13 dBm  | Pass   |
|      | 1907.6                              | 9538           | TM3       | <-13 (See appendix C)         | - 13 dBm  | Pass   |

## 6.5.5 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix C.

## 6.6 Spurious Emission at Antenna Terminal

### 6.6.1 Test Conditions

Table 33 Test Conditions

|                      |                                              |
|----------------------|----------------------------------------------|
| Preconditioning:     | 0.5 hour                                     |
| Measured at:         | Antenna connector                            |
| Ambient temperature: | 25°C                                         |
| Relative humidity:   | 50 %                                         |
| Test Configurations: | TM1/TM2/TM3 at frequency Bottom, Middle, Top |

### 6.6.2 Test Specifications and Limits

#### 6.6.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 24.238

#### 6.6.2.2 Supporting Standards

Table 34 Supporting Standards:

|                       |                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI/TIA-603-C:2004   | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards                                                             |
| 3GPP TS51.010 V5.4.0  | Digital cellular telecommunications system;<br>Mobile Station (MS) conformance specification;                                                   |
| 3GPP TS 34.121 V7.3.0 | Universal Mobile Telecommunications System (UMTS);<br>User Equipment (UE) conformance specification;<br>Radio transmission and reception (FDD); |

#### 6.6.2.3 Limits

Compliance with part 24.238, all spurious emission must be attenuated below the transmitter power by at least  $43 + 10 \log_{10} P$ . (Whereas P is the rated power of the EUT in Watt).

Table 35 Limits for GPRS Mode

|                       | TM1                                     | TM2                                       | TM3                                        |
|-----------------------|-----------------------------------------|-------------------------------------------|--------------------------------------------|
| Rated Power:          | 30 dBm                                  | 26 dBm                                    | 24 dBm                                     |
| Required attenuation: | $43 + 10 \log(1) = 43$ , 30 dBm - 43 dB | $43 + 10 \log(0.4) = 39$ , 26 dBm - 39 dB | $43 + 10 \log(0.25) = 37$ , 24 dBm - 37 dB |
| Absolute level        | - 13 dBm                                | - 13 dBm                                  | - 13 dBm                                   |

### 6.6.3 Test Method and Setup

The EUT was connected to the wireless spectrum analyzer R&S FSQ31 via the one RF connector, the band class is set as PCS and WCDMA1900M. The EUT was controlled to transmit maximum power. Measure and record the Conducted Spurious Emission of the EUT by the R&S FSQ31.

According to part 24.238, the defined measurement bandwidth as following:

24.238 (b) Measurement procedure: Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;  
Measurement bandwidth (RBW) for 150 kHz up to 30MHz: 10 kHz;  
Measurement bandwidth (RBW) for 30 MHz up to 20GHz: 1MHz;

#### Test Set-up




Figure 6. Test Set-up

## 6.6.4 Measurement Results

Table 36 Measurement Results

| Channel Number  | Test Mode | Test Range (Frequency) | Output Power [dBm] | Spurious Level measured [dBm] | FCC limit | Result |
|-----------------|-----------|------------------------|--------------------|-------------------------------|-----------|--------|
| Channel 512(B)  | TM1       | 9 kHz~20GHz            | 30                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
|                 | TM2       | 9 kHz~20GHz            | 26                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
| Channel 9262(B) | TM3       | 9 kHz~20GHz            | 24                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
| Channel 661(M)  | TM1       | 9 kHz~20GHz            | 30                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
|                 | TM2       | 9 kHz~20GHz            | 26                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
| Channel 9400(M) | TM3       | 9 kHz~20GHz            | 24                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
| Channel 810(T)  | TM1       | 9 kHz~20GHz            | 30                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
|                 | TM2       | 9 kHz~20GHz            | 26                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |
| Channel 9538(T) | TM3       | 9 kHz~20GHz            | 24                 | <- 13 dBm<br>(See appendix D) | - 13 dBm  | Pass   |

## 6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
For the measurement results refer to appendix D.

## 6.7 Frequency Stability

### 6.7.1 Test Conditions

Table 37 Test Conditions

|                      |                                 |
|----------------------|---------------------------------|
| Preconditioning:     | 0.5 hour                        |
| Measured at:         | Antenna connector               |
| Ambient temperature: | See below                       |
| Relative humidity:   | 55 % at 25 °C                   |
| Test Configurations: | TM1/TM2/TM3 at frequency Middle |

### 6.7.2 Test Specifications and Limits

#### 6.7.2.1 Specification

CFR 47 (FCC) part 2.1055 and part 24.235

#### 6.7.2.2 Supporting Standards

Table 38 Supporting Standards:

|                       |                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| ANSI/TIA-603-C:2004   | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards                                                       |
| 3GPP TS51.010 V5.4.0  | Digital cellular telecommunications system; Mobile Station (MS) conformance specification;                                                |
| 3GPP TS 34.121 V7.3.0 | Universal Mobile Telecommunications System (UMTS); User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

#### 6.7.2.3 Limits

No specific frequency stability requirement in part 2.1055 and part 24.235.

### 6.7.3 Test Method and Setup

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) From -30 ° to +50 ° centigrade for all equipment except that specified in subparagraphs
- (2) and (3) of paragraph 2.1055

(b) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(d) The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer. Mobile phone can work normally

from 3.6V to 4.2V, test below is done according to this limit.

(3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

(e) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) and (d) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment.)

## Test Set up

Connect the EUT to the Wireless Communication test set CMU200 via the connector. Then measure the frequency error by the Wireless Communication test set CMU200. The EUT's output is matched with a 50  $\Omega$  load.




Figure 7. Test Set up

## 6.7.4 Measurement Results

### 6.7.4.1 Measurement Results vs. Variation of Temperature

- **TM1, 3.7V DC Channel No.661(1880.0MHz)**

Table 39 Measurement Results vs. Variation of Temperature

| Temperature | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|-------------|-------------|-------------------------|------------------------------|--------|
| -30 °C      | 30          | 1880.0                  | -12                          | Pass   |
| -20 °C      | 30          | 1880.0                  | -5                           | Pass   |
| -10 °C      | 30          | 1880.0                  | 10                           | Pass   |
| 0 °C        | 30          | 1880.0                  | -9                           | Pass   |
| +10 °C      | 30          | 1880.0                  | 11                           | Pass   |
| +20 °C      | 30          | 1880.0                  | -10                          | Pass   |
| +30 °C      | 30          | 1880.0                  | -9                           | Pass   |
| +40 °C      | 30          | 1880.0                  | 17                           | Pass   |
| +50 °C      | 30          | 1880.0                  | -10                          | Pass   |

● **TM2, 3.7V DC Channel No.661(1880.0MHz)**

Table 40 Measurement Results vs. Variation of Temperature

| Temperature | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|-------------|-------------|-------------------------|------------------------------|--------|
| -30 °C      | 26          | 1880.0                  | 13                           | Pass   |
| -20 °C      | 26          | 1880.0                  | -12                          | Pass   |
| -10 °C      | 26          | 1880.0                  | -10                          | Pass   |
| 0 °C        | 26          | 1880.0                  | 15                           | Pass   |
| +10 °C      | 26          | 1880.0                  | -10                          | Pass   |
| +20 °C      | 26          | 1880.0                  | -10                          | Pass   |
| +30 °C      | 26          | 1880.0                  | 9                            | Pass   |
| +40 °C      | 26          | 1880.0                  | -12                          | Pass   |
| +50 °C      | 26          | 1880.0                  | 10                           | Pass   |

● **TM3, 3.7V DC Channel No.9400(1880.0MHz)**

Table 41 Measurement Results vs. Variation of Temperature

| Temperature | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|-------------|-------------|-------------------------|------------------------------|--------|
| -30 °C      | 24          | 1880.0                  | -11                          | Pass   |
| -20 °C      | 24          | 1880.0                  | -9                           | Pass   |
| -10 °C      | 24          | 1880.0                  | 10                           | Pass   |
| 0 °C        | 24          | 1880.0                  | -13                          | Pass   |
| +10 °C      | 24          | 1880.0                  | -10                          | Pass   |
| +20 °C      | 24          | 1880.0                  | 9                            | Pass   |
| +30 °C      | 24          | 1880.0                  | -8                           | Pass   |
| +40 °C      | 24          | 1880.0                  | -12                          | Pass   |
| +50 °C      | 24          | 1880.0                  | 11                           | Pass   |

#### 6.7.4.2 Measurement Results vs. Variation of Voltage

- **TM1, 25 °C ,Channel No. 661(1880.0MHz)**

Table 42 Measurement Results vs. Variation of Voltage

| Voltage | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|---------|-------------|-------------------------|------------------------------|--------|
| 3.6     | 30          | 1880.0                  | 13                           | Pass   |
| 3.7     | 30          | 1880.0                  | -12                          | Pass   |
| 4.2     | 30          | 1880.0                  | 9                            | Pass   |

- **TM2, 25 °C ,Channel No. 661(1880.0MHz)**

Table 43 Measurement Results vs. Variation of Voltage

| Voltage | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|---------|-------------|-------------------------|------------------------------|--------|
| 3.6     | 26          | 1880.0                  | -12                          | Pass   |
| 3.7     | 26          | 1880.0                  | -10                          | Pass   |
| 4.2     | 26          | 1880.0                  | 10                           | Pass   |

- **TM3, 25 °C ,Channel No. 9400(1880.0MHz)**

Table 44 Measurement Results vs. Variation of Voltage

| Voltage | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|---------|-------------|-------------------------|------------------------------|--------|
| 3.6     | 24          | 1880.0                  | 9                            | Pass   |
| 3.7     | 24          | 1880.0                  | -10                          | Pass   |
| 4.2     | 24          | 1880.0                  | -12                          | Pass   |

#### 6.7.5 Conclusion

The equipment **PASSED** the requirement of this clause.

## 7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 45 System Measurement Uncertainty

| Items                                           |                         | Extended Uncertainty |
|-------------------------------------------------|-------------------------|----------------------|
| Effective Radiated Power of Transmitter         | ERP (dBm)               | U=3dB; k=2           |
| Band Width                                      | Magnitude (%)           | U=0.2%; k=2          |
| Band Edge Compliance                            | Disturbance Power (dBm) | U=2.0dB; k=2         |
| Conducted Spurious Emission at Antenna Terminal | Disturbance Power (dBm) | U=2.0dB; k=2         |
| Frequency Stability                             | Frequency Accuracy(ppm) | U=0.21ppm; k=2       |



## 8 Appendices

|            |                                                           |          |
|------------|-----------------------------------------------------------|----------|
| Appendix A | Measurement Results Modulation Characteristics            | 4 pages  |
| Appendix B | Measurement Results Occupied Bandwidth                    | 10 pages |
| Appendix C | Measurement Results Band Edges Compliance                 | 7 pages  |
| Appendix D | Measurement Results Spurious Emission at Antenna Terminal | 28 pages |

(END OF REPORT)