

8 7 6 5 4 3 2 1

NOTES: UNLESS OTHERWISE SPECIFIED:

1. RESISTANCE VALUES ARE IN OHMS.

HIGHEST REFERENCE DESIGNATION
C161 D1 EMC1 J5 L8 Q3 R113
T2 TP56 U17

REFERENCE DESIGNATIONS NOT USED
C8 C10 C12 C31 C44 C105 C121
C126-132 C137-139 C143-144
C150-151 C156 C160 R7-9
R30-32 R34 R49 R54-55 R59
R64 R69 R71 R89 R100-102
R105-110 R112 T1 TP18 TP54
U6-7 U12-16

REFERENCE DESIGNATIONS NOT POPULATED
△ = DO NOT POPULATE
C15 C18 C21 C24 C26 C85 C89
C107 C133 C153-155 J1 J5 L1 L3-5
R6 R13 R15-17 R26 R63 R68
R73-74 R79-81 R83 R85
R87-88 R92 R93 R95-96

△ = OPTIONAL COMPONENT - SEE CHART ON SHEET 1 FOR POPULATION OPTIONS
△ = DO NOT INSTALL (DNI) - SEE CHART ON SHEET 1

PRELIMINARY DESIGN
NOTE: THIS SCHEMATIC IS A REFERENCE DESIGN, CONEXANT RESERVES THE RIGHT TO MAKE CHANGES TO THE SCHEMATIC AT ANY TIME WITHOUT NOTICE. CONEXANT ACCEPTS NO LIABILITY OR RESPONSIBILITY WITH THE SCHEMATIC OR ANY DATA HEREIN.
THIS IS PROPRIETORY AND CONFIDENTIAL INFORMATION OF CONEXANT

REVISIONS

ZONE	LTR	DESCRIPTION	DATE	APPR.
------	-----	-------------	------	-------

MECHANICAL PARTS

PART NUMBER	QTY	DESCRIPTION
ISL38601M-REVB-PCB	1	PWB-PCB
ISL38001M-CURREV-	1	COVER
ISL38001M-SLDREV-	1	SHIELD

CONEXANT

TITLE: ISL38601M PRISM GT MINI PCI	REV: B1
ENGINEER: GEORGE VON DOLTEREN	DATE: 5/13/04
DRAWN BY: BILL THORVALDSON	SHEET: 1 OF 3

F
E
D
C
B
A

