



中国认可
国际互认
检测
TESTING
CNAS L0310



FCC Maximum Permissible Exposure(MPE) Estimation Report

Product Name: LTE Module

Model: ME919Bs-567bN

Report No.: SYBH(Z-SAR)007022017-2

FCC ID: QISME919BS-567BN

| | APPROVED (Lab Manager) | PREPARED (Test Engineer) |
|------|---------------------------|-----------------------------|
| BY | <i>Wei Huanbin</i> | <i>Li wei</i> |
| DATE | 2017-02-15 | 2017-02-15 |

Reliability Laboratory of Huawei Technologies Co., Ltd.

(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang
District, Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

※ ※ **Notice** ※ ※

1. The laboratory has passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01 & 2174.02 & 2174.03
3. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named as “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
4. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
5. The test report is invalid if there is any evidence of erasure and/or falsification.
6. The test report is only valid for the test samples.
7. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

※ ※ **Modified History** ※ ※

| REV. | DESCRIPTION | ISSUED DATE | REMARK |
|---------|-----------------------------|-------------|--------|
| Rev.1.0 | Initial Test Report Release | 2017-02-15 | Li Wei |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Table of Contents

| | | |
|------|----------------------------------|----|
| 1 | EUT Description | 5 |
| 1.1 | General Description | 6 |
| 2 | Test specification(s) | 7 |
| 3 | Testing laboratory | 7 |
| 4 | Applicant and Manufacturer | 7 |
| 5 | Application details | 7 |
| 6 | Ambient Condition..... | 7 |
| 7 | RF Exposure Requirements..... | 8 |
| 7.1 | FCC MPE Limits..... | 9 |
| 8 | RF Exposure Evaluation | 10 |
| 8.1 | Operation in GSM850..... | 10 |
| 8.2 | Operation in GSM1900 | 10 |
| 8.3 | Operation in UMTS Band II..... | 11 |
| 8.4 | Operation in UMTS Band IV | 11 |
| 8.5 | Operation in UMTS Band V | 11 |
| 8.6 | Operation in LTE Band II | 12 |
| 8.7 | Operation in LTE Band IV | 12 |
| 8.8 | Operation in LTE Band V | 12 |
| 8.9 | Operation in LTE Band VII | 13 |
| 8.10 | Operation in LTE Band XII | 13 |
| 8.11 | Operation in LTE Band XIII | 13 |

1 EUT Description

| Device Information: | | | |
|---|--|-----------|-----------|
| Product Name : | LTE Module | | |
| Model : | ME919Bs-567bN | | |
| FCC ID: | QISME919BS-567BN | | |
| Device Type : | Mobile Device | | |
| Device Phase: | Identical Prototype | | |
| Exposure Category: | Uncontrolled environment/general population | | |
| Hardware Version : | RM1ME919BSTM | | |
| Software Version : | 11.670.05.00.1400 | | |
| Antenna Type : | External Antenna | | |
| Device Operating Configurations: | | | |
| Supporting Mode(s) | GSM850/1900,UMTS Band II/IV/V, LTE band II/IV/V/VII/XII/XIII/XXIX | | |
| Test Modulation | GSM(GMSK/8PSK),UMTS(QPSK),LTE(QPSK/16QAM) | | |
| Operating Frequency Range(s) | Band | Tx (MHz) | Rx (MHz) |
| | GSM850 | 824-849 | 869-894 |
| | GSM1900 | 1850-1910 | 1930-1990 |
| | UMTS Band II | 1850-1910 | 1930-1990 |
| | UMTS Band IV | 1710-1755 | 2110-2155 |
| | UMTS Band V | 824-849 | 869-894 |
| | LTE Band II | 1850-1910 | 1930-1990 |
| | LTE Band IV | 1710-1755 | 2110-2155 |
| | LTE Band V | 824-849 | 869-894 |
| | LTE Band VII | 2500-2570 | 2620-2690 |
| | LTE Band XII | 699-716 | 728-746 |
| | LTE Band XIII | 777-787 | 746-757 |
| | LTE Band XXIX | / | 716-728 |

1.1 General Description

ME919Bs-567bN LTE/WCDMA(UMTS)/GSM/GPRS/EDGE multimode Wireless Module is subscriber equipment in the LTE /UMTS/GSM system. ME919Bs-567bN implement such functions as RF signal receiving/transmitting, LTE/WCDMA and EDGE/GPRS/GSM protocol processing, data service etc. Externally it provides LGA interface.

2 Test specification(s)

| | |
|---------------------|---|
| ANSI Std C95.1-1992 | Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991) |
| KDB 447498 D01 | General RF Exposure Guidance v06 |

3 Testing laboratory

| | |
|------------------------|--|
| Test Site | The Reliability Laboratory of Huawei Technologies Co., Ltd. |
| Test Location | Section G1,Huawei Base Bantian, Longgang District, Shenzhen 518129, P.R. China |
| Telephone | +86 755 28780808 |
| Fax | +86 755 89652518 |
| State of accreditation | The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01 & 2174.02 & 2174.03 |

4 Applicant and Manufacturer

| | |
|--------------|---|
| Company Name | HUAWEI TECHNOLOGIES CO., LTD |
| Address | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C |

5 Application details

| | |
|--------------------|------------|
| Start Date of test | 2017-02-15 |
| End Date of test | 2017-02-15 |

6 Ambient Condition

| | |
|---------------------|-------------|
| Ambient temperature | 20°C – 24°C |
| Relative Humidity | 30% – 70% |

7 RF Exposure Requirements

An estimation of MPE in this application for product is used to ensure if it complies to the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

EIRP = P * G

The antenna of the product, under normal use condition is at least 20 cm away from the

body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

7.1 FCC MPE Limits

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

Table: Limits For Maximum Permissible Exposure (MPE)

| (A) Limits for Occupational/controlled Exposure | | | | |
|--|---------------------------------|---------------------------------|--|--|
| Frequency Range(MHz) | Electric Field Strength(E)(V/m) | Magnetic Field Strength(H)(A/m) | Power Density (S)(mW/cm ²) | Averaging Time (minute) E ² , H ² or S |
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f ²)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | -- | -- | f/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/uncontrolled Exposure | | | | |
| Frequency Range(MHz) | Electric Field Strength(E)(V/m) | Magnetic Field Strength(H)(A/m) | Power Density (S)(mW/cm ²) | Averaging Time (minute) E ² , H ² or S |
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |
| f=frequency in MHz | | | *Plane-wave equivalent power density | |

8 RF Exposure Evaluation

8.1 Operation in GSM850

(uplink: 824-849MHz, downlink: 869-894MHz)

| Antenna | Mode | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|-----------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|------------|
| External Antenna | 1TS*(1/8) | 33.5 | 2.5 | 36 | 497.63 | 20 | 0.099 | 0.549 | Pass |
| | 2TS*(2/8) | 31.5 | 2.5 | 34 | 627.97 | 20 | 0.125 | 0.549 | Pass |
| | 3TS*(3/8) | 30.5 | 2.5 | 33 | 748.22 | 20 | 0.149 | 0.549 | Pass |
| | 4TS*(4/8) | 28.5 | 2.5 | 31 | 629.46 | 20 | 0.125 | 0.549 | Pass |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.149mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.2 Operation in GSM1900

(uplink: 1850-1910MHz, downlink: 1930-1990MHz)

| Antenna | Mode | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|-----------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|------------|
| External Antenna | 1TS*(1/8) | 30.5 | 2.5 | 33 | 249.41 | 20 | 0.050 | 1.000 | Pass |
| | 2TS*(2/8) | 28.5 | 2.5 | 31 | 314.73 | 20 | 0.063 | 1.000 | Pass |
| | 3TS*(3/8) | 27.5 | 2.5 | 30 | 375.00 | 20 | 0.075 | 1.000 | Pass |
| | 4TS*(4/8) | 25.5 | 2.5 | 28 | 315.48 | 20 | 0.063 | 1.000 | Pass |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.075 mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.3 Operation in UMTS Band II

(uplink: 1850-1910MHz, downlink: 1930-1990MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|------------|
| External Antenna | 24.0 | 2.5 | 26.5 | 446.7 | 20 | 0.089 | 1.000 | Pass |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.089 mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.4 Operation in UMTS Band IV

(uplink: 1710-1755MHz, downlink: 2110-2155MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|------------|
| External Antenna | 24.0 | 2.5 | 26.5 | 446.7 | 20 | 0.089 | 1.000 | Pass |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.089mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.5 Operation in UMTS Band V

(uplink: 824-849MHz, downlink: 869-894MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|------------|
| External Antenna | 24.5 | 2.5 | 27.0 | 501.2 | 20 | 0.100 | 0.549 | PASS |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.100mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.6 Operation in LTE Band II

(uplink: 1850-1910MHz, downlink: 1930-1990MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|-------------|
| External Antenna | 23.5 | 2.5 | 26.0 | 398.1 | 20 | 0.079 | 1.000 | PASS |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.079 mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.7 Operation in LTE Band IV

(uplink: 1710-1755MHz, downlink: 2110-2155MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|-------------|
| External Antenna | 23.5 | 2.5 | 26.0 | 398.1 | 20 | 0.079 | 1.000 | PASS |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.079mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.8 Operation in LTE Band V

(uplink: 824-849MHz, downlink: 869-894MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|-------------|
| External Antenna | 24.0 | 2.5 | 26.5 | 446.7 | 20 | 0.089 | 0.549 | PASS |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.089mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.9 Operation in LTE Band VII

(uplink: 2500-2570MHz, downlink: 2620-2690MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|-------------|
| External Antenna | 23.0 | 2.5 | 25.5 | 354.8 | 20 | 0.071 | 1.000 | PASS |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer
According to the Table, we can conclude the max power density level at 20 cm is 0.071mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.10 Operation in LTE Band XII

(uplink: 699-716MHz, downlink: 728-746MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|--------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|-------------|
| External Antenna 2 | 24.0 | 2.5 | 26.5 | 446.7 | 20 | 0.089 | 0.466 | PASS |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer
According to the Table, we can conclude the max power density level at 20 cm is 0.089mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

8.11 Operation in LTE Band XIII

(uplink: 777-787MHz, downlink: 746-757MHz)

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R(cm) | S (mW/cm ²) | MPE Limit (mW/cm ²) | Conclusion |
|------------------|---------------------|------------|-------------|-----------|-------|-------------------------|---------------------------------|-------------|
| External Antenna | 24.0 | 2.5 | 26.5 | 446.7 | 20 | 0.089 | 0.518 | PASS |

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer
According to the Table, we can conclude the max power density level at 20 cm is 0.089mW/cm², which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

END