



EMC Test Report

Product Name: Mobile WiFi

Model Number: R207

Report No: SYBH(Z-EMC)040042014-2

FCC ID: QISR207

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
5. The test report is invalid if not marked with "exclusive stamp for the test report".
6. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
9. Normally, the test report is only responsible for the samples that have undergone the test.
10. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Applicant: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Date of Receipt Test Item: May.08, 2014
Start Date of Test: May.10, 2014
End Date of Test: May.12, 2014
Test Result: Pass

**Approved By
(Lab Manager)**

2014-05-14
Date

Liu Chunlin
Name

Signature

**Operator
(Test Engineer)**

2014-05-14
Date

Xiang Zaiji
Name

Signature



Modification Record

No.	Last Report No.	Modification Description
1	NA	First Report.

TABLE OF CONTENT

1	General Information	6
1.1	EUT Description	6
1.2	Test Site Information	7
1.3	Applied Standards	7
2	Summary of Results.....	8
3	System Configuration during EMC Test.....	9
3.1	Test Mode	9
3.2	Test System Configuration.....	10
3.3	Cables Used during Test.....	10
3.4	Associated Equipment Used during Test.....	10
4	Electromagnetic Interference (EMI).....	11
4.1	Radiated Disturbance 30MHz to 18GHz	11
4.2	Conducted Disturbance 0.15 MHz to 30MHz.....	13
5	Main Test Instruments.....	14
6	System Measurement Uncertainty	14
7	Test Data and Graph.....	15
7.1	Radiated Disturbance	15
7.2	Conducted Disturbance.....	17

1 General Information

1.1 EUT Description

EUT Description	
Product Name	Mobile WiFi
Model Number	R207
Serials Number	K7T0114411000135
TX Frequency	GSM850: 824MHz To 849MHz GSM1900: 1850MHz To 1910MHz WIFI 2.4G: 2400MHz To 2483.5MHz
RX Frequency	GSM850: 869MHz To 894MHz GSM1900: 1930MHz To 1990MHz WIFI 2.4G: 2400MHz To 2483.5MHz
HW Version	CH1E5330SM05 VER.A
SW Version	21.210.03.00.11
EUT Accessory	
White USB Cable	Terminal Accessory, Data Cable, USB A male to Micro USB 120cm, White, Terminal Dedicated
Black USB Cable	Terminal Accessory, Data Cable, USB A male to Micro USB 120cm, Black no Braid, Can Not Meet USB2.0 Standard, Terminal Dedicated
Adapter	RAND: HUAWEI Model: HW-050100E1W Input Voltage: 100-240V~ 50/60Hz, 0.2A MAX Output: 5.0V  1.0A SN: TPACC1629318 SN: HKAE30280695
Adapter	RAND: HUAWEI Model: HW-050100B1W Input Voltage: 100-240V~ 50/60Hz, 0.2A Output: 5.0V  1.0A SN: TPAE32400729 SN: HKAD3260946
Battery	BRAND: HUAWEI Model: HB554666RAW Rated capacity: 1500mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V SN: 1322SCE402 SN: 1322SIE428

Remark: The information of the EUT is declared by the manufacturer. Please refer to the specifications or user manual for details.



1.2 Test Site Information

Test Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.3 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15:2013, Subpart B

2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
Radiated Emissions Enclosure Port	Mode1 Mode3	CLASS B	Pass	Site1
Conducted Emissions ☒ DC Power Port ☒ AC Power Port ☐ Telecommunication Ports	Mode1~ Mode4	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the uncertainty of test system. 2, ☒ The item has been tested; ☐ The item has not been tested.				

During the measurement, the environmental conditions complied with the range listed as below.

Item	Required
Ambient temperature	15°C ~ 35°C
Relative humidity	25% ~ 75%
Atmospheric pressure	86kPa ~ 106kPa

3 System Configuration during EMC Test

3.1 Test Mode

The EUT was configured, installed, arranged and operated in a manner consistent with typical application. The following mode(s) were applied during the compliance test.

Test Mode	
Mode 1:	EUT with Adapter+ Idle Mode
Mode 2:	EUT with Adapter+ Traffic Mode
Mode 3:	EUT with PC+ Idle Mode
Mode 4:	EUT with PC+ Traffic Mode

Remark:

- 1) If there is one kind of accessories with different models, each one should be applied throughout the compliance test respectively, however, only the worst case will be recorded in this report.
- 2) If EUT has more than one typical operation, only the worst test mode will be recorded in this report.


Traffic Mode:

When the EUT state is switched on and with Radio Resource Control (RRC) connection established.

Idle Mode:

When the EUT state is switched on but without Radio Resource Control (RRC) connection.

3.2 Test System Configuration



3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB Cable	1	120cm	shielded

3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated Deadline	Cal interval (month)
Radio Communication tester	CMU200	R&S	3607033573	2014-10-14	12
Notebook	MS2220	Acer	3107084890	/	/

4 Electromagnetic Interference (EMI)

4.1 Radiated Disturbance 30MHz to 18GHz

4.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4-2009. The test distance is 3m. The set-up and test methods are according to ANSI C63.4-2009.

A preliminary scan and a final scan of the emissions are made from 30 MHz to 18 GHz by using test script of software; The emissions are measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna is 1m to 4m. The azimuth range of turntable is 0° to 360°. The receiving antenna has two polarizations V and H.

Measurement bandwidth (RBW) for 30MHz to 1000 MHz: 120 KHz;

Measurement bandwidth (RBW) for 1000MHz to 18000 MHz: 1MHz;

EUT is configured in idle mode and the test performed at worst emission state.

4.1.2 Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance(above 1GHz)

4.1.3 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.
Refer to the section 7.1 of this report for test data.

Test Limits (Class B)				
Frequency of Emission (MHz)	Radiated Limit			
	Unit(μ V/m)		Unit(dB μ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

4.2 Conducted Disturbance 0.15 MHz to 30MHz

4.2.1 Test Procedure

The Table-top EUT is placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT is connected to LISN and LISN is connected to reference Ground Plane. EUT is 80cm away from LISN. The set-up and test methods are according to ANSI C63.4-2009.

Conducted Disturbance at AC Port measurements are undertaken on the L and N Lines. The emissions are measured using a Quasi-Peak Detector and Average Detector.

EUT is communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.

Measurement bandwidth (RBW) for 150 KHz to 30 MHz: 9 KHz;

The EUT is set in the shielded chamber and operated under nominal conditions.

4.2.2 Test Setup




Figure 3. Test Set-up of conducted disturbance

4.2.3 Test Results

The EUT has met requirements for Conducted disturbance of power lines.
Refer to the section 7.2 of this report for test data.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP (dB μ V)	AV (dB μ V)
0.15MHz~0.5MHz	66-56	56-46
0.5MHz-5MHz	56	46
5MHz~30MHz	60	50

5 Main Test Instruments

Main Test Equipments						
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated deadline	Cal interval (month)
RE	EMI Test receiver	ESU26	100150	R&S	May.08, 2015	12
	Broadband Antenna	VULB 9163	9163-520	SCHWARZBECK	Dec.20, 2015	24
	Horn Antenna	HF906	100683	R&S	Feb.01, 2015	24
CE	Line Impedance Stabilization Network	ENV216	100382	R&S	Dec.23, 2014	12
	Artificial Main Network	ENV4200	100134	R&S	Dec.23, 2014	12
	EMI Test receiver	ESCI	101163	R&S	Dec.23, 2014	12
Software Information						
Test Item	Software Name		Manufacturer		Version	
RE	ES-K1		R&S		1.7.1	
CE	EMC32		R&S		V8.40.0	

6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 are:


System Measurement Uncertainty		
Items		Extended Uncertainty
RE(30MHz-1GHz)	Field strength (dBμV/m)	U=4.1dB; k=2
RE(1GHz-18GHz)	Field strength (dBμV/m)	U=5.1dB; k=2
CE	Disturbance Voltage (dBμV)	U=2.6dB; k=2

7 Test Data and Graph

Only the worst test results are shown.

7.1 Radiated Disturbance

7.1.1 30MHz~1GHz



MEASUREMENT RESULT: QP Detector


Frequency MHz	Level dBμV/m	Transducer dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarisation
34.740000	23.20	14.4	40.0	16.8	100.0	318.00	VERTICAL
65.460000	20.00	11.5	40.0	20.0	100.0	98.00	VERTICAL
85.920000	23.60	11.1	40.0	16.4	147.0	157.00	VERTICAL
198.360000	21.20	12.4	43.5	22.3	100.0	343.00	VERTICAL
400.020000	42.00	17.5	46.0	4.0	100.0	121.00	HORIZONTAL
660.420000	29.50	21.9	46.0	16.5	177.0	23.00	HORIZONTAL

Note:

Level= Reading level+ Transducer (cable loss + correction factor)

The reading level is calculated by software which is not shown in the sheet.

7.1.2 1GHz~18GHz



MEASUREMENT RESULT: PK Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBμV/m	dB	dBμV/m	dB	cm	deg	
5681.400000	42.60	0.4	74.0	31.4	143.0	223.00	VERTICAL
7777.200000	44.10	5.1	74.0	29.9	100.0	282.00	HORIZONTAL
14473.900000	52.30	17.5	74.0	21.7	106.0	256.00	VERTICAL

MEASUREMENT RESULT: AV Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBμV/m	dB	dBμV/m	dB	cm	deg	
5686.000000	29.30	0.5	54.0	24.7	113.0	202.00	VERTICAL
7789.300000	31.00	5.2	54.0	23.0	133.0	101.00	HORIZONTAL
14458.000000	38.80	17.5	54.0	15.2	130.0	230.00	VERTICAL


Note:

Level= Reading level+ Transducer (cable loss + correction factor)

The reading level is calculated by software which is not shown in the sheet.

7.2 Conducted Disturbance

7.2.1 AC Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV	Transducer dB	Limit dBμV	Margin dB	Line	PE
0.151705	33.7	9.7	65.9	32.2	L1	FLO
0.466462	33.1	9.7	56.6	23.5	L1	FLO
1.231530	30.2	9.7	56.0	25.8	L1	FLO
2.962376	30.1	9.7	56.0	25.9	N	FLO
7.627068	25.5	9.9	60.0	34.5	L1	FLO
20.269204	24.5	10.1	60.0	35.5	L1	FLO

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV	Transducer dB	Limit dBμV	Margin dB	Line	PE
0.223984	21.5	9.7	52.7	31.2	L1	FLO
0.461374	25.6	9.7	46.7	21.1	N	FLO
1.219016	17.2	9.7	46.0	28.8	L1	FLO
3.077284	16.8	9.7	46.0	29.2	N	FLO
7.654399	15.7	9.9	50.0	34.3	N	FLO
20.141314	14.5	10.1	50.0	35.5	L1	FLO

Note:

Level= Reading level+ Transducer (cable loss + correction factor)

The reading level is calculated by software which is not shown in the sheet.

-----END-----