

## Declaration of Electromagnetic Field Health Compliance for RRU3203 (LTE band 12)

To whom it may concern,

As to the product **RRU3203** made by Huawei Technologies Co., Ltd., we declare that it complies with the Basic restrictions/Reference levels for electric, magnetic and electromagnetic fields as specified in following standards(s):

Nr.	Standard
1	47CFR FCC Part 1 (10-1-12 Edition)
2	RSS-102 (Issue4, March 2010)

The compliance is demonstrated based on the following calculation model assessment:

- The power density according to far-field model is:

$$S = \frac{P \times G_{(\theta,\phi)}}{4 \times \pi \times R^2}$$

Where:

- $P$  = input power of the antenna.
- $G$  = antenna gain relative to an isotropic antenna.
- $\theta, \phi$  = elevation and azimuth angles.
- $R$  = distance from the antenna to the point of investigation.

- For single or multiple RF sources, the calculated power density should comply with following:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Where:

- $s_i$  = the power density when the  $f$  is  $i$ .
- $S_{Limit,i}$  = the reference level requirement for power density when  $f$  is  $i$ .

- The calculation of the power density or safe distance is:

- NOTE 1: The RF exposure evaluation is base on the far-field and the radiation exposure is over-estimated.
- NOTE 2: The maximum output power level is taken into account as a worst case for the purpose of the calculation of power density or safe distance.
- NOTE 3: The minimum antenna feed cable loss (assumed no cable loss) is taken into account as a worst case for the purpose of the calculation of power density or safe distance.
- NOTE 4: The maximum antenna radiation exposure orientation and maximum antenna gain is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

RF Source	Calculation
RF Source #1	$f = 729.25$ to $744.75$ MHz

RF Source	Calculation
	$S_{Limit,i} = 4.86 \text{ W/m}^2$ $P = 80 \text{ W} (= 49.0 \text{ dBm, measured max})$ $G_{(\theta,\phi)} = 12.589 (= 11 \text{ dBi})$ $\theta, \phi = \text{The worst condition is considered, i.e. the max } G \text{ is used.}$ $S_i = \frac{P \times G_{(\theta,\phi)}}{4 \times \pi \times R^2} = 80.14 / R^2 \text{ W/m}^2$ $\frac{S_i}{S_{Limit,i}} = 16.48 / R^2$
RF Source(s) Combination	$\sum_i \frac{S_i}{S_{Limit,i}} = 16.48 / R^2 \leq 1$ $R \geq 4.06 \text{ m (the minimum Safe Distance)}$

Person responsible for making this declaration:

*Li Guo*

Li Guo  
 RF Engineer, EMC Lab  
 Reliability Laboratory of Huawei Technologies Co., Ltd.  
 January 14, 2014