



Declaration of Electromagnetic Field Health Compliance for RRU3232

To whom it may concern,

As to the product **RRU3232** made by Huawei Technologies Co., Ltd., we declare that it complies with the Basic restrictions/Reference levels for electric, magnetic and electromagnetic fields as specified in following standards(s):

| | |
|---|---------------------------------|
| 1 | RSS-102 (Issue4, March 2010) |
| 2 | OET Bulletin 65 (Edition 97-01) |

The compliance is demonstrated based on the following calculation model assessment:

1. The power density according to far-field model is:

$$S = \frac{P \times G_{(\theta, \phi)}}{4 \times \pi \times R^2}$$

Where:

P = input power of the antenna.

G = antenna gain relative to an isotropic antenna.

θ, ϕ = elevation and azimuth angles.

R = distance from the antenna to the point of investigation.

2. For single or multiple RF sources, the calculated power density should comply with following:

$$\sum_i \frac{S_i}{S_{Limit, i}} \leq 1$$

Where:

S_i = the power density when the f is i .

$S_{Limit, i}$ = the reference level requirement for power density when f is i .

3. The calculation of the power density or safe distance is:

NOTE 1: The RF exposure evaluation is base on the far-field and the radiation exposure is over-estimated.

NOTE 2: The maximum output power level is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 3: The minimum antenna feed cable loss (assumed no cable loss) is taken into account as a worst case for the purpose of the calculation of power density or safe distance.



NOTE 4: The maximum antenna radiation exposure orientation and maximum antenna gain is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

| RF Source | Calculation |
|-----------------------------|---|
| RF Source #1 | $f = 3650 \text{ to } 3675\text{MHz}$ |
| | $S_{Limit,i} = 10 \text{ W/m}^2$ |
| | $P = 0.0944\text{W} (= 19.75 \text{ dBm, measured max at each antenna})$ |
| | $G_{(\theta,\phi)} = 39.81 (= 16\text{dBi})$ |
| | $EIRP = P \times G_{(\theta,\phi)} = 3.758 \text{ W}$ |
| | $\theta, \phi = \text{The worst condition is considered, i.e. the max } G \text{ is used.}$ |
| | $S_i = \frac{P \times G_{(\theta,\phi)}}{4 \times \pi \times R^2} = 0.299 / R^2 \text{ W/m}^2$ |
| | $\frac{S_i}{S_{Limit,i}} = 0.0299 / R^2$ |
| RF Source #2 | (same as RF source #1) |
| RF Source #3 | (same as RF source #1) |
| RF Source #4 | (same as RF source #1) |
| RF Source(s) Combination | $\sum_i \frac{S_i}{S_{Limit,i}} = 4 \times 0.0299 / R^2 \leq 1$ $R \geq 0.35 \text{ m (the minimum Safe Distance)}$ |

Person responsible for making this declaration:

Signature : *Liang Changquan*

Print Name : Liang Changquan

Position/Title : RF Engineer

Date : May 15, 2014