



Declaration of Electromagnetic Field Health Compliance for RRU3256

To whom it may concern,

As to the product **RRU3256** made by Huawei Technologies Co., Ltd., we declare that it complies with the Basic restrictions/Reference levels for electric, magnetic and electromagnetic fields as specified in following standards(s):

1	RSS-102 (Issue4, March 2010)
2	OET Bulletin 65 (Edition 97-01)

The compliance is demonstrated based on the following calculation model assessment:

1. The power density according to far-field model is:

$$S = \frac{P \times G_{(\theta, \phi)}}{4 \times \pi \times R^2}$$

Where:

P = input power of the antenna.

G = antenna gain relative to an isotropic antenna.

θ, ϕ = elevation and azimuth angles.

R = distance from the antenna to the point of investigation.

2. For single or multiple RF sources, the calculated power density should comply with following:

$$\sum_i \frac{S_i}{S_{Limit, i}} \leq 1$$

Where:

S_i = the power density when the f is i .

$S_{Limit, i}$ = the reference level requirement for power density when f is i .

3. The calculation of the power density or safe distance is:

NOTE 1: The RF exposure evaluation is base on the far-field and the radiation exposure is over-estimated.

NOTE 2: The maximum output power level is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 3: The minimum antenna feed cable loss (assumed no cable loss) is taken into account as a worst case for the purpose of the calculation of power density or safe distance.



NOTE 4: The maximum antenna radiation exposure orientation and maximum antenna gain is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

RF Source	Calculation
RF Source #1	$f = 2496 \text{ to } 2690\text{MHz}$
	$S_{Limit,i} = 10 \text{ W/m}^2$
	$P = 29.44\text{W} (= 44.69 \text{ dBm, measured max at each antenna})$
	$G_{(\theta,\phi)} = 50.12(= 17\text{Bi})$
	$EIRP = P \times G_{(\theta,\phi)} = 1475.53\text{W}$
	$\theta, \phi = \text{The worst condition is considered, i.e. the max } G \text{ is used.}$
	$S_i = \frac{P \times G_{(\theta,\phi)}}{4 \times \pi \times R^2} = 117.42 / R^2 \text{ W/m}^2$
	$\frac{S_i}{S_{Limit,i}} = 11.742 / R^2$
RF Source #2	(same as RF source #1)
RF Source #3	(same as RF source #1)
RF Source #4	(same as RF source #1)
RF Source(s) Combination	$\sum_i \frac{S_i}{S_{Limit,i}} = 4 * 11.742 / R^2 \leq 1$ $R \geq 6.85 \text{ m (the minimum Safe Distance)}$

Person responsible for making this declaration:

Signature : *Liang Changguan*

Print Name : Liang Changguan

Position/Title : RF Engineer

Date : July 11, 2014