



Declaration of Compliance for RF Exposure Evaluation

To whom it may concern,

As to the product **RRU3279** made by Huawei Technologies Co., Ltd. as the applicant and Huawei Technologies Co., Ltd. as the manufacturer, we declare that it complies with the following standards(s):

- 47CFR FCC Part 1 & OET Bulletin 65

The compliance is demonstrated based on the following calculation model assessment:

1. The power density according to far-field model is:

$$S = \frac{P \times G_{(\theta, \phi)}}{4 \times \pi \times R^2}$$

Where:

- P = input power of the antenna.
- G = antenna gain relative to an isotropic antenna.
- θ, ϕ = elevation and azimuth angles.
- R = distance from the antenna to the point of investigation.

2. For single or multiple RF sources, the calculated power density should comply with following:

$$\sum_i \frac{S_i}{S_{Limit, i}} \leq 1$$

Where:

- S_i = the power density when the f is i .
- $S_{Limit, i}$ = the reference level requirement for power density when f is i .
- f = operating frequency.

3. The calculation of the power density or safe distance is:

NOTE 1: The RF exposure evaluation is base on the far-field and the radiation exposure is over-estimated.

NOTE 2: The maximum output power level is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 3: The minimum antenna feed cable loss (assumed no cable loss) is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 4: The maximum antenna radiation exposure orientation and maximum antenna gain is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

RF Source	Calculation for Individual Source		
RF Source #1	f	= <u>2496</u> to <u>2690</u> MHz	
	$S_{Limit,i}$	= <u>10</u> W/m ² (for General Public Use)	
	P , $G_{(\theta,\phi)}$	=	<input type="checkbox"/> $EIRP$ (= $P \times G_{(\theta,\phi)}$): $EIRP^{(*)}$ = _____ W (= _____ dBm, all ports)
		=	<input checked="" type="checkbox"/> $P \times G_{(\theta,\phi)}$: $P^{(*)}$ = <u>21.73</u> W (= <u>43.37</u> dBm, per port) $G_{(\theta,\phi)}$ = <u>50.12</u> (= <u>17</u> dBi)
			(*): The value is from: <input checked="" type="checkbox"/> measured max (See relevant RF report), <input type="checkbox"/> rated + declared tolerance, <input type="checkbox"/> max allowed by RF standard. And, the transmission duty cycle is: <input type="checkbox"/> ignored, <input checked="" type="checkbox"/> used, that is: <u>100</u> % (for mode: <u>QPSK</u>).
	θ, ϕ	=	The worst condition is considered, i.e. the max G is used.
	S_i	=	$\frac{P \times G_{(\theta,\phi)}}{4 \times \pi R^2} = \underline{86.67} / R^2$ W/m ²
$\frac{S_i}{S_{Limit,i}}$	=	<u>8.667</u> / R^2	
RF Source #2	(same as RF source #1)		
RF Source #3	(same as RF source #1)		
RF Source #4	(same as RF source #1)		
RF Source #5	(same as RF source #1)		
RF Source #6	(same as RF source #1)		
RF Source #7	(same as RF source #1)		
RF Source #8	(same as RF source #1)		
RF Sources	Calculation for Simultaneous Transmission Sources		
Whole Product	$\sum_i \frac{S_i}{S_{Limit,i}}$	= <u>8*8.667</u> / R^2	
	R	≥ <u>8.33</u> m (the minimum Safe Distance)	
	NOTE: The result is the worst case of each individual source and simultaneous transmission sources (if applicable).		



Beyond the calculated safe distance showed above:

Considering the lower RF field exposure levels and relevant research results collected to date by international organizations, there is no convincing scientific evidence that the RF signals from this product cause adverse effects on human health.

Person responsible for making this declaration:

Liang Changguan
RF Engineer, EMC Lab
Reliability Laboratory of Huawei Technologies Co., Ltd.
June 17, 2015