

TESTING CERT #2174.01

FCC RF Test Report

**Product Name: HSPA /UMTS/GPRS/GSM/EDGE
Mobile Phone**

Product Model: HUAWEI U8686, U8686

Report Number: SYBH(Z-RF)006122012-2002

FCC ID: QISU8686

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C

Tel: +86 755 28780808

Fax: +86 755 89652518

Notice

1. The laboratory has Passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.
2. The laboratory has Passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01.
3. The laboratory has been listed by the US Federal Communications Commission to perform electromagnetic emission measurements. The site recognition number is 97456.
4. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 6369A-2.
5. The laboratory has been listed by the VCCI to perform EMC measurements. The accreditation numbers of test site No.1 are R-2364, G-415, C-2583, and T-256, and the accreditation numbers of test site No.2 are R-3760, G-485, C-4210 and T-1237.
6. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. The test report is only valid for the test samples.
9. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



Applicant: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District, Shenzhen, 518129, P.R.C

Date of Receipt Sample: 2012-12-06
Start Date of Test: 2012-12-07
End Date of Test: 2012-12-14

Test Result: Pass

Approved by Senior Engineer:	2013-1-17	Dai Linjun	
	Date	Name	Signature

Prepared by:	2013-1-17	Feng Nianwei	
	Date	Name	Signature



Modification Record

No.	Last Report No.	Modification Description
		First report



CONTENT

1	General Information	6
1.1	Applied Standard	6
1.2	Test Location	6
1.3	Test Environment Condition	6
2	Test Summary	7
3	Description of the Equipment under Test (EUT)	8
3.1	General Description	8
3.2	EUT Identity	8
3.3	Technical Description	9
4	General Test Conditions / Configurations	10
4.1	EUT Configurations	10
4.2	Test Environments	11
4.3	Test Setups	12
4.4	Test Conditions	15
5	Main Test Instruments	17
6	Main Test Instruments	错误！未定义书签。



1 General Information

1.1 Applied Standard

Applied Rules: 47 CFR FCC Part 2, Subpart J (2011-10-1 Edition)
47 CFR FCC Part 15, Subpart C (2011-10-1 Edition)

Test Method: FCC PUBLIC NOTICE DA 00-705 Filing and Measurement Guidelines for
Frequency Hopping Spread Spectrum Systems (Released March 30, 2000)

ANSI C63.4-2003/-2009, American National Standard for Methods of
Measurement of Radio-Noise Emissions from Low-Voltage Electrical and
Electronic Equipment in the Range of 9 kHz to 40 GHz.

ANSI C63.10-2009, American National Standard for Testing Unlicensed
Wireless Devices.

1.2 Test Location

Test Location 1: Reliability Laboratory of Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.3 Test Environment Condition

Ambient Temperature: 19.5 to 25 °C
Ambient Relative Humidity: 45 to 55 %
Atmospheric Pressure: Not applicable

2 Test Summary

Test Item	FCC Part No.	IC Standard No.	Requirements	Test Result	Verdict (NOTE)
20dB Emission Bandwidth (EBW)	15.247(a)(1)	RSS-210 A8.1(a)	No limit.	Appendix A	Pass
Carrier Frequency Separation	15.247(a)(1)	RSS-210 A8.1(b)	$\geq \text{MAX} \{25\text{kHz}, \text{IIF}\{\text{output power} \leq 125\text{mW}, 2/3 \times 20\text{dB EBW}, 20\text{dB EBW}\}\}$.	Appendix B	Pass
Number of Hopping Channel	15.247(a)(1)(iii)	RSS-210 A8.1(d)	≥ 15 channels.	Appendix C	Pass
Time of Occupancy (Dwell Time)	15.247(a)(1)(iii)	RSS-210 A8.1(d)	$< 0.4\text{s}$ within a period of $(0.4\text{s} \times \text{hopping number})$.	Appendix D	Pass
Maximum Peak Conducted Output Power	15.247(b)(1)	RSS-210 A8.4(2)	$< 1\text{ W}$ if using ≥ 75 non-overlapping channels.	Appendix E	Pass
Band edge spurious emission	15.247(d)	RSS-210, A8.5	$< -20\text{ dBm}/100\text{ kHz}$ if total peak power $\leq$ power limit.	Appendix F	Pass
Conducted RF Spurious Emission				Appendix G	
Radiated Emissions in the Restricted Bands	15.247(d) 15.209	RSS-210, A8.5 RSS-210, 2.2 RSS-Gen, 7.2.2 RSS-Gen, 7.2.5	FCC Part 15.209 field strength limit; RSS-Gen 7.2.5 field strength limit.	Appendix H	Pass
Receiver Spurious Emissions	---	RSS-210, 2.3 RSS-Gen, 6.1	RSS-Gen 6.1 radiated limit.	-----	N/T
AC Power Line Conducted Emissions	15.207	RSS-Gen, 7.2.4	FCC Part 15.207 conducted limit; RSS-Gen, 7.2.4 conducted limit.	Appendix I	Pass
NOTE: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".					

3 Description of the Equipment under Test (EUT)

3.1 General Description

HUAWEI U8686, U8686 is subscriber equipment in the WCDMA/GSM system. The HSPA/UMTS frequency band is Band II and Band IV and Band V. The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900. The Mobile Phone implements such functions as RF signal receiving/transmitting, HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS, AGPS and WIFI etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

3.2 EUT Identity

NOTE: Unless otherwise noted in the report, the functional boards installed in the units shall be selected from the below list, but not means all the functional boards listed below shall be installed in one unit.

3.2.1 Board

Hardware V	Board	
	Serial	Description
HD1H867GM	C9F01A92B1000431	Broadband Control Card

3.2.2 Adapter

AC/DCAdapter Model	HW-050055U1W
Manufacturer	Huawei Technologies Co., Ltd.
Input Voltage	~100-240V 50/60Hz 0.2A
Output Voltage	5V  550mA
Rated Power	2.75W

3.2.3 Battery

Name	Qty.	Manufacture	Description
Rechargeable Li-ion	1	Huawei Technologies Co., Ltd.	Battery Model: HB4W1H Rated capacity: 1750mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V

3.3 Technical Description

Characteristics	Description	
TX/RX Operating Range	2400-2483.5 MHz band	$f_c = 2402 \text{ MHz} + N * 1 \text{ MHz}$, where: - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 0 to 78.
	Carrier	Frequency Hopping Spread Spectrum (FHSS)
Modulation Type	Digital	GFSK, $\pi/4$ -DQPSK, 8DPSK
	Emission Designator	
Emission Designator	GFSK: 1M02GXD	
	$\pi/4$ -DQPSK: 1M34GXD	
	8DPSK: 1M31GXD	
Bluetooth Power Class	Class 1,	

4 General Test Conditions / Configurations

4.1 EUT Configurations

4.1.1 General Configurations

Configuration	Description
Test Antenna Ports	Until otherwise specified, - All TX tests are performed at all TX antenna ports of the EUT, and - All RX tests are performed at all RX antenna ports of the EUT.
Multiple RF Sources	Other than the tested RF source of the EUT, other RF source(s) are disabled or shutdown during measurements.

4.1.2 Customized Configurations

# EUT Conf.	Signal Description	Operating Frequency
TM1_DH5_Hop	GFSK modulation, package type DH5, hopping on.	---
TM1_DH5_Ch0	GFSK modulation, package type DH5, hopping off.	Ch No. 0 / 2402 MHz
TM1_DH5_Ch39	GFSK modulation, package type DH5, hopping off.	Ch No. 39 / 2441 MHz
TM1_DH5_Ch78	GFSK modulation, package type DH5, hopping off.	Ch No. 78 / 2480 MHz
TM2_2DH5_Hop	$\pi/4$ -DQPSK modulation, package type 2DH5, hopping on.	---
TM2_2DH5_Ch0	$\pi/4$ -DQPSK modulation, package type 2DH5, hopping off.	Ch No. 0 / 2402 MHz
TM2_2DH5_Ch39	$\pi/4$ -DQPSK modulation, package type 2DH5, hopping off.	Ch No. 39 / 2441 MHz
TM2_2DH5_Ch78	$\pi/4$ -DQPSK modulation, package type 2DH5, hopping off.	Ch No. 78 / 2480 MHz
TM3_3DH5_Hop	8DPSK modulation, package type 3DH5, hopping on.	---
TM3_3DH5_Ch0	8DPSK modulation, package type 3DH5, hopping off.	Ch No. 0 / 2402 MHz
TM3_3DH5_Ch39	8DPSK modulation, package type 3DH5, hopping off.	Ch No. 39 / 2441 MHz
TM3_3DH5_Ch78	8DPSK modulation, package type 3DH5, hopping off.	Ch No. 78 / 2480 MHz
RX	Receiver Continues Receiving mode.	Ch No. 39 / 2441 MHz



4.2 Test Environments


NOTE: The values used in the test report may be stringent than the declared.

Environment Parameter	Selected Values During Tests		
	Temperature	Voltage	Relative Humidity
NTNV	Ambient	3.7 VDC	Ambient

4.3 Test Setups

4.3.1 Test Setup 1


The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by Bluetooth System Simulator and/or PC/software to emit the specified signals for the purpose of measurements.




4.3.2 Test Setup 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.4. The test distance is 3m. The setup is according to ANSI C63.4 and CAN/CSA-CEI/IEC CISPR 22.

The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).



(Below 1 GHz)




(Above 1 GHz)

4.3.3 Test Setup 3

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.



4.4 Test Conditions

Test Case	Test Conditions	
	Configuration	Description
20dB Emission Bandwidth (EBW)	Meas. Method	DA 00-705
	Test Env.	NTNV
	Test Setup	Test Setup 1
	EUT Conf.	TM1_DH5_Ch0, TM1_DH5_Ch39, TM1_DH5_Ch78, TM2_DH5_Ch0, TM2_DH5_Ch39, TM2_DH5_Ch78, TM3_DH5_Ch0, TM3_DH5_Ch39, TM3_DH5_Ch78.
Carrier Frequency Separation	Meas. Method	DA 00-705
	Test Env.	NTNV
	Test Setup	Test Setup 1
	EUT Conf.	TM1_DH5_Hop, TM2_DH5_Hop, TM3_DH5_Hop.
Number of Hopping Channel	Meas. Method	DA 00-705
	Test Env.	NTNV
	Test Setup	Test Setup 1
	EUT Conf.	TM1_DH5_Hop, TM2_DH5_Hop, TM3_DH5_Hop.
Time of Occupancy (Dwell Time)	Meas. Method	DA 00-705
	Test Env.	NTNV
	Test Setup	Test Setup 1
	EUT Conf.	TM1_DH5_Ch39, TM2_DH5_Ch39, TM3_DH5_Ch39.
Maximum Peak Conducted Output Power	Meas. Method	DA 00-705
	Test Env.	NTNV
	Test Setup	Test Setup 1
	EUT Conf.	TM1_DH5_Ch0, TM1_DH5_Ch39, TM1_DH5_Ch78, TM2_DH5_Ch0, TM2_DH5_Ch39, TM2_DH5_Ch78, TM3_DH5_Ch0, TM3_DH5_Ch39, TM3_DH5_Ch78.
Conducted RF Spurious Emission	Meas. Method	DA 00-705
	Test Env.	NTNV
	Test Setup	Test Setup 1
	EUT Conf.	TM1_DH5_Ch0, TM1_DH5_Ch39, TM1_DH5_Ch78, TM2_DH5_Ch0, TM2_DH5_Ch39, TM2_DH5_Ch78, TM3_DH5_Ch0, TM3_DH5_Ch39, TM3_DH5_Ch78.
Radiated Emissions in the Restricted	Meas. Method	DA 00-705, C63.4, C63.10. (1) 30 MHz to 1 GHz:

Test Case	Test Conditions	
	Configuration	Description
Bands		Pre: RBW = 100 kHz; VBW = 300 kHz; Det. = Peak. Final: RBW = 120 kHz; Det. = CISPR Quasi-Peak. (2) 1 GHz to 26.5 GHz: Average: RBW = 1 MHz; VBW = 10 Hz; Det. = Peak; Sweep-time = Auto; Trace = Single. Peak: RBW = 1 MHz; VBW = 3 MHz; Det. = Peak; Sweep-time = Auto; Trace $\geq$ Max Hold * 100.
	Test Env.	NTNV
	Test Setup	Test Setup 2
	EUT Conf.	30 MHz -1 GHz TM1_DH5_Ch0 (Worst Conf.).
		1-3 GHz TM1_DH5_Ch0, TM1_DH5_Ch39, TM1_DH5_Ch78, TM2_DH5_Ch0, TM2_DH5_Ch39, TM2_DH5_Ch78, TM3_DH5_Ch0, TM3_DH5_Ch39, TM3_DH5_Ch78.
		3-18 GHz TM1_DH5_Ch0 (Worse Conf.), TM1_DH5_Ch39 (Worse Conf.), TM1_DH5_Ch78 (Worse Conf.).
		18-26.5 GHz TM1_DH5_Ch0 (Worst Conf.).
Receiver Spurious Emissions	Meas. Method	☐ Antenna-conducted, ☐ Radiated. NOTE: If the receiver has a detachable antenna of known impedance, antenna conducted spurious emissions measurement is permitted as an alternative to radiated measurement. However, the radiated method is recommended. The antenna conducted test shall be performed with the antenna disconnected and the receiver antenna terminals connected to a measuring instrument having equal impedance to that specified for the antenna. (1) 30 MHz to 1 GHz: Pre: RBW = 100 kHz; VBW = 300 kHz; Det. = Peak. Final: RBW = 120 kHz; Det. = CISPR Quasi-Peak. (2) 1 GHz to 8 GHz: Pre: RBW = 1 MHz; VBW = 3 MHz; Det. = Peak. Final: RBW = 1 MHz; Det. = Average.
	Test Env.	NTNV
	Test Setup	Test Setup 2
	EUT Conf.	RX.
AC Power Line Conducted Emissions	Meas. Method	AC mains conducted. Pre: RBW = 10 kHz; Det. = Peak. Final: RBW = 9 kHz; Det. = CISPR Quasi-Peak & Average.
	Test Env.	NTNV
	Test Setup	Test Setup 3
	EUT Conf.	TM1_DH5_Ch39.

5 Main Test Instruments

NOTE: Unless otherwise specified, the calibration intervals for test instruments were Annual (per year). The other intervals, if applicable, are marked with (##y), which denotes ## years calibration interval.

Equipment Name	Manufacturer	Model	Serial Number	Cal Date	Cal. Due
Power supply	KEITHLEY	2303	1288003	2012-11-09	2013-11-08
Wireless Communication Test set	Agilent	N4010A	MY49081592	2012-11-09	2013-11-08
Spectrum Analyzer	Agilent	E4440A	MY48250119	2012-07-18	2013-07-17
Signal Analyzer	R&S	FSQ31	200021	2012-11-09	2013-11-08
Spectrum Analyzer	Agilent	N9030A	MY49431698	2012-11-09	2013-11-08
Temperature Chamber	WEISS	WKL64	24600294	2012-02-14	2013-02-13
Signal generator	Agilent	E8257D	MY49281095	2012-07-10	2013-07-09
Test receiver	R&S	ESU26	100150	2012-09-30	2013-09-29
Spectrum analyzer	R&S	FSU3	200474	2012-03-06	2013-03-05
Spectrum analyzer	R&S	FSU43	100144	2012-04-06	2013-04-05
Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	100304	2012-04-06	2013-04-05
Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	100391	2012-07-18	2013-07-17
Trilog Broadband Antenna (30M~3GHz)	SCHWARZBECK	VULB 9163	9163-521	2012-02-28	2013-02-27
Pyramidal Horn Antenna(26GHz-40GHz)	ETS-Lindgren	3160-10	00123940	2012-02-28	2013-02-27
Pyramidal Horn Antenna(18GHz-26.5GHz)	ETS-Lindgren	3160-09	00125912	2012-02-28	2013-02-27
EMI Test receiver	R&S	ESCI	101163	2012-03-06	2013-03-05
Artificial Mains Network	R&S	ENV216	100382	2012-03-22	2013-03-21
LOOP Antennas(9kHz-30MHz)	R&S	HFH2-Z2	100263	2012-3-11	2013-3-10

END



Appendix for Test report



CONTENT

APPENDIX A: 20DB EMISSION BANDWIDTH (EBW)	5
1 RESULT TABLE	6
2 TEST PLOT	7
2.1 TM1_DH5_CH0	7
2.2 TM1_DH5_CH39	8
2.3 TM1_DH5_CH78	9
2.4 TM2_2DH5_CH0	10
2.5 TM2_2DH5_CH39	11
2.6 TM2_2DH5_CH78	12
2.7 TM3_3DH5_CH0	13
2.8 TM3_3DH5_CH39	14
2.9 TM3_3DH5_CH78	15
APPENDIX B: CARRIER FREQUENCY SEPARATION	16
1 RESULT TABLE	17
2 TEST PLOT	18
2.1 TM1_DH5_HOP	18
2.2 TM2_2DH5_HOP	19
2.3 TM3_3DH5_HOP	20
APPENDIX C: NUMBER OF HOPPING CHANNEL	21
1 RESULT TABLE	22
2 TEST PLOT	23
2.1 TM1_DH5_HOP	23
2.2 TM2_2DH5_HOP	24
2.3 TM3_3DH5_HOP	25
APPENDIX D: TIME OF OCCUPANCY (DWELL TIME)	26
1 RESULT TABLE	27
2 TEST PLOT	28
2.1 TM1_DH5_CH39	28
2.2 TM2_2DH5_CH39	29
2.3 TM3_3DH5_CH39	30
APPENDIX E: MAXIMUM PEAK CONDUCTED OUTPUT POWER	31
1 RESULT TABLE	32
2 TEST PLOT	33
2.1 TM1_DH5_CH0	33
2.2 TM1_DH5_CH39	34



2.3	TM1_DH5_CH78.....	35
2.4	TM2_2DH5_CH0.....	36
2.5	TM2_2DH5_CH39.....	37
2.6	TM2_2DH5_CH78.....	38
2.7	TM3_3DH5_CH0.....	39
2.8	TM3_3DH5_CH39.....	40
2.9	TM3_3DH5_CH78.....	41

APPENDIX F: BAND EDGE SPURIOUS EMISSION 42

1 RESULT TABLE 43

2 TEST PLOT 44

2.1	TM1_DH5_CH0.....	44
2.2	TM1_DH5_CH78.....	46
2.3	TM2_2DH5_CH0.....	48
2.4	TM2_2DH5_CH78.....	50
2.5	TM3_3DH5_CH0.....	52
2.6	TM3_3DH5_CH78.....	54

APPENDIX G: CONDUCTED RF SPURIOUS EMISSION 56

1 RESULT TABLE 57

2 TEST PLOT 58

2.1	TM1_DH5_CH0.....	58
2.1.1	Pref.....	58
2.1.2	Puw.....	59
2.2	TM1_DH5_CH39.....	65
2.2.1	Pref.....	65
2.2.2	Puw.....	66
2.3	TM1_DH5_CH78.....	72
2.3.1	Pref.....	72
2.3.2	Puw.....	73
2.4	TM2_2DH5_CH0.....	79
2.4.1	Pref.....	79
2.4.2	Puw.....	80
2.5	TM2_2DH5_CH39.....	86
2.5.1	Pref.....	86
2.5.2	Puw.....	87
2.6	TM2_2DH5_CH78.....	93
2.6.1	Pref.....	93
2.6.2	Puw.....	94
2.7	TM3_3DH5_CH0.....	100
2.7.1	Pref.....	100
2.7.2	Puw.....	101
2.8	TM3_3DH5_CH39.....	107



2.8.1	Pref	107
2.8.2	PuW	108
2.9	TM3_3DH5_Ch78.....	114
2.9.1	Pref	114
2.9.2	PuW	115
APPENDIX H: RADIATED EMISSIONS IN THE RESTRICTED BANDS.....		121
3	TEST MODE:	124
3.1	CHANNEL 00	124
3.2	CHANNEL 78	125
APPENDIX I: CONDUCTED EMISSION AT POWER PORT		127
APPENDIX J: PHOTOS OF TEST SETUP		错误！未定义书签。



Appendix A: 20dB Emission Bandwidth (EBW)




1 Result Table

EUT Conf.	EBW [MHz]	Verdict
TM1_DH5_Ch0	0.948	Pass
TM1_DH5_Ch39	0.950	Pass
TM1_DH5_Ch78	1.017	Pass
TM2_2DH5_Ch0	1.335	Pass
TM2_2DH5_Ch39	1.335	Pass
TM2_2DH5_Ch78	1.336	Pass
TM3_3DH5_Ch0	1.310	Pass
TM3_3DH5_Ch39	1.310	Pass
TM3_3DH5_Ch78	1.310	Pass




2 Test Plot

2.1 TM1_DH5_Ch0






2.2 TM1_DH5_Ch39






2.3 TM1_DH5_Ch78






2.4 TM2_2DH5_Ch0






2.5 TM2_2DH5_Ch39






2.6 TM2_2DH5_Ch78




2.7 TM3_3DH5_Ch0






2.8 TM3_3DH5_Ch39



2.9 TM3_3DH5_Ch78





Appendix B: Carrier Frequency Separation




1 Result Table

EUT Conf.	Carrier Frequency Separation [MHz]	Verdict
TM1_DH5_Hop	1.050	Pass
TM2_2DH5_Hop	0.950	Pass
TM3_3DH5_Hop	1.100	Pass




2 Test Plot

2.1 TM1_DH5_Hop






2.2 TM2_2DH5_Hop



2.3 TM3_3DH5_Hop





Appendix C: Number of Hopping Channel




1 Result Table

EUT Conf.	Number of Hopping Channel	Verdict
TM1_DH5_Hop	79	Pass
TM2_2DH5_Hop	79	Pass
TM3_3DH5_Hop	79	Pass


2 Test Plot

2.1 TM1_DH5_Hop






2.2 TM2_2DH5_Hop



2.3 TM3_3DH5_Hop



Appendix D: Time of Occupancy (Dwell Time)

1 Result Table

The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:


- The duration for dwell time calculation: $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 79 \text{ [ch]} = 31.6 \text{ [s*ch]}$;
- The burst width [ms/hop/ch], which is directly measured, refers to the duration on one channel hop.
- The hops per second for all channels: The selected EUT Conf uses a slot type of 5-Tx&1-Rx and a hopping rate of 1600 [ch*hop/s] for all channels. So the final hopping rate for all channels is $1600 / 6 = 266.67 \text{ [ch*hop/s]}$;
- The hops per second on one channel: $266.67 \text{ [ch*hop/s]} / 79 \text{ [ch]} = 3.38 \text{ [hop/s]}$;
- The total hops for all channels within the dwell time calculation duration: $3.38 \text{ [hop/s]} * 31.6 \text{ [s*ch]} = 106.67 \text{ [hop*ch]}$;
- The dwell time for all channels hopping: $106.67 \text{ [hop*ch]} * \text{Burst Width [ms/hop/ch]}$.

EUT Conf.	Burst Width [ms/hop/ch]	Total Hops [hop*ch]	Dwell Time [ms]	Verdict
TM1_DH5_Ch39	2.900	106.67	0.309	Pass
TM2_2DH5_Ch39	2.900	106.67	0.309	Pass
TM3_3DH5_Ch39	2.900	106.67	0.309	Pass


2 Test Plot

NOTE: The test plots are only for Burst Width measurements.

2.1 TM1_DH5_Ch39




2.2 TM2_2DH5_Ch39





2.3 TM3_3DH5_Ch39





Appendix E: Maximum Peak Conducted Output Power




1 Result Table

EUT Conf.	Max. Peak Power [dBm]	Verdict
TM1_DH5_Ch0	5.97	Pass
TM1_DH5_Ch39	7.48	Pass
TM1_DH5_Ch78	7.65	Pass
TM2_2DH5_Ch0	5.77	Pass
TM2_2DH5_Ch39	7.25	Pass
TM2_2DH5_Ch78	7.41	Pass
TM3_3DH5_Ch0	6.23	Pass
TM3_3DH5_Ch39	8.14	Pass
TM3_3DH5_Ch78	7.91	Pass


2 Test Plot

2.1 TM1_DH5_Ch0






2.2 TM1_DH5_Ch39






2.3 TM1_DH5_Ch78






2.4 TM2_2DH5_Ch0






2.5 TM2_2DH5_Ch39






2.6 TM2_2DH5_Ch78






2.7 TM3_3DH5_Ch0






2.8 TM3_3DH5_Ch39





2.9 TM3_3DH5_Ch78





Appendix F: Band edge spurious emission

1 Result Table


EUT Conf.	Channel No.	Carrier Frequency [MHz]	Carrier Power [dBm]	Frequency Hopping	Max. Spurious Level [dBm]	Limit [dBm]	Result
TM1_DH5_Ch0	0	2402	5.75	Off	-47.97	-14.25	Pass
	-	-	5.47	On	-49.53	-14.52	Pass
TM1_DH5_Ch78	78	2480	7.34	Off	-47.57	-12.71	Pass
	-	-	7.05	On	-49.09	-13.00	Pass
TM2_2DH5_Ch0	0	2402	3.41	Off	-50.14	-16.62	Pass
	-	-	2.87	On	-50.82	-17.13	Pass
TM2_2DH5_Ch78	78	2480	4.76	Off	-49.07	-15.24	Pass
	-	-	2.83	On	-52.93	-17.23	Pass
TM3_3DH5_Ch0	0	2402	3.39	Off	-49.86	-16.64	Pass
	-	-	2.82	On	-51.82	-17.25	Pass
TM3_3DH5_Ch78	78	2480	4.78	Off	-49.18	-15.22	Pass
	-	-	4.78	On	-52.44	-15.21	Pass




2 Test Plot

2.1 TM1_DH5_Ch0

No hopping




With hopping




2.2 TM1_DH5_Ch78

No hopping




With hopping




2.3 TM2_2DH5_Ch0

No hopping




With hopping




2.4 TM2_2DH5_Ch78

No hopping




With hopping




2.5 TM3_3DH5_Ch0

No hopping




With hopping




2.6 TM3_3DH5_Ch78

No hopping



With hopping





Appendix G: Conducted RF Spurious Emission

1 Result Table

In this Appendix, the “Pref” refers to the peak power level in any 100 kHz bandwidth within the fundamental emission which is used as the reference level, the “Puw” refers to the maximum emission power in 100 kHz band segments outside of the authorized frequency band.

Considering that the higher ratio of RBW to the span for the frequency ranges below 30 MHz makes the results determination be complicated, a narrower RBW other than 100 kHz is used for these ranges. The measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \times \lg(100 [kHz]/\text{narrower RBW [kHz]})$. As to this Appendix, the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

In the result table, the “< Limit” denotes that “The Puw [dBm] is less than Pref [dBm] - 20 [dB], see test plots for detailed”.


EUT Conf.	Pref [dBm/100 kHz]	Puw [dBm/100 kHz]	Verdict
TM1_DH5_Ch0	6.74	< Limit	Pass
TM1_DH5_Ch39	7.58	< Limit	Pass
TM1_DH5_Ch78	8.60	< Limit	Pass
TM2_2DH5_Ch0	4.29	< Limit	Pass
TM2_2DH5_Ch39	5.15	< Limit	Pass
TM2_2DH5_Ch78	6.02	< Limit	Pass
TM3_3DH5_Ch0	4.29	< Limit	Pass
TM3_3DH5_Ch39	5.18	< Limit	Pass
TM3_3DH5_Ch78	5.44	< Limit	Pass



2 Test Plot


2.1 TM1_DH5_Ch0


2.1.1 Pref








2.1.2 Puw


















2.2 TM1_DH5_Ch39


2.2.1 Pref








2.2.2 Puw


















2.3 TM1_DH5_Ch78


2.3.1 Pref








2.3.2 Puw


















2.4 TM2_2DH5_Ch0


2.4.1 Pref








2.4.2 Puw


















2.5 TM2_2DH5_Ch39


2.5.1 Pref








2.5.2 Puw


















2.6 TM2_2DH5_Ch78


2.6.1 Pref








2.6.2 Puw


















2.7 TM3_3DH5_Ch0


2.7.1 Pref








2.7.2 Puw


















2.8 TM3_3DH5_Ch39


2.8.1 Pref








2.8.2 Puw


















2.9 TM3_3DH5_Ch78


2.9.1 Pref








2.9.2 Puw

















Appendix H: Radiated Emissions in the Restricted Bands

Part 1: Testing Range of “30 MHz to 1 GHz”


- Note 1: The test results and plot for testing range of “30 MHz to 1 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.
- Note 2: The emissions in this range are mainly from the Platform Device (Notepad PC and its ancillary components).



Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Plarization
35.340000	26.80	15.0	40.0	13.2	100.0	360.00	VERTICAL
51.660000	21.90	14.9	40.0	18.1	100.0	29.00	VERTICAL
104.040000	23.80	13.5	43.5	19.7	126.0	107.00	VERTICAL
169.080000	18.00	10.6	43.5	25.5	102.0	106.00	VERTICAL
277.440000	21.90	14.7	46.0	24.1	104.0	339.00	HORIZONTAL
657.060000	29.70	21.9	46.0	16.3	185.0	339.00	HORIZONTAL

Part 2: Testing Range of “18 GHz to 26.5 GHz”

Note: No peak found in pre- test.




Part 3: Testing Range of “2.3GHz to 2.5GHz”

- Note 1: The testing range of “2.3 GHz to 2.5 GHz” is for checking radiated emissions located in restricted bands near the EUT operating bands.
- Note 2: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).
- Note 3: The peak spike exceeds the limit line is EUT’s operating frequency.

3 Test Mode:

3.1 Channel 00



Note: The peak exceeds the limit line is carrier frequency.


MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	59.80	34.8	74.0	14.2	112.0	272.00	HORIZONTAL
2483.500000	59.50	35.1	74.0	14.5	131.0	359.00	VERTICAL

MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	48.80	34.8	54.0	5.2	129.0	171.00	HORIZONTAL
2483.500000	48.70	35.1	54.0	5.3	150.0	216.00	VERTICAL

3.2 Channel 78



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	59.30	34.8	74.0	14.7	102.0	252.00	VERTICAL
2483.500000	59.60	35.1	74.0	14.4	102.0	234.00	HORIZONTAL

MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	48.80	34.8	54.0	5.2	124.0	230.00	HORIZONTAL
2483.500000	48.20	35.1	54.0	5.8	113.0	283.00	HORIZONTAL

Part 4: Testing Range of “1 GHz to 18 GHz”

- Note 1: The test results and plot for testing range of “1 GHz to 18 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.
- Note 2: The testing range of “1 GHz to 18 GHz” is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.
- Note 3: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Height cm	Azimuth deg	Polarization
4959.600000	57.0	-1.8	74.0	17	100.0	345.00	VERTICAL


MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Height cm	Azimuth deg	Polarization
4960.100000	39	-1.8	54.0	15	100.0	346.00	VERTICAL



Appendix I: AC Power Line Conducted Emissions

Channel 40



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.151858	41.6	9.7	65.9	24.3	L1	FLO
0.314558	41.7	9.7	59.8	18.1	L1	FLO
0.516330	40.8	9.7	56.0	15.2	N	FLO
0.834078	41.1	9.7	56.0	14.9	N	FLO
1.295224	40.1	9.7	56.0	15.9	L1	FLO
1.890401	40.3	9.7	56.0	15.7	N	FLO

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.185761	38.0	9.7	54.2	16.2	N	FLO
0.330555	37.3	9.7	49.4	12.1	N	FLO
0.588713	33.0	9.7	46.0	13.0	N	FLO
0.833032	34.1	9.7	46.0	11.9	N	FLO
1.197191	33.3	9.7	46.0	12.7	N	FLO
1.882556	33.1	9.7	46.0	12.9	N	FLO

END