



FCC RF Test Report

**Product Name: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone
with Bluetooth; HUAWEI Ascend G 300+**

Model Number: HUAWEI U8815-71,U8815-71

**Report No: SYBH(Z-RF)021092012-2001
FCC ID:QISU8815-71**

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Applicant: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Date of Receipt Test Item: Sept., 21, 2012
Start Date of Test: Sept., 23, 2012
End Date of Test: Sept., 29, 2012

Test Result: Pass

Approved By Senior Engineer Sept., 29, 2012 Dai Linjun
Date Name Signature

Reviewed By Sept., 29, 2012 Cousy Xu
Date Name Signature

Operator Sept., 29, 2012 Huang Qiuliang
Date Name Signature

Contents

1	<u>General Information</u>	5
1.1	APPLIED STANDARD	5
1.2	TEST LOCATION	5
1.3	TEST ENVIRONMENT CONDITION	5
2	<u>Summary</u>	6
3	<u>Product Description</u>	7
3.1	PRODUCTION INFORMATION	7
4	<u>Test Description</u>	10
4.1	SUPPORTED FREQUENCY RANGE	10
4.2	TRANSMITTER / RECEIVER CHARACTERISTICS	10
4.3	ANTENNA GAIN	10
4.4	POWER SUPPLY	10
5	<u>General Test Conditions / Configurations</u>	11
5.1	RF CHANNELS UNDER TEST	11
5.2	TEST MODES	11
5.3	TEST ENVIRONMENTS	11
5.4	TEST SETUPS	12
5.5	TEST CONDITIONS	14
6	<u>Main Test Instruments</u>	16
7	<u>Test Results</u>	17
8	<u>Measurement Uncertainty</u>	17

1 General Information

1.1 Applied Standard

Applied Rules:	47 CFR FCC Part 2:2010, Subpart J 47 CFR FCC Part 22:2010, Subpart H ANSI/TIA 603C:2004
----------------	---

1.2 Test Location

Test Location 1:	Reliability Laboratory of Huawei Technologies Co., Ltd.
Address:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.3 Test Environment Condition

Ambient Temperature:	20 – 25 °C
Ambient Relative Humidity:	45 – 55 %
Atmospheric Pressure:	101 kPa

2 Summary

Table 1 Summary of results

Test Case	FCC Part No.	Requirements	Result
Cellular Band			
Transmitter Output Power	2.1046 & 22.913	ERP not exceed 7 W	Pass
Modulation Characteristics	2.1047	Digital modulation	Pass
Occupied Bandwidth	2.1049	(Not specified)	Pass
Band Edges Compliance	2.1051 & 917	Below -13 dBm/1%*EBW, in 1 MHz range	Pass
Spurious Emission at Antenna Terminals	2.1051 & 2.917	Below -13 dBm/1 kHz, 9 kHz to 150 kHz Below -13 dBm/10 kHz, 150 kHz to 30 MHz Below -13 dBm/100 kHz, 30 MHz to 10 th harmonics	Pass
Field Strength of Spurious Radiation	2.1053 & 22.917	Below -13 dBm/100 kHz	Pass
Frequency Stability	2.1055 & 22.355	Maintained within the tolerances of ± 2.5 ppm	Pass

3 Product Description

3.1 Production Information

3.1.1 General Description

HUAWEI U8815-71, U8815-71 is subscriber equipment in the WCDMA/GSM system. The HSPA/UMTS frequency band is Band I and Band VIII and Band V, but only band V test data included in this report. The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only GSM850 and PCS1900 bands test data included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS, AGPS and WIFI etc. Externally it provides micro SD card interface, earphone port(to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

The mobile phone U8815-71 is a HSDPA/HSUPA/UMTS/GPRS/GSM/EDGE mobile phone with Bluetooth, which supports GSM850/900/1800/1900 and WCDMA850/900/2100 The mobile phone U8815-51 is a HSDPA/UMTS/GPRS/GSM/EDGE mobile phone with Bluetooth, which supports GSM850/900/1800/1900 and WCDMA850/1900/2100

The difference between U8815-71 and U8815-51 is showed in the following table.

	U8815-71	U8815-51
GSM four bands	the same	the same
WCDMA bands	WCDMA850/900/2100	WCDMA/850/1900/2100
FLASH	the same	the same
PCB	the same	the same
Appearance	the same	the same
Bluetooth mode	the same	the same
WLAN mode	the same	the same
BT/ WLAN antenna	the same	the same
GSM/ WCDMA antenna	the same	the same
External	the same	the same

camera		
internal camera	the same	the same
Adapter	the same	the same
Battery	the same	the same
Chipset	7227A	7227A
Memory	the same	the same
Form factor	Bar type, Internal antenna	Bar type, Internal antenna
RF Parameter	The same RF Parameter in the same band	The same RF Parameter in the same band
BT RF Parameter	the same	the same
Dimension	the same	the same
Weight	the same	the same
Bluetooth	the same	the same
External camera	the same	the same
Main Frequency NV	The same NV in the same band	The same NV in the same band
BT conducted power	the same	the same
WIFI conducted power	the same	the same

So U8815-71 tested WCDMA band only, other bands test data refer to U8815-51 RF report.

1.3.1 Board Information

Table 2 Board Information

HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; HUAWEI Ascend G 300+		
HUAWEI U8815-71,U8815-71		
Board and Module		
Serial Number	Software Version	Hardware Version
F4H01A9290500025	U8815-71V100R001C00B867	HD1U8815M

1.3.2 Adapter Technical Data

AC/DCAdapter Model	HW-050100U1W
Manufacturer	Huawei Technologies Co., Ltd.
Input Voltage	~100-240V 50/60Hz 0.2A
Output Voltage	5V  1A
Rated Power	5W

AC/DCAdapter Model	HW-050100A1W
Manufacturer	Huawei Technologies Co., Ltd.
Input Voltage	~100-240V 50/60Hz 0.2A
Output Voltage	5V  1A
Rated Power	5W

AC/DCAdapter Model	HW-050100E1W
Manufacturer	Huawei Technologies Co., Ltd.
Input Voltage	~100-240V 50/60Hz 0.2A
Output Voltage	5V  1A
Rated Power	5W

3.1.2 Battery Technical Data

Name	Manufacture	Description
Rechargeable Li-ion	Huawei Technologies Co., Ltd.	Battery Model: HB5N1H Rated capacity: 1500mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V

4 Test Description

4.1 Supported Frequency Range

Characteristics	Description
Downlink	869 to 894 MHz;
Uplink	824 to 849 MHz

4.2 Transmitter / Receiver Characteristics

Characteristics	Description
System Type	GSM UMTS
TX Output Power (per Antenna Port)	GSM system: 33dBm; UMTS system: 24dBm;
Channel Spacing(s) / Bandwidth(s)	GSM system: 200 kHz UMTS system: 5 MHz
Designation of Emissions	GSM system: 245KGXW (GMSK modulation), 246KG7W (8PSK modulation) UMTS system: 4M20F9W

4.3 Antenna Gain

Antenna Gain(dBi)	-1.8
Antenna Gain(dBd)	-2.95

4.4 Power Supply

Specification	Description
Power Supply Type	Directly Connected to DC /AC Power Supply
Input to EUT (DC power)	DC Voltage Nominal:  3.7 V DC Voltage Range:  3.6 V to 4.2 V
Input to EUT (AC power)	AC Voltage Nominal: ~ 230 V (50/60 Hz) AC Voltage Range: ~100-240V

5 General Test Conditions / Configurations

5.1 RF Channels under Test

Test Mode	TX / RX	RF Channel		
		Bottom (B)	Middle (M)	Top (T)
TM1/TM2	TX	Channel 128	Channel 192	Channel 251
		824.2MHz	837.0MHz	848.8MHz
	RX	Channel 128	Channel 192	Channel 251
		869.2MHz	882.0MHz	893.8MHz
TM3/TM4/TM5	TX	Channel 4132	Channel 4182	Channel 4233
		826.4MHz	836.4MHz	846.6MHz
	RX	Channel 4357	Channel 4407	Channel 4458
		871.4MHz	881.4MHz	891.6MHz

5.2 Test Modes

Test Mode	Test Modes Description
TM1	GSM/GPRS, GMSK modulation
TM2	EDGE, 8PSK modulation
TM3	WCDMA, QPSK modulation
TM4	HSDPA ,16QAM modulation
TM5	HSUPA, 16QAM modulation

5.3 Test Environments

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	3.6V
	VN	3.7V
	VH	4.2V


NOTE: VL= lower extreme test voltages
VN= nominal voltage
VH= upper extreme test voltage
TN= normal temperature

5.4 Test Setups


5.4.1 General Test Setup Configurations

Configuration	Description
Test Antenna Ports	Until otherwise declared, all TX tests are ONLY performed at the main Transmitter antenna port (e.g. TRXA, TXA and so on) of the EUT, and all RX tests are ONLY performed at the main Receiver antenna port (e.g. TRXA, RXA and so on) of the EUT.
Multiple RF Sources	Other than the tested RF source of the EUT, other RF source(s) are disabled or shutdown during measurements.

5.4.2 Test Setup 1




5.4.3 Test Setup 2




5.4.4 Test Setup 3

NOTE: Effective radiated power (ERP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

Step 1: Pre-test



Step 2: Substitution method to verify the maximum ERP



5.5 Test Conditions

Test Case	Test Conditions	
Transmitter Output Power	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1 & Test Setup 3
	Detector	RMS
	RF Channels (TX)	B, M, T
	Test Mode	TM1/TM2/TM3/TM4/TM5
Modulation Characteristics	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	RF Channels (TX)	M
	Test Mode	TM1/TM2/TM3
Occupied Bandwidth	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	PK
	RF Channels (TX)	B, M, T
	Test Mode	TM1/TM2/TM3
Band Edges Compliance	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	RMS
	RF Channels (TX)	B, T
	Test Mode	TM1/TM2/TM3
Spurious Emission at Antenna Terminals	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	PK
	RF Channels (TX)	B, M, T
	Test Mode	TM1/TM2/TM3
Field Strength of Spurious Radiation	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 3
	Detector	PK
	RF Channels (TX)	M
	Test Mode	TM1/TM2/TM3/TM4/TM5
Frequency Stability	Test Configuration	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage; (2) 85%, 100% and 115% of Rated Voltage at Ambient Temperature.
	Test Setup	Test Setup 2



Test Case	Test Conditions	
	RF Channels (TX)	M
	Test Mode	TM1/TM2/TM3

6 Main Test Instruments

Table 3 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until
Power supply	KEITHLEY	2303	1288003	Sept., 27,2013
Universal Radio Communication Tester	R&S	CMU200	117341	Jan., 12,2013
Universal Radio Communication Tester	Agilent	E5515C	MY50260239	Aug., 31,2013
Spectrum Analyzer	Agilent	E4440A	MY49420179	Jul., 17,2013
Signal Analyzer	R&S	FSQ31	200021	Sept., 27,2013
Temperature Chamber	WEISS	WKL64	24600294	Feb.,13,2013
Signal generator	Agilent	E8257D	MY49281095	Jul.,09,2013
Spectrum analyzer	R&S	FSU3	200474	Mar., 05, 2013
Spectrum analyzer	R&S	FSU43	100144	Mar., 05, 2013
Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	100304	Apr., 05, 2013
Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	100391	Apr., 05, 2013
Trilog Broadband Antenna (30M~3GHz)	SCHWARZBECK	VULB 9163	9163-521	Jul., 07, 2013
Pyramidal Horn Antenna(26GHz-40GHz)	ETS-Lindgren	3160-10	00123940	Feb., 27, 2013
Pyramidal Horn Antenna(18GHz-26.5GHz)	ETS-Lindgren	3160-09	00125912	Feb., 27, 2013

7 Test Results

No.	Test Item	Test Result
1	Transmitter Output Power	Appendix A
2	Modulation Characteristics	Appendix B
3	Occupied Bandwidth	Appendix C
4	Band Edges Compliance	Appendix D
5	Spurious Emission at Antenna Terminals	Appendix E
6	Field Strength of Spurious Radiation	Appendix F
7	Frequency Stability	Appendix G
8	Photos of Field Strength of Spurious Radiation	Appendix H

NOTE: The Appendix H only photos of Field Strength of Spurious Radiation, no test data.

8 Measurement Uncertainty

For a 95% confidence level (k=2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item		Extended Uncertainty
Transmitter Output Power	Power (dBm)	U =0.39 dB
Occupied Bandwidth	Magnitude (%)	U=0.2%
Band Edge Compliance	Disturbance Power (dBm)	U=2.0 dB
Conducted Spurious Emissions	Disturbance Power (dBm)	U=2.0 dB
Field Strength of Spurious Radiation	ERP (dBm)	U=4.6 dB (30 MHz – 1GHz) U=3.0 dB (above 1 GHz)
Frequency Stability	Frequency Accuracy (ppm)	U=0.21 ppm

-----The END-----



Appendix A

Transmitter Output Power

According to FCC Part 2.1046 & Part22.913



Conducted Power of Transmitter

		RF Output Power (Conducted)					
TEST CONDITIONS		Channel128(B) 824.2MHz		Channel192(M) 837.0MHz		Channel251(T) 848.8MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
T _{nom} / V _{nom}		Measured	Limit	Measured	Limit	Measured	Limit
TM1		32.51	38.5	32.68	38.5	32.71	38.5
TM2		27.2	38.5	27.41	38.5	27.46	38.5
TEST CONDITIONS		Channel4132(B) 826.4MHz		Channel4182(M) 836.4MHz		Channel4233(T) 846.6MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
T _{nom} / V _{nom}		Measured	Limit	Measured	Limit	Measured	Limit
TM3		23.91	38.5	23.73	38.5	23.81	38.5
TM4	Case1	23.82	38.5	23.67	38.5	23.69	38.5
	Case2	23.49	38.5	23.41	38.5	23.39	38.5
	Case3	22.79	38.5	23.26	38.5	23.27	38.5
	Case4	23.24	38.5	23.12	38.5	23.18	38.5
TM5	Case1	23.33	38.5	23.23	38.5	23.15	38.5
	Case2	22.13	38.5	22.05	38.5	22.09	38.5
	Case3	22.46	38.5	22.5	38.5	22.21	38.5
	Case4	22.25	38.5	22.47	38.5	22.46	38.5
	Case5	23.35	38.5	23.25	38.5	23.17	38.5



Effective Radiated Power of Transmitter (ERP)

Test Mode	Freq. [MHz]	Meas. Level [dBm]	Substitution Antenna Type	SGP [dBm]	Substitution Gain [dBi]	Cable Loss [dB]	Substitution Level (ERP)	FCC limit [dBm]	Result
							[dBm]		
TM1	824.2	23.87	Dipole Ant.	27.02	-2.75	0.6	23.67	33.2	Pass
TM1	837.0	24.03	Dipole Ant.	27.3	-2.87	0.6	23.83	33.2	Pass
TM1	848.8	24.06	Dipole Ant.	27.31	-2.85	0.6	23.86	33.2	Pass
TM2	824.2	18.65	Dipole Ant.	21.8	-2.75	0.6	18.45	27.7	Pass
TM2	837.0	18.76	Dipole Ant.	22.03	-2.87	0.6	18.56	27.7	Pass
TM2	848.8	18.81	Dipole Ant.	22.31	-2.85	0.6	18.86	27.7	Pass
TM3	826.4	15.26	Dipole Ant.	18.41	-2.75	0.6	15.06	24.5	Pass
TM3	836.4	15.08	Dipole Ant.	18.35	-2.87	0.6	14.88	24.5	Pass
TM3	846.6	15.16	Dipole Ant.	18.41	-2.85	0.6	14.96	24.5	Pass

Note: a, For getting the ERP (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$

b, SGP=Signal Generator Level

-----The END-----




Appendix B

Modulation Characteristics

According to FCC Part 2.1047 & Part22 Subpart H




Channel 192(TM1:GPRS/GSM)






Channel 192(TM2:EDGE)





Channel 4182(TM3: WCDMA)



-----The END-----



Appendix C

Occupied Bandwidth According to FCC Part 2.1049 & Part 22 Subpart H




Result Table
Table 1 Measurement Results




Test Mode	RF Channel	Occupied Bandwidth [kHz]	Verdict
TM1	128	245.19	Pass
	192	243.60	Pass
	251	245.19	Pass
TM2	128	238.78	Pass
	192	241.99	Pass
	251	246.79	Pass
Test Mode	RF Channel	Occupied Bandwidth [MHz]	Verdict
TM3	4132	4.20	Pass
	4182	4.18	Pass
	4233	4.18	Pass



Channel 128(TM1:GPRS/GSM)




Date: 27.JAN.2012 11:06:56



Date: 27.JAN.2012 11:14:22




Channel 4132(TM3: WCDMA)



Date: 23.SEP.2012 17:09:20




Channel 192(TM1:GPRS/GSM)



Date: 27.JAN.2012 11:07:10




Channel 192(TM2:EDGE)



Date: 27.JAN.2012 11:14:36




Channel 4182(TM3: WCDMA)



Date: 23.SEP.2012 17:09:34




Channel 251(TM1:GPRS/GSM)



Date: 27.JAN.2012 11:07:23




Channel 251(TM2:EDGE)



Date: 27.JAN.2012 11:14:50



Channel 4233(TM3: WCDMA)



Date: 23.SEP.2012 17:09:47

-----The END-----




Appendix D

Band Edges Compliance

According to FCC Part 2.1051 & Part 22 Subpart H




TM1:GPRS/GSM Left Edge Channel 128



Date: 27.JAN.2012 11:10:41




Right Edge Channel 251



Date: 27.JAN.2012 11:11:01


TM2:EDGE
Left Edge
Channel 128



Date: 27.JAN.2012 11:18:03



Right Edge Channel 251




Date: 27.JAN.2012 11:18:16



TM3: WCDMA

Left Edge


Channel 4132



Date: 23.SEP.2012 17:10:02



Right Edge Channel 4233



Date: 23.SEP.2012 17:10:15

-----The END-----




Appendix E

Spurious Emission at Antenna Terminal


According to FCC Part 2.1051 & Part 22 Subpart H




TM1:GPRS/GSM Channel 128




Date: 27.JAN.2012 11:07:38



Date: 27.JAN.2012 11:08:22




Date: 27.JAN.2012 11:09:06




Date: 27.JAN.2012 11:09:50




Channel 192




Date: 27.JAN.2012 11:07:53



Date: 27.JAN.2012 11:08:37




Date: 27.JAN.2012 11:09:21




Date: 27.JAN.2012 11:10:05




Channel 251




Date: 27.JAN.2012 11:08:07



Date: 27.JAN.2012 11:08:51



Date: 27.JAN.2012 11:09:35




Date: 27.JAN.2012 11:10:19




TM2:EDGE




Channel 128




Date: 27.JAN.2012 11:15:05



Date: 27.JAN.2012 11:15:48




Date: 27.JAN.2012 11:16:32




Date: 27.JAN.2012 11:17:16




Channel 192




Date: 27.JAN.2012 11:15:19



Date: 27.JAN.2012 11:16:03




Date: 27.JAN.2012 11:16:47




Date: 27.JAN.2012 11:17:31




Channel 251




Date: 27.JAN.2012 11:15:33



Date: 27.JAN.2012 11:16:17




Date: 27.JAN.2012 11:17:01




Date: 27.JAN.2012 11:17:45




TM3: WCDMA Channel 4132



Date: 23.SEP.2012 17:10:30




Date: 23.SEP.2012 17:11:14




Date: 23.SEP.2012 17:11:58




Channel 4182



Date: 23.SEP.2012 17:10:45



Date: 23.SEP.2012 17:11:28




```
* RBW 100 kHz      Marker 1 [T1 ]
* VBW 300 kHz      16.58 dBm
  SWT 1.3 s        825.000000000 MHz
```


Page32, Total35




Channel 4233



Date: 23.SEP.2012 17:10:59



Date: 23.SEP.2012 17:11:43



Ref 35 dBm Att 35 dB SWT 1.3 s 845.384615385 MHz

Offset 12.9 dB

D1 -13 dBm

Start 30 MHz 1.272 GHz/ Stop 12.75 GHz

-----The END-----



Appendix F


Field Strength of Spurious Radiation

According to FCC Part 2.1053 & Part22.917




GSM 850

Traffic Mode (9kHz-30MHz)






Traffic Mode (30MHz-3GHz)






Traffic Mode (3GHz-18GHz)






GPRS 850

Traffic Mode (9kHz-30MHz)






Traffic Mode (30MHz-3GHz)






Traffic Mode (3GHz-18GHz)






EDGE 850

Traffic Mode (9kHz-30MHz)






Traffic Mode (30MHz-3GHz)






Traffic Mode (3GHz-18GHz)






WCDMA Band V

Traffic Mode (9kHz-30MHz)






Traffic Mode (30MHz-3GHz)




Traffic Mode (3GHz-18GHz)






HSDPA Band V

Traffic Mode (9kHz-30MHz)




Traffic Mode (30MHz-3GHz)






Traffic Mode (3GHz-18GHz)






HSUPA Band V

Traffic Mode (9kHz-30MHz)





-----The END-----

--



Appendix G

Frequency Stability

According to FCC Part 2.1055 & Part 22.355



Frequency Error vs. Temperature:

Test Mode	RF Ch.	Volt.	Temp.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Freq. vs. 20 °C [ppm]	Limit [ppm]	Verdict
TM 1	M	100%	-30 °C	-11	-0.01314	---	±2.5	Pass
			-20 °C	17	0.02031	---	±2.5	Pass
			-10 °C	18	0.02151	---	±2.5	Pass
			0 °C	-16	-0.01912	---	±2.5	Pass
			10 °C	-16	-0.01912	---	±2.5	Pass
			20 °C	27	0.03226	---	±2.5	Pass
			30 °C	-10	-0.01195	---	±2.5	Pass
			40 °C	-19	-0.02270	---	±2.5	Pass
			50 °C	-9	-0.01075	---	±2.5	Pass
TM 2	M	100%	-30 °C	-19	-0.02270	---	±2.5	Pass
			-20 °C	18	0.02151	---	±2.5	Pass
			-10 °C	-19	-0.02270	---	±2.5	Pass
			0 °C	22	0.02628	---	±2.5	Pass
			10 °C	-22	-0.02628	---	±2.5	Pass
			20 °C	25	0.02987	---	±2.5	Pass
			30 °C	8	0.00956	---	±2.5	Pass
			40 °C	13	0.01553	---	±2.5	Pass
			50 °C	-12	-0.01434	---	±2.5	Pass
TM 3	M	100%	-30 °C	29	0.03467	---	±2.5	Pass
			-20 °C	9	0.01076	---	±2.5	Pass
			-10 °C	15	0.01793	---	±2.5	Pass
			0 °C	10	0.01196	---	±2.5	Pass
			10 °C	13	0.01554	---	±2.5	Pass
			20 °C	-13	-0.01554	---	±2.5	Pass
			30 °C	-21	-0.02511	---	±2.5	Pass
			40 °C	28	0.03348	---	±2.5	Pass
			50 °C	-11	-0.01315	---	±2.5	Pass



Frequency Error vs. Voltage:

Test Mode	RF Ch.	Temp.	Volt.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Freq. vs. 20 °C [ppm]	Limit [ppm]	Verdict
TM 1	M	20 °C	85 %	-11	-0.01314	---	±2.5	Pass
			100 %	-17	-0.02031	---	±2.5	Pass
			115 %	-9	-0.01075	---	±2.5	Pass
TM 2	M	20 °C	85 %	17	0.02031	---	±2.5	Pass
			100 %	24	0.02867	---	±2.5	Pass
			115 %	16	0.01912	---	±2.5	Pass
TM 3	M	20 °C	85 %	-20	-0.02391	---	±2.5	Pass
			100 %	14	0.01674	---	±2.5	Pass
			115 %	13	0.01554	---	±2.5	Pass

-----The END-----
