



# EMC Test Report

**Product Name: HSPA /UMTS/GSM/GPRS/EDGE Mobile  
Phone with Bluetooth; HUAWEI Ascend G 300+**

**Model Number: HUAWEI U8815-71, U8815-71**

**Report No: SYBH(Z-EMC)006092012-2**

**FCC ID: QISU8815-71**

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,  
Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518



## Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
5. The test report is invalid if not marked with "exclusive stamp for the test report".
6. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
9. Normally, the test report is only responsible for the samples that have undergone the test.
10. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



**Applicant:** Huawei Technologies Co., Ltd.  
**Address:** Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

**Date of Receipt Test Item:** Sep.10, 2012  
**Start Date of Test:** Sep.20, 2012  
**End Date of Test:** Sep.28, 2012

**Test Result:** Pass

**Approved By  
(Lab Manager)**

2012-10-10  
Date

Liuchunlin  
Name

Signature

**Operator**

2012-10-10  
Date

Daniel  
Name

Signature



---

---

**Modification Record**

No.	Last Report No.	Modification Description
1	NA	First report



## TABLE OF CONTENT

1	General Information .....	6
1.1	EUT Description .....	6
1.2	Test Site Information .....	7
1.3	Applied Standards .....	7
2	Summary of Results .....	8
3	System Configuration during EMC Test .....	9
3.1	Test Mode .....	9
3.2	Test System Configuration .....	9
3.3	Associated Equipment Used during Test .....	12
4	Electromagnetic Interference (EMI) .....	13
4.1	Radiated Disturbance 30MHz to 18GHz .....	13
5	Main Test Instruments .....	16
6	System Measurement Uncertainty .....	16
7	Test Data and Graph .....	17
7.1	Radiated Disturbance .....	17
7.2	Conducted Disturbance .....	19



**1 General Information**

**1.1 EUT Description**

EUT Description	
Product Name	HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; HUAWEI Ascend G 300+
Model Number	HUAWEI U8815-71, U8815-71
Serials Number	F4H01A9290500090
TX Frequency	GSM850:824MHz To 849MHz; GSM1900:1850MHz To 1910MHz; WCDMA BAND V: 824MHz To 849MHz Bluetooth/WIFI: 2400MHz To 2483.5MHz;
RX Frequency	GSM850:869MHz To 894MHz; GSM1900:1930MHz To 1990MHz WCDMA BAND V: 869MHz To 894MHz Bluetooth/WIFI: 2400MHz To 2483.5MHz; GPS: 1575.42MHz;
HW Version	HD4U8815M
SW Version	U8815-71V100R001C346B939
EUT Accessory	
Data cable	Data Cable USB A Male to Micro Usb, shielded
Adapter	Brand: HUAWEI Model: HW-050100E1W Input voltage: ~100-240V 50/60Hz, 0.2A Output voltage: 5.0V $\equiv$ 1.0A Rated Power: 5W SN: HKABC1416455 SN: TPAC11824369
Adapter	Brand: HUAWEI Model: HW-050100U1W Input voltage: ~100-240V 50/60Hz, 0.2A Output voltage: 5.0V $\equiv$ 1.0A Rated Power:5W SN:HKABC1787307 SN: TPAC62040783
Adapter	Brand: HUAWEI Model: HW-050100A1W Input voltage: ~100-240V 50/60Hz, 0.2A Output voltage: 5.0V $\equiv$ 1.0A Rated Power:5W SN: HKAC60495732
Rechargeable Li-ion	Brand: HUAWEI Battery Model: HB5N1H Rated capacity: 1500mAh Nominal Voltage: $\equiv$ +3.7V Charging Voltage: $\equiv$ +4.2V S/N: BAAC710FZZZ07628 S/N:GRGC801Z13851092 S/N:CAWC807XXXX00326



Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user manual for more detailed description.

## 1.2 Test Site Information

Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

## 1.3 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15:2011, Subpart B



## 2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode1~ Mode2 Mode5 Mode7~ Mode8	CLASS B	Pass	Site1
<u>Conducted Emissions</u> <input checked="" type="checkbox"/> DC Power Port <input checked="" type="checkbox"/> AC Power Port <input type="checkbox"/> Telecommunication Ports	Mode1~ Mode4	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the measurement uncertainty of measurement system. 2, <input checked="" type="checkbox"/> The item has been tested; <input type="checkbox"/> The item has not been tested.				

During the measurement, the environmental conditions complied with the range listed as below.

Item	Required
Ambient temperature	15°C ~ 35°C
Relative humidity	25% ~ 75%
Atmospheric pressure	86kPa ~ 106kPa

### 3 System Configuration during EMC Test


#### 3.1 Test Mode

Huawei has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was in this test report and defined as below:


Test Mode	
Mode 1:	adapter+earphone+Camera On +Idle
Mode 2:	adapter+earphone+MP3 +Idle
Mode 3:	adapter+earphone+Traffic
Mode 4:	adapter+Traffic
Mode 5:	USB Copy(EUT with PC)+earphone +Idle
Mode 6:	Traffic
Mode 7:	Camera On+earphone+Idle
Mode 8:	earphone+MP3+Idle

Remark: When the EUT have multiple adapters, need separate test with multiple adapters . All test modes are performed, only the worst cases are recorded in this report.


#### 3.2 Test System Configuration



Connection Diagram (Mode 4)




Connection Diagram (Mode 5)



Connection Diagram (Mode 6)



Connection Diagram (Mode 7~Mode 8)





### 3.3 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated Deadline	Cal interval (month)
Radio Communication Tester	CMU200	R&S	3608105673	2012-11-06	12
Notebook	X200	ThinkPad	31090403588	/	/

## 4 Electromagnetic Interference (EMI)

### 4.1 Radiated Disturbance 30MHz to 18GHz

#### 4.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4-2009. The test distance was 3m. The set-up and test methods were according to ANSI C63.4-2009.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; The emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m. The azimuth range of turntable was 0° to 360°. The receiving antenna has two polarizations V and H.

Measurement bandwidth (RBW) for 30MHz to 1000 MHz: 120 kHz;

Measurement bandwidth (RBW) for 1000MHz to 18000 MHz: 1MHz;

EUT was configured in idle mode and the test performed at worst emission state.

#### 4.1.2 Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance(above 1GHz)



### 4.1.3 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.  
The test data see section 7.1 of this report.

Test Limits				
Frequency of Emission (MHz)	Radiated Limit			
	Unit( $\mu$ V/m)		Unit(dB $\mu$ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

#### 4.1.4 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm away from LISN. The set-up and test methods were according to ANSI C63.4-2009. Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.

Measurement bandwidth (RBW) for 150 kHz to 30 MHz: 9 kHz;

The EUT was set in the shielded chamber and operated under nominal conditions.

#### 4.1.5 Test Setup




Figure 3. Test Set-up of conducted disturbance

#### Test Results

The EUT has met requirements for Conducted disturbance of power lines.

The test data see section 7.2 of this report.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66-56dB $\mu$ V	56-46 dB $\mu$ V
0.5MHz-5MHz	56dB $\mu$ V	46 dB $\mu$ V
5MHz~30MHz	60dB $\mu$ V	50 dB $\mu$ V



## 5 Main Test Instruments

Main Test Equipments						
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated Deadline	Cal interval (month)
RE	EMI Test receiver	ESU26	100150	R&S	May.27, 2013	12
	Broadband Antenna	VULB 9163	9163-941	SCHWARZBECK	Jul.07, 2013	24
	Horn Antenna	HF906	100683	R&S	May.15, 2013	24
CE	EMI Test receiver	ESCI	101163	R&S	Mar. 05, 2013	12
	Artificial Mains Network	ENV216	100382	R&S	Mar.21, 2013	12
Software Information						
Test Item	Software Name	Manufacturer		Version		
RE	ES-K1	R&S		1.7.1		
CE	EMC32	R&S		V8.52.0		

## 6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty		
Items	Extended Uncertainty	
RE(30MHz-1GHz)	Field strength (dB $\mu$ V/m)	U=4.1dB; k=2
RE(1GHz-18GHz)	Field strength (dB $\mu$ V/m)	U=5.1dB; k=2
CE	Disturbance Voltage (dB $\mu$ V)	U=2.6dB; k=2




## 7 Test Data and Graph

Only the worst test result was shown in this report.

### 7.1 Radiated Disturbance

#### 30MHz~1GHz



#### MEASUREMENT RESULT: QP Detector


Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
37.260000	26.30	15.1	40.0	13.7	127.0	0.00	VERTICAL
48.780000	27.00	15.0	40.0	13.0	101.0	177.00	VERTICAL
112.620000	21.10	12.5	43.5	22.4	101.0	155.00	VERTICAL
189.060000	20.10	11.9	43.5	23.4	194.0	292.00	HORIZONTAL
362.220000	27.90	16.8	46.0	18.1	100.0	268.00	HORIZONTAL
903.840000	33.00	24.9	46.0	13.0	142.0	292.00	HORIZONTAL

**Note:**

Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)  
 The reading level is used to calculate by software which is not shown in the sheet.



**1GHz~18GHz**



**MEASUREMENT RESULT: PK Detector**

Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
1710.200000	31.40	-13.3	74.0	42.6	150.0	39.00	VERTICAL
3495.400000	37.10	-6.0	74.0	36.9	100.0	61.00	VERTICAL
6761.400000	40.40	1.5	74.0	33.6	100.0	1.00	VERTICAL

**MEASUREMENT RESULT: AV Detector**

Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
2452.200000	20.80	-10.5	54.0	33.2	100.0	36.00	VERTICAL
3735.100000	24.40	-5.4	54.0	29.6	100.0	131.00	VERTICAL
6841.400000	28.40	2.0	54.0	25.6	100.0	331.00	VERTICAL


**Note:**

Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)  
 The reading level is used to calculate by software which is not shown in the sheet.



## 7.2 Conducted Disturbance

### AC Port Test Data



#### MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.579296	51.6	9.7	56.0	4.4	L1	FLO
0.584186	51.8	9.7	56.0	4.2	L1	FLO
1.566157	45.7	9.7	56.0	10.3	L1	FLO
2.103916	44.7	9.7	56.0	11.3	L1	FLO
2.999636	44.0	9.7	56.0	12.0	L1	FLO
3.920752	42.7	9.8	56.0	13.3	L1	FLO

#### MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.287090	35.7	9.7	50.6	14.9	L1	FLO
0.658114	38.1	9.7	46.0	7.9	L1	FLO
1.152949	35.7	9.7	46.0	10.3	L1	FLO
1.654804	34.7	9.7	46.0	11.3	L1	FLO
2.075138	34.9	9.7	46.0	11.1	L1	FLO
2.973563	30.9	9.7	46.0	15.1	L1	FLO

Note:



Level= Reading level+ Transd (cable loss + correction factor)

The reading level is used to calculate by software which is not shown in the sheet.

-----**END**-----