



FCC Part15.247 Test Report

Product Name : HUAWEI Ascend G 500D; Ascend G 500D; Panama;
PANAMA; HSDPA/UMTS/GPRS/GSM/EDGE Mobile
Phone with Bluetooth

Model No. : HUAWEIU8832D-5, U8832D-5

FCC ID : QISU8832D-5

Applicant : Huawei Technologies Co., Ltd.

Address : Bantian, Longgang District, Shenzhen, 518129 Guangdong,
P. R. China

Date of Receipt : 15/06/2012

Test Date : 15/06/2012~05/07/2012

Issued Date : 11/07/2012

Report No. : 126S044R-RF-US-P06V02

Report Version : V1.1

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : 11/07/2012

Report No. : 126S044R-RF-US-P06V02



Product Name : HUAWEI Ascend G 500D; Ascend G 500D; Panama;
 PANAMA; HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone
 with Bluetooth

Applicant : Huawei Technologies Co., Ltd.
 Address : Bantian, Longgang District, Shenzhen, 518129 Guangdong, P.
 R. China

Manufacturer : Huawei Technologies Co., Ltd.
 Address : Bantian, Longgang District, Shenzhen, 518129 Guangdong, P.
 R. China

Model No. : HUAWEIU8832D-5, U8832D-5
 FCC ID : QISU8832D-5
 EUT Voltage : DC 3.7V
 Trade Name : HUAWEI
 Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2012;
 ANSI C63.4: 2009; ANSI C63.10: 2009

Test Result : Complied
 Performed Location : Suzhou EMC Laboratory
 No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech
 Development Zone., Suzhou, China
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
 FCC Registration Number: 800392

Documented By : Alice Ni
 (Engineering ADM: Alice Ni)

Reviewed By : Robin Wu
 (Engineering Supervisor: Robin Wu)

Approved By : Marlin Chen
 (Manager: Marlin Chen)

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	:	BSMI, NCC, TAF
Germany	:	TUV Rheinland
Norway	:	Nemko, DNV
USA	:	FCC, NVLAP
Japan	:	VCCI
China	:	CNAS

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site :<http://www.quietek.com/tw/ctg/cts/accreditations.htm>
The address and introduction of Quietek Corporation's laboratories can be founded in our Web site :
<http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yongxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com

Linkou Testing Laboratory :

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com

Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : service@quietek.com

TABLE OF CONTENTS

Description	Page
1. General Information	6
1.1. EUT Description	6
1.2. Mode of Operation	10
1.3. Tested System Details	11
1.4. Configuration of Tested System	12
1.5. EUT Exercise Software	13
2. Technical Test	14
2.1. Summary of Test Result	14
2.2. Test Environment	15
3. Conducted Emission	16
3.1. Test Equipment	16
3.2. Test Setup	16
3.3. Limit.....	17
3.4. Test Procedure	17
3.5. Uncertainty	17
3.6. Test Result	18
4. Radiated Emission.....	20
4.1. Test Equipment	20
4.2. Test Setup	21
4.3. Limit.....	22
4.4. Test Procedure	22
4.5. Uncertainty	23
4.6. Test Result	24
5. RF Antenna Conducted Spurious.....	27
5.1. Test Equipment	28
5.2. Test Setup	28
5.3. Limit.....	28
5.4. Test Procedure	29
5.5. Uncertainty	29
5.6. Test Result	30
6. Radiated Emission Band Edge	38
6.1. Test Equipment	38
6.2. Test Setup	39
6.3. Limit.....	39
6.4. Test Procedure	39
6.5. Uncertainty	39
6.6. Test Result	40

- 7. Operation Frequency Range of 20dB Bandwidth.....40
 - 7.1. Test Equipment72
 - 7.2. Test Setup72
 - 7.3. Limit.....72
 - 7.4. Test Procedure72
 - 7.5. Uncertainty72
 - 7.6. Test Result73
- 8. Occupied Bandwidth77
 - 8.1. Test Equipment77
 - 8.2. Test Setup77
 - 8.3. Limit.....77
 - 8.4. Test Procedure77
 - 8.5. Uncertainty77
 - 8.6. Test Result78
- 9. Power Output.....86
 - 9.1. Test Equipment86
 - 9.2. Test Setup86
 - 9.3. Limit.....86
 - 9.4. Test Procedure87
 - 9.5. Uncertainty87
 - 9.6. Test Result88
- 10. Power Spectral Density92
 - 10.1. Test Equipment.....92
 - 10.2. Test Setup92
 - 10.3. Limit.....92
 - 10.4. Test Procedure93
 - 10.5. Uncertainty93
 - 10.6. Test Result.....94

1. General Information

1.1. EUT Description

Product Name	HUAWEI Ascend G 500D; Ascend G 500D; Panama; PANAMA; HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth
Model No.	HUAWEIU8832D-5, U8832D-5
Hardware Version	A61_MB_V2.0
Software Version	U8832DV100R001C41B100SP06
Device Category	Portable
RF Exposure Environment	Uncontrolled
Antenna Type	Internal
GPS	
Operate Frequency	1575.42MHz
Type of modulation	BPSK
2G	
Support Band	GSM850/GSM900/DCS1800/PCS1900
GPRS Type	Class B
GPRS Class	Class 12
Uplink	GSM 850: 824~849MHz PCS 1900: 1850~1910MHz
Downlink	GSM 850: 869~894MHz PCS 1900: 1930~1990MHz
Release Version	Rel-6
Type of modulation	GMSK for GSM/GPRS; 8PSK for EDGE
Antenna Gain	GSM 850: -2.0dBi PCS1900: -0.3dBi
3G	
Support Band	WCDMA Band I/WCDMA Band II/WCDMA Band V/ WCDMA Band VIII
Uplink	WCDMA Band V: 824~849MHz WCDMA Band II: 1850~1910MHz
Downlink	WCDMA Band V: 869~894MHz WCDMA Band II: 1930~1990MHz
Release Version	UMTS FDD: Rel-6
Type of modulation	QPSK

Antenna Gain	WCDMA Band V: -2.0dBi WCDMA Band II: -0.3dBi
Bluetooth	
Bluetooth Frequency	2402~2480MHz
Bluetooth Version	V2.1 + EDR
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Gain	-4.0dBi
Wi-Fi	
Hotspots Function	YES
Wi-Fi Frequency	802.11b/g/n(20MHz): 2412 ~ 2462 MHz 802.11n(40MHz): 2422 ~ 2452 MHz
Type of modulation	802.11b: DSSS; 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps
	802.11g: 6/9/12/18/24/36/48/54 Mbps
	802.11n: up to 150 Mbps
Antenna Gain	-4.0dBi
Components	
Headset Model Number #1	HUAWEI/ 125G#+3261# 3.5MM-2
Headset Model Number #2	HUAWEI/ MEMD1532A761A00
Battery #1	Brand Name: HUAWEI M/N: HB5R1 Rated Voltage and Capacitance: 3.7V/1930mAh S/N: AAIC612X04100854
Battery #2	Brand Name: HUAWEI M/N: HB5R1 Rated Voltage and Capacitance: 3.7V/1930mAh S/N: GAGC525Z04102141
Battery #3	Brand Name: HUAWEI M/N: HB5R1H Rated Voltage and Capacitance: 3.7V/1930mAh S/N: SASC507AC3500764
Adapter #1	Brand Name: HUAWEI M/N: HW-050100U1W Input: 100-240V~50/60Hz 0.2A MAX Output: 5Vdc, 1A S/N: HKAB51621442

Adapter #2	Brand Name: HUAWEI M/N: HW-050100U1W Input: 100-240V~50/60Hz 0.2A MAX Output: 5Vdc, 1A S/N: TPAB61442664
------------	--

Note 1: They are only for different marketing requirement.

Note 2: Headset #1 and #2 have the same circuit.

Note 3: Adapter #1 is used for RF test

For 2.4GHz Band

802.11b/g Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz	04	2427 MHz
05	2432 MHz	06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	10	2457 MHz	11	2462 MHz	N/A	N/A

802.11n(40MHz) Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz	N/A	N/A

1.2. Mode of Operation

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmit by 802.11b
Mode 2: Transmit by 802.11g
Mode 3: Transmit by 802.11n(20MHz)
Mode 4: Transmit by 802.11n(40MHz)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z axis, and shown the worst case on this report.
3. This device is a composite device in accordance with Part 15 Subpart B regulations. The function for the receiver was measured and made a test report that the report number is 126S044R-HP-US-P01V01.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	N/A	N/A	N/A	N/A	N/A

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Execute the software provided by applicant on the phone.
4	Select test channel and test mode to test.

2. Technical Test

2.1. Summary of Test Result

- No deviations from the test standards
 Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.209	Yes	No
RF Antenna Conducted Spurious	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2012 15.247(d)	Yes	No
Operation Frequency Range of 20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2012 15.215(c)	Yes	No
Occupied Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(2)	Yes	No
Power Output	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(b)(3)	Yes	No
Power Spectral Density	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(e)	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
EMI Test Receiver	R&S	ESCI	100726	2013.04.18
Two-Line V-Network	R&S	ENV216	100043	2013.04.18
Two-Line V-Network	R&S	ENV216	100044	2012.09.07
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2013.05.04
50ohm Termination	SHX	TF2	07081401	2012.09.22
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2013.01.10

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Engineer: Sunny	
Site: TR1	Time: 2012/06/30 - 14:29
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Line
EUT: Mobile Phone	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		0.151	46.553	36.696	-19.392	65.945	9.857	QP
2		0.151	31.539	21.682	-24.406	55.945	9.857	AV
3		0.218	45.149	35.286	-17.745	62.895	9.863	QP
4		0.218	36.750	26.887	-16.145	52.895	9.863	AV
5		0.302	40.340	30.466	-19.848	60.188	9.874	QP
6		0.302	31.631	21.757	-18.556	50.188	9.874	AV
7		0.414	38.195	28.306	-19.373	57.568	9.889	QP
8		0.414	28.976	19.087	-18.591	47.568	9.889	AV
9		0.662	41.196	31.352	-14.804	56.000	9.843	QP
10	*	0.662	33.422	23.579	-12.578	46.000	9.843	AV
11		1.194	37.816	28.033	-18.184	56.000	9.782	QP
12		1.194	29.255	19.473	-16.745	46.000	9.782	AV

Engineer: Sunny	
Site: TR1	Time: 2012/06/30 - 14:35
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Neutral
EUT: Mobile Phone	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		0.151	42.955	32.969	-22.989	65.945	9.987	QP
2		0.151	25.559	15.572	-30.386	55.945	9.987	AV
3		0.218	41.991	32.082	-20.903	62.895	9.910	QP
4		0.218	32.161	22.252	-20.733	52.895	9.910	AV
5		0.286	40.227	30.284	-20.413	60.640	9.943	QP
6		0.286	30.382	20.439	-20.258	50.640	9.943	AV
7		0.506	30.236	20.198	-25.764	56.000	10.038	QP
8		0.506	18.550	8.512	-27.450	46.000	10.038	AV
9		0.654	34.419	24.508	-21.581	56.000	9.911	QP
10	*	0.654	27.366	17.455	-18.634	46.000	9.911	AV
11		0.958	29.560	19.562	-26.440	56.000	9.999	QP
12		0.958	18.994	8.995	-27.006	46.000	9.999	AV

4. Radiated Emission

4.1. Test Equipment

Radiated Emission / AC-2

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
EMI Test Receiver	R&S	ESCI	100573	2013.04.18
Loop Antenna	R&S	HFH2-Z2	833799/003	2012.11.22
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2012.10.18
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2013.03.02
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2013.05.07


Radiated Emission / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2013.04.18
Preamplifier	Miteq	NSP1800-25	1364185	2013.05.04
Preamplifier	Quietek	AP-040G	CHM-0906001	2013.05.04
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2012.10.18
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2014.06.08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2013.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2013.03.02
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2013.03.02
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2013.03.02
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2013.01.10


Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

4.2. Test Setup


Below 30MHz Test Setup:



Under 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This

is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the “cone of radiation” of EUT. The 3dB beamwidth is 60 degrees for H-plane and 90 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Mode 1: Transmit by 802.11b

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	V	2411.1	68.7	30.4	99.1	Fundamental	/	PK
	H	365.1	1.5	16.7	18.2	46	-27.8	PK
	V	567.4	1.1	21.3	22.4	46	-23.6	PK
	H	3397.0	50.6	-15.1	35.5	54(Note 2)	-18.5	PK
	H	4824.0	62.4	-10.4	52.0	54	-2.0	AV
	H	4824.0	68.0	-10.4	57.6	74	-16.4	PK
	V	7236.0	49.2	-2.2	47.0	54(Note 2)	-7.0	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
6	V	2438.5	68.2	30.4	98.6	Fundamental	/	PK
	H	347.7	2.0	16.2	18.2	46	-27.8	QP
	H	614.4	1.3	21.2	22.5	46	-23.5	PK
	V	3408.5	49.7	-15.1	34.6	54(Note 2)	-19.4	PK
	H	4876.0	60.3	-10.1	50.2	54	-3.8	AV
	H	4876.0	65.6	-10.1	55.5	74	-18.5	PK
	V	7311.0	45.9	-1.9	44.0	54(Note 2)	-10.0	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
11	V	2462.1	67.6	30.5	98.1	Fundamental	/	PK
	H	347.7	2.0	16.2	18.2	46	-27.8	PK
	H	517.4	2.0	20.2	22.2	46	-23.8	PK
	H	3580.5	49.4	-14.7	34.7	54(Note 2)	-19.3	PK
	H	4927.0	58.4	-9.8	48.6	54	-5.4	AV
	H	4927.0	64.2	-9.8	54.4	74	-19.6	PK
	V	7383.5	49.7	-1.7	48.0	54(Note 2)	-6.0	PK
	V	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 2: Transmit by 802.11g

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	V	2405.3	72.4	30.4	102.8	Fundamental	/	PK
	H	365.1	0.0	16.7	16.7	46	-29.3	PK
	V	567.4	1.9	21.3	23.2	46	-22.8	PK
	H	3397.0	49.9	-15.1	34.8	54(Note 2)	-19.2	PK
	V	4825.0	60.3	-10.4	49.9	54(Note 2)	-4.1	PK
	V	7236.0	46.2	-2.2	44.0	54(Note 2)	-10.0	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
6	V	2438.5	71.6	30.4	102.0	Fundamental	/	PK
	V	347.7	0.1	16.2	16.3	46	-29.7	PK
	H	614.4	-1.0	21.2	20.2	46	-25.8	PK
	H	3408.5	49.6	-15.1	34.5	54(Note 2)	-19.5	PK
	H	4876.0	57.4	-10.1	47.3	54(Note 2)	-6.7	PK
	V	7311.0	45.5	-1.9	43.6	54(Note 2)	-10.4	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
11	V	2466.3	70.5	30.5	101.0	Fundamental	/	PK
	V	347.7	-0.4	16.2	15.8	46	-30.2	PK
	V	517.4	0.0	20.2	20.2	46	-25.8	PK
	V	3580.5	48.9	-14.7	34.2	54(Note 2)	-19.8	PK
	H	4927.0	57.1	-9.8	47.3	54(Note 2)	-6.7	PK
	V	7383.5	47.1	-1.7	45.4	54(Note 2)	-8.6	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 3: Transmit by 802.11n(20MHz)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	V	2403.9	71.8	30.4	102.2	Fundamental	/	PK
	V	365.1	-0.3	16.7	16.4	46	-29.6	PK
	V	567.4	1.8	21.3	23.1	46	-22.9	PK
	V	3397.0	49.2	-15.1	34.1	54(Note 2)	-19.9	PK
	H	4816.5	57.7	-10.4	47.3	54(Note 2)	-6.7	PK
	V	7236.0	46.5	-2.2	44.3	54(Note 2)	-9.7	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
6	V	2438.5	71.9	30.4	102.3	Fundamental	/	PK
	V	347.7	1.3	16.2	17.5	46	-28.5	PK
	H	614.4	-0.9	21.2	20.3	46	-25.7	PK
	H	3408.5	50.0	-15.1	34.9	54(Note 2)	-19.1	PK
	H	4867.5	56.1	-10.1	46.0	54(Note 2)	-8.0	PK
	V	7311.0	45.3	-1.9	43.4	54(Note 2)	-10.6	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
11	V	2459.7	72.0	30.5	102.5	Fundamental	/	PK
	V	347.7	-0.3	16.2	15.9	46	-30.1	PK
	V	517.4	-0.1	20.2	20.1	46	-25.9	PK
	V	3580.5	48.6	-14.7	33.9	54(Note 2)	-20.1	PK
	H	4927.0	56.0	-9.8	46.2	54(Note 2)	-7.8	PK
	V	7386.0	46.5	-1.7	44.8	54(Note 2)	-9.2	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 4: Transmit by 802.11n(40MHz)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
3	V	2414.7	69.2	30.4	99.6	Fundamental	/	PK
	H	385.5	-1.6	17.2	15.6	46	-30.4	PK
	H	567.4	0.6	21.3	21.9	46	-24.1	PK
	H	3397.0	50.3	-15.1	35.2	54(Note 2)	-18.8	PK
	H	4842.0	54.5	-10.2	44.3	54(Note 2)	-9.7	PK
	H	7266.0	45.4	-2.1	43.3	54(Note 2)	-10.7	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
6	V	2438.5	67.2	30.4	97.6	Fundamental	/	PK
	V	347.7	0.2	16.2	16.4	46	-29.6	PK
	V	614.4	-1.0	21.2	20.2	46	-25.8	PK
	V	3408.5	49.7	-15.1	34.6	54(Note 2)	-19.4	PK
	H	4876.0	53.8	-10.1	43.7	54(Note 2)	-10.3	PK
	V	7311.0	45.7	-1.9	43.8	54(Note 2)	-10.2	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK
9	V	2450.3	65.5	30.5	96.0	Fundamental	/	PK
	V	368.5	-0.5	16.7	16.2	46	-29.8	PK
	V	547.5	-0.9	21.2	20.3	46	-25.7	PK
	H	3580.5	49.2	-14.7	34.5	54(Note 2)	-19.5	PK
	H	4901.5	52.6	-9.9	42.7	54(Note 2)	-11.3	PK
	H	7356.0	44.8	-1.8	43.0	54(Note 2)	-11.0	PK
	H	24000.0	59.1	-8.9	50.2	54(Note 2)	-3.8	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

5. RF Antenna Conducted Spurious


5.1. Test Equipment

RF Antenna Conducted Spurious / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2013.04.18
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2013.05.07

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2. Test Setup



5.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


5.5. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB


5.6. Test Result

Product	:	Mobile Phone
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit by 802.11b


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	Mobile Phone
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmit by 802.11g


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	Mobile Phone
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmit by 802.11n(20MHz)


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	Mobile Phone
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-8
Test Mode	:	Mode 4: Transmit by 802.11n(40MHz)


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



6. Radiated Emission Band Edge

6.1. Test Equipment


Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2013.04.18
EMI Test Receiver	R&S	ESCI	100573	2013.04.18
Preamplifier	Miteq	NSP1800-25	1364185	2013.05.04
Preamplifier	Quietek	AP-040G	CHM-0906001	2013.05.04
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2012.10.18
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2014.06.08
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2013.03.02
Temperature/Humidity Meter	zhicheng	ZC1-2	AC5-TH	2013.01.10

Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

Note 2: The test instruments marked with "X" are used to measure the final test results.

6.2. Test Setup



6.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

6.5. Uncertainty


The measurement uncertainty above 1G is defined as ± 3.9 dB

6.6. Test Result

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	58.862	28.512	-15.138	74.000	30.350	PK
2		*	2412.520	96.312	65.908	N/A	N/A	30.404	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:29
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	47.427	17.077	-6.573	54.000	30.350	AV
2		*	2413.290	88.252	57.846	N/A	N/A	30.406	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:30
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	58.676	28.326	-15.324	74.000	30.350	PK
2		*	2411.145	99.093	68.693	N/A	N/A	30.400	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:32
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	47.514	17.164	-6.486	54.000	30.350	AV
2		*	2411.365	90.880	60.479	N/A	N/A	30.401	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2462MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2461.975	97.522	66.987	N/A	N/A	30.535	PK
2			2483.500	59.445	28.853	-14.555	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2462MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2461.250	88.941	58.408	N/A	N/A	30.533	AV
2			2483.500	47.832	17.240	-6.168	54.000	30.592	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2462MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2462.050	98.180	67.645	N/A	N/A	30.535	PK
2			2483.500	58.954	28.362	-15.046	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:38
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2462MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2461.400	89.782	59.249	N/A	N/A	30.533	AV
2			2483.500	47.878	17.286	-6.122	54.000	30.592	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/29 - 17:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	61.588	31.238	-12.412	74.000	30.350	PK
2		*	2405.590	97.808	67.420	N/A	N/A	30.388	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 09:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	47.204	16.854	-6.796	54.000	30.350	AV
2		*	2418.130	81.347	50.928	N/A	N/A	30.420	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	66.646	36.296	-7.354	74.000	30.350	PK
2		*	2405.260	102.819	72.432	N/A	N/A	30.388	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:03
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	49.990	19.640	-4.010	54.000	30.350	AV
2		*	2405.590	88.591	58.203	N/A	N/A	30.388	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:04
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2456.900	97.264	66.744	N/A	N/A	30.521	PK
2			2483.500	61.192	30.600	-12.808	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2457.225	83.822	53.301	N/A	N/A	30.521	AV
2			2483.500	47.937	17.345	-6.063	54.000	30.592	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2466.300	101.027	70.481	N/A	N/A	30.546	PK
2			2483.500	62.544	31.952	-11.456	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2456.825	87.238	56.718	N/A	N/A	30.521	AV
2			2483.500	48.528	17.936	-5.472	54.000	30.592	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:12
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	60.818	30.468	-13.182	74.000	30.350	PK
2		*	2404.050	97.209	66.825	N/A	N/A	30.384	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	47.600	17.250	-6.400	54.000	30.350	AV
2		*	2404.050	73.357	42.973	N/A	N/A	30.384	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:18
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	64.071	33.721	-9.929	74.000	30.350	PK
2		*	2403.885	102.224	71.840	N/A	N/A	30.384	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.384	18.034	-5.616	54.000	30.350	AV
2		*	2404.545	77.489	47.103	N/A	N/A	30.385	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2456.675	98.533	68.013	N/A	N/A	30.519	PK
2			2483.500	60.952	30.360	-13.048	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:30
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2460.400	74.523	43.993	N/A	N/A	30.530	AV
2			2483.500	48.151	17.559	-5.849	54.000	30.592	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2459.725	102.497	71.969	N/A	N/A	30.529	PK
2			2483.500	62.872	32.280	-11.128	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2460.150	77.609	47.079	N/A	N/A	30.530	AV
2			2483.500	48.976	18.384	-5.024	54.000	30.592	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	67.109	36.759	-6.891	74.000	30.350	PK
2		*	2420.088	95.365	64.940	N/A	N/A	30.425	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 10:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.014	17.664	-5.986	54.000	30.350	AV
2		*	2424.246	78.236	47.800	N/A	N/A	30.435	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 11:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	70.244	39.894	-3.756	74.000	30.350	PK
2		*	2414.676	99.600	69.190	N/A	N/A	30.409	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 11:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.307	17.957	-5.693	54.000	30.350	AV
2		*	2412.564	78.630	48.226	N/A	N/A	30.404	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 13:06
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2449.136	94.126	63.628	N/A	N/A	30.498	PK
2			2483.500	61.675	31.083	-12.325	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 13:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Horizontal
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz)	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2450.156	77.748	47.247	N/A	N/A	30.500	AV
2			2483.500	48.473	17.881	-5.527	54.000	30.592	AV

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 13:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz)	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2450.258	96.040	65.539	N/A	N/A	30.502	PK
2			2483.500	61.620	31.028	-12.380	74.000	30.592	PK

Engineer: Nancy	
Site: AC5	Time: 2012/06/30 - 13:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA 9120D_499(1-18GHz)	Polarity: Vertical
EUT: Mobile Phone	Power: By Battery
Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz)	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2449.952	79.247	48.747	N/A	N/A	30.500	AV
2			2483.500	49.149	18.557	-4.851	54.000	30.592	AV

7. Operation Frequency Range of 20dB Bandwidth


7.1. Test Equipment

Operation Frequency Range of 20dB Bandwidth / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2013.04.18
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2013.05.07

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

20 dB bandwidth of the emission is contained within the operation frequency band.

7.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Span greater than RBW.


7.5. Uncertainty

The measurement uncertainty is defined as ± 1 kHz


7.6. Test Result

Product	:	Mobile Phone
Test Item	:	Operation Frequency Range of 20dB Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit by 802.11b

Channel 01 (2412MHz)




Channel 11 (2462MHz)




Product	: Mobile Phone
Test Item	: Operation Frequency Range of 20dB Bandwidth
Test Site	: TR-8
Test Mode	: Mode 2: Transmit by 802.11g

Channel 01 (2412MHz)




Channel 11 (2462MHz)




Product	: Mobile Phone
Test Item	: Operation Frequency Range of 20dB Bandwidth
Test Site	: TR-8
Test Mode	: Mode 3: Transmit by 802.11n(20MHz)

Channel 01 (2412MHz)




Channel 11 (2462MHz)




Product	: Mobile Phone
Test Item	: Operation Frequency Range of 20dB Bandwidth
Test Site	: TR-8
Test Mode	: Mode 4: Transmit by 802.11n(40MHz)

Channel 03 (2422MHz)



Channel 09 (2452MHz)



8. Occupied Bandwidth


8.1. Test Equipment

Occupied Bandwidth / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2013.04.18
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2013.05.07

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

The minimum 6 dB bandwidth shall be at least 500 kHz.

8.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Span greater than RBW.

8.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

8.6. Test Result


Product	:	Mobile Phone
Test Item	:	6dB Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit by 802.11b

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	9450	500	Pass
06	2437	9980	500	Pass
11	2462	9200	500	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	: Mobile Phone
Test Item	: 6dB Occupied Bandwidth
Test Site	: TR-8
Test Mode	: Mode 2: Transmit by 802.11g

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	16460	500	Pass
06	2437	16480	500	Pass
11	2462	16480	500	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	: Mobile Phone
Test Item	: 6dB Occupied Bandwidth
Test Site	: TR-8
Test Mode	: Mode 3: Transmit by 802.11n(20MHz)

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	17780	500	Pass
06	2437	17780	500	Pass
11	2462	17780	500	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	: Mobile Phone
Test Item	: 6dB Occupied Bandwidth
Test Site	: TR-8
Test Mode	: Mode 4: Transmit by 802.11n(40MHz)

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
03	2422	35700	500	Pass
06	2437	35700	500	Pass
09	2452	35750	500	Pass


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



9. Power Output


9.1. Test Equipment

Power Output / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
Wideband Peak Power Meter	Anritsu	ML2495A	0905006	2013.01.12
Power Sensor	Anritsu	MA2411B	0846014	2013.01.12
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2013.05.07

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

The maximum peak power shall be less 1 Watt (30dBm).

Note: the conducted output power limit specified above is based on the use the antennas with directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Use the wideband power meter to test peak power and record the result.

9.5. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

9.6. Test Result

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (blue marker) for final test of each channel.

MCS Index for 802.11n	Spatial Streams	Data Rate (Mbps)					
		802.11b	802.11g	20MHz Bandwidth		40MHz Bandwidth	
				800ns GI	400ns GI	800ns GI	400ns GI
0	1	1	6	6.5	7.2	13.5	15.0
1	1	2	9	13.0	14.4	27.0	30.0
2	1	5.5	12	19.5	21.7	40.5	45.0
3	1	11	18	26.0	28.9	54.0	60.0
4	1	---	24	39.0	43.3	81.0	90.0
5	1	---	36	52.0	57.8	108.0	120.0
6	1	---	48	58.5	65.0	121.5	135.0
7	1	---	54	65.0	72.2	135.0	150.0
8	2	---	---	13.0	14.4	27.0	30.0
9	2	---	---	26.0	28.9	54.0	60.0
10	2	---	---	39.0	43.3	81.0	90.0
11	2	---	---	52.0	57.8	108.0	120.0
12	2	---	---	78.0	86.7	162.0	180.0
13	2	---	---	104.0	115.6	216.0	240.0
14	2	---	---	117.0	130.0	243.0	270.0
15	2	---	---	130.0	144.0	270.0	300.0

Power output at various data rates:

Test Mode	Bandwidth	Frequency (MHz)	Channel	Data Rate	Peak Power (dBm)
802.11b	20	2437	6	1	19.39
				5.5	21.03
				11	21.70
802.11g	20	2437	6	6	21.52
				24	21.40
				54	20.89
802.11n(20MHz)	20	2437	6	6.5	21.05
				39	20.60
				65	20.55
802.11n(40MHz)	40	2437	6	13.5	19.82
				81	19.01
				135	18.45

Product	:	Mobile Phone
Test Item	:	Power Output
Test Site	:	TR8
Test Mode	:	Mode 1: Transmit by 802.11b

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
01	2412	21.73	30.00	Pass
06	2437	21.70	30.00	Pass
11	2462	21.52	30.00	Pass

Product	:	Mobile Phone
Test Item	:	Power Output
Test Site	:	TR8
Test Mode	:	Mode 2: Transmit by 802.11g

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
01	2412	21.89	30.00	Pass
06	2437	21.52	30.00	Pass
11	2462	21.29	30.00	Pass

Product	:	Mobile Phone
Test Item	:	Power Output
Test Site	:	TR8
Test Mode	:	Mode 3: Transmit by 802.11n(20MHz)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
01	2412	21.34	30.00	Pass
06	2437	21.05	30.00	Pass
11	2462	20.95	30.00	Pass

Product	:	Mobile Phone
Test Item	:	Power Output
Test Site	:	TR8
Test Mode	:	Mode 4: Transmit by 802.11n(40MHz)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
03	2422	19.75	30.00	Pass
06	2437	19.82	30.00	Pass
09	2452	19.43	30.00	Pass

10. Power Spectral Density


10.1. Test Equipment

Power Spectral Density / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2013.04.18
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2013.05.07

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiated to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

10.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW= 100 kHz, VBW \geq 300KHz, SPAN to 5-30 % greater than the EBW, Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3\text{ kHz}/100\text{kHz} = -15.2\text{ dB})$.

10.5. Uncertainty


The measurement uncertainty is defined as $\pm 1.27\text{ dB}$

10.6. Test Result


Product	:	Mobile Phone
Test Item	:	Power Spectral Density
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit by 802.11b

Channel No.	Frequency (MHz)	Reading Value (dBm)	BWCF (dB)	PSD (dBm)	Limit (dBm)	Result
01	2412	8.39	-15.2	-6.81	8	Pass
06	2437	8.74	-15.2	-6.46	8	Pass
11	2462	8.77	-15.2	-6.43	8	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	Mobile Phone
Test Item	:	Power Spectral Density
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmit by 802.11g

Channel No.	Frequency (MHz)	Reading Value (dBm)	BWCF (dB)	PSD (dBm)	Limit (dBm)	Result
01	2412	4.82	-15.2	-10.38	8	Pass
06	2437	4.64	-15.2	-10.56	8	Pass
11	2462	4.55	-15.2	-10.65	8	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	Mobile Phone
Test Item	:	Power Spectral Density
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmit by 802.11n(20MHz)

Channel No.	Frequency (MHz)	Reading Value (dBm)	BWCF (dB)	PSD (dBm)	Limit (dBm)	Result
01	2412	5.07	-15.2	-10.13	8	Pass
06	2437	5.03	-15.2	-10.17	8	Pass
11	2462	4.44	-15.2	-10.76	8	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	Mobile Phone
Test Item	:	Power Spectral Density
Test Site	:	TR-8
Test Mode	:	Mode 4: Transmit by 802.11n(40MHz)

Channel No.	Frequency (MHz)	Reading Value (dBm)	BWCF (dB)	PSD (dBm)	Limit (dBm)	Result
03	2422	0.57	-15.2	-14.63	8	Pass
06	2437	0.71	-15.2	-14.49	8	Pass
09	2452	0.19	-15.2	-15.01	8	Pass

Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)

