

FCC Part15.247 Test Report

Product Name : HSPA/UMTS/GSM/GPRS/EDGE Mobile
Phone with Bluetooth
Model No. : HUAWEI U8850-5/U8850-5
Marketing Name : HUAWEI U8850/ U8850/HUAWEI VISION/
Huawei Vision/ HUAWEI VISION U8850
FCC ID : QISU8850-5

Applicant : Huawei Technologies Co., Ltd.
Address : Administration Building, Huawei Base, Bantian, Longgang
District, Shenzhen 518129

Date of Receipt : 23/11/2011
Test Date : 23/11/2011~06/12/2011
Issued Date : 12/12/2011
Report No. : 11BS064R-RF-US-P06V01
Report Version : V 2.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : 12/12/2011

Report No. : 11BS064R-RF-US-P06V01



Product Name : HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth

Applicant : Huawei Technologies Co., Ltd.

Address : Administration Building, Huawei Base, Bantian, Longgang District, Shenzhen 518129

Manufacturer : Huawei Technologies Co., Ltd.

Address : Administration Building, Huawei Base, Bantian, Longgang District, Shenzhen 518129

Model No. : HUAWEI U8850-5/U8850-5

Marketing Name : HUAWEI U8850/ U8850/HUAWEI VISION/ Huawei Vision/ HUAWEI VISION U8850

FCC ID : QISU8850-5

EUT Voltage : DC: 3.7V

Trade Name : HUAWEI

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2008
ANSI C63.4: 2003
ANSI C63.10: 2009

Test Result : Complied

Performed Location : Quietek Corporation (Linkou Laboratory)
No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.
TEL:+866-2-8601-3788 / FAX:+886-2-8601-3789
FCC Registration Number: 92195

Documented By : Alice Ni
(Engineering ADM: Alice Ni)

Reviewed By : Robin Wu
(Engineering Supervisor: Robin Wu)

Approved By : Marlin Chen
(Engineering Manager: Marlin Chen)

Laboratory Information

We, **QuietTek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	: BSMI, NCC, TAF
Germany	: TUV Rheinland
Norway	: Nemko, DNV
USA	: FCC, NVLAP
Japan	: VCCI

The related certificate for our laboratories about the test site and management system can be downloaded from QuietTek Corporation's Web Site : <http://www.quietek.com/tw/ctg/cts/accreditations.htm>
 The address and introduction of QuietTek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>
 If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
 TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com



LinKou Testing Laboratory :

No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen, Lin-Kou Shiang, Taipei, Taiwan, R.O.C.
 TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com



Suzhou (China) Testing Laboratory :

No. 99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., Suzhou,China.
 TEL : +86-512-6251-5088 / FAX : +86-512-6251-5098 E-Mail : service@quietek.com



TABLE OF CONTENTS

Description	Page
1. General Information	7
1.1. EUT Description	7
1.2. Mode of Operation.....	11
1.3. Tested System Details.....	12
1.4. Configuration of Tested System	13
1.5. EUT Exercise Software	14
2. Technical Test.....	15
2.1. Summary of Test Result	15
2.2. Test Environment.....	16
3. Conducted Emission.....	17
3.1. Test Equipment	17
3.2. Test Setup	17
3.3. Limit.....	18
3.4. Test Procedure	18
3.5. Uncertainty	18
3.6. Test Result	19
4. Radiated Emission	19
4.1. Test Equipment	21
4.2. Test Setup	22
4.3. Limit.....	23
4.4. Test Procedure	23
4.5. Uncertainty	23
4.6. Test Result	24
5. 20dB Bandwidth	27
5.1. Test Equipment	27
5.2. Test Setup	27
5.3. Limit.....	27
5.4. Test Procedure	28
5.5. Uncertainty	28
5.6. Test Result	29
6. Carrier Frequency Separation	35
6.1. Test Equipment	35
6.2. Test Setup	35
6.3. Limit.....	35
6.4. Test Procedure	36
6.5. Uncertainty	36
6.6. Test Result	37

7. Number of Hopping Frequencies	43
7.1. Test Equipment	43
7.2. Test Setup	43
7.3. Limit.....	43
7.4. Test Procedure	44
7.5. Uncertainty	44
7.6. Test Result	45
8. Time of Occupancy (Dwell Time)	54
8.1. Test Equipment	54
8.2. Test Setup	54
8.3. Limit.....	54
8.4. Test Procedure	55
8.5. Uncertainty	55
8.6. Test Result	56
9. Peak Output Power	62
9.1. Test Equipment	62
9.2. Test Setup	62
9.3. Limit.....	62
9.4. Test Procedure	63
9.5. Uncertainty	63
9.6. Test Result	64
10. Band-edge Compliance of RF Conducted Emissions	70
10.1. Test Equipment	70
10.2. Test Setup	70
10.3. Limit.....	70
10.4. Test Procedure	71
10.5. Uncertainty	71
10.6. Test Result	72
11. Spurious RF Conducted Emissions.....	76
11.1. Test Equipment.....	76
11.2. Test Setup.....	76
11.3. Limit.....	76
11.4. Test Procedure	77
11.5. Uncertainty	77
11.6. Test Result.....	78
12. Radiated Emission Band Edge	84
12.1. Test Equipment	84
12.2. Test Setup	85

12.3. Limit..... 85
12.4. Test Procedure 85
12.5. Uncertainty 86
12.6. Test Result 87

1. General Information

1.1. EUT Description

Product Name	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Model No.	HUAWEI U8850-5/U8850-5
Marketing Name	HUAWEI VISION/ Huawei Vision/ HUAWEI VISION U8850/ UAWEI U8850-5/ U8850-5
IMEI	862446010004712
Hardware Version	PR2
Software Version	U8850V100R001C00B237SP00
Device Category	Portable
RF Exposure Environment	Uncontrolled
Antenna Type	Internal
GPS	
Operate Frequency	1575.42MHz
Type of modulation	BPSK
2G	
Support Band	GSM850/GSM900/DCS1800/PCS1900
GPRS Type	Class B
GPRS Class	Class 10
Tx Frequency Range	GSM 850: 824~849MHz PCS 1900: 1850~1910MHz
Rx Frequency Range	GSM 850: 869~894MHz PCS 1900: 1930~1990MHz
Release Version	GSM: R99
Type of modulation	GMSK for GSM/GPRS; 8PSK for EDGE
Antenna Gain	-0.77dBi for 824~849MHz 1.6dBi for 1850~1910MHz
Max. Output Power (Avg. Power)	GSM850: 32.65 dBm PCS1900: 29.55 dBm
Max. Output Power (Radiated)	GSM850: 30.86 dBm- ERP PCS1900: 30.65 dBm- EIRP
3G	
Support Band	WCDMA Band II/WCDMA BAND V
Frequency Range Tx	WCDMA Band V: 824~849MHz

	WCDMA Band II: 1850~1910MHz
Frequency Range Rx	WCDMA Band V: 869~894MHz WCDMA Band II: 1930~1990MHz
UE Category	HSDPA: Category 10 HSUPA: Category 6
Release Version	UMTS FDD: Rel-6
Type of modulation(Uplink)	QPSK
Antenna Gain	-0.77dBi for 824~849MHz 1.6dBi for 1850~1910MHz
Max. Output Power (Avg. Power)	WCDMA Band II: 23.51dBm WCDMA Band V: 23.47 dBm
Max. Output Power (Radiated)	WCDMA Band II: 23.93 dBm- EIRP WCDMA Band V: 21.45 dBm- ERP
Bluetooth	
Bluetooth Frequency	2402~2480MHz
Bluetooth Version	V2.1 + EDR
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Gain	0.5dBi
Wi-Fi	
Wi-Fi Frequency	2412~2462MHz
Hotspots Function	YES
Type of modulation	802.11b: DSSS; 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps
	802.11g: 6/9/12/18/24/36/48/54 Mbps
	802.11n: up to 65 Mbps
Antenna Gain	0.5dBi
Max. Output Power (Avg. Power)	Wi-Fi: 14.39 dBm
Components	
Headset #1	Manufacturer: Jiangxi Lianchuang Hongsheng Electronic Co., LTD M/N: MEMD1532A726012
Headset #2	Manufacturer: QUANCHENG ELECTRONIC CO., LTD M/N: MEMD1532A726012
Battery	Brand Name: HUAWEI

	M/N: HB5K1H Rated Voltage and Capacitance: 3.7V/1400mAh
Adapter #1	Manufacturer: SHENZHEN HUNTKEY ELECTRIC CO., LTD M/N: HW-050100U1W Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 1.0A
Adapter #2	Manufacturer: TECH-POWER INTERNATIONAL CO., LTD. M/N: HW-050100U1W Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 1.0A

Note 1: Each adapter has two different labels (Show in EUT photo).

2: Adapter #1 was used for RF test.

Bluetooth Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

1.2. Mode of Operation

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmitter-1Mbps(GFSK_DH5)
Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z axis, and shown the worst case on this report.
3. This device is a composite device in accordance with Part 15 Subpart B regulations. The report number is 11BS064R-RF-US-P01V01.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	N/A	N/A	N/A	N/A	N/A

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Execute the software provided by applicant on the phone.
4	Select test channel and test mode to test.

2. Technical Test

2.1. Summary of Test Result

No deviations from the test standards

Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(b)(1)	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d)	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / SR1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCS 30	100366	2012/11/15
LISN	R&S	ESH3-Z5	836679/020	2012/02/10
LISN	R&S	ENV216	100085	2012/02/10
Pulse Limiter	R&S	ESH3-Z2	357.8810.52-1	2012/09/16

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

According to FCC ANSI C63.4: 2003 & ANSI C63.10: 2009.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Site: SR1	Time: 2011/11/29 - 09:19
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_100085(0.009-30MHz)	Polarity: Line
EUT:HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.154	54.463	44.878	-11.318	65.781	9.585	QP
2		0.154	30.756	21.172	-25.025	55.781	9.585	AV
3		0.194	50.219	40.561	-13.644	63.864	9.658	QP
4		0.194	34.109	24.451	-19.755	53.864	9.658	AV
5		0.254	43.818	34.138	-17.808	61.625	9.680	QP
6		0.254	28.322	18.642	-23.303	51.625	9.680	AV
7		0.318	39.073	29.393	-20.686	59.759	9.680	QP
8		0.318	29.164	19.484	-20.595	49.759	9.680	AV
9		0.382	36.265	26.585	-21.970	58.236	9.680	QP
10		0.382	26.671	16.991	-21.565	48.236	9.680	AV
11		21.822	23.255	12.949	-36.745	60.000	10.306	QP
12		21.822	17.049	6.744	-32.951	50.000	10.306	AV

Site: SR1	Time: 2011/11/29 - 09:22
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_100085(0.009-30MHz)	Polarity: Neutral
EUT:HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		0.154	46.590	36.845	-19.192	65.781	9.744	QP
2		0.154	25.016	15.271	-30.766	55.781	9.744	AV
3		0.186	46.400	36.717	-17.813	64.213	9.684	QP
4		0.186	28.240	18.557	-25.973	54.213	9.684	AV
5		0.250	38.988	29.336	-22.769	61.757	9.652	QP
6		0.250	20.433	10.781	-31.324	51.757	9.652	AV
7		0.322	43.646	33.992	-16.009	59.655	9.654	QP
8		0.322	30.568	20.914	-19.087	49.655	9.654	AV
9		0.646	37.967	28.283	-18.033	56.000	9.685	QP
10		0.646	25.698	16.014	-20.302	46.000	9.685	AV
11	*	0.770	40.170	30.475	-15.830	56.000	9.695	QP
12		0.770	27.374	17.679	-18.626	46.000	9.695	AV

4. Radiated Emission

4.1. Test Equipment


Radiated Emission / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Bilog Antenna	Schaffner Chase	CBL6112B	2918	2012/07/28
EMI Test Receiver	R&S	ESCS 30	100121	2012/12/06
Pre-Amplifier	QTK	N/A	N/A	2012/07/07
CXA Signal Analyzer	Agilent	N9000A	MY50510072	2012/02/10
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30
Horn Antenna	Schwarzbeck	9120D	576	2012/11/14
Pre-Amplifier	Quietek	AP-180C	CHM/071920	2012/07/12


Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

4.2. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the "cone of radiation" of EUT. The 3dB beamwidth is 60~10 degrees for H-plane and 90~10 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
 below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor – Preamplifier Gain

Mode 1: Transmitter-1Mbps(GFSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2401.9	60.9	31.2	92.1	Fundamental	/	PK
	H	188.4	30.8	-6.2	24.6	46	-21.4	QP
	H	222.5	25.3	-3.2	22.1	46	-23.9	QP
	H	3122.5	50.2	-15.8	34.4	54(Note)	-19.6	PK
	H	4791.0	55.2	-11.3	43.9	54(Note)	-10.1	PK
	H	7206.0	46.5	-2.6	43.9	54(Note)	-10.1	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	H	2441.1	61.8	31.2	93.0	Fundamental	/	PK
	H	296.1	27.4	-3.7	23.7	46	-22.3	QP
	H	309.8	27.3	-3.5	23.8	46	-22.2	QP
	H	3122.5	50.6	-15.8	34.8	54(Note)	-19.2	PK
	H	4867.5	54.5	-11.8	42.7	54(Note)	-11.3	PK
	H	7323.0	45.6	-3.0	42.6	54(Note)	-11.4	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	H	2480.1	62.6	31.2	93.8	Fundamental	/	PK
	H	311.7	24.6	-3.7	20.9	46	-25.1	QP
	H	122.4	25.0	-3.3	21.7	46	-24.3	QP
	V	3122.5	50.0	-15.8	34.2	54(Note)	-19.8	PK
	H	4944.0	57.9	-11.4	46.5	54(Note)	-7.5	PK
	V	7440.0	44.8	-2.6	42.2	54(Note)	-11.8	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 2: Transmitter-2Mbps(Pi/4 DQPSK _DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2401.8	62.4	31.2	93.6	Fundamental	/	PK
	V	336.7	24.5	-3.7	20.8	46	-25.2	QP
	V	340.1	26.4	-3.1	23.3	46	-22.7	QP
	H	3122.5	51.2	-16.1	35.1	54(Note)	-18.9	PK
	H	4791.0	55.5	-12.0	43.5	54(Note)	-10.5	PK
	H	7206.0	47.7	-3.5	44.2	54(Note)	-9.8	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	H	2441.1	63.1	31.2	94.3	Fundamental	/	PK
	H	160.3	31.7	-7.0	24.7	46	-21.3	QP
	H	181.5	29.8	-3.7	26.1	46	-19.9	QP
	H	3122.5	50.3	-16.1	34.2	54(Note)	-19.8	PK
	H	4867.5	54.7	-11.8	42.9	54(Note)	-11.1	PK
	V	7323.0	45.9	-3.0	42.9	54(Note)	-11.1	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	3.8	PK
78	H	2480.1	63.8	31.2	95.0	Fundamental	/	PK
	V	217.1	28.0	-3.7	24.3	46	-21.7	QP
	V	301.5	25.9	-1.9	24.0	46	-22.0	QP
	H	3122.5	51.2	-16.1	35.1	54(Note)	-18.9	PK
	V	4944.0	57.7	-11.4	46.3	54(Note)	-7.7	PK
	H	7440.0	45.2	-2.6	42.6	54(Note)	-11.4	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 3: Transmitter-3Mbps(8DPSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2402.1	60.1	31.2	91.3	Fundamental	/	PK
	H	66.4	23.3	-3.5	19.8	46	-26.2	QP
	H	140.2	22.6	-2.1	20.5	46	-25.5	QP
	H	3122.5	49.3	-15.1	34.2	54(Note)	-19.8	PK
	H	4791.0	55.1	-12.0	43.1	54(Note)	-10.9	PK
	H	7196.5	47.9	-3.5	44.4	54(Note)	-9.6	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	H	2441.1	61.7	31.2	92.9	Fundamental	/	PK
	V	179.2	26.0	-3.6	22.4	46	-23.6	QP
	V	288.4	24.0	-0.4	23.6	46	-22.4	QP
	H	3122.5	49.7	-15.1	34.6	54(Note)	-19.4	PK
	V	4867.5	55.0	-11.8	43.2	54(Note)	-10.8	PK
	V	7323.0	45.9	-3.0	42.9	54(Note)	-11.1	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	H	2480.1	62.9	31.2	94.1	Fundamental	/	PK
	V	314.3	25.1	-3.2	21.9	46	-24.1	QP
	V	344.4	24.1	-1.6	22.5	46	-23.5	QP
	V	3122.5	49.7	-15.1	34.6	54(Note)	-19.4	PK
	V	4944.0	57.9	-11.4	46.5	54(Note)	-7.5	PK
	H	7440.0	45.1	-2.6	42.5	54(Note)	-11.5	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

5. 20dB Bandwidth


5.1 Test Equipment

20dB Bandwidth / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2 Test Setup



5.3 Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

5.4 Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW \cong 1% of the 20dB bandwidth

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

5.5 Uncertainty


The measurement uncertainty is defined as ± 1 kHz

5.6 Test Result


Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Occupied Bandwidth
Test Site	:	Site 1
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	934.26	868.13
39	2441	931.51	868.60
78	2480	927.50	880.19


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Occupied Bandwidth
Test Site	:	Site 1
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1312.0	1179.3
39	2441	1306.0	1190.2
78	2480	1322.0	1194.7


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Occupied Bandwidth
Test Site	:	Site 1
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1247.0	1161.3
39	2441	1251.0	1151.0
78	2480	1242.0	1153.1


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



6. Carrier Frequency Separation


6.1. Test Equipment

Carrier Frequency Separation / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

6.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) \cong 1% of the span

Video (or Average) Bandwidth VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.5. Uncertainty


The measurement uncertainty is defined as \pm 1 kHz

6.6. Test Result


Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Carrier Frequency Separation
Test Site	:	Site 1
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Carrier Frequency Separation
Test Site	:	Site 1
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Carrier Frequency Separation
Test Site	:	Site 1
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7. Number of Hopping Frequencies


7.1. Test Equipment

Number of Hopping Frequencies / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

7.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW \cong 1% of the span

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.

7.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result


Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Number of Hopping Frequencies
Test Site	:	Site 1
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Number of Hopping Frequencies
Test Site	:	Site 1
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Number of Hopping Frequencies
Test Site	:	Site 1
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz



2462 - 2480 MHz



8. Time of Occupancy (Dwell Time)


8.1. Test Equipment

Time of Occupancy (Dwell Time) / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds

within a 30 second period.

- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW \cong RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

8.5. Uncertainty

The measurement uncertainty is defined as ± 0.1 us

8.6. Test Result


Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	Site 1
Test Mode	:	Transmitter-3Mbps(8DPSK_DH1)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	128.00	< 400	Pass

Test Time Period: $0.4 * 79 = 31.6$ sec, Hopping Times Within 1sec: $40/50$ msec= 800 hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[400 \mu s * 800] / 79 * 31.6 = 128.00$ msec

Channel 39 (2441MHz)-(3DH1)






Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	Site 1
Test Mode	:	Transmitter-3Mbps(8DPSK_DH3)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	261.280	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6$ sec, Hopping Times Within 1sec: $20/50$ msec= 400 hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(1.633 \text{ ms} \times 400) / 79] \times 31.6 = 261.280$ msec

Channel 39 (2441MHz) - (3DH3)






Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	Site 1
Test Mode	:	Transmitter-3Mbps(8DPSK_DH5)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	301.600	< 400	Pass

Test Time Period: $0.4 * 79 = 31.6$ sec, Hopping Times Within 1sec: $13/50$ msec= 260 hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(2.900 \text{ ms} * 260) / 79] * 31.6 = 301.600$ msec

Channel 39 (2441MHz) - (3DH5)





9. Peak Output Power


9.1. Test Equipment

Peak Output Power / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by

the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured.

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

9.5. Uncertainty


The measurement uncertainty is defined as ± 1.0 dB

9.6. Test Result


Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	1.30	30.00	Pass
39	2441	2.48	30.00	Pass
78	2480	2.93	30.00	Pass


DH5 2402MHz



DH5 2441MHz




DH5 2480MHz




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	3.83	30.00	Pass
39	2441	5.14	30.00	Pass
78	2480	5.67	30.00	Pass


2DH5 2402MHz



2DH5 2441MHz




2DH5 2480MHz




Product	: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	: Power Output
Test Mode	: Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	1.93	30.00	Pass
39	2441	3.02	30.00	Pass
78	2480	3.65	30.00	Pass


3DH5 2402MHz



3DH5 2441MHz



3DH5 2480MHz



10. Band-edge Compliance of RF Conducted Emissions


10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter

demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

10.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW \cong 1% of the span

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.


10.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


10.6. Test Result

Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel 00 (2402MHz)





Channel 78 (2480MHz)



Product	: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 1: Transmitter-1Mbps(GFSK_DH5)

Hopping Mode



11. Spurious RF Conducted Emissions


11.1. Test Equipment

Spurious RF Conducted Emissions / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

11.2. Test Setup



11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

11.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.


11.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


11.6. Test Result

Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



12. Radiated Emission Band Edge


12.1. Test Equipment

Radiated Emission Band Edge / Site 1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4440A	MY46185846	2012/11/30
Horn Antenna	Schwarzbeck	9120D	576	2012/11/14
Pre-Amplifier	QuieTek	AP-180C	CHM/071920	2012/07/12

Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

12.2. Test Setup



12.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

12.4. Test Procedure

According to ANSI C63.10: 2009.

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being

corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.

If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative “marker-delta” method may be employed.

12.5. Uncertainty

The measurement uncertainty above 1G is defined as $\pm 3.9 \text{ dB}$

below 1G is defined as $\pm 3.8 \text{ dB}$


12.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Site: Site 1	Time: 2011/11/25 - 14:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	60.472	29.695	N/A	N/A	30.777	PK
2		*	2401.913	92.082	60.809	18.082	74.000	31.272	PK

Site: Site 1	Time: 2011/11/25 - 14:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.275	17.498	-5.725	54.000	30.777	AV
2		*	2401.913	89.488	58.215	N/A	N/A	31.272	AV

Site: Site 1	Time: 2011/11/25 - 14:29
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	59.969	29.192	-14.031	74.000	30.777	PK
2		*	2401.913	90.869	59.596	N/A	N/A	31.272	PK

Site: Site 1	Time: 2011/11/25 - 14:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.275	17.498	-5.725	54.000	30.777	AV
2		*	2401.913	88.180	56.907	N/A	N/A	31.272	AV

Site: Site 1	Time: 2011/11/25 - 14:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.969	93.768	62.463	N/A	N/A	31.305	PK
2			2483.500	59.782	29.055	-14.218	74.000	30.727	PK

Site: Site 1	Time: 2011/11/25 - 14:38
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	90.815	59.510	N/A	N/A	31.305	AV
2			2483.500	48.515	17.788	-5.485	54.000	30.727	AV

Site: Site 1	Time: 2011/11/25 - 14:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.969	90.403	59.098	N/A	N/A	31.305	PK
2			2483.500	59.921	29.194	-14.079	74.000	30.727	PK

Site: Site 1	Time: 2011/11/25 - 14:42
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	87.595	56.290	N/A	N/A	31.305	AV
2			2483.500	48.520	17.793	-5.480	54.000	30.727	AV

Site: Site 1	Time: 2011/11/25 - 14:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	59.442	28.665	-14.558	74.000	30.777	PK
2		*	2401.817	93.555	62.282	N/A	N/A	31.273	PK

Site: Site 1	Time: 2011/11/25 - 14:46
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.287	17.510	-5.713	54.000	30.777	AV
2		*	2402.008	88.109	56.837	N/A	N/A	31.272	AV

Site: Site 1	Time: 2011/11/25 - 14:47
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	59.790	29.013	-14.210	74.000	30.777	PK
2		*	2401.722	92.012	60.738	N/A	N/A	31.273	PK

Site: Site 1	Time: 2011/11/25 - 14:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.281	17.504	-5.719	54.000	30.777	AV
2		*	2402.008	86.209	54.937	N/A	N/A	31.272	AV

Site: Site 1	Time: 2011/11/25 - 14:51
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.804	94.964	63.658	N/A	N/A	31.307	PK
2			2483.500	60.068	29.341	-13.932	74.000	30.727	PK

Site: Site 1	Time: 2011/11/25 - 14:54
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.068	89.410	58.105	N/A	N/A	31.305	AV
2			2483.500	48.538	17.811	-5.462	54.000	30.727	AV

Site: Site 1	Time: 2011/11/25 - 14:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.112	90.475	59.170	N/A	N/A	31.304	PK
2			2483.500	59.889	29.162	-14.111	74.000	30.727	PK

Site: Site 1	Time: 2011/11/25 - 14:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	84.551	53.246	N/A	N/A	31.305	AV
2			2483.500	48.518	17.791	-5.482	54.000	30.727	AV

Site: Site 1	Time: 2011/11/25 - 14:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	60.193	29.416	-13.807	74.000	30.777	PK
2		*	2401.960	91.327	60.054	N/A	N/A	31.272	PK

Site: Site 1	Time: 2011/11/25 - 15:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.275	17.498	-5.725	54.000	30.777	AV
2		*	2402.008	85.761	54.489	N/A	N/A	31.272	AV

Site: Site 1	Time: 2011/11/25 - 15:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	59.768	28.991	-14.232	74.000	30.777	PK
2		*	2402.103	90.054	58.782	N/A	N/A	31.272	PK

Site: Site 1	Time: 2011/11/25 - 15:03
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.269	17.492	-5.731	54.000	30.777	AV
2		*	2402.008	83.842	52.570	N/A	N/A	31.272	AV

Site: Site 1	Time: 2011/11/25 - 15:06
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.980	94.087	62.782	N/A	N/A	31.305	PK
2			2483.500	60.224	29.497	-13.776	74.000	30.727	PK

Site: Site 1	Time: 2011/11/25 - 15:10
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Horizontal
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	87.548	56.243	N/A	N/A	31.305	AV
2			2483.500	48.598	17.871	-5.402	54.000	30.727	AV

Site: Site 1	Time: 2011/11/25 - 15:10
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.936	90.087	58.781	N/A	N/A	31.305	PK
2			2483.500	60.800	30.073	-13.200	74.000	30.727	PK

Site: Site 1	Time: 2011/11/25 - 15:17
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_576(1-18GHz)	Polarity: Vertical
EUT: HSPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	83.523	52.218	N/A	N/A	31.305	AV
2			2483.500	48.561	17.834	-5.439	54.000	30.727	AV