



FCC Part15.247 Test Report

Product Name : WCDMA Digital Mobile Phone
Model No. : HUAWEI Y220-U05
FCC ID : QISY220-U05

Applicant : HUAWEI TECHNOLOGIES CO., LTD
Address : Administration Building, Headquarters of Huawei
Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C

Date of Receipt : 27/06/2013
Test Date : 27/06/2013~26/08/2013
Issued Date : 27/08/2013
Report No. : 136S072R-RF-US-P06V01
Report Version : V 1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : 27/08/2013

Report No. : 136S072R-RF-US-P06V01



Product Name : WCDMA Digital Mobile Phone

Applicant : HUAWEI TECHNOLOGIES CO., LTD.

Address : Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Manufacturer : HUAWEI TECHNOLOGIES CO., LTD.

Address : Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Model No. : HUAWEI Y220-U05

FCC ID : QISY220-U05

EUT Voltage : DC: 3.7V

Trade Name : HUAWEI

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2012
ANSI C63.4: 2009; ANSI C63.10: 2009

Test Result : Complied

Performed Location : Suzhou EMC Laboratory
No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., Suzhou, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By : Alice Mi

Reviewed By : Jack Zhang

Approved By : Jame Yuan

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	:	BSMI, NCC, TAF
Germany	:	TUV Rheinland
Norway	:	Nemko, DNV
USA	:	FCC
Japan	:	VCCI
China	:	CNAS

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site :<http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site :
<http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yongxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com

LinKou Testing Laboratory :

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com

Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : service@quietek.com

TABLE OF CONTENTS

Description	Page
1. General Information.....	7
1.1. EUT Description	7
1.2. Mode of Operation	10
1.3. Tested System Details.....	11
1.4. Configuration of Tested System	12
1.5. EUT Exercise Software	13
2. Technical Test.....	14
2.1. Summary of Test Result	14
2.2. Test Environment	15
3. Conducted Emission	16
3.1. Test Equipment	16
3.2. Test Setup	16
3.3. Limit.....	17
3.4. Test Procedure	17
3.5. Uncertainty	17
3.6. Test Result	18
4. Radiated Emission	20
4.1. Test Equipment	20
4.2. Test Setup	21
4.3. Limit.....	22
4.4. Test Procedure	22
4.5. Uncertainty	23
4.6. Test Result	24
5. 20dB Bandwidth	29
5.1. Test Equipment	29
5.2. Test Setup	29
5.3. Limit.....	29
5.4. Test Procedure	30
5.5. Uncertainty	30
5.6. Test Result	31
6. Carrier Frequency Separation	37
6.1. Test Equipment	37
6.2. Test Setup	37
6.3. Limit.....	37
6.4. Test Procedure	38
6.5. Uncertainty	38
6.6. Test Result	39

7.	Number of Hopping Frequencies	45
7.1.	Test Equipment	45
7.2.	Test Setup	45
7.3.	Limit.....	45
7.4.	Test Procedure	46
7.5.	Uncertainty	46
7.6.	Test Result	47
8.	Time of Occupancy (Dwell Time).....	56
8.1.	Test Equipment	56
8.2.	Test Setup	56
8.3.	Limit.....	56
8.4.	Test Procedure	57
8.5.	Uncertainty	57
8.6.	Test Result	58
9.	Peak Output Power	64
9.1.	Test Equipment	64
9.2.	Test Setup	64
9.3.	Limit.....	64
9.4.	Test Procedure	65
9.5.	Uncertainty	65
9.6.	Test Result	66
10.	Band-edge Compliance of RF Conducted Emissions	72
10.1.	Test Equipment	72
10.2.	Test Setup	72
10.3.	Limit.....	72
10.4.	Test Procedure	73
10.5.	Uncertainty	73
10.6.	Test Result	74
11.	Spurious RF Conducted Emissions.....	78
11.1.	Test Equipment	78
11.2.	Test Setup	78
11.3.	Limit.....	78
11.4.	Test Procedure	79
11.5.	Uncertainty	79
11.6.	Test Result	80
12.	Radiated Emission Band Edge.....	116
12.1.	Test Equipment	116
12.2.	Test Setup	117

12.3. Limit..... 117
12.4. Test Procedure 117
12.5. Uncertainty 118
12.6. Test Result 119

1. General Information

1.1. EUT Description

Product Name	WCDMA Digital Mobile Phone
Model No.	HUAWEI Y220-U05
Hardware Version	V2
Software Version	Y220-U05V100R001C386B204
Device Category	Portable
RF Exposure Environment	Uncontrolled
Antenna Type	Internal
2G	
Support Band	GSM850/PCS1900
GPRS Class	Class 12
Uplink	GSM 850: 824~849MHz PCS 1900: 1850~1910MHz
Downlink	GSM 850: 869~894MHz PCS 1900: 1930~1990MHz
Release Version	R99
Type of modulation	GMSK for GPRS; 8PSK for EDGE(Only for Downlink)
Antenna Gain	GSM 850: -2.6dBi PCS1900: -2.8dBi
3G	
Support Band	WCDMA Band II/WCDMA Band V
Uplink	WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz
Downlink	WCDMA Band II: 1930~1990MHz WCDMA Band V: 869~894MHz
Release Version	Rel-7
Type of modulation	QPSK, 16QAM for Downlink QPSK for Uplink
Antenna Gain	WCDMA Band II: -2.6dBi WCDMA Band V: -3.1dBi
Wi-Fi	
Wi-Fi Frequency	802.11b/g/n(20MHz): 2412 ~ 2462 MHz
Type of modulation	802.11b: DSSS; 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps

	802.11g: 6/9/12/18/24/36/48/54 Mbps
	802.11n: up to 65 Mbps
Peak Antenna Gain	-3.0dBi
Bluetooth	
Bluetooth Frequency	2402~2480MHz
Bluetooth Version	V3.0 + HS
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Gain	-3.0dBi
Components	
Battery #1	Brand Name: HUAWEI M/N: HB5N1 Rated Voltage and Capacitance: 3.7V/1350mAh S/N: GAGD410Z15801389
Battery #2	Brand Name: HUAWEI M/N: HB5N1 Rated Voltage and Capacitance: 3.7V/1350mAh S/N: BAAD316915805110
Adapter #1	Brand Name: HUAWEI M/N: HW-050055U1W Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 550mA S/N: HKAD50574030
Adapter #2	Brand Name: HUAWEI M/N: HW-050055U1W Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 550mA S/N: BYAD31910787

Bluetooth Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

1.2. Mode of Operation

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmitter-1Mbps(GFSK_DH5)
Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z Axis, and shown the worst case on this report.
3. This device is a composite device in accordance with Part 15 Subpart B regulations. The report number is 136S072R-RF-US-P01V02.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Bluetooth Tester	Anritsu	MT8852B	SUA0500090	Non-Shielded, 1.8m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	EUT communicate with Bluetooth Tester, then select test mode and channel to test

2. Technical Test

2.1. Summary of Test Result

- No deviations from the test standards
 Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(b)(1)	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2012 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2012 15.247(d)	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100726	2014.03.30
Two-Line V-Network	R&S	ENV216	100043	2014.03.30
Two-Line V-Network	R&S	ENV216	100044	2013.09.17
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2014.03.01
50ohm Termination	SHX	TF2	07081401	2013.09.17
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2014.01.10

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

According to FCC ANSI C63.4: 2009 & ANSI C63.10: 2009.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Engineer: Milo	
Site: TR1	Time: 2013/08/19 - 13:45
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Neutral
EUT: WCDMA Digital Mobile Phone	Power: AC 120V/60Hz
Note: Mode1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.150	56.965	47.000	-9.035	66.000	9.965	QP
2		0.150	40.465	30.500	-15.535	56.000	9.965	AV
3		0.186	50.894	40.997	-13.319	64.213	9.897	QP
4		0.186	27.752	17.855	-26.461	54.213	9.897	AV
5		0.226	50.124	40.262	-12.472	62.595	9.863	QP
6		0.226	32.397	22.535	-20.198	52.595	9.863	AV
7		0.262	46.499	36.595	-14.868	61.368	9.905	QP
8		0.262	28.596	18.692	-22.771	51.368	9.905	AV
9		0.298	40.208	30.303	-20.090	60.298	9.905	QP
10		0.298	21.584	11.680	-28.714	50.298	9.905	AV
11		2.426	39.280	29.300	-16.720	56.000	9.980	QP
12		2.426	30.480	20.500	-15.520	46.000	9.980	AV

Engineer: Milo	
Site: TR1	Time: 2013/08/19 - 13:57
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Line
EUT: WCDMA Digital Mobile Phone	Power: AC 120V/60Hz
Note: Mode1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.155	48.520	38.688	-17.205	65.725	9.832	QP
2		0.155	29.376	19.544	-26.348	55.725	9.832	AV
3		0.182	46.948	37.126	-17.446	64.394	9.823	QP
4		0.182	31.026	21.204	-23.368	54.394	9.823	AV
5		0.234	42.985	33.169	-19.322	62.307	9.815	QP
6		0.234	27.111	17.296	-25.195	52.307	9.815	AV
7		0.262	40.025	30.183	-21.342	61.368	9.843	QP
8		0.262	24.036	14.194	-27.332	51.368	9.843	AV
9		2.346	38.507	28.700	-17.493	56.000	9.807	QP
10		2.346	28.307	18.500	-17.693	46.000	9.807	AV
11		2.742	37.918	28.100	-18.082	56.000	9.818	QP
12		2.742	27.718	17.900	-18.282	46.000	9.818	AV

4. Radiated Emission

4.1. Test Equipment

Radiated Emission / AC-2


Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
EMI Test Receiver	R&S	ESCI	100573	2014.04.30
Loop Antenna	R&S	HFH2-Z2	833799/003	2013.11.17
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2013.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2014.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2014.01.09

Radiated Emission / AC-5


Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2014.03.30
Preamplifier	Miteq	NSP1800-25	1364185	2014.05.03
Preamplifier	Quietek	AP-040G	CHM-0906001	2014.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2013.10.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	737	2013.11.24
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2013.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2014.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2014.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2014.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2014.01.11

4.2. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the

maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the “cone of radiation” of EUT. The 3dB beamwidth is 60~10 degrees for H-plane and 90~10 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor – Preampifier Gain

Mode 1: Transmitter-1Mbps(GFSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4804.0	44.9	-7.1	37.8	54(Note2)	-16.2	PK
	V	4791.0	48.0	-7.2	40.8	54(Note2)	-13.2	PK
	H	7206.0	43.0	-1.8	41.2	54(Note2)	-12.8	PK
	V	7206.0	43.5	-1.9	41.6	54(Note2)	-12.4	PK
	H	9610.5	41.5	4.3	45.8	54(Note2)	-8.2	PK
	V	9610.5	42.5	4.4	46.8	54(Note2)	-7.2	PK
39	H	4867.5	50.2	-7.0	43.2	54(Note2)	-10.8	PK
	V	4882.0	44.0	-7.0	37.0	54(Note2)	-17.0	PK
	H	7323.0	42.6	-1.6	41.1	54(Note2)	-12.9	PK
	V	7323.0	42.6	-1.6	41.0	54(Note2)	-13.0	PK
	H	9764.0	38.5	4.5	43.0	54(Note2)	-11.0	PK
	V	9764.0	39.2	4.6	43.8	54(Note2)	-10.2	PK
78	H	4944.0	55.5	-7.1	48.4	54(Note2)	-5.6	PK
	V	4944.0	52.0	-7.0	45.1	54(Note2)	-8.9	PK
	H	7443.0	43.9	-1.2	42.7	54(Note2)	-11.3	PK
	V	7443.0	43.4	-1.2	42.2	54(Note2)	-11.8	PK
	H	9920.0	38.7	5.2	43.9	54(Note2)	-10.1	PK
	V	9920.0	38.8	5.2	44.0	54(Note2)	-10.0	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 2: Transmitter-2Mbps(Pi/4 DQPSK _DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4804.0	44.8	-7.1	37.8	54(Note2)	-16.2	PK
	V	4804.0	44.4	-7.2	37.2	54(Note2)	-16.8	PK
	H	7206.0	42.4	-1.8	40.6	54(Note2)	-13.4	PK
	V	7206.0	42.2	-1.9	40.3	54(Note2)	-13.7	PK
	H	9608.0	38.0	4.3	42.3	54(Note2)	-11.7	PK
	V	9608.0	38.5	4.4	42.9	54(Note2)	-11.2	PK
39	H	4867.5	49.9	-7.0	42.9	54(Note2)	-11.1	PK
	V	4867.5	48.4	-7.0	41.3	54(Note2)	-12.7	PK
	H	7323.0	41.1	-1.6	39.5	54(Note2)	-14.5	PK
	V	7323.0	41.0	-1.6	39.4	54(Note2)	-14.6	PK
	H	9764.0	38.1	4.5	42.7	54(Note2)	-11.3	PK
	V	9764.0	38.5	4.6	43.1	54(Note2)	-10.9	PK
78	H	4944.0	54.7	-7.1	47.6	54(Note2)	-6.4	PK
	V	4944.0	51.2	-7.0	44.3	54(Note2)	-9.7	PK
	H	7440.0	41.8	-1.2	40.6	54(Note2)	-13.4	PK
	V	7440.0	42.2	-1.2	41.0	54(Note2)	-13.0	PK
	H	9920.0	38.4	5.2	43.5	54(Note2)	-10.5	PK
	V	9920.0	38.3	5.2	43.5	54(Note2)	-10.5	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 3: Transmitter-3Mbps(8DPSK_DH5)


CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4804.0	45.1	-7.1	38.0	54(Note2)	-16.0	PK
	V	4804.0	44.0	-7.2	36.8	54(Note2)	-17.2	PK
	H	7206.0	42.5	-1.8	40.7	54(Note2)	-13.3	PK
	V	7206.0	43.0	-1.9	41.1	54(Note2)	-12.9	PK
	H	9608.0	38.5	4.3	42.8	54(Note2)	-11.2	PK
	V	9608.0	39.5	4.4	43.8	54(Note2)	-10.2	PK
39	H	4867.5	49.5	-7.0	42.5	54(Note2)	-11.5	PK
	V	4867.5	47.5	-7.0	40.5	54(Note2)	-13.5	PK
	H	7323.0	41.6	-1.6	40.0	54(Note2)	-14.0	PK
	V	7323.0	40.8	-1.6	39.3	54(Note2)	-14.7	PK
	H	9764.0	37.8	4.5	42.3	54(Note2)	-11.7	PK
	V	9764.0	39.5	4.6	44.1	54(Note2)	-9.9	PK
78	H	4944.0	55.2	-7.1	48.1	54(Note2)	-5.9	PK
	V	4944.0	50.6	-7.0	43.7	54(Note2)	-10.3	PK
	H	7440.0	40.8	-1.2	39.6	54(Note2)	-14.4	PK
	V	7440.0	41.7	-1.2	40.4	54(Note2)	-13.6	PK
	H	9920.0	38.2	5.2	43.3	54(Note2)	-10.7	PK
	V	9920.0	37.5	5.2	42.7	54(Note2)	-11.3	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.


The worst case of Radiated Emission below 1GHz:

Engineer: Toms	
Site: AC2	Time: 2013/07/16 - 16:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: CBL6112D_27611(30-1000MHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1 : Transmit at channel at 2402MHz By DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		124.090	25.368	6.598	-18.132	43.500	18.770	QP
2	*	419.212	30.050	5.565	-15.950	46.000	24.485	QP

Engineer: Toms	
Site: AC2	Time: 2013/07/16 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: CBL6112D_27611(30-1000MHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1 : Transmit at channel at 2402MHz By DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		114.390	26.605	7.985	-16.895	43.500	18.620	QP
2	*	180.350	28.662	13.032	-14.838	43.500	15.630	QP

5. 20dB Bandwidth


5.1 Test Equipment

20dB Bandwidth / TR8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2 Test Setup



5.3 Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

5.4 Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW \cong 1% of the 20dB bandwidth

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

5.5 Uncertainty


The measurement uncertainty is defined as ± 1 kHz

5.6 Test Result


Product	:	WCDMA Digital Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	934.0	875.3
39	2441	932.1	872.4
78	2480	932.9	872.7


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1262.0	1174.1
39	2441	1262.0	1177.3
78	2480	1261.0	1180.7


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1271.0	1186.2
39	2441	1271.0	1191.2
78	2480	1268.0	1196.9


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



6. Carrier Frequency Separation


6.1. Test Equipment

Carrier Frequency Separation / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping

channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

6.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) \cong 1% of the span

Video (or Average) Bandwidth VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.5. Uncertainty


The measurement uncertainty is defined as \pm 1 kHz

6.6. Test Result


Product	:	WCDMA Digital Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7. Number of Hopping Frequencies


7.1. Test Equipment

Number of Hopping Frequencies / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

7.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW \cong 1% of the span

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.

7.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result


Product	:	WCDMA Digital Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz



2462 - 2480 MHz



8. Time of Occupancy (Dwell Time)


8.1. Test Equipment

Time of Occupancy (Dwell Time) / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75

hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW \cong RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

8.5. Uncertainty

The measurement uncertainty is defined as ± 0.1 us

8.6. Test Result


Product	:	WCDMA Digital Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps (8DPSK_DH1)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	122.56	< 400	Pass

Test Time Period: 0.4*79=31.6sec, Hopping Times Within 1sec: 40/50msec=800hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(0.383ms * 800) / 79] * 31.6 = 122.56msec$

Channel 39 (2441MHz)-(3DH1)






Product	:	WCDMA Digital Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps (8DPSK_DH3)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	260.80	< 400	Pass

Test Time Period: $0.4 * 79 = 31.6\text{sec}$, Hopping Times Within 1sec: $20/50\text{msec} = 400\text{hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(1.63\text{ms} * 400) / 79] * 31.6 = 260.80\text{msec}$

Channel 39 (2441MHz) - (3DH3)






Product	:	WCDMA Digital Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps (8DPSK_DH5)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	322.56	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6$ sec, Hopping Times Within 1sec: $14/50$ msec= 280 hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(2.88 \text{ ms} \times 280) / 79] \times 31.6 = 322.56$ msec

Channel 39 (2441MHz) - (3DH5)





9. Peak Output Power


9.1. Test Equipment

Peak Output Power / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with

directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured.

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

9.5. Uncertainty


The measurement uncertainty is defined as ± 1.0 dB

9.6. Test Result


Product	:	WCDMA Digital Mobile Phone
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	6.53	30.00	Pass
39	2441	6.96	30.00	Pass
78	2480	6.66	30.00	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	6.79	30.00	Pass
39	2441	7.13	30.00	Pass
78	2480	6.78	30.00	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	: WCDMA Digital Mobile Phone
Test Item	: Power Output
Test Mode	: Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	6.85	30.00	Pass
39	2441	7.25	30.00	Pass
78	2480	6.91	30.00	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



10. Band-edge Compliance of RF Conducted Emissions


10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz

bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

10.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW \cong 1% of the span

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.


10.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


10.6. Test Result

Product	:	WCDMA Digital Mobile Phone
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel 00 (2402MHz)





Channel 78 (2480MHz)



Product	: WCDMA Digital Mobile Phone
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 1: Hopping Mode

Hopping Mode



11. Spurious RF Conducted Emissions


11.1. Test Equipment

Spurious RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100159	2014.03.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

11.2. Test Setup



11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in

Section 15.209(a) of FCC part 15 is not required.

11.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.


11.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


11.6. Test Result

Product	:	WCDMA Digital Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel 00 (30MHz – 1G)



Channel 00 (1G - 5G)



Channel 00 (5G - 9G)




Channel 00 (9G - 13G)



Channel 00 (13G - 17G)




Channel 00 (17G - 21G)




Channel 00 (21G - 25G)



Channel 39 (30MHz – 1G)



Channel 39 (1G - 5G)



Channel 39 (5G - 9G)




Channel 39 (9G - 13G)




Channel 39 (13G - 17G)




Channel 39 (17G - 21G)



Channel 39 (21G - 25G)



Channel 78 (30MHz – 1G)



Channel 78 (1G - 5G)




Channel 78 (5G - 9G)



Channel 78 (9G - 13G)



Channel 78 (13G - 17G)



Channel 78 (17G - 21G)




Channel 78 (21G - 25G)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel 00 (30MHz – 1G)



Channel 00 (1G - 5G)



Channel 00 (5G - 9G)



Channel 00 (9G - 13G)




Channel 00 (13G - 17G)




Channel 00 (17G - 21G)




Channel 00 (21G - 25G)



Channel 39 (30MHz – 1G)



Channel 39 (1G - 5G)




Channel 39 (5G - 9G)




Channel 39 (9G - 13G)



Channel 39 (13G - 17G)




Channel 39 (17G - 21G)




Channel 39 (21G - 25G)



Channel 78 (30MHz – 1G)



Channel 78 (1G - 5G)




Channel 78 (5G - 9G)




Channel 78 (9G - 13G)



Channel 78 (13G - 17G)



Channel 78 (17G - 21G)




Channel 78 (21G - 25G)




Product	:	WCDMA Digital Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel 00 (30MHz – 1G)




Channel 00 (1G - 5G)



Channel 00 (5G - 9G)



Channel 00 (9G - 13G)




Channel 00 (13G - 17G)



Channel 00 (17G - 21G)




Channel 00 (21G - 25G)



Channel 39 (30MHz – 1G)



Channel 39 (1G - 5G)



Channel 39 (5G - 9G)



Channel 39 (9G - 13G)



Channel 39 (13G - 17G)



Channel 39 (17G - 21G)




Channel 39 (21G - 25G)



Channel 78 (30MHz – 1G)



Channel 78 (1G - 5G)



Channel 78 (5G - 9G)




Channel 78 (9G - 13G)




Channel 78 (13G - 17G)



Channel 78 (17G - 21G)



Channel 78 (21G - 25G)




12. Radiated Emission Band Edge

12.1. Test Equipment

Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2014.03.30
EMI Test Receiver	R&S	ESCI	100573	2014.03.30
Preamplifier	Miteq	NSP1800-25	1364185	2014.05.03
Preamplifier	QuieTek	AP-040G	CHM-0906001	2014.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2013.10.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	737	2013.11.24
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2014.03.01
Temperature/Humidity Meter	zhicheng	ZC1-2	AC5-TH	2014.01.11

12.2. Test Setup



12.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

12.4. Test Procedure

According to ANSI C63.10: 2009.

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.

If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative “marker-delta” method may be employed.

12.5. Uncertainty

The measurement uncertainty above 1G is defined as $\pm 3.9 \text{ dB}$

below 1G is defined as $\pm 3.8 \text{ dB}$


12.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	53.615	16.456	-20.385	74.000	37.159	PK
2		*	2402.073	104.411	67.146	N/A	N/A	37.265	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	39.654	2.495	-14.346	54.000	37.159	AV
2		*	2401.885	74.308	37.044	N/A	N/A	37.263	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	53.110	16.611	-20.890	74.000	36.499	PK
2		*	2402.073	99.970	63.413	N/A	N/A	36.556	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	38.831	2.332	-15.169	54.000	36.499	AV
2		*	2401.885	71.554	34.998	N/A	N/A	36.556	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:29
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2480MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	106.777	68.838	N/A	N/A	37.939	PK
2			2483.500	65.605	27.635	-8.395	74.000	37.969	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2480MHz by DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.914	76.056	38.118	N/A	N/A	37.938	AV
2			2483.500	42.105	4.135	-11.895	54.000	37.969	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2480MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.079	101.470	64.551	N/A	N/A	36.919	PK
2			2483.500	58.694	21.758	-15.306	74.000	36.935	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 17:42
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode1: Transmit at channel 2480MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	72.035	35.116	N/A	N/A	36.919	AV
2			2483.500	39.851	2.915	-14.149	54.000	36.935	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 18:32
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode2: Transmit at channel 2402MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	52.525	15.366	-21.475	74.000	37.159	PK
2		*	2401.932	104.968	67.704	N/A	N/A	37.264	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 18:34
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode2: Transmit at channel 2402MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	39.790	2.631	-14.210	54.000	37.159	AV
2		*	2402.073	87.472	50.207	N/A	N/A	37.265	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 18:34
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode2: Transmit at channel 2402MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	51.408	14.909	-22.592	74.000	36.499	PK
2		*	2402.120	99.666	63.109	N/A	N/A	36.558	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 18:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode2: Transmit at channel 2402MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	38.869	2.370	-15.131	54.000	36.499	AV
2		*	2401.885	83.847	47.291	N/A	N/A	36.556	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 18:44
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WIFI	Power: DC 3.7V
Note: Mode2: Transmit at channel 2480MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	106.246	68.307	N/A	N/A	37.939	PK
2			2483.500	63.575	25.605	-10.425	74.000	37.969	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WIFI	Power: DC 3.7V
Note: Mode2: Transmit at channel 2480MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	89.529	51.590	N/A	N/A	37.939	AV
2			2483.500	43.394	5.424	-10.606	54.000	37.969	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WIFI	Power: DC 3.7V
Note: Mode2: Transmit at channel 2480MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	102.193	65.274	N/A	N/A	36.919	PK
2			2483.500	59.638	22.702	-14.362	74.000	36.935	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WIFI	Power: DC 3.7V
Note: Mode2: Transmit at channel 2480MHz by 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.991	86.309	49.390	N/A	N/A	36.919	AV
2			2483.500	41.243	4.307	-12.757	54.000	36.935	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:17
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	51.993	14.834	-22.007	74.000	37.159	PK
2		*	2401.932	104.048	66.784	N/A	N/A	37.264	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	39.863	2.704	-14.137	54.000	37.159	AV
2		*	2402.214	87.314	50.048	N/A	N/A	37.267	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	51.864	15.365	-22.136	74.000	36.499	PK
2		*	2402.120	99.394	62.837	N/A	N/A	36.558	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	38.837	2.338	-15.163	54.000	36.499	AV
2		*	2401.885	83.547	46.991	N/A	N/A	36.556	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:24
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2480MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.024	106.235	68.296	N/A	N/A	37.939	PK
2			2483.500	62.327	24.357	-11.673	74.000	37.969	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2480MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.057	89.503	51.564	N/A	N/A	37.939	AV
2			2483.500	43.504	5.534	-10.496	54.000	37.969	AV

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2480MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.079	102.926	66.007	N/A	N/A	36.919	PK
2			2483.500	58.519	21.583	-15.481	74.000	36.935	PK

Engineer: Toms	
Site: AC5	Time: 2013/08/17 - 19:29
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: WCDMA Digital Mobile Phone	Power: DC 3.7V
Note: Mode3: Transmit at channel 2480MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.090	86.724	49.805	N/A	N/A	36.919	AV
2			2483.500	41.520	4.584	-12.480	54.000	36.935	AV

The End