

Prüfbericht - Nr.: **14021914 001**
Test Report No.:
Seite 1 von 15
Page 1 of 15
Auftraggeber: **Bluetrek Technologies Limited**
Client:
8/F., Tai Yip Building
141 Thomson Road
Wanchai
Hong Kong
Gegenstand der Prüfung: **Bluetooth Headset**
Test Item:
Bezeichnung: **BLUETREK X3DSP** **Serien-Nr.:** **Engineering sample**
Identification: *Serial No.:*
Wareneingangs-Nr.: **00090722078-001,** **Eingangsdatum:** **22.07.2009, 06.08.2009**
Receipt No.: *Date of Receipt:* **00090806021-003**
Prüfort: **TÜV Rheinland Hong Kong Ltd.**
Testing Location: 9-10/F., Emperor International Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong
Hong Kong Productivity Council
 HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage: **FCC Part 15 Subpart C**
Test Specification: **ANSI C63.4-2003**
CISPR 22:1997
Prüfergebnis: **Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.**
Test Results: The above mentioned product was tested and **passed**.

Prüflaboratorium: **TÜV Rheinland Hong Kong Ltd.**
Testing Laboratory: 9-10/F., Emperor International Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

geprüft/ tested by:
kontrolliert/ reviewed by:

31.08.2009

 Ryan Chen
 Engineer



31.08.2009

 Sharon Li
 Project Manager


Datum
Date
Name/Stellung
Name/Position
Unterschrift
Signature
Datum
Date
Name/Stellung
Name/Position
Unterschrift
Signature
Sonstiges:
Other Aspects
FCCID: QIT44SBD
Abkürzungen:
 P(pass) = entspricht Prüfgrundlage
 F(fail) = entspricht nicht Prüfgrundlage
 N/A = nicht anwendbar
 N/T = nicht getestet

Abbreviations:
 P(pass) = passed
 F(fail) = failed
 N/A = not applicable
 N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
 This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	3
Manufacturers declarations	3
Product function and intended use.....	4
Submitted documents.....	4
Special accessories and auxiliary equipment	4
List of Test and Measurement Instruments.....	5
Results FCC Part 15 – Subpart C	6
Subclause 15.203 – Antenna Information	Pass.....
Subclause 15.204 – Antenna Information	Pass.....
Subclause 15.207 – Disturbance Voltage on AC Mains.....	Pass.....
Subclause 15.247 (a)(1) – Carrier Frequency Separation.....	Pass.....
Subclause 15.247 (a)(1)(iii) – Number of hopping channels	Pass.....
Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time)	Pass.....
Subclause 15.247 (a) – 20 dB Bandwidth.....	Pass.....
Subclause 15.247 (a) – Hopping Sequence	Pass.....
Subclause 15.247 (a) – Equal Hopping Frequency Use.....	Pass.....
Subclause 15.247 (a) – Receiver Input Bandwidth.....	Pass.....
Subclause 15.247 (a) – Receiver Hopping Capability	Pass.....
Subclause 15.247 (b)(1) – Peak Output Power	Pass.....
Subclause 15.247 (d) – Band edge compliance of conducted emissions	Pass.....
Subclause 15.205 – Band edge compliance of radiated emissions	Pass.....
Subclause 15.247 (d) – Spurious Conducted Emissions	Pass.....
Subclause 15.247 (c) – Spurious Radiated Emissions	Pass.....
Appendix 1 – Test protocols	25 pages
Appendix 2 – Test setup	3 pages
Appendix 3 – Photo documentation	7 pages
Appendix 4 – Product documentation	18 pages

www.tuv.com

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK; Pi/4 DQPSK; 8 DPSK
Number of channels	79
Channel separation	1 MHz
Type of antenna	Integrated Antenna
Antenna gain (dBi)	0
Power level	fix
Type of equipment	stand alone, plug-in radio device
Connection to public utility power line	No
Nominal voltage	V_{nor} : 3.7 V
Independent Operation Modes	Page scan Inquiry scan Connection state - ACL Link Connection state - SCO Link

www.tuv.com

Product function and intended use

The test item is a Bluetooth Headset based on the Bluetooth technology.

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s.

An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using phase shift keying (PSK) techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a Pi/4-DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation.

Submitted documents

Circuit Diagram

Block Diagram

Bill of material

User manual

Remark

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases.

Special accessories and auxiliary equipment

The product has been tested together with the following additional accessory:

AC/DC Power adaptor

Model number: SSA-5W-05 EU 050025F

Input: 100-240VAC, 50/60Hz, 0.2A

Output: 5.0VDC 250mA

List of Test and Measurement Instruments

	Equipment used	Manufacturer	Model No.	S/N	Due Date
<input checked="" type="checkbox"/>	Semi-anechoic Chamber	Frankonia	Nil	Nil	28-May-10
<input checked="" type="checkbox"/>	Test Receiver	R & S	ESU8	100141	15-Jun-10
<input checked="" type="checkbox"/>	Bi-conical Antenna	R & S	HK116	100242	22-May-10
<input checked="" type="checkbox"/>	Log Periodic Antenna	R & S	HL223	841516/020	21-May-10
<input checked="" type="checkbox"/>	Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 002	15-May-10
<input checked="" type="checkbox"/>	Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-09
<input checked="" type="checkbox"/>	High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	31-Oct-09
<input checked="" type="checkbox"/>	Horn Antenna	EMCO	3115	9002-3351	27-Feb-10
<input checked="" type="checkbox"/>	Spectrum Analyser	R & S	FSP 30	100416	09-Oct-09
<input checked="" type="checkbox"/>	Active Loop Antenna	EMCO	6502	9107-2651	20-Dec-09
<input checked="" type="checkbox"/>	Test Receiver	R & S	ESCS 30	100201	22-Dec-09
<input checked="" type="checkbox"/>	Artificial Mains Network	R & S	ESH3-Z5	100230	22-Dec-09
<input checked="" type="checkbox"/>	Pulse Limiter	R & S	ESH3-Z2	100161	22-Dec-09

Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Permanent attached antenna	
Verdict:	Pass	

Subclause 15.204 – Antenna Information		Pass
Requirement:	Provide information for every antenna proposed for the use with the EUT	
Results:	a) Antenna type: Integrated Antenna b) Manufacturer and model no: N.A. c) Gain with reference to an isotropic radiator: 0 dBi	
Verdict:	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains		Pass				
Test Port: AC mains input port of the charger						
Applied voltage: 100VAC						
Applicable only to equipment designed to be connected to the public utility power line.						
1) Mode of operation: Charging (Test Adaptor: SSA-5W-05 EU 050025F)						
Live measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB μ V	Average dB μ V	Limit QP (dB μ V)	Limit AV (dB μ V)	Verdict
0,15 – 0,5	-	-	-	66 - 56	56 - 46	Pass
> 0,5 - 5	-	-	-	56	46	Pass
> 5 - 30	-	-	-	60	50	Pass
Neutral measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB μ V	Average dB μ V	Limit QP (dB μ V)	Limit AV (dB μ V)	Verdict
0,15 – 0,5	0.168	18.9	4.1	66 - 56	56 - 46	Pass
	0.282	18.0	10.5	66 - 56	56 - 46	Pass
	0.366	19.0	6.7	66 - 56	56 - 46	Pass
> 0,5 - 5				56	46	Pass
> 5 - 30	-	-	-	60	50	Pass
Results:	The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz does not exceed the limits. For test Results plots refer to Appendix 1, page 2-3.					

Subclause 15.247 (a)(1) – Carrier Frequency Separation		Pass
Requirement:		Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation	: Tx mode (hopping on), GFSK	
Port of testing	: Temporary antenna port	
Detector	: Peak	
RBW/VBW	: 100 kHz / 300 kHz	
Supply voltage	: 3.7VDC from DC power supply	
Temperature	: 23°C	
Humidity	: 50%	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. The centre frequencies of the hopping channels are separated by more than the 2/3*20dB bandwidth. For test Results plots refer to Appendix 1, page 4.	
Verdict:	Pass	

Subclause 15.247 (a)(1)(iii) – Number of hopping channels		Pass
Requirement:		Frequency hopping systems operating in the 2400MHz-2483.5MHz bands shall use at least 15 hopping frequencies.
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation	: Tx mode (hopping on), GFSK	
Port of testing	: Temporary antenna port	
Detector	: Peak	
RBW/VBW	: 1 MHz / 3 MHz	
Supply voltage	: 3.7VDC from DC power supply	
Temperature	: 23°C	
Humidity	: 50%	
Results:	The total number of hopping frequencies is more than 15. For test Results plots refer to Appendix 1, page 5.	
Verdict:	Pass	

Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time)		Pass
Requirement: Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.		
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), DH5 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Results: Time period calculation = $0.4 \times 79 = 31.6\text{s}$ Dwell time = $64 \times 2.88 \times 10^{-3} = 184.3 \times 10^{-3}$ $\leq 400 \times 10^{-3} \text{ s}$		
For test protocols please refer to Appendix 1, page 7.		
Verdict: Pass		

Subclause 15.247 (a) – 20 dB Bandwidth		Pass
Requirement: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.		
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), (8DPSK) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 30 kHz / 100 kHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.		
For test protocols refer to Appendix 1, page 8-12.		

Pi/4 DQPSK

Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.690	0.624	1.314
2441	0.696	0.624	1.320
2480	0.702	0.624	1.326

8 DPSK Modulation


Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)

www.tuv.com

2402	0.696	0.618	1.314
2441	0.696	0.618	1.314
2480	0.702	0.624	1.326

GFSK Modulation

Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.534	0.444	0.978
2441	0.534	0.444	0.978
2480	0.534	0.456	0.990

Subclause 15.247 (a) – Hopping Sequence	Pass
Requirement: The hopping sequence is generated and provided with an example.	
Hopping sequence	
<p>The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto the hop frequencies.</p> 	

www.tuv.com

Example data:

Hop sequence {k} for CONNECTION STATE:

CLK start: 0x00000010

ULAP: 0x00000000

#ticks: 00 02 | 04 06 | 08 0a | 0c 0e | 10 12 | 14 16 | 18 1a | 1c 1e |

0x00000010:	08	66	10	70	12	19	14	23	16	01	18	05	20	33	22	37	
0x00000030:	24	03	26	07	28	35	30	39	32	72	34	76	36	25	38	29	
0x00000050:	40	74	42	78	44	27	46	31	48	09	50	13	52	41	54	45	
0x00000070:	56	11	58	15	60	43	62	47	32	17	36	19	34	49	38	51	
0x00000090:	40	21	44	23	42	53	46	55	48	33	52	35	50	65	54	67	
0x00000b0:	56	37	60	39	58	69	62	71	64	25	68	27	66	57	70	59	
0x00000d0:	72	29	76	31	74	61	78	63	01	41	05	43	03	73	07	75	
0x00000f0:	09	45	13	47	11	77	15	00	64	49	66	53	68	02	70	06	
0x0000110:	01	51	03	55	05	04	07	08	72	57	74	61	76	10	78	14	
0x0000130:	09	59	11	63	13	12	15	16	17	65	19	69	21	18	23	22	
0x0000150:	33	67	35	71	37	20	39	24	25	73	27	77	29	26	31	30	
0x0000170:	41	75	43	00	45	28	47	32	17	02	21	04	19	34	23	36	
0x0000190:	33	06	37	08	35	38	39	40	25	10	29	12	27	42	31	44	
0x00001b0:	41	14	45	16	43	46	47	48	49	18	53	20	51	50	55	52	
0x00001d0:	65	22	69	24	67	54	71	56	57	26	61	28	59	58	63	60	
0x00001f0:	73	30	77	32	75	62	00	64	49	34	51	42	57	66	59	74	
0x0000210:	53	36	55	44	61	68	63	76	65	50	67	58	73	03	75	11	
0x0000230:	69	52	71	60	77	05	00	13	02	38	04	46	10	70	12	78	
0x0000250:	06	40	08	48	14	72	16	01	18	54	20	62	26	07	28	15	
0x0000270:	22	56	24	64	30	09	32	17	02	66	06	74	10	19	14	27	
0x0000290:	04	70	08	78	12	23	16	31	18	03	22	11	26	35	30	43	
0x00002b0:	20	07	24	15	28	39	32	47	34	68	38	76	42	21	46	29	
0x00002d0:	36	72	40	01	44	25	48	33	50	05	54	13	58	37	62	45	
0x00002f0:	52	09	56	17	60	41	64	49	34	19	36	35	50	51	52	67	
0x0000310:	38	21	40	37	54	53	56	69	42	27	44	43	58	59	60	75	
0x0000330:	46	29	48	45	62	61	64	77	66	23	68	39	03	55	05	71	
0x0000350:	70	25	72	41	07	57	09	73	74	31	76	47	11	63	13	00	
0x0000370:	78	33	01	49	15	65	17	02	66	51	70	67	03	04	07	20	
0x0000390:	68	55	72	71	05	08	09	24	74	59	78	75	11	12	15	28	
0x00003b0:	76	63	01	00	13	16	17	32	19	53	23	69	35	06	39	22	
0x00003d0:	21	57	25	73	37	10	41	26	27	61	31	77	43	14	47	30	
0x00003f0:	29	65	33	02	45	18	49	34	19	04	21	08	23	20	25	24	

www.tuv.com

Subclause 15.247 (a) – Equal Hopping Frequency Use		Pass
Requirement: Each of the transmitter's hopping channels is used equally on average.		
Equal hopping frequency use		
The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.		

Subclause 15.247 (a) – Receiver Input Bandwidth		Pass
Requirement: The associated receiver(s) complies with the requirement that its input bandwidth matches the bandwidth of the transmitted signal.		
Receiver input bandwidth		
The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth was verified during Bluetooth RF conformance testing.		

Subclause 15.247 (a) – Receiver Hopping Capability		Pass
Requirement: The associated receiver has the ability to shift frequencies in synchronisation with the transmitted signals.		
Receiver hopping Capability		
The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.		

Subclause 15.247 (b)(1) – Peak Output Power		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31		
Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz)		
Port of testing : Temporary antenna port		
Detector : Peak		
RBW/VBW : 3 MHz / 10 MHz		
Supply voltage : 3.7VDC from DC power supply		
Temperature : 23°C		
Humidity : 50%		
Requirement: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400 – 2483.5 MHz band: 0.125 Watts.		
Results: For test protocols please refer to Appendix 1, page 13-17.		

GFSK Modulation

Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	5.26	3.52	8.780	1 / 30.0	Pass
2441	4.98	3.65	8.630	1 / 30.0	Pass

www.tuv.com

2480	4.83	3.60	8.430	1 / 30.0	Pass
------	------	------	-------	----------	------

Pi/4 DQPSK Modulation

Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	3.18	3.52	6.700	1 / 30.0	Pass
2441	2.88	3.65	6.530	1 / 30.0	Pass
2480	2.91	3.60	6.510	1 / 30.0	Pass

8 DPSK Modulation

Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	5.17	3.52	8.690	1 / 30.0	Pass
2441	4.98	3.65	8.630	1 / 30.0	Pass
2480	5.17	3.60	8.770	1 / 30.0	Pass

Subclause 15.247 (d) – Band edge compliance of conducted emissions		Pass
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation	: Tx mode (2402MHz, 2480MHz), 8DPSK	
Port of testing	: Temporary antenna port	
Detector	: Peak	
RBW/VBW	: 100 kHz / 300 kHz	
Supply voltage	: 3.7VDC from DC power supply	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. There is no peak found outside any 100 kHz bandwidth of the operating frequency band. For test protocols refer to Appendix 1, page 18-19.	

Subclause 15.205 – Band edge compliance of radiated emissions		Pass
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation	: Tx mode (2402MHz, 2480MHz), 8DPSK	
Port of testing	: Temporary antenna port	
Detector	: Peak	
RBW/VBW	: 1 MHz / 3 MHz	
Supply voltage	: 3.7VDC from DC power supply	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	Radiated emissions which fall in the restricted bands, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results:	There is no peak found in the restricted bands. For test protocols refer to Appendix 1, page 20-23.	

Subclause 15.247 (d) – Spurious Conducted Emissions		Pass			
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31				
Mode of operation	: Tx mode (2402MHz, 2441MHz, 2480MHz), 8DPSK				
Port of testing	: Temporary antenna port				
Detector	: Peak				
RBW/VBW	: 100 kHz / 300 kHz				
Supply voltage	: 3.7VDC from DC power supply				
Temperature	: 23 °C				
Humidity	: 50 %				
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Results:	<p>Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.</p> <p>There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(d). For test protocols refer to Appendix 1, page 24-25.</p>				
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	4800.000	-32.98	-1.66	-31.32	Pass
2441	4850.000	-34.15	0.38	-34.53	Pass
2480	4950.000	-40.22	-1.67	-38.55	Pass

www.tuv.com

Subclause 15.247 (c) – Spurious Radiated Emissions		Pass
Test Specification	: ANSI C63.4 – 2003	
Mode of operation	: Tx mode (2402MHz, 2441MHz, 2480MHz), 8DPSK	
Port of testing	: Enclosure	
Detector	: Peak	
RBW/VBW	: 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz	
Supply voltage	: internal batteries has been activated	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.205(c).	
Results:	<p>Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.</p> <p>All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.</p>	
Tx frequency 2402MHz	Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
no peak found	-	43.5 / QP
4804.167	48.68	74.0 / P
4803.926	31.38	54.0 / A
Tx frequency 2402MHz	Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
189.331	36.60	43.5 / QP
435.980	34.60	46 / QP
4803.990	49.06	74.0 / P
4803.990	31.45	54.0 / A
Tx frequency 2441MHz	Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
no peak found	-	43.5 / QP
4881.891	49.76	74.0 / P
4881.891	31.27	54.0 / A
Tx frequency 2441MHz	Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
189.331	34.80	43.5 / QP
409.340	33.50	46 / QP
4882.115	47.08	74.0 / P
4881.891	31.43	54.0 / A
Tx frequency 2480MHz	Vertical Polarization	

www.tuv.com

Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
no peak found	-	43.5 / QP
4960.577	45.64	74.0 / P
4960.577	31.52	54.0 / A
Tx frequency 2480MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
189.331	36.10	43.5 / QP
431.990	34.30	46 / QP
4959.776	46.46	74.0 / P
4959.988	31.60	54.0 / A