

Produkte
Products

Prüfbericht - Nr.: 14028205 001

Test Report No.:

Seite 1 von 14
Page 1 of 14

Auftraggeber: Bluetrek Technologies Limited
Client:
 8/F, Tai Yip Building
 141 Thomson Road
 Wanchai, Hong Kong

Gegenstand der Prüfung: Bluetooth Headset
Test Item:

Bezeichnung: BLUETREK® tattoo+ **Serien-Nr.:** Engineering sample
Identification: Serial No.:

Wareneingangs-Nr.: 00110922063-003 **Eingangsdatum:** 22.09.2011
Receipt No.: Date of Receipt:

Prüfort: Hong Kong Productivity Council
Testing Location: HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage: FCC Part 15 Subpart C
Test Specification: ANSI C63.4-2003
 CISPR 22:1997

Prüfergebnis: Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.
Test Results: The above mentioned product was tested and **passed**.

Prüflaboratorium: TÜV Rheinland Hong Kong Ltd.
Testing Laboratory: 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

geprüft/ tested by:

kontrolliert/ reviewed by:

14.11.2011 Joey Leung
 Test Engineer



14.11.2011 Sharon Li
 Assistant Manager



Datum
Date

Name/Stellung
Name/Position

Unterschrift
Signature

Datum
Date

Name/Stellung
Name/Position

Unterschrift
Signature

Sonstiges:
Other Aspects

FCCID: QITC30T

Abkürzungen: P(ass) = entspricht Prüfgrundlage
 F(ail) = entspricht nicht Prüfgrundlage
 N/A = nicht anwendbar
 N/T = nicht getestet

Abbreviations: P(ass) = passed
 F(ail) = failed
 N/A = not applicable
 N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
 This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	3
Manufacturers declarations	3
Product function and intended use.....	4
Submitted documents.....	4
Remark	4
List of Test and Measurement Instruments.....	5
Results FCC Part 15 – Subpart C	6
Subclause 15.203 – Antenna Information	Pass.....6
Subclause 15.204 – Antenna Information	Pass.....6
Subclause 15.207 – Disturbance Voltage on AC Mains.....	N/A.....6
Subclause 15.247 (a)(1) – Carrier Frequency Separation	Pass.....6
Subclause 15.247 (a)(1)(iii) – Number of hopping channels	Pass.....7
Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time)	Pass.....7
Subclause 15.247 (a) – 20 dB Bandwidth.....	Pass.....8
Subclause 15.247 (a) – Hopping Sequence	Pass.....8
Subclause 15.247 (a) – Equal Hopping Frequency Use.....	Pass.....9
Subclause 15.247 (a) – Receiver Input Bandwidth.....	Pass.....9
Subclause 15.247 (a) – Receiver Hopping Capability	Pass.....10
Subclause 15.247 (b)(1) – Peak Output Power	Pass.....10
Subclause 15.247 (d) – Band edge compliance of conducted emissions	Pass.....11
Subclause 15.205 – Band edge compliance of radiated emissions	Pass.....11
Subclause 15.247 (d) – Spurious Conducted Emissions	Pass.....12
Subclause 15.247 (c) – Spurious Radiated Emissions	Pass.....13
Appendix 1 – Test protocols	16 pages
Appendix 2 – Test setup	2 pages
Appendix 3 – Photo documentation	5 pages
Appendix 4 – Product documentation	9 pages

www.tuv.com

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	FHSS modulation
Number of channels	79
Channel separation	1 MHz
Type of antenna	PCB antenna
Antenna gain (dBi)	0
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V _{nor} : 3.7V
Independent Operation Modes	Page scan Inquiry scan Connection state - ACL Link Connection state - SCO Link

www.tuv.com

Product function and intended use

The test item is a Bluetooth Headset based on the Bluetooth technology. Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices. Bluetooth operates in the unlicensed ISM Band at 2.4 GHz. In the US a band of 83.5 MHz width is available. In this band, 79 RF channels spaced 1 MHz apart are defined. The channel is represented by a pseudo-random hopping sequence through the 79 channels. The channel is divided into time slots, with a nominal slot length of 625 µs, where each slot corresponds to different RF hop frequencies. The nominal hop rate is 1600 hops/s. The symbol rate on the channel is 1 Ms/s.

Submitted documents

- Circuit Diagram
- Block Diagram
- Bill of material
- User Manual
- Label Artwork

Remark

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases.

Client declares that the product is not able to operate during charging.

www.tuv.com

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Equipment used	Manufacturer	Model No.	S/N	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	25-May-12
Test Receiver	R & S	ESU40	100190	26-May-12
Bi-conical Antenna	R & S	HK116	100241	05-May-13
Log Periodic Antenna	R & S	HL223	841516/020	06-May-13
Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	08-Dec-11
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-13
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	30-Oct-13
Horn Antenna	EMCO	3115	9002-3351	11-May-13
Active Loop Antenna	EMCO	6502	9107-2651	19-Apr-12
FSP 30 Spectrum Analyser	R & S	FSP 30	100007	25-May-12


Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Permanent attached antenna	
Verdict:	Pass	
Subclause 15.204 – Antenna Information		Pass
Requirement:	Provide information for every antenna proposed for the use with the EUT	
Results:	a) Antenna type: b) Manufacturer and model no: c) Gain with reference to an isotropic radiator:	PCB antenna N.A. 0 dBi
Verdict:	Pass	
Subclause 15.207 – Disturbance Voltage on AC Mains		N/A
Applicable only to equipment designed to be connected to the public utility power line.		
Subclause 15.247 (a)(1) – Carrier Frequency Separation		Pass
Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.	
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation	: Tx mode (hopping on), GFSK	
Port of testing	: Temporary antenna port	
Detector	: Peak	
RBW/VBW	: 100 kHz / 300 kHz	
Supply voltage	: 3.7VDC, internal battery	
Temperature	: 23°C	
Humidity	: 50%	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. The centre frequencies of the hopping channels are separated by more than the 2/3*20dB bandwidth. For test Results plots refer to Appendix 1, page 2.	
Verdict:	Pass	

www.tuv.com

Subclause 15.247 (a)(1)(iii) – Number of hopping channels		Pass
Requirement: Frequency hopping systems operating in the 2400MHz-2483.5MHz bands shall use at least 15 hopping frequencies.		
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), GFSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC, internal battery Temperature : 23°C Humidity : 50%		
Results: The total number of hopping frequencies is more than 15. For test Results plots refer to Appendix 1, page 3.		
Verdict: Pass		

Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time)		Pass
Requirement: Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.		
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), DH5 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC, internal battery Temperature : 23°C Humidity : 50%		
Results: Time period calculation = $0.4 \times 79 = 31.6\text{s}$ Dwell time = $64 \times 2.92 \times 10^{-3} = 186.88 \times 10^{-3}$ $\leq 400 \times 10^{-3} \text{ s}$		
For test protocols please refer to Appendix 1, page 4.		
Verdict: Pass		

Subclause 15.247 (a) – 20 dB Bandwidth		Pass	
Requirement: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.			
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 30 kHz / 100 kHz Supply voltage : 3.7VDC, internal battery Temperature : 23°C Humidity : 50%			
Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. For test protocols refer to Appendix 1, page 5-6.			
GFSK Modulation			
Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.420	0.408	0.828
2441	0.420	0.414	0.834
2480	0.408	0.414	0.822
Subclause 15.247 (a) – Hopping Sequence		Pass	
Requirement: The hopping sequence is generated and provided with an example.			
Hopping sequence The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto the hop frequencies.			
			

www.tuv.com

Example data:

Hop sequence {k} for CONNECTION STATE:

CLK start: 0x00000010

ULAP: 0x00000000

#ticks: 00 02 | 04 06 | 08 0a | 0c 0e | 10 12 | 14 16 | 18 1a | 1c 1e |

0x00000010:	08 66	10 70	12 19	14 23	16 01	18 05	20 33	22 37
0x00000030:	24 03	26 07	28 35	30 39	32 72	34 76	36 25	38 29
0x00000050:	40 74	42 78	44 27	46 31	48 09	50 13	52 41	54 45
0x00000070:	56 11	58 15	60 43	62 47	32 17	36 19	34 49	38 51
0x00000090:	40 21	44 23	42 53	46 55	48 33	52 35	50 65	54 67
0x000000b0:	56 37	60 39	58 69	62 71	64 25	68 27	66 57	70 59
0x000000d0:	72 29	76 31	74 61	78 63	01 41	05 43	03 73	07 75
0x00000f0:	09 45	13 47	11 77	15 00	64 49	66 53	68 02	70 06
0x0000110:	01 51	03 55	05 04	07 08	72 57	74 61	76 10	78 14
0x0000130:	09 59	11 63	13 12	15 16	17 65	19 69	21 18	23 22
0x0000150:	33 67	35 71	37 20	39 24	25 73	27 77	29 26	31 30
0x0000170:	41 75	43 00	45 28	47 32	17 02	21 04	19 34	23 36
0x0000190:	33 06	37 08	35 38	39 40	25 10	29 12	27 42	31 44
0x00001b0:	41 14	45 16	43 46	47 48	49 18	53 20	51 50	55 52
0x00001d0:	65 22	69 24	67 54	71 56	57 26	61 28	59 58	63 60
0x00001f0:	73 30	77 32	75 62	00 64	49 34	51 42	57 66	59 74
0x0000210:	53 36	55 44	61 68	63 76	65 50	67 58	73 03	75 11
0x0000230:	69 52	71 60	77 05	00 13	02 38	04 46	10 70	12 78
0x0000250:	06 40	08 48	14 72	16 01	18 54	20 62	26 07	28 15
0x0000270:	22 56	24 64	30 09	32 17	02 66	06 74	10 19	14 27
0x0000290:	04 70	08 78	12 23	16 31	18 03	22 11	26 35	30 43
0x00002b0:	20 07	24 15	28 39	32 47	34 68	38 76	42 21	46 29
0x00002d0:	36 72	40 01	44 25	48 33	50 05	54 13	58 37	62 45
0x00002f0:	52 09	56 17	60 41	64 49	34 19	36 35	50 51	52 67
0x0000310:	38 21	40 37	54 53	56 69	42 27	44 43	58 59	60 75
0x0000330:	46 29	48 45	62 61	64 77	66 23	68 39	03 55	05 71
0x0000350:	70 25	72 41	07 57	09 73	74 31	76 47	11 63	13 00
0x0000370:	78 33	01 49	15 65	17 02	66 51	70 67	03 04	07 20
0x0000390:	68 55	72 71	05 08	09 24	74 59	78 75	11 12	15 28
0x00003b0:	76 63	01 00	13 16	17 32	19 53	23 69	35 06	39 22
0x00003d0:	21 57	25 73	37 10	41 26	27 61	31 77	43 14	47 30
0x00003f0:	29 65	33 02	45 18	49 34	19 04	21 08	23 20	25 24

Subclause 15.247 (a) – Equal Hopping Frequency Use Pass

Requirement: Each of the transmitter's hopping channels is used equally on average.

Equal hopping frequency use

The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.

Subclause 15.247 (a) – Receiver Input Bandwidth Pass

Requirement: The associated receiver(s) complies with the requirement that its input bandwidth matches the bandwidth of the transmitted signal.

Receiver input bandwidth

The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth was verified during Bluetooth RF conformance testing.

Subclause 15.247 (a) – Receiver Hopping Capability		Pass
Requirement: The associated receiver has the ability to shift frequencies in synchronisation with the transmitted signals.		
Receiver hopping Capability The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.		

Subclause 15.247 (b)(1) – Peak Output Power		Pass			
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 3 MHz / 10 MHz Supply voltage : 3.7VDC, internal battery Temperature : 23°C Humidity : 50%					
Requirement: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400 – 2483.5 MHz band: 0.125 Watts.					
Results: For test protocols please refer to Appendix 1, page 7-8.					
GFSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	3.34	3.52	6.860	1 / 30.0	Pass
2441	3.03	3.65	6.680	1 / 30.0	Pass
2480	2.64	3.60	6.240	1 / 30.0	Pass

Subclause 15.247 (d) – Band edge compliance of conducted emissions		Pass
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation	: Tx mode (2402MHz, 2480MHz), GFSK	
Port of testing	: Temporary antenna port	
Detector	: Peak	
RBW/VBW	: 100 kHz / 300 kHz	
Supply voltage	: 3.7VDC, internal battery	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Results:	<p>Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.</p> <p>There is no peak found outside any 100 kHz bandwidth of the operating frequency band. For test protocols refer to Appendix 1, page 9-10.</p>	

Subclause 15.205 – Band edge compliance of radiated emissions		Pass
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation	: Tx mode (2402MHz, 2480MHz), GFSK	
Port of testing	: Temporary antenna port	
Detector	: Peak	
RBW/VBW	: 1 MHz / 3 MHz	
Supply voltage	: 3.7VDC, internal battery	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	Radiated emissions which fall in the restricted bands, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results:	There is no peak found in the restricted bands. For test protocols refer to Appendix 1, page 11-14.	

Subclause 15.247 (d) – Spurious Conducted Emissions		Pass			
Test Specification	: FCC Part 15 Subpart A – Subclause 15.31				
Mode of operation	: Tx mode (2402MHz, 2441MHz, 2480MHz), GFSK				
Port of testing	: Temporary antenna port				
Detector	: Peak				
RBW/VBW	: 100 kHz / 300 kHz				
Supply voltage	: 3.7VDC, internal battery				
Temperature	: 23 °C				
Humidity	: 50 %				
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Results:	<p>Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.</p> <p>There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(d). For test protocols refer to Appendix 1, page 15-16.</p>				
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	9600	-36.49	1.54	-38.03	Pass
2441	7600	-37.42	2.80	-40.22	Pass
2480	3450	-35.98	2.24	-38.22	Pass

Subclause 15.247 (c) – Spurious Radiated Emissions		Pass
Test Specification	: ANSI C63.4 – 2003	
Mode of operation	: Tx mode (2402MHz, 2441MHz, 2480MHz), GFSK	
Port of testing	: Enclosure	
Detector	: Peak	
RBW/VBW	: 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz	
Supply voltage	: 3.7VDC, internal battery	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.205(c).	
Results:	<p>Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.</p> <p>All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.</p>	
Tx frequency 2402MHz	Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
1602.212	43.25	74.0 / P
1601.971	37.98	54.0 / A
4804.022	53.99	74.0 / P
4803.926	33.01	54.0 / A
Tx frequency 2402MHz	Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
1602.083	48.68	74.0 / P
1601.955	45.12	54.0 / A
4803.958	57.83	74.0 / P
4803.990	33.82	54.0 / A
Tx frequency 2441MHz	Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
1627.965	44.62	74.0 / P
1627.981	40.75	54.0 / A
4881.891	57.91	74.0 / P
4881.939	36.97	54.0 / A
Tx frequency 2441MHz	Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
1628.077	47.74	74.0 / P
1627.965	44.10	54.0 / A
4882.003	56.37	74.0 / P
4881.939	37.03	54.0 / A

www.tuv.com

Tx frequency 2480MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
1653.990	44.05	74.0 / P	
1653.974	38.79	54.0 / A	
4859.968	56.32	74.0 / P	
4959.952	38.04	54.0 / A	

Tx frequency 2480MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
1654.071	47.77	74.0 / P	
1653.974	44.09	54.0 / A	
4960.064	54.09	74.0 / P	
4959.920	36.77	54.0 / A	