


**5.8 GHZ RADOME OMNI - 10DBI
OMNIDIRECTIONAL ANTENNA****R380.700.212**
Series : ANTENNA**Scale 2:5**

All dimensions are in mm

**Issue : 0546**

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

RADIALL/LARSEN
antenna technologies

**5.8 GHZ RADOME OMNI - 10DBI
OMNIDIRECTIONAL ANTENNA**

R380.700.212
Series : ANTENNA

ELECTRICAL CHARACTERISTICS

Frequency :	5.725-5.875 GHz
Nominal Impedance :	50 Ω
VSWR :	
Normal & Icing Conditions :	1.5 Max
Omni cut plane gain measurement over the frequency band.	
Average Gain :	10 dBi ± 1 dB
Radiation Pattern :	
360°Omni-directional in the Horizontal Plane :	
Undulation Ratio in the Horizontal Plane :	2.4 dB (Typ)
-3 dB beamwidth in the Vertical Plane :	8.5 ° ± 0.5 °
Cross Polarization level :	
Horizontal Plane :	>23 dB
Vertical Plane :	>23 dB
Electrical tilt across band :	0 °
Polarization :	VERTICAL
Power withstanding :	20 W
DC Grounding :	YES
Connector type :	N Male (865.49.140)

Issue : 0546

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

RADIALL/LARSEN
antenna technologies

**5.8 GHZ RADOME OMNI - 10DBI
OMNIDIRECTIONAL ANTENNA**

R380.700.212
Series : ANTENNA

MECHANICAL CHARACTERISTICS

Plastic radome :	Acrylonitrile Styrene Acrylate (ASA) UL File-N°. E41871 (UL 94 – HB)
Color :	PANTONE COOL GRAY 1C
Ingress Protection :	IP 67
Weight :	134 g
Wind-loading in accordance with the ETS 300 019-1-4.1E:	200 Km/h
Overall length :	383 mm

ENVIRONMENTAL CHARACTERISTICS

Transportation :	In accordance with the ETS 300-019-1-2 T2.3
Temperature :	
Stationary :	-40/+55 °C (1), (2)
Cyclic :	-40°C - +55°C Rate 0.5°C/min (3)
Humidity :	
Stationary :	93% @ 30° C (4)
Vibration :	
Sinusoidal :	± 3 mm / 10 m/s² (5)
Shocks :	250 m/s² (6)
Salt mist :	22 Hours 40°C 93% HR 72 Hours 23°C 45-55% HR (7)
Drop test :	1 & 3 m (8)

5.8 GHZ RADOME OMNI - 10DBI
OMNIDIRECTIONAL ANTENNA

R380.700.212
 Series : **ANTENNA**

TESTS ENVIRONMENTAL



Test report n° 2002-46-8549

- (1) Tests following IEC 68-2-1 Ad
Duration: 16 hours @ -40° C
- (2) Tests following IEC 68-2-2 Bd
Duration: 16 hours @ +55° C
- (3) Tests following IEC 68-2-14 Nb
temperature changing rate: 0.5°C/min
time at each temperature: 16 hours
6 cycles
- (4) Tests following IEC 68-2-3
Stationary : 93% @ +30° C during 21 days
- (5) Tests following IEC 68-2-6 Fc
5 to 9 Hz : 3mm peak, 9 to 200 Hz : 10 m/s²
variation : 1 Octave/min.
5 cycles 5-200-5 Hz on each of the 2 axes
- (6) Tests following IEC 68-2-29 Eb
Half sinus shocks, duration: 6 ms
500 bumps in each of the 3 axes
- (7) Tests following IEC 68-2-52 Kb
Salted solution atomized during 2 hours
Concentration : 5% / 6.5 < pH < 7.2 @ 20°C
Solution collected : 1 < v < 2mL/h
- (8) Tests following IEC 68-2-32 Ed
Height : 1 m and 3 m
2 Drops along 3 directions

Issue : 0546

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



RADIALL/LARSEN
 antenna technologies

**5.8 GHZ RADOME OMNI - 10DBI
OMNIDIRECTIONAL ANTENNA****R380.700.212**
Series : ANTENNACURVES

Issue : 0546

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

RADIALL/LARSEN
antenna technologies

**5.8 GHZ RADOME OMNI - 10DBI
OMNIDIRECTIONAL ANTENNA****R380.700.212**
Series : ANTENNA

Issue : 0546

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

RADIALL/LARSEN
antenna technologies