

APPLICANT: MESH NETWORKS

FCC ID: QJEAPWR4000902

TABLE OF CONTENTS

TEST REPORT CONTAINING:

PAGE	1.....	LETTER OF EXPLANATION
PAGE	2-4.....	LIST OF TEST EQUIPMENT
PAGE	5.....	TEST PROCEDURES
PAGE	6.....	POWERLINE CONDUCTED INTERFERENCE
PAGE	7-8.....	POWERLINE CONDUCTED PLOTS
PAGE	9.....	OCCUPIED BANDWIDTH AND POWER OUTPUT
PAGE	10.....	6 dB BANDWIDTH PLOT
PAGE	11.....	METHOD OF MEASURING RF CONDUCTED AND SPURIOUS EMISSIONS AT ANTENNA TERMINALS DATA
PAGE	12.....	RADIATION INTERFERENCE TEST DATA
PAGE	13.....	METHOD OF MEASURING RADIATED SPURIOUS EMISS.
PAGE	14.....	RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BANDS
PAGE	15-16.....	BANDEdge PLOTS
PAGE	17.....	POWER SPECTRAL DENSITY
PAGE	18.....	POWER SEPCTRAL DENSITY PLOTS

EXHIBIT ATTACHMENTS:

EXHIBIT 1.....	REQUEST FOR CONFIDENTIALITY LETTER
EXHIBIT 2.....	FCC ID LABEL SAMPLE
EXHIBIT 3.....	SKETCH OF FCC ID LABEL LOCATION
EXHIBIT 4.....	EXTERNAL PHOTOGRAPHS
EXHIBIT 5.....	INTERNAL PHOTGRAPHS
EXHIBIT 6.....	BLOCK DIAGRAM
EXHIBIT 6.....	SCHEMATIC
EXHIBIT 7.....	USERS MANUAL
EXHIBIT 8.....	OPEATIONAL DESCRIPTION
EXHIBIT 9.....	DUTY CYCLE CORRECTION FACTOR
EXHIBIT 10.....	ANTENNA SPECIFICATIONS
EXHIBIT 11.....	MPE CALCULATION
EXHIBIT 12.....	TEST SETUP PHOTOGRAPHS

APPLICANT: MESH NETWORKS

FCC ID: QJEAPWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2TestReport.doc

TA BLE OF CONTENTS LIST

October 26, 2002

Federal Communications Commission  
Authorization and Evaluation Division  
7435 Oakland Mills Road  
Columbia, MD 21046

SUBJECT: MESH NETWORKS' FCC ID QJEAPWR4000902

To Whom It May Concern:

The attached application is for a direct sequence spread spectrum assembly, made up of a PCMIA card transceiver in an enclosure, designated as an access point.

MESH NETWORKS purchases standard antennas from the manufacturer. The antennas have a gain of 2.15 dBi.

Should you have any questions or require any further information with regards to this, please feel free to contact me.

Sincerely,

Mario R. de Aranzeta C.E.T.

MRD/sh  
Encl.

# EMC Equipment List

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
X	3-Meter OATS	TEI	N/A	N/A	Listed 12/22/99	12/22/02
	3/10-Meter OATS	TEI	N/A	N/A	Listed 3/26/01	3/26/04
	Receiver, Beige Tower Spectrum Analyzer (Tan)	HP	8566B Opt 462	3138A07786 3144A20661	CAL 8/31/01	8/31/03
	RF Preselector (Tan)	HP	85685A	3221A01400	CAL 8/31/01	8/31/03
	Quasi-Peak Adapter (Tan)	HP	85650A	3303A01690	CAL 8/31/01	8/31/03
X	Receiver, Blue Tower Spectrum Analyzer (Blue)	HP	8568B	2928A04729 2848A18049	CHAR 10/22/01	10/22/03
X	RF Preselector (Blue)	HP	85685A	2926A00983	CHAR 10/22/01	10/22/03
X	Quasi-Peak Adapter (Blue)	HP	85650A	2811A01279	CHAR 10/22/01	10/22/03
X	Biconnical Antenna	Electro-Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
	Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
	Biconnical Antenna	Eaton	94455-1	1057	CHAR 3/15/00	3/15/02
	BiconiLog Antenna	EMCO	3143	9409-1043		
X	Log-Periodic Antenna	Electro-Metrics	LPA-25	1122	CAL 10/2/01	10/2/03
	Log-Periodic Antenna	Electro-Metrics	EM-6950	632	CHAR 10/15/01	10/15/03
	Log-Periodic Antenna	Electro-Metrics	LPA-30	409	CHAR 10/16/01	10/16/03
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	152	CAL 3/21/01	3/21/04
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 11/24/00	11/24/03
X	Double-Ridged Horn Antenna	Electro-Metrics	RGA -180	2319	CAL 12/19/01	12/19/03
	Horn Antenna	Electro-Metrics	EM-6961	6246	CAL 3/21/01	3/21/03
	Horn Antenna	ATM	19-443-6R	None	No Cal Required	
	Passive Loop Antenna	EMC Test Systems	EMCO 6512	9706-1211	CHAR 7/10/01	7/10/03
	Line Impedance Stabilization . . .	Electro-Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03

APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2\TestReport.doc

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
X	Line Impedance Stabilization . . .	Electro-Metrics	EM-7820	2682	CAL 3/16/01	3/16/03
	Termaline Wattmeter	Bird Electronic Corporation	611	16405	CAL 5/25/99	5/25/01
	Termaline Wattmeter	Bird Electronic Corporation	6104	1926	CAL 12/12/01	12/12/03
	Oscilloscope	Tektronix	2230	300572	CHAR 2/1/01	2/1/03
	Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 1/22/02	1/22/04
	AC Voltmeter	HP	400FL	2213A14499	CAL 10/9/01	10/9/03
	AC Voltmeter	HP	400FL	2213A14261	CHAR 10/15/01	10/15/03
	AC Voltmeter	HP	400FL	2213A14728	CHAR 10/15/01	10/15/03
X	Digital Multimeter	Fluke	77	35053830	CHAR 1/8/02	1/8/04
	Digital Multimeter	Fluke	77	43850817	CHAR 1/8/02	1/8/04
	Digital Multimeter	HP	E2377A	2927J05849	CHAR 1/8/02	1/8/04
	Multimeter	Fluke	FLUKE-77-3	79510405	CAL 9/26/01	9/26/03
	Peak Power Meter	HP	8900C	2131A00545	CHAR 1/26/01	1/26/03
	Digital Thermometer	Fluke	2166A	42032	CAL 1/16/02	1/16/04
	Thermometer	Traulsen	SK-128		CHAR 1/22/02	1/22/04
X	Temp/Humidity gauge	EXTech	44577F	E000901	CHAR 1/22/02	1/22/04
	Frequency Counter	HP	5352B	2632A00165	CAL 11/28/01	11/28/03
	Power Sensor	Agilent Technologies	84811A	2551A02705	CAL 1/26/01	1/26/03
	Service Monitor	IFR	FM/AM 500A	5182	CAL 11/22/00	11/22/02
	Comm. Serv. Monitor	IFR	FM/AM 1200S	6593	CAL 5/12/02	5/12/04
	Signal Generator	HP	8640B	2308A21464	CAL 11/15/01	11/15/03
	Modulation Analyzer	HP	8901A	3435A06868	CAL 9/5/01	9/5/03
	Near Field Probe	HP	HP11940A	2650A02748	CHAR 2/1/01	2/1/03
	BandReject Filter	Lorch Microwave	5BR4-2400/ 60-N	Z1	CHAR 3/2/01	3/2/03

APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2\TestReport.doc

DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
BandReject Filter	Lorch Microwave	6BR6-2442/300-N	Z1	CHAR 3/2/01	3/2/03
BandReject Filter	Lorch Microwave	5BR4-10525/900-S	Z1	CHAR 3/2/01	3/2/03
High Pas Filter	Microlab	HA-10N		CHAR 10/4/01	10/4/03
Audio Oscillator	HP	653A	832-00260	CHAR 3/1/01	3/1/03
Frequency Counter	HP	5382A	1620A03535	CHAR 3/2/01	3/2/03
Frequency Counter	HP	5385A	3242A07460	CHAR 12/11/01	12/11/03
Preamplifier	HP	8449B-H02	3008A00372	CHAR 3/4/01	3/4/03
Amplifier	HP	11975A	2738A01969	CHAR 3/1/01	3/1/03
Egg Timer	Unk			CHAR 8/31/01	8/31/03
Measuring Tape, 20M	Kraftixx	0631-20		CHAR 2/1/02	2/1/04
Measuring Tape, 7.5M	Kraftixx	7.5M PROFI		2/1/02	2/1/04
Coaxial Cable #51	Insulated Wire Inc.	NPS 2251-2880	Timco #51	CHAR 1/23/02	1/23/04
Coaxial Cable #64	Semflex Inc.	60637	Timco #64	CHAR 1/24/02	1/24/04
Coaxial Cable #65	General Cable Co.	E9917 RG233/U	Timco #65	CHAR 1/23/02	1/23/04
Coaxial Cable #106	Unknown	Unknown	Timco #106	CHAR 1/23/02	1/23/04

APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2TestReport.doc

Page 4 of 18

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

A test program was run which simulated a normal data transmission on a network.

R&O FCC 97-114 Appendix C: Guidance on Measurements for Direct Sequence Spread Spectrum Systems:

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50 uH LISN. Both lines were observed with the UUT transmitting. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 78°F with a humidity of 55%.

BANDWIDTH 6.0dB: The measurements were made with the spectrum analyzer's resolution bandwidth(RBW)=1 MHz and the video bandwidth(VBW) =3 MHz and the span set as shown on plot.

POWER OUTPUT: The RF power output was measured at the antenna feed point using a peak power meter.

ANTENNA CONDUCTED EMISSIONS: The RBW=100 kHz, VBW=300 kHz and the span set to 10 MHz and the spectrum was scanned from 30 MHz to the 10th Harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a Agilent spectrum analyzer with a preselector. The bandwidth(RBW) of the spectrum analyzer was 100 kHz up to 1GHz and 1.0MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was = 3 MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 83°F with a humidity of 47%.

APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2TestReport.doc

Page 5 of 18

APPLICANT: MESH NETWORKS  
FCC ID: QJEAPWR4000902  
NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE  
RULES PART NUMBER: 15.207(a)  
REQUIREMENTS: .45 - 30 MHz 250 uV OR 47.96 dBuV  
TEST PROCEDURE: ANSI STANDARD C63.4-1992. The spectrum was scanned from .45 to 30 MHz.  
TEST DATA:


THE HIGHEST EMISSION READ FOR LINE 1 WAS 124.30 uV @ 2.49 MHz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 112.06 uV @ 2.78 MHz.

THE PLOTS IN THE FOLLOWING PAGES REPRESENT THE EMISSIONS TAKEN FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

POWERLINE CONDUCTED PLOT - LINE 1




START 450 kHz  
RES BW 10 kHz

VBW 10 kHz

STOP 30.00 MHz  
SWP 750 msec

POWERLINE CONDUCTED LINE 2 PLOT



APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2TestReport.doc

Page 8 of 18

APPLICANT: MESH NETWORKS

FCC ID: QJEAPWR4000902

NAME OF TEST: 6.0 dB BANDWIDTH

RULES PART NUMBER: 15.247(a)(2)

REQUIREMENTS: The 6 dB bandwidth must be greater than 500 kHz.

MEASUREMENT: The 6 dB bandwidth measured @ 2461.9MHz was 12.56 MHz.


MEASUREMENT DATA: See the following page.

NAME OF TEST: POWER OUTPUT


RULES PART NUMBER: 15.247(b) 1.0Watt or +30dBm


MEASUREMENT: .05 WATTS or 17 dBm @ 2433.0MHz

15.247(c) Method of Measuring RF Power output:  
The Peak power Sensor was connected in place of the antenna.



6 dB BANDWIDTH PLOT





NAME OF TEST: SPURIOUS EMISSIONS AT ANTENNA TERMINALS

REQUIREMENTS: Emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

EMISSION FREQUENCY MHz	dB BELOW CARRIER
2442	0
4884	40.3
7327	76
9768	80

NOTE: THE SPECTRUM WAS SCANNED TO THE TENTH HARMONIC.

APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2\TestReport.doc

Page 11 of 18

15.247(c), 15.205 & 15.209(b) Field\_strength\_of\_spurious\_emissions:

REQUIREMENTS:

FIELD STRENGTH of Fundamental:	FIELD STRENGTH of Harmonics	S15.209
902-928MHz	30 - 88 MHz	40 dBuV/m @3M
2.4-2.4835GHz	88 - 216 MHz	43.5
127.38dBuV/m @3m	216 - 960 MHz	46
	54 dBuV/m @3m	ABOVE 960 MHz 54dBuV/m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BAND SHALL BE AT LEAST 20 dB BELOW THE LEVEL OF THE FUNDAMENTAL. ATTENUATION BELOW THE LIMITS SPECIFIED IN 15.209 IS NOT REQUIRED.

REQUIREMENTS: Emissions that fall in the restricted bands (15.205) must comply with the requirements as specified in Section 15.209(a).

TEST DATA:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
2462.0	200.00	19.7	V	1.80	12.60	34.10	48.22
2462.0	240.00R	20.8	H	1.96	13.60	36.36	17.64
2462.0	280.00	21.9	V	2.12	15.48	39.50	42.82
2462.0	320.00R	25.8	H	2.32	16.52	44.64	9.36
2462.0	360.00	26.1	V	2.56	16.62	45.28	37.04
2462.0	400.00R	11.7	V	2.80	16.40	30.90	23.10
2462.0	440.00	19.9	H	2.92	17.02	39.84	42.48
2462.0	480.00	9.9	H	3.04	18.84	31.78	50.54
2462.0	520.00	13.9	H	3.16	29.56	46.62	35.70
2462.0	600.00	11.4	H	3.40	21.70	36.50	45.82
2462.0	680.00	9.4	V	3.64	23.62	36.66	45.66
2462.0	760.00	11.1	V	3.88	23.18	38.16	44.16
2462.0	920.00	11.9	H	3.75	24.66	40.31	42.01
2462.0	960.00R	8.8	V	2.85	25.44	37.09	16.91
2462.0	1,000.00	9.8	V	1.95	26.90	38.65	43.67
2462.0	2,461.00	70.0	H	3.37	28.95	102.32	25.06
2,462.0	4,924.00R	12.9	H	6.09	33.91	52.90	1.10

Three channels in the band were measured and the worst case is presented above.


METHOD OF MEASUREMENT: The procedure used was ANSI STANDARD C63.4-1992 & the FCC/OET Guidance on Measurements for Direct Sequence Spread Spectrum Systems - Public Notice 54797 Dated July 12, 1995. Measurements were made at the open field test site of TIMCO ENGINEERING INC. located at 849 N.W. State Road 45, Newberry, FL 32669.

APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2\TestReport.doc

Method of Measuring Radiated Spurious Emissions



APPLICANT: MESH NETWORKS

FCC ID: QJEAPWR4000902

NAME OF TEST: RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND

REQUIREMENTS: Emissions that fall in the restricted bands (15.205). These emissions must be less than or equal to 500 uV/m (54 dBuV/m).

TEST PROCEDURE: An in band field strength measurement of the fundamental Emission using the RBW and detector function required by C63.4-2000 and FCC Rules. The procedure was repeated with an average detector and a plot made. The calculated field strength in the adjacent restricted band is presented below.

**CHANNEL FREQUENCY: 2410 MHz**

Frequency: 2390.7 MHz


+ 0.70 dBuV  
+28.88 ACF  
+3.31 Coax Loss  
+10.00 dB Attn.  
+42.89 dBuV

**CHANNEL FREQUENCY: 2470 MHz**


Frequency: 2484.70 MHz

+10.30 dBuV  
+28.95 ACF  
+ 3.37 Coax Loss  
+10.00 dB Attn.  
+52.62 dBuV

BANDEDGE PLOT



BANDEDGE PLOT



APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2TestReport.doc

Page 16 of 18

APPLICANT: MESH NETWORKS

FCC ID: QJEAPWR4000902

NAME OF TEST: POWER SPECTRAL DENSITY

RULES PART NUMBER: 15.247(d)


REQUIREMENTS: The peak level measured must be no greater than +8.0dBm.

DATA: THE PLOT IS SHOWN ON THE FOLLOWING PAGE.

The level at 2443.7 MHz was -73.70 dBm.

-73.70	dBm
+20	dB Attn.
+35	dB Correction Factor
<hr/>	
-18.7	dBm

POWER SPECTRAL DENSITY PLOT



APPLICANT: MESH NETWORKS

FCC ID: QJEA PWR400

REPORT #: M/MeshNetworks\980UAT2\980UAT2TestReport.doc

Page 18 of 18