

Curtis-Straus

Worldwide Regulatory Approvals Experts

(A2LA Certificate Number 1627-01)

Technical Report

Company: Escort, Inc.
FRN: 0007508732
Model: Passport 7500
FCC ID: QKL7500
Equipment Code: CRD

Report prepared for:

Escort, Inc.
5440 West Chester Road
West Chester, OH 45069
Phone: (513)-870-8535
FAX: (513)-870-8523

Report prepared by:

Evan D. Gould
Curtis-Straus LLC
527 Great Road
Phone: (978)-486-8880
FAX: (978)-486-8828



EMC Manager

Introduction

This report is an application for Certification of a Radar Detector operating pursuant to 47 CFR 15.109, as amended by ET Docket No. 01-278; FCC 02-211, published in the Federal Register Vol. 67, No. 145 on Monday July 29, 2002.

Statement of Conformity

47 CFR 15.109(h) states that "*Radar detectors shall comply with the emissions limits...of [section 15.109(a)] over the frequency range of 11.7 – 12.2GHz.*" The applicable limit being 500µV/m measured at a distance of 3m. The Escort Passport 7500 has been tested and found to comply with this requirement.

Test Methodology

Radiated emission testing was performed according to the procedures in ANSI C63.4 (2001). The testing was performed at an antenna to EUT distance of 1 meter. Performance was investigated in the range 11.7-12.2GHz. The Passport 7500 was powered by a R.O.C. SPN4025A 12VDC 400mA power supply. Since the device is a hand-held unit, the emissions were maximized around the three orthogonal axes and the maximum reading was recorded. The integrated antenna cannot be maximized separately.

Test Equipment

SPECTRUM ANALYZERS					
x	Analyzer	Model No.	Company	Serial No.	Calibration Due
X	ORANGE 9kHz-26.5GHz	E4407B	HP	US39440975	07-JUN-2003

OPEN AREA TEST SITES (OATS)					
x	Site	FCC Code	IC Code	VCCI Code	Calibration Due
X	"T" Texas	93448	IC 2762-T	R-905/ C-480	04-FEB-2004

ANTENNAS					
x	Antenna	Model No.	Company	Serial No.	Calibration Due
X	BLACK Horn: 1-18GHz	3115	EMCO	9703-5148	12-JUN-2003

PREAMPLIFIERS / ATTENUATORS					
x	Preamplifier	Model No.	Company	Serial No.	Calibration Due
X	ORANGE-BLACK 1-20GHz	SMC-12A	MITEQ	690639	06-SEP-2002

Unless otherwise noted the calibration interval is one year. All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard. All Open Area Test Sites are located at 527 Great Road, Littleton, MA 01460.

Setup Photo



Model: Passport 7500

Measurement Results

All measurements taken were peak detector readings of the noise floor.
There were no emissions detected from the EUTs.

Radiated Emissions Table							Curtis-Straus LLC		
Date: 08-Aug-02			Company: Escort				Table 1		
Engineer: Evan Gould			EUT Desc: Passport 7500				Work Order: C0610		
Frequency Range: 11.7-12.2GHz					Measurement Distance: 1 m				
Notes: Emissions maximized Horizontally and Vertically. All measurements are noise floor readings.									
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBµV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBµV/m)	47 CFR 15.209(a)		
							Limit (dBµV/m)	Margin (dB)	Result (Pass/Fail)
7500	12228.0	32.2	19.9	38.9	4.7	55.9	63.5	-7.6	Pass
Test Sites: "T" Pre-Amp: Or-Blk Cable: 3m Microflex Analyzer: Orange Antennas: Black Horn									

Emission Plot

* Agilent 11:14:14 Aug 8, 2002

PASSPORT 7500 (max hold) 1m Mkr1 12.2284 GHz

Ref 75 dB μ V #Atten 0 dB 32.32 dB μ V

Peak Log 10 dB/

V1 S2

S3 FC

Start 11.66 GHz

#Res BW 1 MHz VBW 1 MHz

Stop 12.24 GHz

Sweep 4 ms (401 pts)

A:\7500.GIF file saved

Trace

Trace

1 2 3

Clear Write

Max Hold

Min Hold

View

Blank

More

1 of 2