



Test Report – FCC 15 Radar Detector Report

Applicant: Escort Incorporated

Approved for Release By:

Signature: *Bruno Clavier*

Name & Title: Bruno Clavier, General Manager

Date of Signature 4/14/2022

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



Table of Contents

1. CUSTOMER INFORMATION.....	3
1.1 TEST RESULT SUMMARY.....	3
2. LOCATION OF TESTING.....	3
2.1 TEST LABORATORY	3
2.2 TESTING WAS PERFORMED, REVIEWED BY	4
3. TEST SAMPLE(S) (EUT/DUT).....	5
3.1 DESCRIPTION OF THE EUT.....	5
3.2 CONFIGURATION OF EUT	6
3.3 TEST SETUP OF EUT	6
4. TEST METHODS & APPLICABLE REGULATORY LIMITS.....	7
4.1 TEST METHODS/STANDARDS/GUIDANCE	7
5. MEASUREMENT UNCERTAINTY.....	7
6. ENVIRONMENTAL CONDITIONS	7
7. LIST OF TEST EQUIPMENT AND TEST FACILITY.....	8
8. TEST RESULTS	9
8.1 RADIATED EMISSIONS.....	10
8.1.1 <i>Test Data: 11.7 – 12.2 GHz, Measurement Plot.</i>	11
9. ANNEX-A - PHOTOGRAPHS OF THE EUT.....	12
10. ANNEX-B – TEST SETUP PHOTOGRAPHS.....	12
11. HISTORY OF TEST REPORT CHANGES.....	12



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

1. Customer Information

Applicant: Escort Incorporated
Address: 5440 West Chester Road
West Chester Ohio, 45069, United States

1.1 Test Result Summary

The following test procedure was used ANSI C63.4-2014.

No additions to the test methods were needed. There were no deviations, or exclusions from the test methods. No test results are from external providers or from the customer. The test results relate only to the items tested. Timco does not offer opinions and interpretations, only a pass/fail statement.

Clauses	Description of the Requirements	Result (Pass, Fail or N/A)
Applicable Clauses from FCC 15 B		
15.109 (h)	Radiated Emission Limits	Pass

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780
FCC Designation # US1070
FCC site registration is under A2LA certificate # 0955.01
ISED Canada test site registration # 2056A
EU Notified Body # 1177
For all designations see A2LA scope # 0955.01



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

2.2 Testing was performed, reviewed by

Dates of Testing: 2/16/2022 – 2/21/2022

Signature:

A handwritten signature of Tim Royer.

Sr. EMC Engineer
EMC-003838-NE
The logo for iMARIE (International Association of EMC Test Engineers) is a circular emblem. It contains the text "CERTIFIED" at the top and "ENGINEER" at the bottom. In the center, the letters "iMARIE" are written in a stylized, italicized font, with "i" and "M" being particularly prominent.

Name & Title:

Tim Royer, EMC Engineer

Date of Signature

4/14/2022

Signature:

A handwritten signature of Kristoffer Costa.

Name & Title:

Kristoffer Costa, EMC Technician

Date of Signature

4/14/2022



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

3. Test Sample(s) (EUT/DUT)

The test sample was received: 2/16/2022

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	QKLM13C
Brief Description	MAX360c MKII Radar Detector
Model(s) #	MAX360c MKII
Firmware version	n/a
Software version	n/a
Serial Number	n/a

Technical Characteristics	
Technology	Radar Detector
Frequency Range	10.525GHz(X-Band), 24.150 GHz (K-Band), 33.4-36.0G Hz (Ka Band)
Antenna Connector	n/a
Voltage Rating (AC or Batt.)	12 VDC

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	n/a	n/a	0 dBi

- Note: Information such as antenna gain, firmware/software numbers are provide by manufacturer and cannot be validated by the test lab.



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

3.2 Configuration of EUT

Band (MHz)	Mode	Number of Ant.
11.7 to 12.2GHz	Receive	1

Operating conditions during Testing:

No modifications of the device under test (including firmware, specific software settings, and input/output signal levels to the EUT).

Peripherals used during Testing:

No peripherals used.

3.3 Test Setup of EUT

Equipment, antenna, and cable arrangement. The setup of the equipment and cable or wire placement on the test site that produces the highest radiated and the highest ac power-line conducted emissions shall be shown clearly and described. Information on the orientation of portable equipment during testing shall be included. Drawings or photographs may be used for this purpose.

Test Setups are included in the test report.



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance

The measurement was performed as per ANSI C63.4 referencing FCC KDB 214146. Test results are available in this report.

Limits and Regulatory Limits:

- 1) FCC 15.109 (h)
- 2) FCC KDB 214146

5. Measurement Uncertainty

Parameter	Uncertainty (dB)
Conducted Emissions	± 3.14 dB
Radiated Emissions (9kHz – 30 MHz)	± 3.08 dB
Radiated Emissions (30 – 200 MHz)	± 2.16 dB
Radiated Emissions (200 – 1000 MHz)	± 2.15 dB
Radiated Emissions (1 GHz – 18 GHz)	± 2.14 dB
Radiated Emissions (18 GHz – 40 GHz)	± 2.31 dB

Note: The uncertainties provided in this table represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of K=2.

6. Environmental Conditions

Temperature & Humidity

Measurements performed at the test site did not exceed the following:

Parameter	Measurement
Temperature	23 C +/- 5%
Humidity	55% +/- 5%
Barometric Pressure	30.05 in Hg

Note: Specific environmental conditions that are applicable to a specific test are available in the test result section.



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

7. List of Test Equipment and Test Facility

The test equipment used identified by type, manufacturer, serial number, or other identification and the date on which the next calibration or service check is due.

Description of the firmware or software used to operate EUT for testing purposes.

A complete list of all test equipment used shall be included with the test report. The manufacturer's model and serial numbers, and date of last calibration, and calibration interval shall be included. Measurement cable loss, measuring instrument bandwidth and detector function, video bandwidth, if appropriate, and antenna factors shall also be included where applicable.

List of Test Equipment

Test Equipment						
Type	Device	Manufacturer	Model	SN#	Current Cal	Cal Due
Antenna	Biconical 1057	Eaton	94455-1	1057	10/16/20	10/16/2023
Antenna, NSA	Log-Periodic 1243	Eaton	96005	1243	5/4/21	5/3/2024
Antenna	Double-Ridged Horn/ETS Horn 1	ETS-Lindgren	3117	00035923	2/25/20	2/24/2023
CHAMBER	CHAMBER	Panashield	3M	N/A	3/12/19	3/11/2022
Pre-amp	Pre-amp	RF-LAMBDA	RLNA00M45GA	NA	2/27/19	2/26/2022
Receiver	EMI Test Receiver R&S ESU 40	Rohde & Schwarz	ESU 40	100320	5/27/21	5/26/2024



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8. Test Results

The results of the test are usually indicated in the form of tables, spectrum analyzer plots, charts, sample calculations, as appropriate for each test procedure.

A description and/or a block diagram of the test setup is usually provided.

The measurement results, along with the appropriate limits for comparison, may be presented in tabular or graphical form. In addition, any variation in the measurement environment may be reported if applicable (e.g., a significant change of temperature that could affect the cable loss and amplifier response).

Units of measurement

Unless noted otherwise in the referenced standard, the measurements of ac power-line conducted emissions and conducted power output will be reported in units of dB μ V. Unless noted otherwise in the referenced standard, the measurements of radiated emissions will be reported in units of decibels, referenced to one microvolt per meter (dB μ V/m) for electric fields, or to one ampere per meter (dBA/m) for magnetic fields, at the distance specified in the appropriate standards or requirements. The measurements of antenna-conducted power for receivers may be reported in units of dB μ V if the impedance of the measuring instrument is also reported. Otherwise, antenna-conducted power will be reported in units of decibels referenced to one milliwatt (dBm). All formulas for data conversions and conversion factors, if used, will be included in this measurement report.


Example:

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB μ V	+ 10.36 dB/m	+0.40 dB	= 30.36 dB μ V/m @ 3m


EIRP = Pcond (dBm) + dBi

8.1 Radiated Emissions

Limits from FCC 15.109 and test procedure from ANSI C63.4-2014.



8.1.1 Test Data: 11.7 – 12.2 GHz, Measurement Plot



Date: 21.FEB.2022 08:56:33

Note: Blue trace is vertical and Red trace is horizontal



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

9. ANNEX-A - Photographs of the EUT

Photographs of the EUT and any manufacturer supplied accessories to be used with the EUT are in a separate document.

10. ANNEX-B – Test Setup Photographs

Test setup photographs are located in a separate document.

11. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_0778-22_FCC_15 Radar Detector_	1	Initial release	2/21/2022
	2	Updated Model # on Page 5	4/6/2022
	3	Updated Page 7	4/14/2022



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

END OF TEST REPORT
