

FCC Part 22/24/27 Compliance Test Report

Test Report no.:	FCC22&24&27_RM-927_19.docx	Date of Report:	21-Aug-13
Number of pages:	13	Customer's Contact person:	Victoria Abadilla
Testing laboratory:	TCC Nokia San Diego Laboratory 16620 West Bernardo Drive San Diego, CA 92127 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500	Customer:	Nokia, Inc. 16620 West Bernardo Drive San Diego, CA 92127 USA Tel. +1 858 831 5000 Fax. +1 858 385 1598
FCC listing no.:	586140		
IC recognition no.:	10162A-1		
Tested devices/ accessories:	Phone RM-927 / Salcomp AC Charger AC-60 / Cable CA-190 / Headset WH-902		
FCC ID:	QMND	IC:	661X-D
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 22/24/27 , TIA-603-C-2004 and IC standards, RSS-GEN (Issue 3, December 2010), RSS-132 (Issue 2, September 2005), RSS-133 (Issue 5, February 2009). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Feng You, Senior Specialist

1. Summary for FCC Part 22/24/27 Compliance Test Report

Date of receipt	20-Jul-2013
Testing completed	20-Aug-13
The customer's contact person	Victoria Abadilla
Test Plan referred to	T:\Projects\RM-927\TestPlan\RS_testplan_RM-927.xlsm
Notes	-
Document name	T:\Projects\RM-927\EMC\FCC22&24&27_RM-927_19.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:
GSM/CDMA/WCDMA/LTE/WLAN/Bluetooth
The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-927	35590605001377	0160	-	1028.0305.1329.2000	30759
Salcomp AC Charger	AC-60	4090493152610300459	-	-	-	30744
Cable	CA-190	-	-	-	-	30745
Headset	WH-902	-	-	-	-	30746

1.2. Summary of Test Results

CDMA800:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	PASSED
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	PASSED
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

CDMA1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	PASSED
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	PASSED
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Laboratory.

CONTENTS


1. Summary for FCC Part 22/24/27 Compliance Test Report	2
1.1. EUT and Accessory Information.....	2
1.2. Summary of Test Results.....	2
2. Radiated RF output power	
(FCC §22.913(a), §24.232(b), §27.53(h), §27.53(c)(2)(4), RSS-132 4.4, RSS-133 6.4)....	4
2.2. Test method and limit.....	4
2.3. CDMA800 TX test results.....	5
2.4. CDMA1900 TX test results.....	5
3. Band edge compliance	
(FCC §22.917(a), §24.238(a), §27.53(h), §27.53(c)(2)(4), RSS-132 4.5, RSS-133 6.5)....	6
3.2. Test method and limit.....	6
3.3. CDMA800 test results	7
3.4. CDMA1900 test results	8
4. Spurious radiated emissions	
(FCC §22.917(a), §2.1053, §24.238(a), §2.1053, §27.53(h), §27.53(c)(2)(4), RSS-132 4.5, RSS-133 6.5).....	9
4.2. Test method and limit.....	9
4.3. CDMA800 TX test results.....	11
4.4. CDMA1900 TX test results.....	11
5. Test Equipment.....	12
5.1. Conducted measurements	12
5.2. Radiated measurements	12

2. Radiated RF output power

(FCC §22.913(a), §24.232(b), §27.53(h), §27.53(c)(2)(4), RSS-132 4.4, RSS-133 6.4)

EUT with DUT number	RM-927, DUT 30759
Accessories with DUT numbers	
Operation Voltage [V] / [Hz]	Internal Battery
Results	PASSED
Remarks	
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	16.8 / 46.4 / 1050
Date of measurements	07-Aug-2013
Measured by	Tyrone Hawes

2.1.1 Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. The measurement results are obtained as described below:

$$P[\text{dBm}] = P_{\text{SUBST TX}} + P_{\text{MEAS}} - P_{\text{SUBST RX}} - L_{\text{SUBST CABLES}} + G_{\text{SUBST TX ANT}}$$

Where $P_{\text{SUBST TX}}$ is signal generator level. P_{MEAS} is measured power level from the EUT. $P_{\text{SUBST RX}}$ is measured power level in substitute measurement. $L_{\text{SUBST CABLE}}$ is the loss of the cable between the signal generator and the substitution antenna and $G_{\text{SUBST TX ANT}}$ is substitution antenna gain.

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
777 - 787	3 ERP	34.8
824 - 849	7 ERP	38.5
1710 - 1755	1 EIRP	30
1850 - 1910	2 EIRP	33

2.3. CDMA800 TX test results

Peak detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
1013 / 824.7	24.13	0.259	-10.31	34.44	VERTICAL	PASSED
384 / 836.52	24.44	0.278	-10.14	34.58	VERTICAL	PASSED
777 / 848.31	24.82	0.304	-9.17	33.99	VERTICAL	PASSED

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
1013 / 824.7	19.99	0.1	-14.45	34.44	VERTICAL	PASSED
384 / 836.52	20.89	0.123	-13.69	34.58	VERTICAL	PASSED
777 / 848.31	20.35	0.108	-13.64	33.99	VERTICAL	PASSED

2.4. CDMA1900 TX test results

Peak detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
25 / 1851.25	28.34	0.682	-16.49	44.83	VERTICAL	PASSED
600 / 1880	26.22	0.419	-17.91	44.13	VERTICAL	PASSED
1175 / 1908.75	25.14	0.326	-18.99	44.13	VERTICAL	PASSED

RMS detector


Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
25 / 1851.25	24.37	0.273	-20.46	44.83	VERTICAL	PASSED
600 / 1880	21.55	0.143	-22.58	44.13	VERTICAL	PASSED
1175 / 1908.75	21.13	0.13	-23	44.13	VERTICAL	PASSED

3. Band edge compliance

(FCC §22.917(a), §24.238(a), §27.53(h), §27.53(c)(2)(4), RSS-132 4.5, RSS-133 6.5)

EUT with DUT number	RM-927, DUT 30759
Accessories with DUT numbers	
Operation Voltage [V] / [Hz]	Internal Battery
Results	PASSED
Remarks	
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	16.6 / 45.9 / 1050
Date of measurements	08-Aug-2013
Measured by	Tyrone Hawes

3.1.1 Test setup




3.2. Test method and limit

The measurement is made according to FCC rules parts 22, 24, 27 and IC standards , RSS-132, RSS-133.

Limits for band edge compliance measurements


Operation band	Frequency range [MHz]	Limit [dBm]
LTE 700 Upper	776.9 - 777 and 787 - 787.1 Below 776.9 and above 787.1 763-775 and 793-805	-13 (RBW = 30 kHz, ERP) -13 (RBW = 100 kHz, ERP) -35 (RBW = 6.25 kHz, ERP)
GSM850 / WCDMA850	Below 824 and above 849	-13
LTE1700	Below 1710 and above 1755	-13
GSM1900 / / WCDMA1900	Below 1850 and above 1910	-13

3.3. CDMA800 test results



RMS (RBW: 20 kHz, VBW: 20 kHz, video averaging)


Operation mode (TX on)	Channel fc [MHz]	Level [dBm]	Results
CDMA	777 / 848.31	-13.64	PASSED



RMS (RBW: 20 kHz, VBW: 20 kHz, video averaging)


Operation mode (TX on)	Channel fc [MHz]	Level [dBm]	Results
CDMA	1013 / 824.7	-16.33	PASSED

3.4. CDMA1900 test results



RMS (RBW: 20 kHz, VBW: 20 kHz, video averaging)

Operation mode (TX on)	Channel fc [MHz]	Level [dBm]	Results
CDMA	25 / 1851.25	-32.69	PASSED



RMS (RBW: 20 kHz, VBW: 20 kHz, video averaging)


Operation mode (TX on)	Channel fc [MHz]	Level [dBm]	Results
CDMA	1175 / 1908.75	-33.24	PASSED

4. Spurious radiated emissions

(FCC §22.917(a), §2.1053, §24.238(a), §2.1053, §27.53(h), §27.53(c)(2)(4), RSS-132 4.5, RSS-133 6.5)

EUT with DUT number	RM-927, DUT 30743
Accessories with DUT numbers	AC-60, DUT 30744 ; CA-190, DUT 30745 ; WH-902, DUT 30746 ; RM-927, DUT 30759
Operation Voltage [V] / [Hz]	115V / 60Hz
Results	PASSED
Remarks	
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	16.8 / 46.4 / 1050
Date of measurements	07-Aug-2013
Measured by	Tyrone Hawes

4.1.1 Test setup



4.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The substitution method is used.

The measurement results are obtained as described below:

$$P [dBm] = P_{SUBST\ TX} + G_{SUBST\ TX\ ANT} - L_{SUBST\ CABLE}$$

Where $P_{SUBST\ TX}$ is signal generator level, which produces the same receiver reading P_{MEAS} in dBm as EUT. $G_{SUBST\ TX\ ANT}$ is substitution antenna gain and $L_{SUBST\ CABLE}$ is the loss of the cable between the signal generator and the substitution antenna.

Limits for spurious radiated emissions measurements

Operation band	Frequency range [MHz]	Limit [dBm]
LTE 700 Upper	30 – 8000	-13 (RBW = 100 kHz, ERP)
	763-775 and 793-805	-35 (RBW = 6.25 kHz, ERP)
	1559 – 1610	-40 (RBW = 1 MHz)
	1559 – 1610	-50 (RBW = 700 Hz)
GSM850 / WCDMA850	30 - 8500	-13
LTE1700 / / GSM1900 / WCDMA1900	30 - 18000	-13

4.3. CDMA800 TX test results

Channel 384 / 836.52 MHz

Peak detector

Frequency [MHz]	P [dBm]	P [μ W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarization	Results
2414.329	-50.33	0.00927	-67.95	17.62	HORIZONTAL	PASSED
2423.226	-50.94	0.00806	-68.34	17.4	HORIZONTAL	PASSED
2431.082	-50.39	0.00915	-68.21	17.82	HORIZONTAL	PASSED
2440.301	-49.99	0.01001	-68.37	18.38	HORIZONTAL	PASSED
2441.022	-50.13	0.0097	-68.48	18.35	HORIZONTAL	PASSED
2516.774	-47.59	0.01742	-67.54	19.95	VERTICAL	PASSED

4.4. CDMA1900 TX test results

Channel 600 / 1880 MHz

Peak detector

Frequency [MHz]	P [dBm]	P [μ W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarization	Results
2925.858	-43.83	0.04144	-67.23	23.4	HORIZONTAL	PASSED
2927.483	-45.06	0.0312	-68.36	23.3	VERTICAL	PASSED
2989.495	-44.96	0.03189	-68.64	23.68	VERTICAL	PASSED
9920.862	-44.65	0.0343	-63.4	18.75	VERTICAL	PASSED
9969.639	-44.98	0.03177	-63.74	18.76	HORIZONTAL	PASSED
11953.908	-43.82	0.04151	-64.47	20.65	VERTICAL	PASSED

5. Test Equipment

5.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
4406	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
7602	Communication Tester	CMW500	R&S	22/24/27, 15C, 15B
7151	Bluetooth Tester	CBT	R&S	15B
-	GPS RX Antenna w/AMP	L1A-PM-NF	GPS Source	15C
-	GPS Inline amplifier	A11M-V-NF-NM	GPS Source	15C
-	GPS signal Splitter	S12-P110/5-NF	GPS Source	15C
-	GPS TX Antenna	L1P-PV-NF	GPS Source	15C
7912	Spectrum Analyzer	FSV-30	R&S	22/24/27, 15C
-	Thermal Chamber	VT-4002	Vötsch	22/24/27, 15C
-	Power splitter	11667B	Agilent	22/24/27, 15C
3396	EMC Analyzer	E7405A	HP	-
7451	EMI Receiver	ESU-26	R&S	22/24/27, 15C, 15B
4188	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
6981	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
-	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
7582	Signal Generator	SMB100A	R&S	15C, 15B

5.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
7591	Antenna	HL562	R&S	22/24/27, 15C, 15B
7572	Double Ridge Horn Antenna	3117	ETS-Lindgren	22/24/27, 15C
7607	Standard Gain Horn Antenna	SAS 586	A.H. System	22/24/27, 15C
7624	Standard Gain Horn Antenna	SAS 587	A.H. System	22/24/27, 15C
7561	Antenna	HFH2-Z2	R&S	15C, 15B
5715	Antenna	MBA-3030	EMC Automation	22/24/27, 15C
5712	Antenna	PLP3003	EMC Automation	22/24/27, 15C
7457	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
7459	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
5729	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
5728	EMI Receiver	ESIB26	R&S	22/24/27, 15C, 15B
4406	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
7602	Communication Tester	CMW500	R&S	22/24/27, 15C, 15B
7151	Bluetooth Tester	CBT	R&S	15B
3406	Controller	Sc99V	Sunol	22/24/27, 15C, 15B
-	Controller	G-1000DXC	Yaesu	22/24/27, 15C, 15B
-	Computer Controller	GS-232B	Yaesu	22/24/27, 15C, 15B
7040	Preamplifier	TS-PR3	R&S	22/24/27, 15C, 15B
-	Preamplifier	AMF-6D-020180-29-20P	Miteq	22/24/27, 15C, 15B
-	Preamplifier	AMF-4D-01000800-30-29P	Miteq	22/24/27, 15C, 15B
-	Preamplifier	AMF-5F-18002650-25-10P	Miteq	22/24/27, 15C, 15B
-	High Pass Filter	4HC1700-1-KK	R&S	22
-	High Pass Filter	F-15041	RLC	22/24/27, 15C
-	Band Reject Filter	WRCA824/849-0.2-6SS	Wainwright	22
-	Band Reject Filter	WRCC1800/2000-0.2-10SS	Wainwright	24
-	Band Reject Filter	WRCG2400/2483-2390/2493-35/10SS	Wainwright	15C
-	Band Reject Filter	WRCG832/838-825/845-40/5SS	Wainwright	22
-	Band Reject Filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27

Eq. No	Equipment	Type	Manufacturer	Used in
-	Band Reject Filter	WRCG1877/1883 - 1870/1890-40/6SS	Wainwright	24
-	Notch Filter	WRCD1880-1.1.25/50-10SS	Wainwright	22/24/27
-	Notch Filter	WRCT902.4-0.4/40-8SS	Wainwright	-
Planned	Notch Filter	WRCJV2531/2539-2523/2547-60/12SS	Wainwright	22/24/27
-	GPS RX Antenna w/AMP	L1A-PM-NF	GPS Source	15C
-	GPS Inline amplifier	A11M-V-NF-NM	GPS Source	15C
-	GPS signal Splitter	S12-P110/5-NF	GPS Source	15C
-	GPS TX Antenna	L1P-PV-NF	GPS Source	15C