

CFR 47 Part 2,22,24 Test Report

Test Report Number: WR1155.201

Terminal device: FCC ID: QMNRM-193, Model: 2865i, HWID: F3.0, SW: FL100_05w21_46.nep

Originator: Hai To
Function: TCC - Dallas – EMC
Version/Status: 1.0 Approved
Location: QATrax Directories
Date: 11-Jul-06

Change History:

Version	Date	Status	Handled By	Comments
0.1	7-Jul-06	Draft	Hai To	
0.2	7-Jul-06	Proposal	Hai To	
0.3	11-Jul-06	Reviewed	Viet Do	
1.0	11-Jul-06	Approved	Viet Do	

Testing laboratory:

Test & Certification Center (TCC) Dallas
Nokia Inc
6021 Connection Drive
Irving, Texas 75039
U.S.A.

Tel. 972-894-5000

Client:

Nokia Inc.
San Diego
12278 Script Summit Drive.
San Diego, Ca 92131
USA
Tel. +1858 831 5000
Fax. +1858 8316500

Date and signatures:

11-Jul-06

For the contents:

Hai To
Test Operator

Viet Do
Technical Review

TABLE OF CONTENTS

1. GENERAL	4
1.1 QUALITY SYSTEM	4
1.2 OBJECTIVE	4
1.3 TEST SUMMARY	4
2. STANDARDS BASIS	5
3. LIST OF ABBREVIATIONS, ACRONYMS AND TERMS	6
3.1 ABBREVIATIONS	6
3.2 ACRONYMS	6
3.3 TERMS	6
4. EQUIPMENT-UNDER-TEST (EUT)	7
4.1 DESCRIPTION OF TESTED DEVICE(S):	7
4.2 PHOTOGRAPH OF TESTED DEVICE(S):	7
5. TEST EQUIPMENT LIST	8
6. OCCUPIED BANDWIDTH (TRANSMITTER CONDUCTED MEASUREMENTS)	9
6.1 SETUP	9
6.2 PASS/FAIL CRITERIA	9
6.3 DETAILED TEST RESULTS	9
7. SPURIOUS EMISSIONS AT ANTENNA TERMINALS	17
7.1 SETUP	17
7.2 PASS/FAIL CRITERIA	17
7.3 DETAILED TEST RESULTS	17

TCC

Company Confidential



3 (26)

Test & Certification Center (TCC) - Dallas

FCC ID: QMNRM-193

Test Report #: WR1155.201

11-Jul-06

Accredited Laboratory
Certificate Number: 1819-01

Ver 1.0

© ***No part of this report shall be reproduced out of the context of the report without the written approval of Nokia Mobile Phones, Inc., Dallas Product Creation, TCC – Dallas.***

1. GENERAL

1.1 Quality System

The quality system in place for TCC-Dallas conforms to ISO/IEC 17025 and has been audited to the standard by A2LA (American Association of Laboratory Accreditation). TCC - Dallas has also been audited using the ISO 9000 Quality System, as part of Nokia Mobile Phones, Inc., by ABS (American Bureau of Shipping) Quality Evaluations Inc.

TCC-Dallas is a recognized laboratory with the Federal Communications Commission in filing applications for Certification under Parts 15 and 18, Registration Number 100060, and Industry Canada, Registration Number IC 661N.

1.2 Objective

All tests and measurement data shown was performed to determine whether the selected handset was in compliance as specified in FCC: CFR47 Parts 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, Part 22, and Part 24.

1.3 Test Summary

Test Results: *The test result relates only to those tested devices mentioned in Section 4 of this test report.*

Test Performed	Reference	Section of Report	Complies / Does not comply / Not Tested
Occupied Bandwidth: Transmitter Conducted Measurements	FCC Part 2.1049	6	Complies
Spurious Emissions at Antenna Terminals	FCC Part 2.1051	7	Complies

2. STANDARDS BASIS

Testing has been carried out in accordance with:

REF.	Code of the standard	Name of the standard
1	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz.
2	FCC: CFR 47 Part 2	Code of Federal Regulations (CFR) Title 47, Part 2 – Frequency Allocations and Radio Treaty Matters; General Rules and Regulations: Subpart J – Equipment Authorization Procedures
3	FCC: CFR 47 Part 22	Code of Federal Regulations (CFR) Title 47, Part 22 – Public Mobile Services: Subpart H – Cellular Radiotelephone Service
4	FCC: CFR 47 Part 24	Code of Federal Regulations (CFR) Title 47, Part 24 – Personal Communications Services: Subpart E – Broadband PCS
5	RSS-129	800 MHz Dual-Mode CDMA Cellular Telephones
6	RSS-132	800 MHz Cellular Telephones Employing New Technologies
7	RSS-133	2 GHz Personal Communications Services, Industry Canada
8	RSS-212	Test Facilities and Test Methods for Radio Equipment, Industry Canada (Provisional)
9	RSP-100	Radio Equipment Certification Procedure

Note: Unless otherwise stated, (by reference to a version number and a publication date), the latest version of the above documents applies.

Deviations:

Not Applicable.

3. LIST OF ABBREVIATIONS, ACRONYMS AND TERMS

3.1 Abbreviations

dB - decibel

dBc - decibels from carrier

dBm - decibels per milliwatt (absolute measurement)

GHz - gigahertz or 1000000000 hertz

kHz - kilohertz or 1000 hertz

MHz - megahertz or 1000000 hertz

3.2 Acronyms

AMPS - Advanced Mobile Phone System

BSS - Base Station Simulator

CDMA - Code Division Multiple Access

EDRP - Effective Dipole Radiated Power

EIRP - Effective Isotropic Radiated Power

EMC - Electromagnetic Compatibility

EMI - Electromagnetic Interference

ERP - Effective Radiated Power

EUT - Equipment under Test

GSM - Global System for Mobile communications

PCS - Personal Communications Services

RF - Radio Frequency

TDMA - Time Division Multiple Access

3.3 Terms

Base Station Simulator (BSS) - simulates all the necessary signals that a phone would experience while on a live network. There are many types of base station simulators catering for all current protocols, i.e., GSM, AMPS, TDMA, and CDMA.

Cellular - refers to a frequency in the 800MHz band.

PCS - refers to a frequency in the 1900MHz band.

4. EQUIPMENT-UNDER-TEST (EUT)

The results in this report relate only to the items listed below:

4.1 Description of Tested Device(s):

Test Performed	Mode of Operation	Date of Receipt	Condition of Sample	Item	Identifying Information
FCC Part 2.1049 FCC Part 2.1051	CDMA 800/1900 AMPS	7-Jul-06	Working	Phone	FCC ID: QMNRM-193 Model: 2865i HW: F3.0 SW: FL100_05w21_46.nep ESN: 02603344862
FCC Part 2.1049 FCC Part 2.1051	CDMA 800/1900 AMPS	7-Jul-06	Working	Battery	Type: BL-6C

4.2 Photograph of Tested Device(s):

Refer to attached EXHIBITS

5. TEST EQUIPMENT LIST

The listing below indicates the test equipment utilized for the test (s). Calibration interval on all items listed can be obtained from the Engineering Services Group within NMP, Product Creation - Dallas. Where relevant, measuring equipment is subjected to in-service checks between testing. TCC - Dallas shall notify clients promptly, in writing, of identification of defective measuring equipment that casts doubt on the validity of results given in this report.

Section of Report	NMP#	Test Equipment	Mfr. #	Model #	Calibration Due Date	Calibration Interval
6,7	N/A	6dB Attenuator	Weinshcel	Model 2	Na	12 months
6,7		Base Station	R&S	CMU200	6-Sept-06	12 months
6,7	02679	EMI Receiver	HP	E7405A	6-Sept-07	12 Months
6,7	00087	Synthesized Fun/Sweep Generator	HP	3324A	31-Oct-06	12Months

6. OCCUPIED BANDWIDTH (TRANSMITTER CONDUCTED MEASUREMENTS)

Specification: FCC Part 2.1049(c)(1), 24.238(a)(b)

6.1 Setup

Testing was performed with the EUT connected to a 6dB attenuator, 6dB splitter, filter bank and then to the EMI receiver. The base station simulator was connected to the other port of the splitter to establish a call.

6.2 Pass/Fail Criteria

Occupied Bandwidth, Out of Band

Band	Frequency Range (MHz)	FCC Limits (dBm)
Cellular 800, Low Channel	< 824	-13
Cellular 800, High Channel	> 849	-13
PCS 1900, Low Channel	< 1850	-13
PCS 1900, High Channel	> 1910	-13

Occupied Bandwidth, In Band

No pass/fail, these plots are used to determine the emission designators.


6.3 Detailed Test Results

Test Technician / Engineer	Hai To
Date of Measurement	6-Jul-06
Temperature	23 °C
Humidity	46 %RH
Test Result	Complies with FCC Part 2.1049(c)(1), 24.238(a)(b)


Note1: AMPS measurements were performed with 300Hz RBW/VBW.

Occupied Bandwidth, Out of Band


AMPS - Channel 991 (824.04 MHz)



AMPS - Channel 799 (848.97 MHz)




CDMA 800 - Channel 1013 (824.70 MHz)




Date: 7.JUL.2006 22:14:38

CDMA 800 - Channel 777 (848.31 MHz)




Date: 7.JUL.2006 22:18:57

CDMA 1900 – Channel 25 (1851.25 MHz)




CDMA 1900 – Channel 1175 (1908.75 MHz)




Occupied Bandwidth, In Band

AMPS – Channel 384, CW:




AMPS - Channel 384 Voice + Sat:




Test & Certification Center (TCC) - Dallas


AMPS - Channel 384; Sat :



AMPS - Channel 384; ST:




AMPS – Channel 384; WBD:




CDMA 800 - Channel 384

30KHz RBW/VBW



CDMA 1900 - Channel 600



7. SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Specification: FCC Part 2.1051

7.1 Setup

Testing was performed with the EUT connected to a 6dB attenuator, 6dB splitter, filter bank and then to the EMI receiver. The base station simulator was connected to the other port of the splitter to establish a call. Filters were introduced to reduce or eliminate spurious emission, which could be generated internally in the EMI receiver.

7.2 Pass/Fail Criteria

Band	Frequency Range (MHz)	FCC Limits (dBm)
Cellular / PCS	30 – 20000 *	-13

* Frequency to be investigated up to the 10th harmonic of the highest clock or frequency used.


7.3 Detailed Test Results

Test Technician / Engineer	Hai To
Date of Measurement	7-Jul-06
Temperature	22 °C
Humidity	47 %RH
Test Result	Complies with FCC Part 2.1051

Note 1: EMI (dBm) = trace (dBuV) + cable loss (dB) + filter loss (dB).


Note 2: measurements were performed with 1MHz RBW/VBW.

AMPS - Channel 991, 824.04 MHz




Freq (Max) [MHz]	(PEAK) Trace [dBm]	Cable [dB]	Filter [dB]	(PEAK) EMI [dBm]	Limit [dBm]
1650.1	-64.3	0.4	14.67	-49.2	-13.0
2472.1	-40.5	0.6	15.45	-24.5	-13.0
3295.4	-64.0	0.8	16.01	-47.2	-13.0
4120.2	-65.9	0.9	16.13	-48.9	-13.0
4944.6	-65.3	1.1	17.03	-47.3	-13.0
5767.9	-65.6	1.2	19.93	-44.5	-13.0
6592.2	-65.0	1.2	18.06	-45.7	-13.0
7416.8	-61.7	1.3	18.11	-42.3	-13.0
8241.0	-61.9	1.4	18.93	-41.5	-13.0

AMPS - Channel 384, 836.52 MHz




Freq (Max) (MHz)	(PEAK) Trace (dBm)	Cable (dB)	Filter (dB)	(PEAK) EMI (dBm)	Limit (dBm)
1672.9	-63.6	0.4	14.60	-48.7	-13.0
2509.6	-43.0	0.6	15.65	-26.8	-13.0
3345.3	-62.9	0.8	16.10	-46.0	-13.0
4181.4	-64.8	0.9	16.12	-47.8	-13.0
5018.6	-66.2	1.1	17.16	-48.0	-13.0
5855.6	-65.3	1.2	21.33	-42.8	-13.0
6691.7	-65.7	1.3	17.75	-46.7	-13.0
7528.2	-62.8	1.3	18.06	-43.4	-13.0
8366.7	-63.0	1.4	19.00	-42.5	-13.0

AMPS - Channel 799, 848.97 MHz




Freq (Max) (MHz)	(PEAK) Trace (dBm)	Cable (dB)	Filter (dB)	(PEAK) EMI (dBm)	Limit (dBm)
1698.0	-63.6	0.4	14.59	-48.7	-13.0
2546.9	-43.8	0.6	15.49	-27.7	-13.0
3396.4	-62.4	0.8	16.02	-45.5	-13.0
4245.0	-64.2	0.9	16.39	-46.8	-13.0
5094.7	-63.3	1.1	17.25	-45.0	-13.0
5942.0	-66.2	1.2	22.11	-42.9	-13.0
6790.9	-62.9	1.3	17.87	-43.7	-13.0
7642.1	-61.5	1.3	17.97	-42.2	-13.0
8491.1	-63.2	1.4	18.55	-43.3	-13.0

CDMA 800 - Channel 1013, 824.70 MHz




Freq (Max) (MHz)	(PEAK) Trace (dBm)	Cable (dB)	Filter (dB)	(PEAK) EMI (dBm)	Limit (dBm)
1649.7	-65.3	0.4	14.67	-50.3	-13.0
2475.2	-40.8	0.6	15.46	-24.8	-13.0
3298.7	-64.5	0.8	15.98	-47.7	-13.0
4123.4	-65.1	0.9	16.09	-48.1	-13.0
4947.5	-64.4	1.1	17.03	-46.3	-13.0
5773.6	-66.0	1.2	19.98	-44.8	-13.0
6596.1	-64.9	1.2	18.06	-45.6	-13.0
7423.1	-61.6	1.3	17.98	-42.3	-13.0
8248.5	-63.6	1.4	18.97	-43.2	-13.0

CDMA 800 - Channel 384, 836.52 MHz




Freq (Max) [MHz]	(PEAK) Trace [dBm]	Cable [dB]	Filter [dB]	(PEAK) EMI [dBm]	Limit [dBm]
1674.8	-64.8	0.4	14.60	-49.8	-13.0
2510.7	-40.3	0.6	15.65	-24.1	-13.0
3345.0	-63.3	0.8	16.10	-46.5	-13.0
4182.2	-65.1	0.9	16.12	-48.1	-13.0
5019.8	-65.7	1.1	17.16	-47.4	-13.0
5853.8	-65.7	1.2	21.33	-43.2	-13.0
6691.4	-66.0	1.3	17.75	-47.0	-13.0
7528.3	-62.4	1.3	18.06	-43.0	-13.0
8365.4	-63.8	1.4	19.00	-43.4	-13.0

CDMA 800 - Channel 777, 848.31 MHz




Freq (Max) [MHz]	(PEAK) Trace [dBm]	Cable [dB]	Filter [dB]	(PEAK) EMI [dBm]	Limit [dBm]
1695.9	-63.8	0.4	14.59	-48.9	-13.0
2545.9	-41.9	0.6	15.53	-25.8	-13.0
3393.5	-62.7	0.8	16.05	-45.9	-13.0
4241.6	-64.2	0.9	16.35	-46.9	-13.0
5088.3	-64.7	1.1	17.26	-46.4	-13.0
5937.6	-65.5	1.2	22.09	-42.3	-13.0
6786.3	-61.3	1.3	17.96	-42.1	-13.0
7635.2	-60.6	1.3	17.98	-41.3	-13.0
8483.3	-63.6	1.4	18.53	-43.7	-13.0

CDMA 1900 - Channel 25, 1851.25 MHz




Freq (Max) (MHz)	(PEAK) Trace (dBm)	Cable (dB)	Filter (dB)	(PEAK) EMI (dBm)	Limit (dBm)
3703.1	-63.6	0.85	16.2	-46.5	-13.0
5553.9	-64.8	1.13	18.4	-45.2	-13.0
7404.6	-62.4	1.32	18.4	-42.7	-13.0
9254.9	-63.1	1.48	19.5	-42.1	-13.0
11106.5	-63.8	1.60	20.2	-42.0	-13.0
12959.9	-62.5	1.71	22.6	-38.2	-13.0
14810.8	-59.0	1.80	22.8	-34.5	-13.0
16662.4	-59.6	1.88	23.8	-34.0	-13.0
18512.6	-59.8	1.95	24.9	-33.0	-13.0

CDMA 1900 - Channel 600, 1880.00 MHz



Freq (Max) [MHz]	(PEAK) Trace [dBm]	Cable [dB]	Filter [dB]	(PEAK) EMI [dBm]	Limit [dBm]
3758.9	-62.6	0.86	16.8	-45.0	-13.0
5640.0	-62.8	1.14	18.5	-43.1	-13.0
7520.4	-62.1	1.34	18.1	-42.7	-13.0
9399.0	-63.0	1.49	18.9	-42.6	-13.0
11280.4	-63.0	1.61	20.2	-41.2	-13.0
13160.7	-62.6	1.72	21.8	-39.1	-13.0
15040.5	-59.6	1.81	23.7	-34.1	-13.0
16918.7	-60.0	1.89	25.0	-33.1	-13.0
18798.3	-59.2	1.96	25.1	-32.1	-13.0

CDMA 1900 - Channel 1175, 1908.75 MHz



Freq (Max) [MHz]	(PEAK) Trace [dBm]	Cable [dB]	Filter [dB]	(PEAK) EMI [dBm]	Limit [dBm]
3817.3	-64.0	0.87	16.7	-46.4	-13.0
5725.5	-62.8	1.15	19.4	-42.3	-13.0
7636.4	-63.8	1.35	18.0	-44.5	-13.0
9545.4	-60.9	1.50	20.3	-39.1	-13.0
11452.7	-63.8	1.62	20.5	-41.6	-13.0
13362.3	-60.2	1.73	22.0	-36.4	-13.0
15269.1	-58.9	1.82	23.3	-33.8	-13.0
17178.7	-60.8	1.90	24.3	-34.7	-13.0
19088.5	-60.1	1.97	26.3	-31.8	-13.0