

## ATTACHMENT O – SAR TEST PLOTS (2 of 3)

Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : in / Channel : 25

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1851.25$  MHz;  $\sigma = 1.42$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn614; Calibrated: 2005-04-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 25/Area Scan (61x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.41 mW/g

**Left touch 25/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 18.4 V/m; Power Drift = 0.009 dB

Peak SAR (extrapolated) = 1.84 W/kg

**SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.743 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.36 mW/g

**Left touch 25/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm


Reference Value = 18.4 V/m; Power Drift = 0.009 dB

Peak SAR (extrapolated) = 1.51 W/kg

**SAR(1 g) = 0.952 mW/g; SAR(10 g) = 0.564 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.19 mW/g



Test Laboratory: HCT

Company: Nokia Inc.

Mode: PCS1900 / Antenna: out / Channel: 25

Liquid Temperature: 21.7 °C

Date Tested: February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1851.25$  MHz;  $\sigma = 1.42$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 25/Area Scan (51x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.702 mW/g

**Left touch 25/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 17.5 V/m; Power Drift = -0.186 dB

Peak SAR (extrapolated) = 0.957 W/kg

**SAR(1 g) = 0.624 mW/g; SAR(10 g) = 0.370 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.668 mW/g

**Left touch 25/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm


Reference Value = 17.5 V/m; Power Drift = -0.186 dB

Peak SAR (extrapolated) = 0.917 W/kg

**SAR(1 g) = 0.548 mW/g; SAR(10 g) = 0.301 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.621 mW/g



0 dB = 0.621mW/g

Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : in / Channel : 600

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 600/Area Scan (51x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Maximum value of SAR (interpolated) = 1.23 mW/g


**Left touch 600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 19.7 V/m; Power Drift = -0.047 dB

Peak SAR (extrapolated) = 1.63 W/kg

**SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.659 mW/g**

Maximum value of SAR (measured) = 1.17 mW/g



Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : out / Channel : 600

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 600/Area Scan (51x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Maximum value of SAR (interpolated) = 0.526 mW/g

**Left touch 600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 16.8 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.762 W/kg

**SAR(1 g) = 0.455 mW/g; SAR(10 g) = 0.250 mW/g**

Maximum value of SAR (measured) = 0.517 mW/g


**Left touch 600/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 16.8 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.727 W/kg

**SAR(1 g) = 0.467 mW/g; SAR(10 g) = 0.275 mW/g**

Maximum value of SAR (measured) = 0.501 mW/g



Test Laboratory: HCT

Company : Nokia Inc.  
Mode : PCS1900 / Antenna : in / Channel : 1175  
Liquid Temperature : 21.7 °C  
Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1908.75$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn614; Calibrated: 2005-04-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 1175/Area Scan (61x101x1):** Measurement grid:  $\Delta x = 15$ mm,  $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.  
Maximum value of SAR (interpolated) = 1.30 mW/g

**Left touch 1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $\Delta x = 8$ mm,  $\Delta y = 8$ mm,  $\Delta z = 5$ mm

Reference Value = 18.3 V/m; Power Drift = -0.137 dB

Peak SAR (extrapolated) = 2.16 W/kg

**SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.649 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.  
Maximum value of SAR (measured) = 1.24 mW/g


**Left touch 1175/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $\Delta x = 8$ mm,  $\Delta y = 8$ mm,  $\Delta z = 5$ mm

Reference Value = 18.3 V/m; Power Drift = -0.137 dB

Peak SAR (extrapolated) = 1.61 W/kg

**SAR(1 g) = 0.783 mW/g; SAR(10 g) = 0.454 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.  
Maximum value of SAR (measured) = 0.940 mW/g



0 dB = 0.940mW/g

Test Laboratory: HCT

Company: Nokia Inc.  
Mode: PCS1900 / Antenna: out / Channel: 1175  
Liquid Temperature: 21.7 °C  
Date Tested: February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1908.75 \text{ MHz}$ ;  $\sigma = 1.44 \text{ mho/m}$ ;  $\epsilon_r = 39.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

DASY4 Configuration:


- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn614; Calibrated: 2005-04-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 1175/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.  
Maximum value of SAR (interpolated) = 0.524 mW/g

**Left touch 1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 15.7 V/m; Power Drift = -0.012 dB  
Peak SAR (extrapolated) = 0.957 W/kg  
**SAR(1 g) = 0.464 mW/g; SAR(10 g) = 0.244 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.  
Maximum value of SAR (measured) = 0.519 mW/g



Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : in / Channel : 25

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1851.25$  MHz;  $\sigma = 1.42$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 25/Area Scan (61x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.34 mW/g

**Right touch 25/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm


Reference Value = 24.3 V/m; Power Drift = -0.006 dB

Peak SAR (extrapolated) = 1.79 W/kg

**SAR(1 g) = 1.25 mW/g; SAR(10 g) = 0.798 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.35 mW/g



0 dB = 1.35mW/g

Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : out / Channel : 25

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1851.25$  MHz;  $\sigma = 1.42$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn614; Calibrated: 2005-04-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 25/Area Scan (61x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.728 mW/g

**Right touch 25/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm


Reference Value = 23.5 V/m; Power Drift = -0.205 dB

Peak SAR (extrapolated) = 1.07 W/kg

**SAR(1 g) = 0.665 mW/g; SAR(10 g) = 0.372 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.762 mW/g



Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : in / Channel : 600

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 600/Area Scan (61x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Maximum value of SAR (interpolated) = 1.10 mW/g


**Right touch 600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 22.1 V/m; Power Drift = 0.157 dB

Peak SAR (extrapolated) = 1.50 W/kg

**SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.649 mW/g**

Maximum value of SAR (measured) = 1.12 mW/g



0 dB = 1.12mW/g

Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : out / Channel : 600

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 600/Area Scan (61x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Maximum value of SAR (interpolated) = 0.670 mW/g


**Right touch 600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 22.4 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.912 W/kg

**SAR(1 g) = 0.575 mW/g; SAR(10 g) = 0.323 mW/g**

Maximum value of SAR (measured) = 0.664 mW/g



0 dB = 0.664mW/g

Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : in / Channel : 1175

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1908.75$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 1175/Area Scan (61x101x1):** Measurement grid:  $\Delta x = 15$ mm,  $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.27 mW/g

**Right touch 1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $\Delta x = 8$ mm,  $\Delta y = 8$ mm,  $\Delta z = 5$ mm

Reference Value = 24.0 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 2.17 W/kg

**SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.703 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.27 mW/g

**Right touch 1175/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $\Delta x = 8$ mm,  $\Delta y = 8$ mm,  $\Delta z = 5$ mm


Reference Value = 24.0 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 1.90 W/kg

**SAR(1 g) = 0.981 mW/g; SAR(10 g) = 0.582 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.12 mW/g



0 dB = 1.12mW/g

Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : out / Channel : 1175

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1908.75$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607, ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 1175/Area Scan (61x101x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.670 mW/g

**Right touch 1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm


Reference Value = 19.4 V/m; Power Drift = -0.176 dB

Peak SAR (extrapolated) = 1.27 W/kg

**SAR(1 g) = 0.636 mW/g; SAR(10 g) = 0.340 mW/g**

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.712 mW/g



Test Laboratory: HCT

Company : Nokia Inc.  
Mode : PCS1900 / Antenna : in / Channel : 600  
Liquid Temperature : 21.7 °C  
Date Tested : February 17, 2006

DUT: Nokia 6215i; Type: Folder; Serial: #1


Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.44 \text{ mho/m}$ ;  $\epsilon_r = 40.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn614; Calibrated: 2005-04-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left tilt 1175/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.132 mW/g

**Left tilt 1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 6.13 V/m; Power Drift = 0.129 dB  
Peak SAR (extrapolated) = 0.174 W/kg  
**SAR(1 g) = 0.119 mW/g; SAR(10 g) = 0.070 mW/g**  
Maximum value of SAR (measured) = 0.130 mW/g



Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : out / Channel : 600

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

DUT: Nokia 6215i; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left tilt 600/Area Scan (61x101x1):** Measurement grid:  $\Delta x = 15$ mm,  $\Delta y = 15$ mm

Maximum value of SAR (interpolated) = 0.252 mW/g


**Left tilt 600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $\Delta x = 8$ mm,  $\Delta y = 8$ mm,  $\Delta z = 5$ mm

Reference Value = 5.40 V/m; Power Drift = 0.029 dB

Peak SAR (extrapolated) = 0.329 W/kg

**SAR(1 g) = 0.225 mW/g; SAR(10 g) = 0.137 mW/g**

Maximum value of SAR (measured) = 0.245 mW/g



0 dB = 0.245mW/g

Test Laboratory: HCT

Company : Nokia Inc.  
Mode : PCS1900 / Antenna : in / Channel : 600  
Liquid Temperature : 21.7 °C  
Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**


Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.44 \text{ mho/m}$ ;  $\epsilon_r = 40.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn614; Calibrated: 2005-04-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right tilt 600/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.082 mW/g

**Right tilt 600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 5.63 V/m; Power Drift = 0.188 dB  
Peak SAR (extrapolated) = 0.108 W/kg  
**SAR(1 g) = 0.073 mW/g; SAR(10 g) = 0.046 mW/g**  
Maximum value of SAR (measured) = 0.078 mW/g



Test Laboratory: HCT

Company : Nokia Inc.

Mode : PCS1900 / Antenna : out / Channel : 600

Liquid Temperature : 21.7 °C

Date Tested : February 17, 2006

**DUT: Nokia 6215i; Type: Folder; Serial: #1**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right tilt 600/Area Scan (61x101x1):** Measurement grid:  $\Delta x = 15$ mm,  $\Delta y = 15$ mm

Maximum value of SAR (interpolated) = 0.183 mW/g


**Right tilt 600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $\Delta x = 8$ mm,  $\Delta y = 8$ mm,  $\Delta z = 5$ mm

Reference Value = 5.60 V/m; Power Drift = 0.166 dB

Peak SAR (extrapolated) = 0.278 W/kg

**SAR(1 g) = 0.162 mW/g; SAR(10 g) = 0.101 mW/g**

Maximum value of SAR (measured) = 0.179 mW/g



0 dB = 0.179mW/g