

FCC Part 15C Compliance Test Report

Test Report no.:	Salo_FCC_0738_11.doc	Date of Report:	27.11.2007
Number of pages:	36	Customer's Contact person:	Bill Griffin
Testing laboratory:	TCC Nokia Salo Laboratory P.O. Box 86 Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Customer:	Nokia Corporation 12278 Scripps Summit Drive SAN DIEGO CA. 92131 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500
FCC listing no.:	533467		
IC recognition no.:	661V-1		
Tested devices/ accessories:	Phone RM-257 / Battery BL-5C, AC-Charger AC-3U and Headset HS-47		
FCC ID:	QMNRM-257	IC:	-
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards RSS-GEN (Issue 2, June 2007) and RSS-210 (Issue 7, June 2007). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Sami Lehtonen, System Manager

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	19.09.2007
Testing completed	03.10.2007
The customer's contact person	Bill Griffin
Test Plan referred to	T:\Projects\RM-257\TestPlan_RS\RM-257_RS_test_plan.xls
Notes	-
Document name	T:\Projects\RM-257\EMC\Results\FCC\Salo_FCC_0738_11.doc

1.1. EUT and Accessory Information

The EUT is a 5-band (GSM850/900/1800/1900/IV(1700)) mobile phone with GPRS, EGPRS and Bluetooth. Bluetooth is tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-257	004401/01/111764/1	4604	-	4.40	12244
Phone	RM-257	004401/01/111759/1	4604	-	4.40	12243
Battery	BL-5C	0670398382066O035M1TS03332	-	-	-	12245
AC-Charger	AC-3E	3997915472051200095;0675370	-	-	-	11574
Headset	HS-47	3508536425020000003	4.1	3.0	-	11683
Phone	RM-257	004401/01/111753/4	4604	-	4.40	12258
Battery	BL-5C	0670398382066O035M1TS03335	-	-	-	12257
AC- Charger	AC-3U	4090495306981001075;0675372	-	-	-	12259
Headset	HS-47	0694579706512110817	-	-	-	12233

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4 (2)	Conducted peak output power	PASSED
15.247(d)	A8.5	Band edge compliance of RF emissions	-
15.247(d)	A8.5	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8.5	Spurious radiated emissions	PASSED
15.207	7.2.2	AC powerline conducted emissions	PASSED
15.247(a)(1)	A8.1 (1)	20 dB bandwidth	PASSED
15.247(a)(1)	A8.1 (2)	Carrier frequency separation	PASSED
15.247(a)(1)(iii)	A8.1 (4)	Number of hopping frequencies	PASSED
15.247(a)(1)(iii)	A8.1 (4)	Time of occupancy	PASSED

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Salo Laboratory.


CONTENTS

1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results.....	2
2. Test setups.....	5
2.1. Conducted RF test setup	5
2.2. AC powerline conducted emissions test setup.....	5
2.3. Spurious radiated emissions test setup	5
3. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2))	6
3.1. Test method and limit.....	6
3.2. Bluetooth Test results	7
4. Spurious RF conducted emissions (FCC §15.247(d), RSS-A8.5).....	10
4.1. Test method and limit.....	10
4.2. Bluetooth Test results	11
5. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5).....	14
5.1. Test method and limit.....	14
5.2. Bluetooth Test results	15
6. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)	18
6.1. Test method and limit.....	18
6.2. Bluetooth Test results	19
7. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (1))	21
7.1. Test method and limit.....	21
7.2. Bluetooth Test results	22
8. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (2))	26
8.1. Test method and limit.....	26
8.2. Bluetooth Test results	27
9. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))	29
9.1. Test method and limit.....	29
9.2. Bluetooth Test results	30
10. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))	32
10.1. Test method and limit.....	32
10.2. Bluetooth test results.....	33
11. Test Equipment	35


11.1.	Conducted measurements	35
11.2.	Radiated measurements	35

2. Test setups


2.1. Conducted RF test setup



2.2. AC powerline conducted emissions test setup



2.3. Spurious radiated emissions test setup



3. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4 (2))

EUT with DUT number	RM-257, DUT 12244
Accessories with DUT numbers	BL-5C, DUT 12245; HS-47, DUT 11683; AC-3E, DUT 11574
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 101
Date of measurements	01.10.2007
Measured by	Anni Manninen

3.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for conducted peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5	≤ 1	≤ 30

3.2. Bluetooth Test results


3.2.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	-2.30	0.589	PASSED
40 / 2442	-2.10	0.617	PASSED
78 / 2480	-3.10	0.490	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)




Channel 78 / 2480 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)




3.2.2 8DPSK modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	-1.50	0.708	PASSED
40 / 2442	-1.80	0.661	PASSED
78 / 2480	-2.70	0.537	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



Channel 78 / 2480 MHz (Peak detector, RBW: 1 MHz, VBW: 3 MHz)



4. Spurious RF conducted emissions (FCC §15.247(d), RSS-A8.5)

EUT with DUT number	RM-257, DUT 12244
Accessories with DUT numbers	BL-5C, DUT 12245; HS-47, DUT 11683; AC-3E, DUT 11574
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 101
Date of measurements	01.10.2007
Measured by	Anni Manninen

4.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	≤ -20

4.2. Bluetooth Test results


4.2.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Frequency [MHz]	P [dBc]	Result
4948.400000	-27.605504	PASSED
7320.000000	-28.905504	PASSED
7500.000000	-28.605504	PASSED

Channel 40 / 2442 MHz



Frequency [MHz]	P [dBc]	Result
4812.800000	-27.125555	PASSED
7500.000000	-28.125555	PASSED
7500.000000	-29.125555	PASSED


Channel 78 / 2480 MHz



Frequency [MHz]	P [dBc]	Result
4864.400000	-27.989470	PASSED
5000.000000	-27.189470	PASSED
7218.000000	-27.789470	PASSED


4.2.2 8DPSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Frequency [MHz]	P [dBc]	Result
4830.800000	-27.627309	PASSED
5000.000000	-27.927309	PASSED
7485.600000	-28.827309	PASSED

Channel 40 / 2442 MHz



Frequency [MHz]	P [dBc]	Result
4862.800000	-28.290091	PASSED
7323.600000	-28.690091	PASSED
7500.000000	-27.290091	PASSED

Channel 78 / 2480 MHz



Frequency [MHz]	P [dBc]	Result
4903.600000	-26.951828	PASSED
5000.000000	-26.751828	PASSED
7450.800000	-27.751828	PASSED

5. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)

EUT with DUT number	RM-257, DUT 12258
Accessories with DUT numbers	BL-5C, DUT 12257; AC-3U, DUT 12259; HS-47, DUT 12233
Operation Voltage [V] / [Hz]	110 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 103
Date of measurements	01.10.2007
Measured by	Sami Lehtonen

5.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu\text{V/m}$]	Limit [dB $\mu\text{V/m}$]	Detector
30 – 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

5.2. Bluetooth Test results

5.2.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	44.60	169.82	44.40	0.2	VERTICAL	PASSED
7206.000000	45.80	194.98	43.60	2.2	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	30.70	34.28	30.50	0.2	VERTICAL	PASSED
7206.000000	33.10	45.19	30.90	2.2	VERTICAL	PASSED

Channel 40 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
38.135872	22.20	12.88	41.00	-18.8	VERTICAL	PASSED
65.450701	20.60	10.72	50.90	-30.3	HORIZONTAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4834.665331	43.50	149.62	42.80	0.7	VERTICAL	PASSED
12473.443888	52.70	431.52	41.90	10.8	VERTICAL	PASSED
13339.179359	53.40	467.74	40.20	13.2	VERTICAL	PASSED
15360.713427	52.80	436.52	37.80	15.0	VERTICAL	PASSED
15880.753507	54.10	506.99	37.50	16.6	VERTICAL	PASSED
16191.384770	54.90	555.90	37.50	17.4	VERTICAL	PASSED
17919.833667	56.90	699.84	37.90	19.0	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4831.665331	30.90	35.08	30.30	0.6	VERTICAL	PASSED

12467.943888	39.60	95.50	28.80	10.8	VERTICAL	PASSED
13341.179359	41.00	112.20	27.80	13.2	VERTICAL	PASSED
15358.713427	39.40	93.33	24.40	15.0	VERTICAL	PASSED
15873.253507	41.30	116.14	24.90	16.4	VERTICAL	PASSED
16195.884770	42.10	127.35	24.60	17.5	VERTICAL	PASSED
17917.333667	43.00	141.25	24.10	18.9	VERTICAL	PASSED

Channel 78 / 2480 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	43.10	142.89	43.50	-0.4	VERTICAL	PASSED
7440.000000	47.20	229.09	44.10	3.1	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	30.00	31.62	30.40	-0.4	VERTICAL	PASSED
7440.000000	34.10	50.70	31.00	3.1	VERTICAL	PASSED

5.2.2 8DPSK modulation, PRBS packet type

Channel 0 / 2402 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	43.80	154.88	43.60	0.2	VERTICAL	PASSED
7206.000000	46.00	199.53	43.80	2.2	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	30.70	34.28	30.50	0.2	VERTICAL	PASSED
7206.000000	33.10	45.19	30.90	2.2	VERTICAL	PASSED

Channel 40 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
38.176353	22.30	13.03	41.10	-18.8	VERTICAL	PASSED
65.510220	20.40	10.47	50.60	-30.2	HORIZONTAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4820.139279	27.80	24.55	27.40	0.4	VERTICAL	PASSED
13323.141283	53.40	467.74	40.50	12.9	VERTICAL	PASSED
13349.707415	53.40	467.74	40.10	13.3	VERTICAL	PASSED

15440.373747	52.50	421.70	37.20	15.3	VERTICAL	PASSED
15825.149299	54.80	549.54	38.00	16.8	VERTICAL	PASSED
16190.874749	55.50	595.66	38.10	17.4	VERTICAL	PASSED
17842.677355	56.40	660.69	38.30	18.1	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4819.139279	30.80	34.67	30.40	0.4	VERTICAL	PASSED
13319.641283	40.80	109.65	27.90	12.9	VERTICAL	PASSED
13353.207415	40.80	109.65	27.40	13.4	VERTICAL	PASSED
15434.873747	39.90	98.86	24.60	15.3	VERTICAL	PASSED
15820.649299	41.20	114.82	24.50	16.7	VERTICAL	PASSED
16190.874749	42.10	127.35	24.70	17.4	VERTICAL	PASSED
17835.177355	42.40	131.83	24.20	18.2	VERTICAL	PASSED

Channel 78 / 2480 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	42.70	136.46	43.10	-0.4	VERTICAL	PASSED
7440.000000	47.10	226.46	44.00	3.1	VERTICAL	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	30.10	31.99	30.50	-0.4	VERTICAL	PASSED
7440.000000	34.20	51.29	31.10	3.1	VERTICAL	PASSED

6. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-257, DUT 12243
Accessories with DUT numbers	BL-5C, DUT 12245; HS-47, DUT 11683; AC-3E, DUT 11574
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 101
Date of measurements	01.10.2007
Measured by	Anni Manninen

6.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

6.2. Bluetooth Test results

6.2.1 GFSK modulation, PRBS packet type

Channel 40 / 2442 MHz




Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
27.205000	12.40	L1	PASSED
27.990000	11.90	N	PASSED

6.2.2 8DPSK modulation, PRBS packet type

Channel 40 / 2442 MHz



Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
1.020000	23.00	N	PASSED
1.300000	20.40	N	PASSED
1.365000	20.20	N	PASSED
1.555000	18.30	N	PASSED
1.615000	17.90	N	PASSED
1.990000	19.40	N	PASSED
3.530000	24.10	L1	PASSED
3.845000	16.20	L1	PASSED
4.125000	14.60	N	PASSED
4.130000	14.00	N	PASSED
4.555000	16.80	L1	PASSED
4.625000	16.10	L1	PASSED

7. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (1))

EUT with DUT number	RM-257, DUT 12244
Accessories with DUT numbers	BL-5C, DUT 12245; HS-47, DUT 11683; AC-3E, DUT 11574
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 101
Date of measurements	01.10.2007
Measured by	Anni Manninen

7.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for 20 dB bandwidth measurements


Limit [MHz]
N/A

7.2. Bluetooth Test results


7.2.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	20 dB bandwidth [kHz]	Result
0 / 2402	756.000	PASSED
40 / 2442	788.000	PASSED
78 / 2480	792.000	PASSED


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz




Channel 78 / 2480 MHz




7.2.2 8DPSK modulation, PRBS packet type

Channel / f _c [MHz]	20 dB bandwidth [kHz]	Result
0 / 2402	1256.000	PASSED
40 / 2442	1256.000	PASSED
78 / 2480	1256.000	PASSED


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz



Channel 78 / 2480 MHz



8. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (2))

EUT with DUT number	RM-257, DUT 12244
Accessories with DUT numbers	BL-5C, DUT 12245; HS-47, DUT 11683; AC-3E, DUT 11574
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 101
Date of measurements	01.10.2007
Measured by	Anni Manninen

8.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for carrier frequency separation measurements


Limit [MHz]
≥ 0.025 or 2/3 of the 20 dB bandwidth

8.2. Bluetooth Test results

8.2.1 GFSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1000	PASSED


Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



8.2.2 8DPSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1040	PASSED

Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



9. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))

EUT with DUT number	RM-257, DUT 12244
Accessories with DUT numbers	BL-5C, DUT 12245; HS-47, DUT 11683; AC-3E, DUT 11574
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 101
Date of measurements	01.10.2007
Measured by	Anni Manninen

9.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for number of hopping frequencies measurements


Limit [number]
≥ 15

9.2. Bluetooth Test results

9.2.1 GFSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
79	PASSED


Hopping on, number of hopping frequencies



9.2.2 8DPSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
72	PASSED

Hopping on, number of hopping frequencies



10. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (4))

EUT with DUT number	RM-257, DUT 12244
Accessories with DUT numbers	BL-5C, DUT 12245; HS-47, DUT 11683; AC-3E, DUT 11574
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 42 / 101
Date of measurements	01.10.2007
Measured by	Anni Manninen

10.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The total time of occupancy is get by multiplying the measured number of transmissions occurred during 31.6 second period with the duration of one transmission.

Limits for time of occupancy measurements


Limit [s]
≤ 0.4

10.2. Bluetooth test results


10.2.1 GFSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μ s]	Time of occupancy [s]	Result
82	2 960	0.242720	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz




Hopping on, duration of one transmission, channel 40 / 2442 MHz




10.2.2 8DPSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μ s]	Time of occupancy [s]	Result
89	2 984	0.265576	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz



Hopping on, duration of one transmission, channel 40 / 2442 MHz



11. Test Equipment

11.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1742	EMI Test Receiver	ESMI	R&S	15C, 15B
1759	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
1872	Thermo- Hygrograph	00.02520.150700	Lambrecht	15C, 15B
1916	Radio Communication tester	CMTA84	R&S	15C, 15B
2039	Power Supply	PL330QMD	THURLBY	15C, 15B
2060	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
2068	CDN-Antenna line	S1	NMP	15C, 15B
2097	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
2111	Multimeter	TX3	Tektronix	15C, 15B
2156	Digital Radio Communication Tester	CMU200	R&S	15C, 15B
2206	Signal generator	SMX	R&S	15C, 15B
2335	GPIB Switch 2 to 1	-	National Instruments	15C, 15B
2347	Digital Radio Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2352	Spectrum Analyzer	FSP	R&S	22/24/27, 15C
2359	Temperature Test system	VT4002	Vötsch Industrietechnik	22/24/27
2360	Serial Bus Converter	Serial 488A	IO Tech	22/24/27
2362	Power Supply	NGPX 70/5	R&S	22/24/27
2388	Bluetooth Tester	CBT	R&S	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B

11.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1748	Log. per. Antenna	HL025	R&S	22/24/27, 15C
1749	Log. per. Antenna	HL025	R&S	22/24/27, 15C
1875	Thermo- Hygrograph	00.02520.150700	Lambrecht	22/24/27, 15C, 15B
1917	Radio Communication tester	CMTA84	R&S	22/24/27, 15C, 15B
1933	Precision half-wave dipole antennas	HZ-13	R&S	22/24/27, 15C
1938	Precision half-wave dipole antennas	HZ-12	R&S	22/24/27, 15C
2006	Radiation Reference Source	VSQ	MEB	22/24/27, 15C, 15B
2009	Signal generator	SMP 22	R&S	22/24/27, 15C, 15B
2019	Multimeter	34401A	HP	22/24/27, 15C, 15B
2027	Coupling and Decoupling Network	M2 (modified) DC1	MEB	22/24/27, 15C, 15B
2028	Coupling and Decoupling Network	M3 (modified) DC2	MEB	22/24/27, 15C, 15B
2029	Power Supply	PL330	THURLBY	22/24/27, 15C, 15B
2043	Band Reject Filter	WRCA824/849-0.2-6SS	Wainwright	22, 15C, 15B
2047	Band Reject Filter	WRCC1800/2000-0.2-10SS	Wainwright	24, 15C, 15B
2048	Band Reject Filter	WRCC1700/1800-0.2-10SS	Wainwright	27, 15C, 15B
2051	High Pass Filter	4HC1700-1-KK	R&S	22/24/27, 15C
2057	Log. per. Antenna	HL025	R&S	22/24/27, 15C
2109	Power Supply	PL330QMD	THURLBY	22/24/27, 15C, 15B
2110	Multimeter	34401A	HP	22/24/27, 15C, 15B
2112	Multimeter	TX3	Tektronix	22/24/27, 15C, 15B
2116	Controller	EMCO MODEL 2090	ETS	22/24/27, 15C, 15B
2133	Power Meter	NRVS	R&S	22/24/27, 15C

Eq. No	Equipment	Type	Manufacturer	Used in
2134	Power Sensor	NRV-Z32	R&S	22/24/27, 15C
2135	Coupling and Decoupling Network	CDN 801-M3	LÜTHI	22/24/27, 15C, 15B
2138	Ultra Broadband Antenna	HL562	R&S	22/24/27, 15C, 15B
2140	Biconical Antenna	EMCO93110B	EMCO	22/24/27, 15C
2142	Log.-per.-dipol Antenna	3146	EMCO	22/24/27, 15C
2144	Attenuator	6803.17B	Huber-Suhner	22/24/27, 15C, 15B
2150	High Pass Filter	F-15041	RLC ELECTRONICS	22/24/27, 15C
2176	Coupling and Decoupling Network	CDN 801-M3	LÜTHI	22/24/27, 15C, 15B
2180	Digital Radio Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2188	Preamplifier	AFS4-00100300-20-23P-6	MITEQ	22/24/27, 15C, 15B
2330	EMI Test receiver	ESIB26	R&S	22/24/27, 15C, 15B
2334	GPIB Switch 2 to 1	-	National Instruments	22/24/27, 15C, 15B
2348	Yaesu controller	G-1000DXC	YAESU	22/24/27, 15C, 15B
2349	Computer controller (Yaesu)	GS-232B	YAESU	22/24/27, 15C, 15B
2350	Preamplifier	AMF-6D-020180-29-20P	MITEQ	22/24/27, 15C
2361	Anechoic chamber	3 meter semi/full anechoic chamber	Euroshield	22/24/27, 15C, 15B
2398	Horn antenna	HF906	R&S	22/24/27, 15C
2363	Band Reject Filter	WRCG 832/838-825/845/5SS	Wainwright	22/24/27
2364	Band Reject Filter	WRCG1877/1883 - 1870/1890-40/6SS	Wainwright	22/24/27
2365	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2366	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2384	Band Reject Filter	WRCG832/838-825/845-40/5SS	Wainwright	22/24/27
2388	Bluetooth Tester	CBT	R&S	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B