

TEST REPORT

of

FCC Part 22, 24, Part 2

FCC ID: QMNRN-375

Equipment Under Test : CDMA 2000 1xRTT Mobile Phone
Model Name : RM-375
Serial No. : N/A
Applicant : Nokia Inc.
Manufacturer : Compal Communications(Nanjing) Co., Ltd.
Date of Test(s) : 2008-04-05 ~ 2008-05-13
Date of Issue : 2008-05-23

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date:

2008-05-23

Feol Jeong

Approved By:



Date:

2008-05-23

Jim Kim

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

	<u>TABLE OF CONTENTS</u>	Page
1. General Information -----		3
2. RF Radiated Output Power -----		8
3. Field Strength of Spurious Radiation -----		11
4. Conducted Output Power -----		15
5. Occupied Bandwidth 26 dB -----		18
6. Spurious Emissions at Antenna Terminal-----		24
7. Band Edge -----		29
8. Frequency Stability -----		32

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General Information

1-1. Testing Laboratory

SGS Testing Korea Co., Ltd.

- 705, Dongchun-Dong Sooji-Gu, Yongin-Shi, Kyungki-Do, South Korea.

www.electrolab.kr.sgs.com

Telephone : +82 +31 428 5700

FAX : +82 +31 427 2371

1-2. Details of Applicant

Applicant : Nokia Inc.
Address : 12278 Scripps Summit Dr. San Diego CA92131 USA
Contact Person : Stephen Walmsley
Phone No. : +1 604 456 5544
Fax No. : -

1.3. Basic Description of Equipment under Test

Kind of Product		CDMA 2000 1xRTT Mobile Phone
Model Name		RM-375
AC Adapter	Manufacture	Astec
	Brand Name	Nokia
	Model Name	AC-6U
	Power Rating	I/P: 100 - 240 V _{ac} , 50 - 60 Hz, 150 mA O/P: 5.0 V _{dc} , 550 mA
	AC Power Cord Type	1.7 m non-shielded cable without ferrite core
Battery	Manufacture	Panasonic
	Brand Name	Nokia
	Model Name	BL-4B
	Power Rating	3.7 V _{dc} , 700mAh
	Type	Li-ion
Earphone	Manufacture	Hosiden
	Brand Name	Nokia
	Model Name	HS-49
	Signal Line Type	1.7 meter non-shielded cable without ferrite core
USB Cable	Manufacture	Cheng Uei
	Brand Name	Nokia
	Model Name	CA-101
	Signal Line Type	1.1 m shielded cable without ferrite core

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1-4. Description of EUT

Kind of Product		CDMA 2000 1xRTT Mobile Phone
Model Name		RM-375
Serial Number		N/A
Power Supply	Manufacture	Panasonic
	Brand Name	Nokia
	Model Name	BL-4B
	Power Rating	3.7 V _{dc} , 700mAh
	Type	Li-ion
Tx Frequency Range		Cellular: 824 ~ 849 MHz AWS: 1710 ~ 1755 MHz PCS: 1850 ~ 1910 MHz BT: 2402 ~ 2480 MHz
Rx Frequency Range		Cellular: 869 ~ 894 MHz AWS: 2110 ~ 2155 MHz PCS: 1930 ~ 1990 MHz BT: 2402 ~ 2480 MHz
Transmit Power		CDMA : ERP 24.51 dBm (282.49 mW) US PCS : EIRP 29.80 dBm (955.00 mW) AWS : EIRP 29.06 dBm (805.38 mW)
Modulation Technique		CDMA2000 :QPSK Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
Emission Designation		1M28F9W(CDMA), 1M27F9W(AWS), 1M28F9W(PCS),
Operating Conditions		-30 ~ 60 °C
Antenna Type		Fixed type(BT, CDMA, US PCS, AWS)
H/W Version		4000
S/W Version		DS-1100B-GEN
MEID		268435456102530121

* The spurious emission was measured in three orthogonal EUT positions (X-axis, Y-axis and Z-axis). Worst case is X-axis (CDMA 800), Z-axis(PCS 1900)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1-5. Details of modification

-N/A

1.6. Test Equipment List

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Signal Generator	Agilent	E4438C	May 09 2009
Spectrum Analyzer	Agilent	E4440A	May 09 2009
Spectrum Analyzer	H.P	8593E	May 09 2009
Power Meter	Agilent	E4416A	May 09 2009
Power Sensor	Agilent	E9327A	May 09 2009
DC Power Supply	Agilent	6674A	May 09 2009
Test Receiver	Rohde & Schwarz	ESVS10	Mar. 21 2009
Ultra-Broadband Antenna	Rohde & Schwarz	HL562	Oct. 02 2009
Horn Antenna	Rohde & Schwarz	HF906	Nov. 13 2009
Dipole Antenna	VHAP/UHAP	975/958	Jan. 18 2010
Communication Antenna	AR	AT 4002	N/A
Band Reject Filter	Wainwright	WRCG824/849-814/85960/10SS	May 09 2009
Highpass Filter	Wainwright	WHK3.0/18G-10SS	Dec. 06 2008
Mobile Test Unit	Agilent	E5515C	May 09 2009

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Preamplifier	Agilent	8449B	May 09 2009
Preamplifier	Agilent	8447F	Sep. 17 2008
Power Amplifier	Empower RF System, Inc.	2001-BBS3Q7ECK	May 09 2009
Dual Directional Coupler	Agilent	778D	Feb. 04 2009
Anechoic Chamber	SY Corporation	L x W x H 9.6 m x 6.4 m x 6.4 m	Feb. 15 2009

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.7. Summary of Test Results

APPLIED STANDARD: FCC Part 2,22, 24		
Section in FCC Part 2,22,24	Test Item	Result
§22.913 §24.232(b)	RF Radiated Output Power	Complied
§2.1053 §22.917(e) §24.238(a)	Field Strength of Spurious Radiation	Complied
§2.1046	Conducted Output Power	Complied
§2.1049	Occupied Bandwidth 26dB	Complied
§2.1051 §22.917(e) §24.238(a)	Spurious Emission at Antenna Terminal	Complied
§2.1055(a)(1) §22.355 §24.235	Frequency Stability	Complied
§22.917(e) §24.238(c)	Band Edge	Complied

1.8 Test Report Revision

Revision	Report number
0	F690501/RF-RTL001999
1	F690501/RF-RTL002003
2	F690501/RF-RTL002023
3	F690501/RF-RTL002042

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. RF Radiated Output Power

2.1. Limit

§22.913(a), the ERP of mobile transmitters must not exceed 7 watts.


§24.232(b) Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

2.2. Test Procedure


1. On a test site, the EUT shall be placed at 80cm height on a turn table, and in the position closest to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3m from EUT to correspond to the frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. The transmitter shall be switched on, the measuring receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
6. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
7. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The transmitter shall be replaced by a horn (substitution antenna).
10. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
11. The substitution antenna shall be connected to a calibrated signal generator.
12. In necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
13. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
14. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
15. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
16. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
17. The measure of the effective radiated power is the large of the two levels recorded, at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
18. The ERP/EIPR test under RC3/SO55 (CDMA 800), RC2/SO55 (PCS1900)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 18 GHz Emissions.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.3. Test Results

Ambient temperature : 21 °C Relative humidity : 48 %

ERP: CDMA 800

Frequency (MHz)	Ant. Pol. (H/V)	C.L. (dB)	S.G. Reading +Amp (dBm)	Antenna Gain (dBD)	E. R. P.	
					(dBm)	(mW)
824.700	H	0.62	35.57	-10.44	24.51	282.49
	V	0.62	27.98	-10.44	16.92	49.20
836.520	H	0.64	34.34	-10.45	23.25	211.35
	V	0.64	25.24	-10.45	14.15	26.00
848.310	H	0.56	35.53	-10.53	24.44	277.97
	V	0.56	25.35	-10.53	14.26	26.67

EIRP: PCS 1900

Frequency (MHz)	Ant. Pol. (H/V)	C.L. (dB)	S.G. Reading +Amp (dBm)	Antenna Gain (dBi)	E. I. R. P.	
					(dBm)	(mW)
1851.25	H	0.99	14.85	8.79	22.65	184.08
	V	0.99	22.00	8.79	29.80	955.00
1880.00	H	0.97	15.37	8.90	23.30	213.80
	V	0.97	20.92	8.90	28.85	767.36
1908.75	H	1.14	14.12	9.00	21.98	157.76
	V	1.14	19.87	9.00	27.73	592.92

Remake: 1. ERP/EIRP= SG Reading +Amp-C.L. +Gain

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3. Field Strength of Spurious Radiation

3.1. Limit


§ 22.917(e) and §24.238 (a) Out of band emissions. The power of any emission outside of the authorized operating frequency must be attenuated below the transmitting (P) by a factor of at least $43+10\log(P)$ dB.

3.2. Test Procedure


1. On a test site, the EUT shall be placed at 0.8cm height on a turn table, and in the position closest to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3m from EUT to correspond to the frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. The transmitter shall be switched on, the measuring receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
6. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
7. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The transmitter shall be replaced by a horn (substitution antenna).
10. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
11. The substitution antenna shall be connected to a calibrated signal generator.
12. In necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
13. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
14. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
15. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
16. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
17. The measure of the effective radiated power is the large of the two levels recorded, at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary
18. Spurious radiated emission was tested under RC3/S055 (CDMA 800), RC3/S02(AWS), RC2/S055 (PCS1900).

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 18 GHz Emissions.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.3. Test Result

Ambient temperature : 21 °C Relative humidity : 48 %

CDMA 800

Frequency (MHz)	Ant.Pol. (H/V)	S.G. reading (dBm)	CL (dB)	Gain (dBi)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
TX LOW channel (824.70 MHz)								
1649.40	H	-40.85	1.03	8.08	5.93	-35.95	-13.00	22.95
	V	-41.19	1.03	8.08	5.93	-36.29	-13.00	23.29
2474.10	H	-36.78	1.16	9.91	7.76	-30.18	-13.00	17.18
	V	-35.81	1.16	9.91	7.76	-29.21	-13.00	16.21
3298.80	H	-40.10	0.94	10.84	8.69	-32.35	-13.00	19.35
	V	-45.55	0.94	10.84	8.69	-37.80	-13.00	24.80
4123.50	H	-38.19	1.67	11.42	9.27	-30.59	-13.00	17.59
	V	-43.50	1.67	11.42	9.27	-35.90	-13.00	22.90
TX MID Channel (836.52 MHz)								
1673.04	H	-48.11	0.98	8.10	5.95	-43.14	-13.00	30.14
	V	-50.20	0.98	8.10	5.95	-45.23	-13.00	32.23
2509.56	H	-35.95	1.19	9.92	7.77	-29.37	-13.00	16.37
	V	-43.21	1.19	9.92	7.77	-36.63	-13.00	23.63
3346.08	H	-40.87	1.24	10.88	8.73	-33.38	-13.00	20.38
	V	-46.98	1.24	10.88	8.73	-39.49	-13.00	26.49
4182.60	H	-36.56	1.67	11.40	9.25	-28.98	-13.00	15.98
	V	-41.40	1.67	11.40	9.25	-33.82	-13.00	20.82
TX HIGH Channel (848.31 MHz)								
1696.62	H	-42.03	0.91	8.25	6.10	-36.84	-13.00	23.84
	V	-42.13	0.91	8.25	6.10	-36.94	-13.00	23.94
2544.93	H	-36.83	1.24	10.00	7.85	-30.22	-13.00	17.22
	V	-42.92	1.24	10.00	7.85	-36.31	-13.00	23.31
3393.24	H	-42.41	1.32	10.92	8.77	-34.96	-13.00	21.96
	V	-45.14	1.32	10.92	8.77	-37.69	-13.00	24.69
4241.55	H	-36.66	1.70	11.38	9.23	-29.13	-13.00	16.13
	V	-38.79	1.70	11.38	9.23	-31.26	-13.00	18.26

Remake: 1. No more harmonic above 6th harmonic for all channel.
2. ERP= SG Reading -Cable Loss +Gain

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

PCS 1900

Frequency (MHz)	Ant.Pol. (H/V)	S.G. reading (dBm)	CL (dB)	Gain (dBi)	Gain (dBd)	EIRP (dBm)	Limit (dBm)	Margin (dB)
TX LOW channel (1851.25 MHz)								
3702.50	H	-43.89	2.37	11.20	9.05	-35.06	-13.00	22.06
	V	-44.89	2.37	11.20	9.05	-36.06	-13.00	23.06
TX MID Channel (1880.00 MHz)								
3760.00	H	-43.42	2.33	11.25	9.10	-34.50	-13.00	21.50
	V	-46.99	2.33	11.25	9.10	-38.07	-13.00	25.07
TX HIGH Channel (1908.75 MHz)								
3817.50	H	-28.57	2.36	11.31	9.16	-19.62	-13.00	6.62
	V	-30.22	2.36	11.31	9.16	-21.27	-13.00	8.27

Remake: 1. No more harmonic above 2rd harmonic for all channel.

2. EIRP= SG Reading -Cable Loss +Gain

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


4. Conducted Output Power

4.1. Limit

Requirements: CFR 47, Section §2.1046

4.2. Test Procedure

1. The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.
2. The Agilent 8960 Test Set has the following procedure.
 - Call Setup >Shift & Preset - Protocol Rev >6 (IS-2000-0)
 - Radio Config.(RC)>RC 11(Fwd1, Rvs1)
 - Traffic Data Rate > Full - Cell Info > Cell Parameters >Primary Ch (358:CDMA, 600:PCS 1900)
3. Once "Active Cell" show "Connected" then change "Rvs. Power Ctrl" from " Active bits" to "All Up bits" to get the maximum power.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4.3. Test Results

Ambient temperature : 23 °C Relative humidity : 46 %

Conducted Average Power Output Table (CDMA 1xRTT)

Band	Channel	CDMA2000 RC	S02 (dBm)	S09 (dBm)	S032(+SCH) (dBm)	S032(+F-SCH) (dBm)	S055 (dBm)
CDMA 800	Middle(384)	(Fwd1,Rvs1)	24.82				24.62
		(Fwd2,Rvs2)		24.72			24.60
		(Fwd3,Rvs3)	24.67		24.20	24.31	24.73
		(Fwd4,Rvs3)	24.53		23.84	24.22	24.63
		(Fwd5,Rvs4)		24.50			24.70

Band	Channel	CDMA2000 RC	S02 (dBm)	S09 (dBm)	S032(+SCH) (dBm)	S032(+F-SCH) (dBm)	S055 (dBm)
PCS 1900	Middle(600)	(Fwd1,Rvs1)	23.19				23.35
		(Fwd2,Rvs2)		23.18			23.38
		(Fwd3,Rvs3)	23.25		22.35	22.86	23.34
		(Fwd4,Rvs3)	23.20		22.48	22.96	23.17
		(Fwd5,Rvs4)		23.23			23.20

Remake: RF Power measurements were made in 'closed' position.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

CDMA 850 (1xRTT)

Channel	Frequency (MHz)	Average Output Power (dBm)	Average Output Power (W)	Limit (W)
Low(1013)	824.70	25.10	0.32	7
Middle(384)	836.52	24.73	0.30	7
High(777)	848.31	24.30	0.27	7

PCS 1900 (1xRTT)

Channel	Frequency (MHz)	Average Output Power (dBm)	Average Output Power (W)	Limit (W)
Low(25)	1851.25	23.63	0.23	2
Middle(600)	1880.00	23.38	0.22	2
High(1175)	1908.75	23.44	0.22	2

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


5. Occupied Bandwidth 26 dB

5.1. Limit

Requirements: CFR 47, Section §2.1049.

5.2. Test Procedure

1. The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.
2. The resolution bandwidth of the spectrum analyzer was set at 30 kHz.
Occupied Bandwidth 26dB was tested under



6.3 Test Results

Ambient temperature : 23 °C Relative humidity : 46 %


CDMA 800

Channel	Frequency(MHz)	-26 dB Bandwidth(MHz)
Low(1013)	824.70	1.402
Middle(384)	836.52	1.414
High(777)	848.31	1.418


Please refer to the following plots.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Low Channel




Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


PCS 1900

Channel	Frequency(MHz)	-26 dB Bandwidth(MHz)
Low(25)	1851.25	1.410
Middle(600)	1880.00	1.457
High(1175)	1908.75	1.394


Please refer to the following plots.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Low Channel




Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


6. Spurious Emissions at Antenna Terminal

6.1. Limit

§ 22.917(e) and §24.238 (a) Out of band emissions. The power of any emission outside of the authorized operating frequency must be attenuated below the transmitting (P) by a factor of at least $43+10\log(P)$ dB.

6.2. Test Procedure

1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
2. The resolution bandwidth of the spectrum analyzer was set at 1 MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.
3. Spurious Emission was tested under RC5/SO55



6.3. Test Results


Ambient temperature : 23 °C Relative humidity : 46 %

Please refer to the following plots.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

CDMA 800

Low Channel




Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

PCS 1900

Low Channel




Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


7. Band Edge

7.1. Limit

§ 22.917(e) and §24.238 (a) Out of band emissions. The power of any emission outside of the authorized operating frequency must be attenuated below the transmitting (P) by a factor of at least $43+10\log(P)$ dB.

7.2. Test Procedure

1. The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.
2. The center of the spectrum analyzer was set to block edge frequency, RBW set to 15 kHz.



7.3. Test Results


Ambient temperature : 23 °C Relative humidity : 46 %

Please refer to the following plots.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

CDMA 800

Low Channel




High Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

PCS 1900

Low Channel



High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

8. Frequency Stability

8.1. Limit

Requirements: FCC § 2.1055 (a), § 2.1055 (d) & following:


According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table of this section.

For Mobile devices operating in the 824 to 849 MHz band at a power level less than or equal to 3 Watts, the limit specified in Table C-1 is +/- 2.5 ppm.

§24.235 The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

8.2. Test Procedure

1. Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed-through attenuators.
2. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.
3. After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.
4. Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

8.3. Test Results

Ambient temperature : 23 °C Relative humidity : 46 %

Frequency Stability versus Temperature

CDMA 800

Reference Frequency: 836.52 MHz, Limit: 2.5 ppm			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
20(Ref.)	3.7	-2.5	-0.003
60	3.7	-1.0	-0.001
50	3.7	1.5	0.002
40	3.7	-1.9	-0.002
30	3.7	-1.0	-0.001
20	3.7	-2.4	-0.003
10	3.7	3.8	0.005
0	3.7	4.8	0.006
-10	3.7	3.8	0.005
-20	3.7	-2.8	-0.003
-30	3.7	-8.2	-0.010

PCS 1900

Reference Frequency: 1880.00 MHz, Limit: 2.5 ppm			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapse	
		Frequency Error (Hz)	ppm
20(Ref.)	3.7	-4.3	-0.002
60	3.7	-3.7	-0.002
50	3.7	-2.9	-0.002
40	3.7	-5.6	-0.003
30	3.7	-4.7	-0.003
20	3.7	-4.0	-0.002
10	3.7	-7.2	-0.004
0	3.7	-9.2	-0.005
-10	3.7	-11.2	-0.006
-20	3.7	-10.0	-0.005
-30	3.7	-11.7	-0.006

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Frequency Stability versus Battery Voltage**CDMA 800**

Reference Frequency:836.52 MHz, Limit: 2.5ppm			
Power Supplied (Vdc)	Environment Temperature (°C)	Frequency Error (Hz)	ppm
4.26	20	2.3	0.003
3.15	20	3.0	0.004

PCS 1900

Reference Frequency:1880.00 MHz, Limit:2.5ppm			
Power Supplied (Vdc)	Environment Temperature (°C)	Frequency Error (Hz)	ppm
4.26	20	-3.6	-0.002
3.15	20	-3.9	-0.002

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.