



HCT CO., LTD.

Product Compliance Division

TEL : +82 31 639 8518 FAX : +82 31 639 8525

CERTIFICATE OF COMPLIANCE

FCC Certification

Applicant Name:

Nokia, Inc.

Date of Issue:

April 29, 2009

Location:

HCT CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si,
Kyungki-do, Korea

Test Report No.: HCT-RF09-0402-5

HCT FRN: 0005866421

IC Recognition No.: IC 5944A

FCC ID	: QMNRN-464
IC	: 661X-RM464
APPLICANT	: Nokia, Inc.

Model(s): RM-464

EUT Type: Dual-Band CDMA Phone with+BT2.1+EDR

Tx Frequency: 824.70 — 848.31 MHz (CDMA)
1 851.25 — 1 908.75 MHz (PCS CDMA)

Rx Frequency: 869.70 — 893.31 MHz (CDMA)
1 931.25 — 1 988.75 MHz (PCS CDMA)

Max. RF Output Power: 0.434 W ERP CDMA (26.37 dBm) / 0.551 W EIRP PCS CDMA (27.41 dBm)

Emission Designator(s): 1M28F9W (CDMA), 1M28F9W (PCS CDMA)

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s): §22, §24, §2

IC Rule: RSS-129 Issue 2_September 25, 1999, RSS-133 Issue 5_February 2009,
RSS-GEN Issue 2_June 2007

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Jong Seok Lee

Report prepared by

: Jong Seok Lee

Test engineer of RF Part

Sang Jun Lee

Approved by

: Sang Jun Lee

Manager of RF Part

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Date of Issue: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF09-0402-1	April 15, 2009	<ul style="list-style-type: none">■ IC registration number update■ SW &HW version update■ Revised the page of test plot
HCT-RF09-0402-2	April 17, 2009	<ul style="list-style-type: none">■ Revised the page of test plot■ Change the information for Conducted Spurious Emissions
HCT-RF09-0402-3	April 21, 2009	<ul style="list-style-type: none">■ Page numbering update
HCT-RF09-0402-4	April 23, 2009	<ul style="list-style-type: none">■ Version control update■ Update the IC Rule■ Update the information for Minimum Controlled Output Power
HCT-RF09-0402-5	April 29, 2009	<ul style="list-style-type: none">■ Change from "IC ID" to "IC"■ The uncertainty update■ Revised the name and pate of test plot■ Add the version for IC rule

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	www.hct.co.kr

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION.....	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS.....	6
3.1 Effective Radiated Power/Equivalent Isotropic Radiated Power.....	6
3.2 Peak- to- Average Ratio	7
3.3 Occupied bandwidth.....	8
3.4 Spurious and Harmonic Emissions at Antenna Terminal.....	9
3.5 Radiated Spurious and Harmonic Emissions	10
3.6 Frequency stability / variation of ambient temperature.....	12
4. LIST OF TEST EQUIPMENT	14
5. SUMMARY OF TEST RESULTS	15
6. SAMPLE CALCULATION.....	16
7. TEST DATA	17
7.1 Conducted Output Power.....	17
7.1.1 Minimum Controlled Output Power	17
7.1.2 Standby Output Power	18
7.2 Peak-to-Average Ratio	18
7.3 Occupied Bandwidth.....	19
7.4 Conducted Spurious Emissions.....	19
7.4.1 Band Edge	20
7.5 Effective Radiated Power Output (CDMA)	20
7.6 Equivalent Isotropic Radiated Power (E.I.R.P.) (PCS CDMA).....	21
7.7 Radiated Spurious Emissions	22
7.7.1 Radiated Spurious Emissions (CDMA Mode)	22
7.7.2 Radiated Spurious Emissions (PCS CDMA Mode)	23
7.8 Frequency stability / variation of ambient temperature.....	24
7.8.1 FREQUENCY STABILITY (CDMA).....	24
7.8.2 FREQUENCY STABILITY (PCS CDMA).....	25
8. TEST PLOTS	26

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: Nokia, Inc.

Applicant Address: 12278 Scripps Summit Drive, San Diego, CA 92131

Contact: TEL : + 858-831-5000 / FAX : + 858-831-6500

FCC ID: QMNRN-464

IC: 661X-RM464

Application Type: Certification

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s): §22, §24, §2

EUT Type: Dual-Band CDMA Phone with+BT2.1+EDR

Model(s): RM-464

S/N : A0000001593C24

HW Version : 4200

SW Version : ST_4020T11_VZW_116

Battery Model Name: BL-4C(Standard)

Power Rating: 3.7 V, 860mAh

Type: Li-ion

Tx Frequency: 824.70 — 848.31 MHz (CDMA)
1 851.25 — 1 908.75 MHz (PCS CDMA)

Rx Frequency: 869.70 — 893.31 MHz (CDMA)
1 931.25 — 1 988.75 MHz (PCS CDMA)

Max. RF Output Power: 0.434 W ERP CDMA (26.37 dBm) / 0.551 W EIRP PCS CDMA (27.41 dBm)

Emission Designator(s): 1M28F9W (CDMA), 1M28F9W (PCS CDMA)

Antenna Specification

Manufacturer:	E.M.W Antenna Co., Ltd.
Antenna type:	Internal Antenna
Peak Gain:	2.65 dBi

Date(s) of Tests: March 27, 2009 ~ April 20, 2009

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	www.hct.co.kr



2. INTRODUCTION

2.1. EUT DESCRIPTION

The RM-464 Dual-Band CDMA Phone with+BT2.1+EDR consists of Cellular CDMA, PCS.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY


The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 6, 2006(Registration Number: 90661)

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	

3. DESCRIPTION OF TESTS

3.1 Effective Radiated Power/Equivalent Isotropic Radiated Power

Test Set-up



Test Procedure

Radiated emission measurements were performed at an open Site.

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

Measurement Uncertainty

For a 95 % confidence level, the measurement uncertainties for defined system.

30 MHz ~ 1 GHz	± 5.6 dB (k=2)
Above 1 GHz	± 5.8 dB (k=2)

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	



3.2 Peak- to- Average Ratio

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA and WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. Plots of the EUT's Peak- to- Average Ratio are shown herein.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.


Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (dB)
Absolute error	Rectangular	0.61
Frequency response	Rectangular	0.58
Error of the input attenuator	Rectangular	0.40
Error of bandwidth switching	Rectangular	0.03
Drift of temperature for DUT	Rectangular	0.15
Time-duty cycle error for DUT	Rectangular	0.05
Supply voltage dependancy for DUT	Rectangular	0.08
Mismatch: Spectrum : Divider	U-Shaped	0.25
Mismatch: Divider : DUT	U-Shaped	0.16
Combined standard uncertainty		0.99
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of $k = 2$)		1.99

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464

3.3 Occupied bandwidth.

Test set-up



Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Plots of the EUT's occupied bandwidth are shown herein.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (Hz)
Year aging of oscillator Drift of temperature Readout uncertainty Marker count accuracy DUT drift of temperature	Rectangular	577.35
	Rectangular	11.55
	normal	290.00
	Rectangular	1039.81
	Rectangular	115.47
Combined standard uncertainty	1229.67	
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of k = 2)	2459.35	

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



3.4 Spurious and Harmonic Emissions at Antenna Terminal.

Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the – 13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 30 MHz to 10 GHz. (PCS CDMA Mode: 30 MHz to 20 GHz). A display line was placed at – 13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

- Band Edge Requirement : In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.


Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (dB)
Absolute error	Rectangular	0.61
Frequency response	Rectangular	0.58
Error of the input attenuator	Rectangular	0.40
Error of bandwidth switching	Rectangular	0.03
Drift of temperature for DUT	Rectangular	0.15
Time-duty cycle error for DUT	Rectangular	0.05
Supply voltage dependancy for DUT	Rectangular	0.08
Mismatch: Spectrum : Divider	U-Shaped	0.25
Mismatch: Divider : DUT	U-Shaped	0.16
Combined standard uncertainty		0.99
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of $k = 2$)		1.99

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464

3.5 Radiated Spurious and Harmonic Emissions

Test Set-up



The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section § 2.948. The open field test site is situated in open field with ground screen whose site attenuation characteristics meet ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a rotatable wooden platform mounted at three from the antenna mast.

- 1) The unit mounted on a wooden table $1.5 \text{ m} \times 1.0 \text{ m} \times 0.80 \text{ m}$ is 0.8 meter above test site ground level.
- 2) During the emission test, the turntable is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
- 3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
- 4) The spectrum shall be scanned up to the 10th harmonic of the fundamental frequency.

Test Procedure

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

Measurement Uncertainty


For a 95 % confidence level, the measurement uncertainties for defined system.

30 MHz ~ 1 GHz	± 5.6 dB (<i>k</i> =2)
Above 1 GHz	± 5.8 dB (<i>k</i> =2)

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	

3.6 Frequency stability / variation of ambient temperature

Test Set-up



* Nominal Operating Voltage

Test Procedure

The frequency stability of the transmitter is measured by:

a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.000\ 25\% (\pm 2.5\ ppm)$ of the center frequency.

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

FCC CERTIFICATION REPORT				
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464



Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (Hz)
Year aging of oscillator	Rectangular	415.69
Drift of temperature	Rectangular	51.96
Frequency Error	Rectangular	8.66
DUT drift of temperature	Rectangular	115.47
Combined standard uncertainty		434.64
Expanded uncertainty (Confidence interval of 95.45 %, Coverage Factor of $k = 2$)		869.27

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
R&S	ESI40/ Spectrum Analyzer	831564/003	Annual	10/31/2009
Agilent	E4416A/ Power Meter	GB41291412	Annual	01/21/2010
Agilent	E9327A/ Power Sensor	MY4442009	Annual	07/28/2009
Agilent	8960 (E5515C)/ Base Station	GB44400269	Annual	02/10/2010
MITEQ	AMF-60-0010 1800-35-20P / AMP	1200937	Annual	05/20/2009
Wainwright	WHK1.2/15G-10EF/H.P.F	2	Annual	06/28/2009
Wainwright	WHK3.3/18G-10EF/H.P.F	1	Annual	06/28/2009
Agilent	775D/ Dual Directional Coupler	12922	Annual	12/24/2009
Agilent	11636B/ Power Divider	11377	Annual	12/24/2009
Digital	EP-3010/ Power Supply	3110117	Annual	01/07/2010
Schwarzbeck	UHAP/ Dipole Antenna	585	Annual	02/13/2011
Schwarzbeck	UHAP/ Dipole Antenna	558	Annual	02/13/2011
Korea Engineering	KR-1005L / Chamber	KRAB07063-2CH	Annual	12/31/2009
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	Biennial	03/26/2010
Schwarzbeck	BBHA 9120D/ Horn Antenna	1201	Biennial	05/02/2009
Agilent	E4440A/Spectrum Analyzer	US45303008	Annual	12/23/2009

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	IC Rule	Test Description	Test Limit	Test Condition	Test Result
2.1049, 22.917(a), 24.238(a)	RSS-129, Section 6.3 RSS-GEN, Section 4.6.1	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 22.917(a), 24.238(a)	RSS-129, Section 8.1.1 (Cell) RSS-133, Section 6.5 (PCS) RSS-GEN, Section 4.9	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	< 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS
2.1046	-	Conducted Output Power	-		PASS
24.232(d)	-	Peak- to- Average Ratio	< 13 dB		PASS
2.1055, 22.355, 24.235	RSS-129, Section 9.2.1 RSS-133, Section 6.3 RSS-GEN, Section 4.7	Frequency stability / variation of ambient temperature	< 2.5 ppm		PASS
-	RSS-129, Section 9.3	Standby Output Power	< -61 dBm/MHz		PASS
-	RSS-129, Section 9.4	Minimum Controlled Output Power	< -51 dBm/MHz		PASS
22.913(a)(2) 24.232(c)	RSS-GEN, Section 4.8 RSS-129, Section 9.1 (ERP, Cell) RSS-133, Section 6.4 (EIRP, PCS) RSS-139, Section	Effective Radiated Power Equivalent Isotropic Radiated Power	< 7 Watts max. ERP < 6.3 Watts max. ERP (IC) < 2 Watts max. EIRP	RADIATED	PASS
2.1053, 22.917(a), 24.238(a)	RSS-129, Section 8.1.1 (Cell) RSS-133, Section 6.5 (PCS) RSS-GEN, Section 4.9	Radiated Spurious and Harmonic Emissions	< 43 + 10log ₁₀ (P[Watts]) for all out-of band emissions		PASS

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464



6. SAMPLE CALCULATION

A. ERP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	384	836.52	-10.96	24.81	2.50	1.19	H	0.41	26.12

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
- 2) During the test , the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power (**ERP**).

B. Emission Designator

CDMA Emission Designator

Emission Designator = 1M27F9W

CDMA BW = 1.27 MHz (Measured at the 99% power bandwidth)

F = Frequency Modulation

9 = Composite Digital Info


W = Combination (Audio/Data)

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:	
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464	

7. TEST DATA

7.1 Conducted Output Power

A base station simulator was used to establish communication with The EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Band	Channel	SO2	SO2	SO55	SO55	TDSO SO32
		RC1/1 (dBm)	RC3/3 (dBm)	RC1/1 (dBm)	RC3/3 (dBm)	RC3/3 (dBm)
CDMA	1013	24.42	24.39	24.32	24.37	24.30
	384	24.63	24.59	24.62	24.62	24.62
	777	24.48	24.53	24.60	24.56	24.53
PCS	25	24.47	24.49	24.40	24.33	24.46
	600	24.60	24.61	24.63	24.60	24.55
	1175	24.35	24.39	24.34	24.41	24.24

(Maximum Conducted Output Powers)

7.1.1 Minimum Controlled Output Power

Open Loop mode

Band	Channel	Data(dBm)
CDMA	1013	-58.51
	384	-57.99
	777	-57.97

The output power of a mobile transmitter was tested with both closed loop and open loop power control functions set to minimum. Open loop is worst case.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464

Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (dB)
Absolute Accuracy	Rectangular	0.02
Power sensor linearity	Rectangular	0.11
Power range	Rectangular	0.02
Drift of temperature for DUT	Rectangular	0.15
Time-duty cycle error for DUT	Rectangular	0.05
Supply voltage dependancy for DUT	Rectangular	0.08
Mismatch: Sensor : Divider	U-Shaped	0.05
Mismatch: Power meter : sensor	U-Shaped	0.01
Mismatch: Divider : DUT	U-Shaped	0.16
Combined standard uncertainty	0.26	
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of $k = 2$)	0.53	

7.1.2 Standby Output Power

- Plots of the EUT's Standby Output Power are shown Page 41 ~ 42.

7.2 Peak-to-Average Ratio

- Plots of the EUT's Peak- to- Average Ratio are shown Page 30.

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



7.3 Occupied Bandwidth

Band	Channel	Frequency(MHz)	Data (MHz)
CDMA	1013	824.4	1.2831
	384	836.5	1.2709
	777	848.3	1.2729
PCS	25	1851.25	1.2774
	600	1880.00	1.2780
	1175	1908.75	1.2753

Plots of the EUT's Occupied Bandwidth are shown Page 27 ~ 29.

7.4 Conducted Spurious Emissions

Band	Channel	Frequency of Maximum Harmonic (GHz)	Maximum Harmonic Data (dBm)
CDMA	1013	1.648	-35.39
	384	2.512	-40.31
	777	1.697	-34.60
PCS	25	3.702	-35.47
	600	3.762	-33.66
	1175	3.815	-31.64

- Plots of the EUT's Conducted Spurious Emissions are shown Page 35 ~ 40.

FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464



7.4.1 Band Edge

- Plots of the EUT's Band Edge are shown Page 31 ~ 34.

7.5 Effective Radiated Power Output (CDMA)

(CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	1013	824.70	-11.92	33.91	-8.31	1.17	V	0.28	24.43
	384	836.52	-12.02	34.47	-8.22	1.19	V	0.32	25.06
	777	848.31	-11.43	35.70	-8.13	1.20	V	0.43	26.37

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all configurations and the highest power is reported.

FCC CERTIFICATION REPORT				
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464



7.6 Equivalent Isotropic Radiated Power (E.I.R.P.) (PCS CDMA)

(PCS CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol.	EIRP	
	channel	Freq.(MHz)						W	dBm
PCS	25	1,851.25	-13.21	18.40	10.05	1.91	H	0.45	26.53
	600	1,880.00	-12.51	19.31	10.05	1.95	H	0.55	27.41
	1175	1,908.75	-12.92	18.98	10.06	1.97	H	0.51	27.07

Note: Standard batteries are the only options for this phone

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported.

FCC CERTIFICATION REPORT				
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464



7.7 Radiated Spurious Emissions

7.7.1 Radiated Spurious Emissions (CDMA Mode)

MEASURED OUTPUT POWER: 26.37 dBm = 0.434 W

MODULATION SIGNAL: CDMA

DISTANCE: 3 meters

LIMIT: $-(43 + 10 \log_{10}(W)) =$ - 39.37 dBc

Ch.	Freq.(MHz)	<u>Measured Level</u> [dBm]	Ant. Gain	<u>Substitute</u> <u>Level</u> [dBm]	C.L	Pol.	ERP (dBm)	dBc
1013	1,649.40	-38.08	7.09	-48.61	1.73	H	-43.25	-69.62
	2,474.10	-38.42	8.12	-45.53	2.28	V	-39.69	-66.06
	3,298.80	-54.98	9.72	-62.56	2.57	V	-55.41	-81.78
384	1,673.04	-51.53	7.23	-62.29	1.79	V	-56.85	-83.22
	2,509.56	-44.98	8.14	-52.11	2.33	H	-46.30	-72.67
	3,346.08	-54.70	9.99	-62.73	2.66	V	-55.40	-81.77
777	1,696.62	-41.66	7.41	-52.27	1.83	H	-46.69	-73.06
	2,544.93	-45.09	8.21	-52.37	2.34	H	-46.50	-72.87
	3,393.24	-55.53	9.91	-63.16	2.85	V	-56.10	-82.47

NOTES:

1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for
all channel.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:	
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464	



7.7.2 Radiated Spurious Emissions (PCS CDMA Mode)

MEASURED OUTPUT POWER: 27.41 dBm = 0.551 W
 MODULATION SIGNAL: PCS CDMA
 DISTANCE: 3 meters
 LIMIT: - (43 + 10 log₁₀ (W)) = - 40.41 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	dBc
25	3,702.50	-43.21	12.46	-49.48	2.73	H	-39.75	-67.16
	5,553.75	-47.33	12.70	-48.91	3.60	H	-39.81	-67.22
	7,405.00	-55.04	11.36	-46.16	3.88	V	-38.68	-66.09
600	3,760.00	-40.41	12.47	-46.38	2.73	H	-36.64	-64.05
	5,640.00	-47.75	12.75	-49.40	3.60	H	-40.25	-67.66
	7,520.00	-55.71	11.33	-46.61	3.88	V	-39.16	-66.57
1175	3,817.50	-33.43	12.49	-39.31	2.73	H	-29.55	-56.96
	5,726.25	-49.77	12.80	-51.08	3.60	H	-41.88	-69.29
	7,635.00	-56.18	11.30	-46.85	3.88	H	-39.43	-66.84

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004;
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for
all channel.


FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:	
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	661X-RM464	

7.8 Frequency stability / variation of ambient temperature

7.8.1 FREQUENCY STABILITY (CDMA)

OPERATING FREQUENCY: 836,520,000 Hz
 CHANNEL: 384
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	836 519 997	-2.84	0.000 000	-0.003
100%		-30	836 520 002	1.58	0.000 000	0.002
100%		-20	836 519 998	-1.63	0.000 000	-0.002
100%		-10	836 520 003	3.12	0.000 000	0.004
100%		0	836 520 001	1.36	0.000 000	0.002
100%		+10	836 519 999	-0.74	0.000 000	-0.001
100%		+20	836 520 002	1.84	0.000 000	0.002
100%		+30	836 519 999	-1.11	0.000 000	-0.001
100%		+40	836 520 002	2.15	0.000 000	0.003
100%		+50	836 519 999	-0.98	0.000 000	-0.001
115%	4.255	+20	836 520 002	1.61	0.000 000	0.002
Batt. Endpoint	3.400	+20	836 519 998	-1.54	0.000 000	-0.002




FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:	
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464		661X-RM464

7.8.2 FREQUENCY STABILITY (PCS CDMA)

OPERATING FREQUENCY: 1880,000,000 Hz
 CHANNEL: 600
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	1879 999 994	-5.88	0.000 000	-0.003
100%		-30	1880 000 002	2.00	0.000 000	0.001
100%		-20	1879 999 996	-3.94	0.000 000	-0.002
100%		-10	1880 000 002	2.08	0.000 000	0.001
100%		0	1879 999 997	-3.12	0.000 000	-0.002
100%		+10	1880 000 002	2.42	0.000 000	0.001
100%		+20	1879 999 995	-4.77	0.000 000	-0.003
100%		+30	1880 000 002	1.70	0.000 000	0.001
100%		+40	1879 999 993	-6.82	0.000 000	-0.004
100%		+50	1880 000 003	2.56	0.000 000	0.001
115%	4.255	+20	1880 000 000	0.30	0.000 000	0.000
Batt. Endpoint	3.400	+20	1879 999 997	-3.14	0.000 000	-0.002




FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	




8. TEST PLOTS

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464

■ CDMA MODE (1013 CH.) Occupied Bandwidth



■ CDMA MODE (384 CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT


www.hct.co.kr

Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464
------------------------------------	-------------------------------	---	----------------------	-------------------

■ CDMA MODE (777 CH.) Occupied Bandwidth



■ PCS CDMA MODE (25 CH.) Occupied Bandwidth



FCC CERTIFICATION REPORT

www.hct.co.kr

Test Report No.
HCT-RF09-0402-5


Test Dates:
April 29, 2009

EUT Type:
Dual-Band CDMA Phone with+BT 2.1+EDR


FCC ID:
QMNRN-464

IC:
661X-RM464

■ PCS CDMA MODE (600 CH.) Occupied Bandwidth



■ PCS CDMA MODE (1175 CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT

www.hct.co.kr


Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464
------------------------------------	-------------------------------	---	----------------------	-------------------

■ PCS CDMA MODE (600 CH.) Peak-to-Average Ratio




FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	

■ CDMA MODE (1013 CH.) Band Edge




■ CDMA MODE (777 CH.) Band Edge




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	www.hct.co.kr
------------------------------------	-------------------------------	---	----------------------	--

■ CDMA MODE (1013 CH.) 4 MHz Span




■ CDMA MODE (777 CH.) 4 MHz Span




FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	www.hct.co.kr IC: 661X-RM464

■ PCS CDMA MODE (25 CH.) Band Edge



■ PCS CDMA MODE (1175 CH.) Band Edge



FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	www.hct.co.kr
------------------------------------	-------------------------------	---	----------------------	--

■ PCS CDMA MODE (25 CH.) 4 MHz Span




■ PCS CDMA MODE (1175 CH.) 4 MHz Span




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464
------------------------------------	-------------------------------	---	----------------------	-------------------

■ CDMA MODE (1013 CH.) Conducted Spurious Emissions 1




■ CDMA MODE (1013 CH.) Conducted Spurious Emissions 2




FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	

■ CDMA MODE (384 CH.) Conducted Spurious Emissions 1




■ CDMA MODE (384 CH.) Conducted Spurious Emissions 2




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464
------------------------------------	-------------------------------	---	----------------------	-------------------

■ CDMA MODE (777 CH.) Conducted Spurious Emissions 1




■ CDMA MODE (777 CH.) Conducted Spurious Emissions 2




FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	

■ PCS CDMA MODE (25 CH.) Conducted Spurious Emissions 1




■ PCS CDMA MODE (25 CH.) Conducted Spurious Emissions 2




FCC CERTIFICATION REPORT				
Test Report No.	Test Dates:	EUT Type:	FCC ID:	www.hct.co.kr
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464	IC: 661X-RM464

■ PCS CDMA MODE (600 CH.) Conducted Spurious Emissions 1




■ PCS CDMA MODE (600 CH.) Conducted Spurious Emissions 2




FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:	
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464		661X-RM464

■ PCS CDMA MODE (1175 CH.) Conducted Spurious Emissions 1




■ PCS CDMA MODE (1175 CH.) Conducted Spurious Emissions 2




FCC CERTIFICATION REPORT				
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	www.hct.co.kr IC: 661X-RM464

■ CDMA MODE (1013 CH.) Standby Output Power




■ CDMA MODE (384 CH.) Standby Output Power



FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	IC:	
HCT-RF09-0402-5	April 29, 2009	Dual-Band CDMA Phone with+BT 2.1+EDR	QMNRN-464		661X-RM464

■ CDMA MODE (777 CH.) Standby Output Power



FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0402-5	Test Dates: April 29, 2009	EUT Type: Dual-Band CDMA Phone with+BT 2.1+EDR	FCC ID: QMNRN-464	IC: 661X-RM464	